

LIGHT Impressions

2026 | 2027



Lamps from Essen



LIGHT Impressions 2026 | 2027


Lamps from Essen

Professional lighting solutions. Tailor-made. Available quickly.

For more than 30 years, KS Licht, a lighting wholesaler based in Essen, has been a partner to electricians, designers and businesses. With LIGHT Impressions 2026 | 2027, we present a carefully selected range of luminaires for professional applications, commercial projects and sophisticated residential projects.

B2B ONLINE SHOP & DIGITAL PROCUREMENT

In the KS Multi Brand Business online shop (ks-lys.dk) you will find the latest products, new arrivals, special offers and all the key information you need for your day-to-day work. Check availability online, find and order suitable spare parts, and use catalogues, flip-through catalogues and pro-duct links for quick support with customer advice, quotations and project management.




LIGHTING DESIGN & PROJECT SUPPORT

Whether for offices, retail, catering, hotels, medical practices or commercial premises: we can help you select the right luminaires and develop practical lighting solutions for your project. Our lighting designers will advise you personally and, on request, provide you with technical data, tender documents, light distribution curves and LDT files for planning and implementation.



SHOWROOM & CONSULTATION BY APPOINTMENT

In our showroom in Essen, we display a selection of lighting fixtures from various manufacturers across more than 300 m². By prior appointment, we'd be happy to advise you in person, compare products and demonstrate lighting effects and quality right there on site.



COLLECTION CENTRE IN ESSEN-FRILLENDORF

Items ordered for collection in Essen will be ready for you once we have notified you:
Manderscheidtstraße 12, 45141 Essen.
Mon–Thu 8.30 am–4.00 pm, Fri 8.30 am–3.00 pm

Discover our range now, book an appointment or request a lighting design: ks-lys.dk

KS Licht- und Elektrotechnik GmbH
Manderscheidtstraße 8 C
45141 Essen
Germany

Tel.: +49 (0)201-89924-0
verkauf@ks-germany.com
www.ks-germany.com

LIGHTING DESIGN, VISUALISATION AND PROJECT SUPPORT

Professional lighting design provides confidence when implementing lighting projects. Realistic 3D visualisations, lighting calculations and lighting designs allow lighting effects, illuminance levels and potential energy savings to be evaluated before installation.

Comprehensive planning resources are available for the products featured in this catalogue. These include LDT data, DIALux data, technical product information and specification texts. This enables projects to be planned quickly, accurately and in compliance with applicable standards.

From the initial concept through to implementation, professional planning services support efficient, cost-effective and goal-oriented project execution.



In our main catalogue, you will find our complete product range as well as practical system solutions that combine luminaires, accessories and technology to form comprehensive concepts for a wide variety of applications.

DISCOVER

- 01 service
- 03 table of contents
- 04 areas of application
- 06 refurbishment solutions
- 08 product highlights

INTERIOR LIGHTS

- 20 pendant lights
- 40 surface mounted ceiling lights
- 86 built in ceiling lights
- 129 downlights
- 144 insert panels
- 162 surface mounted wall lights
- 172 built in wall lights
- 180 reading lights
- 190 table and floor lights
- 200 office lights
- 219 hall floodlight
- 229 damp-proof luminaires

TRUNKING SYSTEMS

- 240 trunking systems



SANOTRUNK UNIVERSAL
tool-free universal trunking refurbishment

POWER RAILS

- 266 D ONE 1-phase power rail system
- 287 1-phase power rail luminaires
- 302 D LINE 3-phase power rail system
- 334 D LINE DALI 3-phase power rail system
- 364 power rail luminaires



D LINE DALI
flexible multifunctional track system

BATTERY LIGHTS

- 414 battery lights

OUTDOOR LIGHTS

- 422 bollard lights
- 442 surface mounted wall lights
- 484 ceiling and wall lights
- 488 built in wall lights
- 494 spherical lamps
- 498 energy distributor
- 508 surface mounted / ground spike lights
- 520 wall washer
- 524 ground recessed lights
- 540 floodlight
- 544 display lights

SYSTEM LAUTARO


- 550 pendant lights
- 558 surface mounted ceiling lights



LAUTARO
circular lighting solution with system

SYSTEM PLANO

- 564 luminaire system
- 582 profile system



PLANO
individually configurable lighting system

SYSTEM COMBO

- 590 concrete profile
- 596 built-in profile
- 600 facade profile
- 604 insulation profile
- 606 click profile



COMBO
innovative profile-in-profile solution

ALUMINIUM PROFILES

- 614 linear light in 5 steps
- 618 assembly
- 620 homogeneous light image
- 622 U-profiles - flat + high - built-in / built-on
- 644 T-profiles - flat + high - built in
- 658 H- and groove-profiles
- 662 step/plinth/angle/corner-profiles - built-in/-on
- 684 dry construction profiles
- 704 tile profiles
- 712 profiles for outdoor usw - walk-/trafficable

LED STRIPES

- 724 quick finder
- 728 COB
- 744 12V
- 746 24V
- 770 48V
- 784 230V
- 786 mounting material for LED strips

POWER SUPPLIES

- 792 DC - CV
- 808 DC - CC
- 818 AC - CV

CONTROLLER

- 824 RF-smart
- 850 Casambi Bluetooth
- 852 DALI / DMX dimmer

ILLUMINANTS

- 860 MR16 / GU53
- 861 G9 - GU10
- 864 E27
- 867 GX53

ACCESSORIES

- 872 indoor
- 875 outdoor
- 883 chemical products

LOOK UP

- 884 legend
- 886 lighting solutions
- 890 index

THE RIGHT LIGHTING FOR EVERY APPLICATION

Our versatile range for professional building lighting offers you the right solution - whether for refurbishment, modernisation or new build. With well thought-out lighting concepts and innovative products, we create optimum conditions for every application situation.



industrie

High-performance, efficient lighting creates optimal working conditions in industry, logistics, and manufacturing. DEKO-LIGHT offers durable lighting solutions that sustainably reduce energy consumption, maintenance requirements, and operating costs.



hotel and restaurant industry

Lighting creates atmosphere and shapes the character of hotels, restaurants, and cafés. Decorative fixtures and flexible lighting solutions help create inviting spaces with a special ambience.



residential

The right lighting lends every living space personality and comfort. Our versatile product range offers customized lighting solutions for stylish home designs.



retail

Professional lighting draws attention to products and creates a pleasant shopping experience. From track lighting to accent lighting, DEKO-LIGHT offers the right solution for modern retail spaces.



outdoor areas

Outdoor lighting combines safety, wayfinding, and architectural highlighting. Our extensive portfolio enables customized lighting concepts for facades, pathways, and outdoor areas.



office

Modern office lighting combines functionality, comfort, and design. High-quality lighting solutions create work environments that promote concentration, communication, and well-being.



educational institutions

Optimal lighting supports concentration, wayfinding, and a pleasant learning atmosphere. DEKO-LIGHT offers efficient lighting solutions for schools, universities, and educational institutions.



healthcare facilities

Professional lighting creates optimal conditions for treatment, orientation, and well-being. Our lighting solutions combine functionality with a pleasant and reassuring atmosphere.




SYSTEMATIC RETROFITTING


Rising energy costs, new efficiency requirements and outdated lighting systems make the modernisation of existing lighting systems more important than ever. With the SANOTRUNK UNIVERSAL and PRO OFFICE SANO refurbishment solutions, DEKO-LIGHT offers two cost-effective systems for quick and straightforward conversion to modern LED technology.

SANOTRUNK UNIVERSAL enables the refurbishment of existing T5 and T8 continuous lighting systems and is compatible with almost all standard track systems. PRO OFFICE SANO has been specially developed for replacing conventional grid-mounted luminaires and, thanks to its optimised dimensions, reliably covers existing installation channels.

Both systems offer the benefits of simple installation, high energy efficiency and modern light quality, whilst meeting the requirements for BEG funding. This allows existing lighting systems to be modernised quickly, cost-effectively and with minimal disruption to the existing infrastructure.







CERES – MAXIMUM FLEXIBILITY, SUPERIOR LIGHT QUALITY

Flexible 3-phase track spotlight with high energy efficiency and excellent light quality. Thanks to its extensive range of accessories, various power levels and colour temperatures of 3000 K and 4000 K, the luminaire can be perfectly adapted to individual lighting requirements. Available in ON/OFF and DALI versions and eligible for BEG funding.





FOCARIS – MAXIMUM PRECISION, COMPLETE FLEXIBILITY

The FOCARIS track spotlight combines maximum flexibility with precision lighting technology. Thanks to its continuously adjustable beam angle from 15° to 50° or 60°, the light can be precisely adapted to any application – without the need to change reflectors. The homogeneous light distribution ensures high-quality illumination of retail areas, exhibitions and display objects. Optional honeycomb louvres provide additional glare control. FOCARIS is available in TRI-AC and DALI versions, making it the ideal solution for demanding lighting applications.






CURVED D LINE – NEW FREEDOM FOR CREATIVE LIGHTING CONCEPTS

The CURVED D LINE track opens up entirely new design possibilities for modern lighting concepts. With its 90° bend [radius 1 m], it allows for the creation of semicircles, circles or waves. The 1.57 m-long segments can be used as both D LINE DALI and D LINE standard tracks. A wide range of mounting options ensures maximum flexibility during installation. Never before have there been so many possibilities for designing track lighting systems.





OFFICE SERIES – PROVEN LIGHTING QUALITY, NEW POSSIBILITIES

For years, the OFFICE THREE series has been synonymous with high-quality workplace lighting, offering excellent light quality and a high level of visual comfort. With the new pendant luminaire, the successful product family is expanding to include yet another solution for modern office and working environments. It is complemented by the LINEAR PRO OFFICE – the office version of the tried-and-tested LINEAR PRO track lighting series. Together, both product families offer comprehensive lighting solutions for modern working environments.

Whether for individual workstations, open-plan offices or meeting areas – thanks to their suitability for computer workstations, high colour rendering and eligibility for BEG funding, both the OFFICE THREE series and the LINEAR PRO OFFICE meet the requirements of modern office concepts. From table, floor and pendant luminaires to track lighting, DEKO-LIGHT offers the right solution for every lighting task.





FARO – PREMIUM BOLLARD LIGHTING FOR DEMANDING OUTDOOR AREAS

The FARO bollard luminaire series stands for high-quality outdoor lighting with exceptionally uniform light distribution and excellent glare control. With the new FARO ON/OFF, DEKO-LIGHT complements the existing FARO DALI with a more compact version for a wide range of lighting applications.

Robust materials, seawater-resistant properties and premium workmanship make FARO the ideal solution for pathways, public spaces and demanding outdoor environments.



RF-SMART SPOT – SMARTLY CONTROLLED, PERFECTLY STAGED

The RF-smart ground spike spotlights offer dimmable brightness and colour saturation, as well as 16 million colours and a continuously adjustable colour temperature. 18 pre-installed automatic programmes, together with the ability to synchronise multiple RF-smart components, ensure maximum flexibility. Control is conveniently carried out via RF-smart wireless remote controls [2.4 GHz, range approx. 30 m, not included] or via any Zigbee 3.0-compatible control systems and apps such as Amazon Alexa, Google Assistant or Tuya [corresponding gateway required]. The RF-smart WIDE-SPOT provides even, wide-area illumination, whilst the RF-smart SPOT, with its narrow beam angle, is ideal for precise accent lighting.






COB STRIPS – GREATER EFFICIENCY, PERFECT LINES OF LIGHT

With the new COB Standard and Professional series, DEKO-LIGHT introduces a completely redesigned portfolio for modern linear lighting and architectural illumination. The new series impress with improved efficiency, expanded colour temperature options and attractive variants for a wide range of project requirements.

While the Standard series stands out with high light quality, RGBW technology and an excellent price-performance ratio, the Professional series sets new benchmarks in luminous efficacy, efficiency and light uniformity. Thanks to the dot-free COB technology, both series are ideally suited for demanding lighting concepts and premium lighting applications.

The portfolio is complemented by the proven specialist solutions for sauna and façade applications, which remain available.





INTERIOR LIGHTS

- 24 pendant lights
- 44 surface mounted ceiling lights
- 90 built in ceiling lights
- 132 downlights
- 148 insert panels
- 166 surface mounted wall lights
- 176 built in wall lights
- 184 reading lights
- 194 table and floor lights
- 204 office lights
- 222 hall floodlight
- 232 damp-proof luminaires

pendant lights



   
page 20



   
page 22



 
page 24



 
page 26



 
page 28



 
page 29



 
page 30




page 32



 
page 33



 
page 34



 
page 35



 
page 36





MENKAR

The pendant lights in the MENKAR series impress with clever lighting functions and high-quality aluminium accents. The separate rear light (approx. 15 - 20 % indirect light component) enables permanent indirect lighting. The light colour can be adjusted in 2 stages [3000/4000K] via a CCT switch.






MENKAR

- Indirect and direct lighting
- High light intensity
- Light colour adjustable in two stages
- Can be suspended by up to 1,800/3,000 mm [depending on model]
- Optional diffuser lens for UGR<19

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000/4000 K	Control	Leading-edge dimmer, Trailing-edge dimmer
Rated Input Voltage	220-240 V/AC	CRI (Ra)	80
Height	90 mm	IK Protection Class	IK04
Base Height	30 mm		



342201

Article	Housing Color		Luminous Flux	Power	Ø	Pendulum Length	Base Ø	Price
342201	White	WW NW	3300/3500 lm	45.0 W	400 mm	1800 mm	100 mm	€ 191.95
342202	Black	WW NW	3300/3500 lm	45.0 W	400 mm	1800 mm	100 mm	€ 191.95
342203	Light grey	WW NW	3300/3500 lm	45.0 W	400 mm	1800 mm	100 mm	€ 191.95
342204	Dark brown	WW NW	3300/3500 lm	45.0 W	400 mm	1800 mm	100 mm	€ 191.95
342205	White	WW NW	5600/6000 lm	65.0 W	600 mm	1800 mm	120 mm	€ 319.95
342206	Black	WW NW	5600/6000 lm	65.0 W	600 mm	1800 mm	120 mm	€ 319.95
342207	Light grey	WW NW	5600/6000 lm	65.0 W	600 mm	1800 mm	120 mm	€ 319.95
342208	Dark brown	WW NW	5600/6000 lm	65.0 W	600 mm	1800 mm	120 mm	€ 319.95
342209	White	WW NW	8400/8700 lm	90.0 W	800 mm	3000 mm	150 mm	€ 447.95
342210	Black	WW NW	8400/8700 lm	90.0 W	800 mm	3000 mm	150 mm	€ 447.95
342211	Light grey	WW NW	8400/8700 lm	90.0 W	800 mm	3000 mm	150 mm	€ 447.95
342212	Dark brown	WW NW	8400/8700 lm	90.0 W	800 mm	3000 mm	150 mm	€ 447.95



Accessories for **342201, 342202, 342203, 342204**

930709 Diffusing lenses UGR 19 for Menkar 400 lamp

€ 11.95

Accessories for **342205, 342206, 342207, 342208**

930710 Diffusing lenses UGR 19 for Menkar 600 lamp

€ 19.95

Accessories for **342205, 342206, 342207, 342208, 342209, 342210, 342211, 342212**

843340 DALI, Triac dimmer, 100-240 V, 400 W, IP20

€ 59.95

Accessories for **342209, 342210, 342211, 342212**

930711 Diffusing lenses UGR 19 for Menkar 800 lamp

€ 31.95

Accessories for **342210, 342211, 342212**

843503 RF-smart, Triac dimmer, 230 V, 300 W, IP20

€ 55.95



MEROPE

The pendant lamps of the MEROPE series combine timeless elegance and subdued modernity. Available in the diameters 380, 580 and 780 mm, the light colour [3,000/4,000 K] can be selected before installation using a CCT switch. The exterior finish is brushed aluminium in the colours coffee and silver or matt powder-coated in black and white.






MEROPE

- Light colour adjustable in two stages
- Can be suspended by up to 1,800/3,000 mm [depending on model]

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000/4000 K	Control	Leading-edge dimmer, Trailing-edge dimmer
Rated Input Voltage	220-240 V/AC	CRI (Ra)	80
Height	35 mm	IK Protection Class	IK04
Base Height	65 mm		



342189

Article	Housing Color		Luminous Flux	Power	Ø	Pendulum Length	Base Ø	Price
342189	White	WW NW	2100/2200 lm	30.0 W	380 mm	1800 mm	220 mm	€ 167.95
342190	Black	WW NW	2100/2200 lm	30.0 W	380 mm	1800 mm	220 mm	€ 167.95
342191	Light grey	WW NW	2100/2200 lm	30.0 W	380 mm	1800 mm	220 mm	€ 167.95
342192	Dark brown	WW NW	2100/2200 lm	30.0 W	380 mm	1800 mm	220 mm	€ 167.95
342193	White	WW NW	3100/3200 lm	42.0 W	580 mm	1800 mm	220 mm	€ 223.95
342194	Black	WW NW	3100/3200 lm	42.0 W	580 mm	1800 mm	220 mm	€ 223.95
342195	Light grey	WW NW	3100/3200 lm	42.0 W	580 mm	1800 mm	220 mm	€ 223.95
342196	Dark brown	WW NW	3100/3200 lm	42.0 W	580 mm	1800 mm	220 mm	€ 223.95
342197	White	WW NW	4800/4900 lm	60.0 W	780 mm	3000 mm	275 mm	€ 375.95
342198	Black	WW NW	4800/4900 lm	60.0 W	780 mm	3000 mm	275 mm	€ 375.95
342199	Light grey	WW NW	4800/4900 lm	60.0 W	780 mm	3000 mm	275 mm	€ 375.95
342200	Dark brown	WW NW	4800/4900 lm	60.0 W	780 mm	3000 mm	275 mm	€ 375.95



Accessories

- 843503** RF-smart, Triac dimmer, 230 V, 300 W, IP20
- 843340** DALI, Triac dimmer, 100-240 V, 400 W, IP20





SLIM ROUND

SLIM series lights include single-luminaire and triple-luminaire pendant lamps, recessed ceiling lights and matching pendant lamps for the DEKO-LIGHT current track system. The die-cast aluminium light body is the same size for all variants [300 x 39 mm]. Several SLIM models therefore can also be combined with each other in larger spaces. The pendant lamps for ceiling installation with max. 180 cm suspended mounting are available in a one or three-luminaire variant; three-luminaire variant both with long or round base depending on the arrangement of the lights.

While the fixed SLIM models create a pleasant warm white light in dining rooms, reading nooks and more, the single-luminaire SLIM current track light is ideal for gastronomy and retail projects with changing room layouts. The premium SLIM series is rounded off with the opportunity for customisation using interchangeable reflector rings and lenses.






SLIM ROUND

- Extra-soft fabric cable
- Glare-free, due to low UGR value [<19]
- Slim design at just 39 mm in diameter
- Incl. silver-coloured reflector ring

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Base Height	25 mm
Colour Temperature	2700 K	Power Supply Unit incl.	Yes
Rated Input Voltage	220-240 V/AC	Light Beam Angle	24 Degree
Height	300 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	39 mm	CRI (Ra)	90
Pendulum Length	1800 mm		



342237

Article	Housing Color	Luminous Flux	Power	Base Ø	Price
342237	Black	500 lm	5.0 W	100 mm	€ 67.95
342238	White	500 lm	5.0 W	100 mm	€ 67.95
342241	Black	1500 lm	15.0 W	240 mm	€ 167.95
342242	White	1500 lm	15.0 W	240 mm	€ 167.95



Accessories

930744	Reflector ring white for Slim series		€ 3.95
930745	Reflector ring black for Slim series		€ 3.95
930746	Reflector ring gold-coloured for Slim series		€ 4.75
930747	24° lens for Slim series		€ 3.95
930748	36° lens for Slim series		€ 3.95
930749	60° lens for Slim series		€ 3.95

Accessories for 342237

930914	68 mm Recessed Ceiling Adapter for Pendant Luminaires, black		€ 23.95
---------------	--	--	---------

Accessories for 342238

930913	68 mm Recessed Ceiling Adapter for Pendant Luminaires, white		€ 23.95
---------------	--	--	---------

Accessories for 342241, 342242

843340	DALI, Triac dimmer, 100-240 V, 400 W, IP20		€ 59.95
843503	RF-smart, Triac dimmer, 230 V, 300 W, IP20		€ 55.95



LUCEA CCT

LUCEA series pendant lights with CCT are available in 10, 15 and 20 W versions and offer up to 2,000 lumens of light output. The maximum suspended mounting is 1,800 mm. Optional lenses can be used to narrow or expand the light emission angle of the individual models. LUCEA lights feature a die-cast aluminium housing.



page 60

page 62

page 400

page 404




LUCEA CCT

- Light colour adjustable in two stages
- Incl. black reflector ring

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Trade fair construction / shop fitting

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000/4000 K	Light Beam Angle	36 Degree
Rated Input Voltage	220-240 V/AC	Control	Leading-edge dimmer, Trailing-edge dimmer
Pendulum Length	1800 mm	CRI (Ra)	90
Base Height	29 mm	IK Protection Class	IK03
Base Ø	104,5 mm		



342177

Article	Housing Color		Luminous Flux	Power	Height	Ø	Price
342177	White		930/1000 lm	10.0 W	157 mm	65 mm	€ 111.95
342178	Black		930/1000 lm	10.0 W	157 mm	65 mm	€ 111.95
342181	White		1930/2000 lm	20.0 W	178 mm	85 mm	€ 143.95
342182	Black		1930/2000 lm	20.0 W	178 mm	85 mm	€ 143.95



Accessories for **342177, 342178**

930679	Lens 24° for Lucea 6/10		€ 7.95
930756	Reflector ring for Lucea 6/10 white		€ 3.95
930757	Reflector ring for Lucea 6/10 black		€ 3.95
930758	Reflector ring for Lucea 6/10 gold		€ 3.95

Accessories for **342177, 342181**

930913	68 mm Recessed Ceiling Adapter for Pendant Luminaires, white		€ 23.95
---------------	--	--	----------------

Accessories for **342178, 342182**

930914	68 mm Recessed Ceiling Adapter for Pendant Luminaires, black		€ 23.95
---------------	--	--	----------------

Accessories for **342181, 342182**

930680	Lens 24° for Lucea 15/20		€ 9.95
930681	Lens 60° for Lucea 15/20		€ 9.95
930759	Reflector ring for Lucea 15/20 white		€ 4.75
930760	Reflector ring for Lucea 15/20 black		€ 4.75
930761	Reflector ring for Lucea 15/20 gold		€ 4.75



LUCEA

- Extra-soft fabric cable
- Incl. black reflector ring

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Base Ø	104.5 mm
Colour Temperature	2700 K	Power Supply Unit incl.	Yes
Rated Input Voltage	200-240 V/AC	Light Beam Angle	36 Degree
Height	157 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	65 mm	CRI (Ra)	90
Pendulum Length	1800 mm	IK Protection Class	IK03
Base Height	29 mm		

Article	Housing Color		Luminous Flux	Power	Price
342243		White	800 lm	6.0 W	€ 103.95
342244		Black	800 lm	6.0 W	€ 103.95
342245		White	1300 lm	10.0 W	€ 111.95
342246		Black	1300 lm	10.0 W	€ 111.95



Accessories

930679	Lens 24° for Lucea 6/10		€ 7.95
930756	Reflector ring for Lucea 6/10 white		€ 3.95
930757	Reflector ring for Lucea 6/10 black		€ 3.95
930758	Reflector ring for Lucea 6/10 gold		€ 3.95


Accessories for 342243, 342245

930913	68 mm Recessed Ceiling Adapter for Pendant Luminaires, white		€ 23.95
--------	--	--	---------

Accessories for 342244, 342246

930914	68 mm Recessed Ceiling Adapter for Pendant Luminaires, black		€ 23.95
--------	--	--	---------





LUCEA DTW

- Extra-soft fabric cable
- Dim-to-warm 1,800 K-2,700 K
- Incl. black reflector ring

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium	Pendulum Length	1800 mm
Colour Temperature	1800-2700 K	Power Supply Unit incl.	Yes
Luminous Flux	750 lm	Light Beam Angle	36 Degree
Power	10 W	Control	Leading-edge dimmer, Trailing-edge dimmer
Rated Input Voltage	200-240 V/AC	CRI (Ra)	90
Height	157 mm	IK Protection Class	IK03
Ø	65 mm		

Article	Housing Color		Price
342247	White		€ 119.95
342248	Black		€ 119.95



Accessories

930756	Reflector ring for Lucea 6/10 white		€ 3.95
930757	Reflector ring for Lucea 6/10 black		€ 3.95
930758	Reflector ring for Lucea 6/10 gold		€ 3.95

Accessories for 342247

930913	68 mm Recessed Ceiling Adapter for Pendant Luminaires, white		€ 23.95
---------------	--	--	---------

Accessories for 342248

930914	68 mm Recessed Ceiling Adapter for Pendant Luminaires, black		€ 23.95
---------------	--	--	---------



page 60



page 62



page 400



page 404



CAN

The CAN pendant light in lengths 150 mm and 350 mm combines modern design with practical functionality. The GU10 base enables quick and simple replacement of the lamp. The screw-on cylinder enables tool-free maintenance and optional decorative rings allow colourful accents to be created. The pendant light is part of the CAN series, which also contains ceiling, wall, reading and outdoor lights and therefore provides versatile application options for private and commercial spaces.



page 68




page 70



page 167



page 168



CAN

- Flat and discreet lamp base
- Can be customised with a wide range of accessories
- Replaceable lamp to offer an individual lighting solution
- Can be combined with the comprehensive CAN series product family

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Max. Power	1x max. 7.5 W
Ø	60 mm	Rated Input Voltage	220-240 V/AC
Pendulum Length	1700 mm	Control	Dimmable via optional light source
Base Height	27 mm		
Base Ø	60 mm		

Article	Housing Color	Height	Price
342254	White	150 mm	€ 51.95
342255	Black	150 mm	€ 51.95
342256	White	350 mm	€ 59.95
342257	Black	350 mm	€ 59.95



Accessories

930301	Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930302	Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930303	Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930366	Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
931065	Acrylic attachment for Can		€ 3.95

Accessories for **342254, 342256**

930913	68 mm Recessed Ceiling Adapter for Pendant Luminaires, white		€ 23.95
---------------	--	--	----------------

Accessories for **342255, 342257**


930914	68 mm Recessed Ceiling Adapter for Pendant Luminaires, black		€ 23.95
---------------	--	--	----------------



LAMP SOCKET SEGULA DESIGN BULBS

The pendant lights are fitted with textile cables. This generous cable length enables flexible installation even in high rooms and allows individual height adjustment depending on the installation situation. The housing is characterised by a reduced, clear design language and is therefore ideal for modern architectural and lighting concepts in interiors. The E27 sockets used are deliberately oversized. The enlarged sleeve creates a visually harmonious unit between the socket and light source - without visible transitions or technical breaks. Compatible with our DESIGN-BULB light sources, this pendant luminaire is particularly suitable for project-oriented applications in the interior design, shop fitting or catering sectors. It provides an ideal basis for decorative lighting solutions with design requirements.






LAMP SOCKET SEGULA DESIGN BULBS

- Sliding E27 socket sleeve(s) for adapting to lamps with special dimensions
- Ideal for use in conjunction with our designer bulb series
- Soft textile cable
- High-quality surface finish

Housing	Metal, Plastic	Rated Input Voltage	220-240 V/AC
Height	80 mm	Connection Type	Connectionbox IP20
Ø	50 mm		

Article	Housing Color	Max. Power	Base Length	Base Width	Base Height	Base Ø	Price
930908	Black	1x max. 60.0 W			20 mm	100 mm	€ 47.95
930909	Black	1x max. 60.0 W			20 mm	100 mm	€ 55.95
930965	Black	3x max. 57.0 W			25 mm	125 mm	€ 155.95
930966	Black	3x max. 57.0 W	990 mm	150 mm	25 mm		€ 263.95



DEKO-LIGHT LED DESIGN-BULB ORBIT E27 DIMMABLE

- Glass body is manufactured by hand
- Filigree lamp
- Reflections create the impression of floating light
- Patented soft filament technology
- Suitable for decorative and creative lights with and without lampshade
- Ideal for use in combination with our sockets with sliding socket sleeve

Housing	Glass	Rated Input Voltage	220-240 V/AC
Light Beam Angle	330 Degree	Life Time	20000 h
Height	120 mm	Control	Trailing-edge dimmer
Ø	220 mm	Channels	1

Article	Housing Color	Colour Temperature	Luminous Flux	Power	Power Consumption	CRI (Ra)	EEI	Price
180731	Smoky	1900 K	185 lm	4.5 W	5 kWh/1000h	85		€ 109.95
180730	Gold	2200 K	240 lm	4.0 W	4 kWh/1000h	90		€ 109.95





DEKO-LIGHT LED DESIGN BULB SHINE E27 DIMMABLE

Let our new designer light series ORBIT, SHINE and MOON take you into the world of style. The sophisticated luminous elements and the reflections generated in the glass create the impression of floating light. Whether light and airy in your living room at home or opulent and spacious in the hotel lobby - the dimmable LED lamps from the designer bulb series are perfect for open lights without shades or lampholders with E27 sockets and are a real eye-catcher wherever they are used.






DEKO-LIGHT LED DESIGN BULB SHINE E27 DIMMABLE

- Glass body is manufactured by hand
- Filigree lamp
- Reflections create the impression of floating light
- Patented soft filament technology
- Suitable for decorative and creative lights with and without lampshade
- Ideal for use in combination with our sockets with sliding socket sleeve

Housing	Glass	Rated Input Voltage	220-240 V/AC
Light Beam Angle	330 Degree	Life Time	20000 h
Height	190 mm	Control	Trailing-edge dimmer
Ø	200 mm	Channels	1
Power Consumption	5 kWh/1000h		


Article	Housing Color	Colour Temperature	Luminous Flux	Power	CRI (Ra)	EEI	Price
180733	Smoky	1900 K	210 lm	5.0 W	85		€ 93.95
180732	Gold	2200 K	300 lm	4.5 W	90		€ 93.95



DEKO-LIGHT LED DESIGN BULB MOON E27 DIMMABLE

Housing	Glass	Control	Trailing-edge dimmer
Light Beam Angle	330 Degree	Channels	1
Rated Input Voltage	220-240 V/AC		

Article	Housing Color	Colour Temperature	Luminous Flux	Power	Height	Ø	EEI	Price
180734	Smoky	1900 K	220 lm	6.0 W	165 mm	125 mm		€ 56.95
180735	Smoky	1900 K	260 lm	6.0 W	185 mm	150 mm		€ 64.95
180736	Smoky	1900 K	300 lm	6.0 W	230 mm	200 mm		€ 89.95
180737	Smoky	1900 K	350 lm	8.0 W	320 mm	300 mm		€ 199.95
180741	Black	2200 K	240 lm	4.0 W	165 mm	125 mm		€ 71.95
180742	Black	2200 K	240 lm	4.0 W	200 mm	150 mm		€ 91.95
180743	Black	2200 K	240 lm	4.0 W	230 mm	200 mm		€ 119.95





68 MM CEILING MOUNT ADAPTER FOR PENDANT LAMPS

The recessed ceiling adapter is the ideal solution for discreetly and securely installing pendant lights weighing up to 2.5 kg. Thanks to the integrated three-pin connection box with strain relief and feed-through wiring, the adapter can be connected to the power supply quickly and reliably. Suitable for cable diameters of 5-7 mm and ceiling thicknesses of 2-15 mm, the adapter ensures that the light is seamlessly integrated into the ceiling. The result: A simple, high-quality look that discreetly conceals all electrical components and meets the highest aesthetic demands.





68 MM CEILING MOUNT ADAPTER FOR PENDANT LAMPS

- Secure installation of pendant lamps in 68 mm ceiling recesses
- Includes three-pin connection box with strain relief and feed-through wiring
- Suitable for cable diameters of 5-7 mm
- Suitable for ceiling thicknesses of 2-15 mm

Housing	Polycarbonate, Steel	Installation Depth	27 mm
Height	32 mm	Cut Out Ø	65-75 mm
Ø	90 mm		

Article	Housing Color	Price
930913	☐ White	€ 23.95
930914	☒ Black	€ 23.95



Lighting design

Interested in our lighting design service?

Your contact person will be happy to answer any questions you may have.

surface mounted ceiling lights



page 40



page 42



page 44



page 46



page 48



page 50



page 51



page 54



page 55



page 56



page 57



page 58



☐ ☒
page 59



☐ ☒
page 60



☐ ☒
page 62



☐ ☒
page 64



☐ ☒
page 64



☐ ☒
page 66



☐ ☒
page 67



☐ ☒
page 68



☐ ☒
page 69



☐ ☒
page 70



☐ ☒
page 72



☐ ☒
page 76



☐ ☒
page 76



☐ ☒ ☐
page 78



☐ ☒ ☐
page 79



☐
page 80



☐
page 83



MENKAR

MENKAR series ceiling and wall lights feature clever lighting functions and high-quality aluminium accents. The rear light (approx. 15-20 % indirect light) also allows additional indirect lighting.





MENKAR


- Direct and indirect lighting (light proportion approx. 15-20 %)
- Light colour adjustable in two steps
- Optional diffuser lens for UGR<19
- Can be used as a wall or ceiling light (depending on model)



Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium, Polycarbonate, Steel	Power Supply Unit incl. Control	Yes Leading-edge dimmer, Trailing-edge dimmer
Colour Temperature	3000/4000 K	CRI (Ra)	80
Height	90 mm	IK Protection Class	IK04
Rated Input Voltage	220-240 V/AC		



348198

Article	Housing Color	Luminous Flux	Surface	Ø	Power	Price
348200	Light grey	3300/3500 lm	Brushed	400 mm	45.0 W	€ 175.95
348201	Dark brown	3300/3500 lm	Brushed	400 mm	45.0 W	€ 175.95
348198	White	3300/3500 lm	Matt	400 mm	45.0 W	€ 175.95
348199	Black	3300/3500 lm	Matt	400 mm	45.0 W	€ 175.95
348204	Light grey	5600/6000 lm	Brushed	600 mm	65.0 W	€ 303.95
348205	Dark brown	5600/6000 lm	Brushed	600 mm	65.0 W	€ 303.95
348202	White	5600/6000 lm	Matt	600 mm	65.0 W	€ 303.95
348203	Black	5600/6000 lm	Matt	600 mm	65.0 W	€ 303.95
348208	Light grey	8400/8700 lm	Brushed	800 mm	90.0 W	€ 431.95
348209	Dark brown	8400/8700 lm	Brushed	800 mm	90.0 W	€ 431.95
348206	White	8400/8700 lm	Matt	800 mm	90.0 W	€ 431.95
348207	Black	8400/8700 lm	Matt	800 mm	90.0 W	€ 431.95



Accessories for **348198, 348199, 348200, 348201**

930709 Diffusing lenses UGR 19 for Menkar 400 lamp

€ 11.95

Accessories for **348202, 348203, 348204, 348205**

930710 Diffusing lenses UGR 19 for Menkar 600 lamp

€ 19.95

Accessories for **348206, 348207, 348208, 348209**

930711 Diffusing lenses UGR 19 for Menkar 800 lamp

€ 31.95

Accessories

843503 RF-smart, Triac dimmer, 230 V, 300 W, IP20

€ 55.95

843340 DALI, Triac dimmer, 100-240 V, 400 W, IP20

€ 59.95



MEROPE

The timeless MEROPE demonstrates not only impressively high luminous flux and a low assembly height, it is also highly visually appealing thanks to its elegant outer aluminium ring – available in sand-blasted white or black, brushed in silver or on-trend coffee. Available in the diameters 380 mm, 580 mm and 780 mm, the MEROPE can be integrated into very different environments even more flexibly.

In addition, the light colour can be adjusted in 2 stages, 3,000 K or 4,000 K.





MEROPE


- High luminous flux
- Light colour adjustable in 2 stages
- Low assembly height

Application Area

Home / Living

Housing	Aluminium
Colour Temperature	3000/4000 K
Height	60 mm
Rated Input Voltage	220-240 V/AC
Power Supply Unit incl.	Yes

Control	Leading-edge dimmer, Trailing-edge dimmer
CRI (Ra)	80
IK Protection Class	IK04



348186


Article	Housing Color	Luminous Flux	Surface	Ø	Power	Price
348188	Light grey	2100/2200 lm	Brushed	380 mm	30.0 W	€ 151.95
348189	Dark brown	2100/2200 lm	Brushed	380 mm	30.0 W	€ 151.95
348186	White	2100/2200 lm	Matt	380 mm	30.0 W	€ 151.95
348187	Black	2100/2200 lm	Matt	380 mm	30.0 W	€ 151.95
348192	Light grey	3100/3200 lm	Brushed	580 mm	42.0 W	€ 219.95
348193	Dark brown	3100/3200 lm	Brushed	580 mm	42.0 W	€ 219.95
348190	White	3100/3200 lm	Matt	580 mm	42.0 W	€ 219.95
348191	Black	3100/3200 lm	Matt	580 mm	42.0 W	€ 219.95
348196	Light grey	4800/4900 lm	Brushed	780 mm	60.0 W	€ 359.95
348197	Dark brown	4800/4900 lm	Brushed	780 mm	60.0 W	€ 359.95
348194	White	4800/4900 lm	Matt	780 mm	60.0 W	€ 359.95
348195	Black	4800/4900 lm	Matt	780 mm	60.0 W	€ 359.95



Accessories

843503	RF-smart, Triac dimmer, 230 V, 300 W, IP20
843340	DALI, Triac dimmer, 100-240 V, 400 W, IP20

	€ 55.95
	€ 59.95



SCULPTORIS

Modern elegance for ceilings; the ceiling lights from the SCULPTORIS series can be used in a number of ways indoors thanks to different outputs, sizes and colour temperatures. The surface-mounted ceiling lights provide extensive illumination for rooms and also look great as wall lights.

The light is softly and extensively diffused through the large, circumferential diffuser with matt aluminium design and illuminates rooms pleasantly and evenly.

The light colours warm white (3,000 K) or neutral white (4,000 K) can be set for each variant.






SCULPTORIS

- Light colour adjustable in 2 stages
- Uniform illumination
- Circumferential diffuser

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Light Beam Angle	150 Degree
Colour Temperature	3000/4000 K	Control	Leading-edge dimmer, Trailing-edge dimmer
Surface	Matt	CRI (Ra)	80
Rated Input Voltage	220-240 V/AC	IK Protection Class	IK04
Power Supply Unit incl.	Yes		



Article	Housing Color		Luminous Flux	Height	Ø	Power	Price
348180	White		2000/2100 lm	100 mm	400 mm	30.0 W	€ 215.95
348181	Black		2000/2100 lm	100 mm	400 mm	30.0 W	€ 215.95
348182	White		3000/3100 lm	130 mm	600 mm	42.0 W	€ 279.95
348183	Black		3000/3100 lm	130 mm	600 mm	42.0 W	€ 279.95



Accessories

843503	RF-smart, Triac dimmer, 230 V, 300 W, IP20		€ 55.95
843340	DALI, Triac dimmer, 100-240 V, 400 W, IP20		€ 59.95




Technical data sheet

New in the onlineshop: The technical data sheets offer even more information: Light and energy data, light distribution curves, dimensional drawings and more.



ZANIAH

Whilst flat surfaces and covers are the go-to for most surface-mounted ceiling lights, the ZANIAH places special emphasis on its 360° lamp [either a 12 W, 18 W or 24 W variant]. Replaceable covers allow the visual appearance of ZANIAH to be changed even after installation. The covers are available in eight colour variants, allowing plenty of scope for customisation.





ZANIAH


- Can be customised using coloured covers
- 360° light emission angle
- Can be used as a wall or ceiling light

Application Area

Reception / Communication, Corridor / stairwell, Home / Living, Hotel / catering

Housing	Aluminium	Control	Leading-edge dimmer, Trailing-edge dimmer
Colour Temperature	3000 K	CRI (Ra)	80
Rated Input Voltage	220-240 V/AC	IK Protection Class	IK05
Power Supply Unit incl.	Yes		
Light Beam Angle	120 Degree		

Article	Housing Color		Luminous Flux	Height	Ø	Power	EEI	Price
620033	Light grey		1510 lm	42 mm	290 mm	12.0 W		€ 79.95
620034	Blue		1510 lm	42 mm	290 mm	12.0 W		€ 79.95
620035	Green		1510 lm	42 mm	290 mm	12.0 W		€ 79.95
620036	Red		1510 lm	42 mm	290 mm	12.0 W		€ 79.95
620037	Yellow		1510 lm	42 mm	290 mm	12.0 W		€ 79.95
620038	Dark grey		1510 lm	42 mm	290 mm	12.0 W		€ 79.95
620039	Black		1510 lm	42 mm	290 mm	12.0 W		€ 79.95
620040	White		1510 lm	42 mm	290 mm	12.0 W		€ 79.95
620041	Light grey		2020 lm	46 mm	370 mm	18.0 W		€ 87.95
620042	Blue		2020 lm	46 mm	370 mm	18.0 W		€ 87.95
620043	Green		2020 lm	46 mm	370 mm	18.0 W		€ 87.95
620044	Red		2020 lm	46 mm	370 mm	18.0 W		€ 87.95
620045	Yellow		2020 lm	46 mm	370 mm	18.0 W		€ 87.95
620046	Dark grey		2020 lm	46 mm	370 mm	18.0 W		€ 87.95
620047	Black		2020 lm	46 mm	370 mm	18.0 W		€ 87.95
620048	White		2020 lm	46 mm	370 mm	18.0 W		€ 87.95
620049	Light grey		2565 lm	46 mm	420 mm	24.0 W		€ 95.95
620050	Blue		2565 lm	46 mm	420 mm	24.0 W		€ 95.95
620051	Green		2565 lm	46 mm	420 mm	24.0 W		€ 95.95
620052	Red		2565 lm	46 mm	420 mm	24.0 W		€ 95.95
620053	Yellow		2565 lm	46 mm	420 mm	24.0 W		€ 95.95
620054	Dark grey		2565 lm	46 mm	420 mm	24.0 W		€ 95.95
620055	Black		2565 lm	46 mm	420 mm	24.0 W		€ 95.95
620056	White		2565 lm	46 mm	420 mm	24.0 W		€ 95.95





ALTAIS 2 ROUND

The ALTAIS 2 Round is a modern ceiling and wall luminaire that is ideal for lighting solutions in commercial, public and private areas. Its clear, round design blends into a wide variety of architectural settings - from technical rooms, corridors and stairwells to modern residential and commercial areas. Thanks to the integrated CCT switch, the light colour can be adjusted in three stages (2700K / 3000K / 4000K). The output can also be adjusted in two stages to optimise energy efficiency and luminous efficacy depending on the room requirements. With through-wiring and surface-mounted cable entries, the installation options are very flexible. Installation is convenient thanks to a practical and time-saving click system.

As an eligible product in accordance with the requirements of the Federal Subsidy for Efficient Buildings (BEG), the ALTAIS 2 Round also contributes to energy-efficient refurbishment - a plus point for sustainable projects.






ALTAIS 2 ROUND

- Light colour adjustable in 3 stages
- Power adjustable in 2 steps
- through-wiring possible
- Easy installation thanks to click system
- Optional surface-mounted cable entry
- BEG eligible

Application Area

Bathroom / WC, Corridor / stairwell, Wellness / Spa / Gym, Workshop / Craft / Warehouse, Home / Living, Retrofit / Refurbishment

Housing	Polycarbonate	Rated Input Voltage	100-240 V/AC
Colour Temperature	2700/3000/4000 K	Light Beam Angle	120 Degree
Height	52 mm	CRI (Ra)	85
Base Height	20.5 mm	IK Protection Class	IK10



348276

Article	Housing Color		Luminous Flux	Ø	Base Ø	Power Selectable	Price
348276	☐ White	☐ WW ☐ NW	1725/1800/1800 lm	220 mm	180 mm	10.0 W / 15.0 W	€ 55.95
348277	☐ White	☐ WW ☐ NW	2070/2160/2160 lm	280 mm	240 mm	13.0 W / 18.0 W	€ 67.95
348278	☐ White	☐ WW ☐ NW	2875/3000/3000 lm	330 mm	280 mm	18.0 W / 25.0 W	€ 79.95



Onlineshop

You can find more information about the products in the onlineshop:
Detailed images, videos, project reports, LDT files, EPREL data sheets and more.



ALTAIS 2 ROUND MOTION


- Light colour adjustable in 3 stages
- Power adjustable in 2 levels
- Adjustable motion detector with corridor function
- through-wiring possible
- Easy installation thanks to click system
- Optional surface-mounted cable entry
- BEG eligible



Application Area

Bathroom / WC, Corridor / stairwell, Wellness / Spa / Gym, Workshop / Craft / Warehouse, Home / Living, Retrofit / Refurbishment

Housing	Polycarbonate	Light Beam Angle	120 Degree
Colour Temperature	2700/3000/4000 K	CRI (Ra)	85
Height	52 mm	Motion Detector	Yes
Base Height	20.5 mm	IK Protection Class	IK10
Rated Input Voltage	100-240 V/AC		



348279

Article	Housing Color		Luminous Flux	Ø	Base Ø	Power Selectable	Price
348279	☐ White		1725/1800/1800 lm	220 mm	180 mm	10.0 W / 15.0 W	€ 79.95
348280	☐ White		2070/2160/2160 lm	280 mm	240 mm	13.0 W / 18.0 W	€ 91.95
348281	☐ White		2875/3000/3000 lm	330 mm	280 mm	18.0 W / 25.0 W	€ 103.95



Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.




ALTAIS 2 ROUND MOTION MS

- Light colour adjustable in 3 stages
- Power adjustable in 2 levels
- Adjustable motion detector with corridor function
- Multi-master-slave configuration with up to 8 groups
- through-wiring possible
- Easy installation thanks to click system
- Optional surface-mounted cable entry
- BEG eligible


Application Area

Bathroom / WC, Corridor / stairwell, Wellness / Spa / Gym, Workshop / Craft / Warehouse, Home / Living, Retrofit / Refurbishment

Housing	Polycarbonate	Light Beam Angle	120 Degree
Colour Temperature	2700/3000/4000 K	CRI (Ra)	85
Height	52 mm	Motion Detector	Yes
Base Height	20.5 mm	IK Protection Class	IK10
Rated Input Voltage	100-240 V/AC		



Article	Housing Color		Luminous Flux	Ø	Base Ø	Power Selectable	Price
348285	☐ White	☐ WW ☐ NW	2070/2160/2160 lm	280 mm	240 mm	13.0 W / 18.0 W	€ 107.95
348286	☐ White	☐ WW ☐ NW	2875/3000/3000 lm	330 mm	280 mm	18.0 W / 25.0 W	€ 119.95



Accessories

931075 Remote control for Altais 2 Motion MS



€ 19.95



5-year guarantee
Benefit from the maximum quality promise:
All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.

UNI II

The UNI II series comprises high-quality surface-mounted luminaires and track-mounted spotlights for use on walls and ceilings in commercial and private premises.

The rotating and swivelling luminaire heads of the UNI II series – available in white and black aluminium housing versions – are equipped with warm white COB LEDs and can be folded flush onto the base if required to shine vertically downwards like a ceiling spotlight. In addition to the single, double and triple versions, both a MINI version [with smaller luminaire head and base] and a MAX version are available.

THE SERIES AT A GLANCE



UNI II

The standard version [TILT] with 3,000 K is also available with two [DOUBLE] and three [TRIPLE] luminaire heads on a base and as a wall-mounted version.



UNI II MINI

The MINI version [optionally 2,700 K or 3,000 K] is available with one [MINI II TILT] or two [MINI II DOUBLE] luminaire heads and is suitable for particularly discreet use in small rooms.



UNI II MAX

THE MAX version [3,000 K] with its 2,410 lumens also makes a big impression on its own.



UNI II TRACK SPOT

Whether private [1-phase] or commercial [3-phase]: As a track spotlight, the UNI II can be aligned even more flexibly in the room. Available as a standard version [UNI II TILT] and as a MINI version [MINI II TILT].



UNI II RECESSED LIGHT

The rotatable and swivelling luminaire head of the UNI II recessed luminaire [also available as a MINI and MAX version] can be folded flush onto the base if required in order to shine vertically downwards like a ceiling spotlight.

VERSATILE ACCESSORIES

THE UNI II series offers numerous options to further individualise the light and appearance of the luminaires:






UNI 2

- „Glow“ effect on reflector ring
- Can be rotated and swivelled
- Can be customised with a comprehensive range of accessories

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000 K	Light Beam Angle	36 Degree
Height	103 mm	Rotation Angle	350 Degree
Ø	100 mm	Swivelling Angle	90 Degree
Power	12 W	Control	Leading-edge dimmer, Trailing-edge dimmer
Base Height	14.5 mm	CRI (Ra)	90
Base Ø	96 mm		
Rated Input Voltage	220-240 V/AC		



Article	Housing Color	Luminous Flux	Price
348179	Black	780 lm	€ 115.95
348124	White	835 lm	€ 115.95



Accessories

930305	36° reflector for Klara/Nihal Mini/Uni II series		€ 2.95
930306	48° reflector for Klara/Nihal Mini/Uni II series		€ 6.95
930307	Honeycomb filter for Klara/Nihal Mini/Uni II series		€ 6.95
930308	Spread lens for Klara/Nihal Mini/Uni II series		€ 6.95
930309	Softening lens for Klara/Nihal Mini/Uni II series		€ 6.95
930310	Linear spread lens for Klara/Nihal Mini/Uni II series		€ 6.95
930334	Rear white cover for Uni II series		€ 2.95
930335	Rear black cover for Uni II series		€ 2.45
930336	White heat sink cover for Uni II series		€ 2.95
930337	Black heat sink cover for Uni II series		€ 6.45
930338	Reflector ring white for Uni II series		€ 9.95
930339	Reflector ring black for Uni II series		€ 8.95
930340	Reflector ring gold for Uni II series		€ 8.95
930341	Reflector ring chrome for Uni II series		€ 8.95






UNI 2 DOUBLE

- „Glow“ effect on reflector ring
- Can be rotated and swivelled
- Can be customised with a comprehensive range of accessories

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Colour Temperature	3000 K	Power Supply Unit incl.	Yes
Length	212 mm	Light Beam Angle	36 Degree
Width	100 mm	Rotation Angle	350 Degree
Height	103 mm	Swivelling Angle	90 Degree
Power	20 W	Control	Leading-edge dimmer, Trailing-edge dimmer
Base Length	212 mm	CRI (Ra)	90
Base Width	20 mm		
Base Height	14 mm		



348125

Article	Housing Color	Luminous Flux	Price
348175	Black	1440 lm	€ 207.95
348125	White	1730 lm	€ 207.95



Accessories

930305	36° reflector for Klara/Nihal Mini/Uni II series		€ 2.95
930306	48° reflector for Klara/Nihal Mini/Uni II series		€ 6.95
930307	Honeycomb filter for Klara/Nihal Mini/Uni II series		€ 6.95
930308	Spread lens for Klara/Nihal Mini/Uni II series		€ 6.95
930309	Softening lens for Klara/Nihal Mini/Uni II series		€ 6.95
930310	Linear spread lens for Klara/Nihal Mini/Uni II series		€ 6.95
930334	Rear white cover for Uni II series		€ 2.95
930335	Rear black cover for Uni II series		€ 2.45
930336	White heat sink cover for Uni II series		€ 2.95
930337	Black heat sink cover for Uni II series		€ 6.45
930338	Reflector ring white for Uni II series		€ 9.95
930339	Reflector ring black for Uni II series		€ 8.95
930340	Reflector ring gold for Uni II series		€ 8.95
930341	Reflector ring chrome for Uni II series		€ 8.95






UNI 2 TRIPLE

- „Glow“ effect on reflector ring
- Can be rotated and swivelled
- Can be customised with a comprehensive range of accessories

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Base Height	14.5 mm
Colour Temperature	3000 K	Rated Input Voltage	220-240 V/AC
Length	324 mm	Power Supply Unit incl.	Yes
Width	100 mm	Light Beam Angle	36 Degree
Height	103 mm	Rotation Angle	350 Degree
Ø	100 mm	Swivelling Angle	90 Degree
Power	30 W	Control	Leading-edge dimmer, Trailing-edge dimmer
Base Length	315 mm	CRI (Ra)	90
Base Width	25 mm		



348107

Article	Housing Color	Luminous Flux	Price
348210	Black	2150 lm	€ 295.95
348107	White	2420 lm	€ 295.95



Accessories

930305	36° reflector for Klara/Nihal Mini/Uni II series		€ 2.95
930306	48° reflector for Klara/Nihal Mini/Uni II series		€ 6.95
930307	Honeycomb filter for Klara/Nihal Mini/Uni II series		€ 6.95
930308	Spread lens for Klara/Nihal Mini/Uni II series		€ 6.95
930309	Softening lens for Klara/Nihal Mini/Uni II series		€ 6.95
930310	Linear spread lens for Klara/Nihal Mini/Uni II series		€ 6.95
930334	Rear white cover for Uni II series		€ 2.95
930335	Rear black cover for Uni II series		€ 2.45
930336	White heat sink cover for Uni II series		€ 2.95
930337	Black heat sink cover for Uni II series		€ 6.45
930338	Reflector ring white for Uni II series		€ 9.95
930339	Reflector ring black for Uni II series		€ 8.95
930340	Reflector ring gold for Uni II series		€ 8.95
930341	Reflector ring chrome for Uni II series		€ 8.95






UNI 2 MINI

- „Glow“ effect on reflector ring
- Can be rotated and swivelled
- Can be customised with a comprehensive range of accessories

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Light Beam Angle	36 Degree
Height	75 mm	Rotation Angle	350 Degree
Ø	91 mm	Swivelling Angle	90 Degree
Base Height	44 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Base Ø	75 mm	CRI (Ra)	90
Rated Input Voltage	220-240 V/AC		
Power Supply Unit incl.	Yes		



348122

Article	Housing Color	Colour Temperature	Luminous Flux	Power	EEL	Price
348234	Black	2700 K	700 lm	11.3 W		€ 103.95
348233	White	2700 K	730 lm	11.3 W		€ 103.95
348178	Black	3000 K	540 lm	8.0 W		€ 95.95
348122	White	3000 K	630 lm	8.0 W		€ 95.95



Accessories

930327	Rear black cover for Uni II Mini series		€ 2.95
930328	White heat sink cover for Uni II Mini series		€ 2.95
930329	Black heat sink cover for Uni II Mini series		€ 2.45
930330	Reflector ring white for Uni II Mini series		€ 8.95
930331	Reflector ring black for Uni II Mini series		€ 8.95
930332	Reflector ring gold for Uni II Mini series		€ 8.95
930333	Reflector ring chrome for Uni II Mini series		€ 8.95
930770	Reflector 24° for Uni II Mini series		€ 8.95
930771	Reflector 48° for Uni II Mini series		€ 8.95



Technical data sheet

New in the onlineshop: The technical data sheets offer even more information: Light and energy data, light distribution curves, dimensional drawings and more.




UNI 2 MINI DOUBLE

- „Glow“ effect on reflector ring
- Can be rotated and swivelled
- Can be customised with a comprehensive range of accessories

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Length	160 mm	Light Beam Angle	36 Degree
Width	75 mm	Rotation Angle	350 Degree
Height	91 mm	Swivelling Angle	90 Degree
Base Length	160 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Base Width	75 mm	CRI (Ra)	90
Base Height	44 mm		
Rated Input Voltage	220-240 V/AC		



348123

Article	Housing Color	Colour Temperature	Luminous Flux	Power	EEL	Price
348236	Black	2700 K	1300 lm	21.0 W		€ 167.95
348235	White	2700 K	1400 lm	21.0 W		€ 167.95
348177	Black	3000 K	1020 lm	15.0 W		€ 159.95
348123	White	3000 K	1210 lm	15.0 W		€ 159.95



Accessories

930327	Rear black cover for Uni II Mini series		€ 2.95
930328	White heat sink cover for Uni II Mini series		€ 2.95
930329	Black heat sink cover for Uni II Mini series		€ 2.45
930330	Reflector ring white for Uni II Mini series		€ 8.95
930331	Reflector ring black for Uni II Mini series		€ 8.95
930332	Reflector ring gold for Uni II Mini series		€ 8.95
930333	Reflector ring chrome for Uni II Mini series		€ 8.95
930770	Reflector 24° for Uni II Mini series		€ 8.95
930771	Reflector 48° for Uni II Mini series		€ 8.95




UNI 2 MAX

- „Glow“ effect on reflector ring
- Can be rotated and swivelled
- Can be customised with a comprehensive range of accessories

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000 K	Light Beam Angle	36 Degree
Height	128 mm	Rotation Angle	350 Degree
Ø	125 mm	Swivelling Angle	90 Degree
Power	32 W	Control	Leading-edge dimmer, Trailing-edge dimmer
Base Height	62 mm	CRI (Ra)	90
Base Ø	125 mm		
Rated Input Voltage	220-240 V/AC		



348127

Article	Housing Color	Luminous Flux	Price
348176	Black	2730 lm	€ 199.95
348127	White	2830 lm	€ 199.95



Accessories

930390	24° reflector for Uni II Max		€ 8.95
930391	36° reflector for Uni II Max		€ 9.95
930392	48° reflector for Uni II Max		€ 8.95
930393	Rear white cover for Uni II Max series		€ 8.95
930394	Rear black cover for Uni II Max series		€ 8.95
930395	White heat sink cover for Uni II Max series		€ 8.95
930396	Black heat sink cover for Uni II Max series		€ 8.95
930397	Reflector ring white for Uni II Max series		€ 9.95
930398	Reflector ring black for Uni II Max series		€ 8.95
930399	Reflector ring gold for Uni II Max series		€ 11.95






LUCEA CCT

- Incl. black reflector ring
- Comprehensive range of accessories for customisation
- Light colour adjustable in two steps



Application Area
 Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Trade fair construction / shop fitting

Housing	Aluminium	Control	Leading-edge dimmer, Trailing-edge dimmer
Colour Temperature	3000/4000 K	CRI (Ra)	90
Rated Input Voltage	220-240 V/AC	IK Protection Class	IK03
Power Supply Unit incl.	Yes		
Light Beam Angle	36 Degree		



348153

Article	Housing Color		Luminous Flux	Height	Ø	Power	Price
348153	White		930/1000 lm	157 mm	65 mm	10.0 W	€ 95.95
348154	Black		930/1000 lm	157 mm	65 mm	10.0 W	€ 95.95
348155	White		1460/1500 lm	178 mm	85 mm	15.0 W	€ 111.95
348156	Black		1460/1500 lm	178 mm	85 mm	15.0 W	€ 111.95
348157	White		1930/2000 lm	178 mm	85 mm	20.0 W	€ 127.95
348158	Black		1930/2000 lm	178 mm	85 mm	20.0 W	€ 127.95
348159	White		2700/2900 lm	211 mm	100 mm	30.0 W	€ 143.95
348160	Black		2700/2900 lm	211 mm	100 mm	30.0 W	€ 143.95



Accessories for 348153, 348154

930679	Lens 24° for Lucea 6/10		€ 7.95
930756	Reflector ring for Lucea 6/10 white		€ 3.95
930757	Reflector ring for Lucea 6/10 black		€ 3.95
930758	Reflector ring for Lucea 6/10 gold		€ 3.95

Accessories for 348155, 348156, 348157, 348158

930680	Lens 24° for Lucea 15/20		€ 9.95
930681	Lens 60° for Lucea 15/20		€ 9.95
930759	Reflector ring for Lucea 15/20 white		€ 4.75
930760	Reflector ring for Lucea 15/20 black		€ 4.75
930761	Reflector ring for Lucea 15/20 gold		€ 4.75

Accessories for 348159, 348160

930682	Lens 24° for Lucea 30		€ 12.95
930684	Lens 60° for Lucea 30		€ 12.95
930762	Reflector ring for Lucea 30/40 white		€ 5.45
930763	Reflector ring for Lucea 30/40 black		€ 5.45
930764	Reflector ring for Lucea 30/40 gold		€ 5.45






LUCEA TILT CCT

- Incl. black reflector ring
- Comprehensive range of accessories for customisation
- Light colour adjustable in two steps

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Swivelling Angle	90 Degree
Colour Temperature	3000/4000 K	Control	Leading-edge dimmer, Trailing-edge dimmer
Rated Input Voltage	220-240 V/AC	CRI (Ra)	90
Power Supply Unit incl.	Yes	IK Protection Class	IK03
Light Beam Angle	36 Degree		
Rotation Angle	350 Degree		



348161

Article	Housing Color		Luminous Flux	Height	Ø	Power	Price
348161	White	WW NW	930/1000 lm	218 mm	65 mm	10.0 W	€ 103.95
348162	Black	WW NW	930/1000 lm	218 mm	65 mm	10.0 W	€ 103.95
348163	White	WW NW	1460/1500 lm	241 mm	85 mm	15.0 W	€ 119.95
348164	Black	WW NW	1460/1500 lm	241 mm	85 mm	15.0 W	€ 119.95
348165	White	WW NW	1930/2000 lm	241 mm	85 mm	20.0 W	€ 135.95
348166	Black	WW NW	1930/2000 lm	241 mm	85 mm	20.0 W	€ 135.95
348167	White	WW NW	2700/2900 lm	274 mm	100 mm	30.0 W	€ 151.95
348168	Black	WW NW	2700/2900 lm	274 mm	100 mm	30.0 W	€ 151.95



Accessories for 348161, 348162

930679	Lens 24° for Lucea 6/10		€ 7.95
930752	Door panel for Lucea 6/10 white		€ 17.95
930753	Door panel for Lucea 6/10 black		€ 17.95
930756	Reflector ring for Lucea 6/10 white		€ 3.95
930757	Reflector ring for Lucea 6/10 black		€ 3.95
930758	Reflector ring for Lucea 6/10 gold		€ 3.95

Accessories for 348163, 348164, 348165, 348166

930680	Lens 24° for Lucea 15/20		€ 9.95
930681	Lens 60° for Lucea 15/20		€ 9.95
930754	Door panel for Lucea 15/20 white		€ 18.95
930755	Door panel for Lucea 15/20 black		€ 18.95
930759	Reflector ring for Lucea 15/20 white		€ 4.75
930760	Reflector ring for Lucea 15/20 black		€ 4.75
930761	Reflector ring for Lucea 15/20 gold		€ 4.75

Accessories for **348167, 348168**

- 930677** Door panel for Lucea 30/40 white
- 930678** Door panel for Lucea 30/40 black
- 930682** Lens 24° for Lucea 30
- 930684** Lens 60° for Lucea 30
- 930762** Reflector ring for Lucea 30/40 white
- 930763** Reflector ring for Lucea 30/40 black
- 930764** Reflector ring for Lucea 30/40 gold

	€ 19.95
	€ 19.95
	€ 12.95
	€ 12.95
	€ 5.45
	€ 5.45
	€ 5.45



page 26



page 400



page 404



Lighting design

Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.



LUCEA

- Incl. black reflector ring
- Can be customised with a comprehensive range of accessories

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Light Beam Angle	36 Degree
Colour Temperature	2700 K	Control	Leading-edge dimmer, Trailing-edge dimmer
Height	157 mm	CRI (Ra)	90
Ø	65 mm	IK Protection Class	IK03
Rated Input Voltage	200-240 V/AC		
Power Supply Unit incl.	Yes		

Article	Housing Color		Luminous Flux	Power	Price
348213	 White		800 lm	6.0 W	€ 95.95
348214	 Black		800 lm	6.0 W	€ 95.95
348215	 White		1300 lm	10.0 W	€ 103.95
348216	 Black		1300 lm	10.0 W	€ 103.95



Accessories

930679	Lens 24° for Lucea 6/10		€ 7.95
930756	Reflector ring for Lucea 6/10 white		€ 3.95
930757	Reflector ring for Lucea 6/10 black		€ 3.95
930758	Reflector ring for Lucea 6/10 gold		€ 3.95





LUCEA TILT

- Incl. black reflector ring
- Can be customised with a comprehensive range of accessories

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Light Beam Angle	36 Degree
Colour Temperature	2700 K	Rotation Angle	350 Degree
Height	157 mm	Swivelling Angle	90 Degree
Ø	65 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Base Height	29 mm	CRI (Ra)	90
Base Ø	103.5 mm	IK Protection Class	IK03
Rated Input Voltage	200-240 V/AC		
Power Supply Unit incl.	Yes		

Article	Housing Color		Luminous Flux	Power	Price
348223	 White		800 lm	6.0 W	€ 95.95
348224	 Black		800 lm	6.0 W	€ 95.95
348225	 White		1300 lm	10.0 W	€ 103.95
348226	 Black		1300 lm	10.0 W	€ 103.95



Accessories

930679	Lens 24° for Lucea 6/10		€ 7.95
930752	Door panel for Lucea 6/10 white		€ 17.95
930753	Door panel for Lucea 6/10 black		€ 17.95
930756	Reflector ring for Lucea 6/10 white		€ 3.95
930757	Reflector ring for Lucea 6/10 black		€ 3.95
930758	Reflector ring for Lucea 6/10 gold		€ 3.95



page 28



page 296



page 297



LUCEA DTW

- Dim-to-warm 1,800 K-2,700 K
- Incl. black reflector ring
- Can be customised with a comprehensive range of accessories

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	1800-2700 K	Light Beam Angle	36 Degree
Luminous Flux	750 lm	Control	Leading-edge dimmer, Trailing-edge dimmer
Height	157 mm	CRI (Ra)	90
Ø	65 mm	IK Protection Class	IK03
Power	10 W		
Rated Input Voltage	200-240 V/AC		


Article	Housing Color		Price
348237	 White		€ 103.95
348238	 Black		€ 103.95



Accessories

930752	Door panel for Lucea 6/10 white		€ 17.95
930753	Door panel for Lucea 6/10 black		€ 17.95
930756	Reflector ring for Lucea 6/10 white		€ 3.95
930757	Reflector ring for Lucea 6/10 black		€ 3.95
930758	Reflector ring for Lucea 6/10 gold		€ 3.95





LUCEA TILT DTW

- Dim-to-warm 1,800 K-2,700 K
- Incl. black reflector ring
- Can be customised with a comprehensive range of accessories

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium	Light Beam Angle	36 Degree
Colour Temperature	1800-2700 K	Rotation Angle	350 Degree
Luminous Flux	750 lm	Swivelling Angle	90 Degree
Height	218 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	65 mm	CRI (Ra)	90
Power	10 W	IK Protection Class	IK03
Rated Input Voltage	200-240 V/AC		
Power Supply Unit incl.	Yes		

Article	Housing Color		Price
348239	White		€ 103.95
348240	Black		€ 103.95



Accessories

930752	Door panel for Lucea 6/10 white		€ 17.95
930753	Door panel for Lucea 6/10 black		€ 17.95
930756	Reflector ring for Lucea 6/10 white		€ 3.95
930757	Reflector ring for Lucea 6/10 black		€ 3.95
930758	Reflector ring for Lucea 6/10 gold		€ 3.95



page 26



page 400



page 404



CAN IP20

- Can be customised with a wide range of accessories
- Replaceable light source to offer an individual lighting solution
- Can be combined with the comprehensive CAN series product family

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Height	105 mm	Control	Dimmable via optional light source
Ø	60 mm		
Max. Power	1x max. 7.5 W		

Article	Housing Color	Price
348241	 White	€ 23.95
348242	 Black	€ 23.95



Accessories

930301	Reflector ring white for Klara/Nihal Mini/Can series		€ 3.95
930302	Reflector ring black for Klara/Nihal Mini/Can series		€ 3.95
930303	Reflector ring gold for Klara/Nihal Mini/Can series		€ 3.95
930307	Honeycomb filter for Klara/Nihal Mini/Uni II series		€ 6.95
930308	Spread lens for Klara/Nihal Mini/Uni II series		€ 6.95
930309	Softening lens for Klara/Nihal Mini/Uni II series		€ 6.95
930310	Linear spread lens for Klara/Nihal Mini/Uni II series		€ 6.95
930366	Reflector ring silver for Klara/Nihal Mini/Can series		€ 3.95
931065	Acrylic attachment for Can		€ 3.95





CAN IP44

- customised lighting solution thanks to replaceable light source
- can be combined with the extensive product family of the CAN series
- suitable for damp rooms

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, Bathroom / WC, Hotel bathrooms / commercial wet areas

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Height	105 mm	Control	Dimmable via optional light source
Ø	60 mm		
Max. Power	1x max. 7.5 W		

Article	Housing Color	Price
348243	White	€ 27.95
348244	Black	€ 27.95



Accessories

930301	Reflector ring white for Klara/Nihal Mini/Can series		€ 3.95
930302	Reflector ring black for Klara/Nihal Mini/Can series		€ 3.95
930366	Reflector ring silver for Klara/Nihal Mini/Can series		€ 3.95
930303	Reflector ring gold for Klara/Nihal Mini/Can series		€ 3.95



page 30



page 167



page 182



page 184



page 383




page 467





CANTILT SQUARE

The square CAN surface-mounted ceiling light provides a flexible lighting solution for commercial and private spaces. Available as a one-, two- and three-luminaire variant in the colours black and white, it enables precise alignment of the light using rotating and swivelling luminous elements. The widely used GU10 base enables quick and simple replacement of the lamp, while the screw-on cylinder housing enables tool-free access. Installation for rigid and flexible conductors is easy and efficient due to the integrated push terminals. The CAN surface-mounted ceiling light is part of a versatile series, which also contains pendant, wall, reading and outdoor lights.



page 30



page 167



page 182



page 184



CAN TILT SQUARE

- Flat and discreet lamp base
- Can be customised with a wide range of accessories
- Replaceable lamp to offer an individual lighting solution
- Can be combined with the comprehensive CAN series product family

Application Area

Home / Living, Hotel / catering

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Height	125 mm	Control	Dimmable via optional light source
Ø	60 mm	Rotation Angle	350 Degree
Base Width	90 mm	Swivelling Angle	90 Degree
Base Height	15 mm		

Article	Housing Color	Base Length	Max. Power	Price
348245	□ White	110 mm	1x max. 7.5 W	€ 35.95
348246	■ Black	110 mm	1x max. 7.5 W	€ 35.95
348247	□ White	305 mm	2x max. 7.5 W	€ 67.95
348248	■ Black	305 mm	2x max. 7.5 W	€ 67.95
348249	□ White	480 mm	3x max. 7.5 W	€ 99.95
348250	■ Black	480 mm	3x max. 7.5 W	€ 99.95



Accessories

930301	Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930302	Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930303	Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930366	Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
931065	Acrylic attachment for Can		€ 3.95



CAN TILT ROUND

The round CAN surface-mounted ceiling light provides a flexible lighting solution for commercial and private spaces. Available as a one-, two- and three-luminaire variant in the colours black and white, it enables precise alignment of the light using rotating and swivelling luminous elements. The widely used GU10 base enables quick and simple replacement of the lamp, while the screw-on cylinder housing enables tool-free access. Installation for rigid and flexible conductors is easy and efficient due to the integrated push terminals. The CAN surface-mounted ceiling light is part of a versatile series, which also contains pendant, wall, reading and outdoor lights.



page 30

page 167

page 182

page 184



CAN TILT ROUND

- Flat and discreet lamp base
- Replaceable lamp to offer an individual lighting solution
- Can be customised with a wide range of accessories
- Can be combined with the comprehensive CAN series product family

Application Area

Home / Living, Hotel / catering

Housing	Aluminium	Control	Dimmable via optional light source
Height	125 mm		
Ø	60 mm	Rotation Angle	350 Degree
Base Height	15 mm	Swivelling Angle	90 Degree
Rated Input Voltage	220-240 V/AC		

Article	Housing Color	Base Ø	Max. Power	Price
348251	White	80 mm	1x max. 7.5 W	€ 35.95
348252	Black	80 mm	1x max. 7.5 W	€ 35.95
348253	White	200 mm	2x max. 7.5 W	€ 67.95
348254	Black	200 mm	2x max. 7.5 W	€ 67.95
348255	White	250 mm	3x max. 7.5 W	€ 95.95
348256	Black	250 mm	3x max. 7.5 W	€ 95.95



Accessories

930301	Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930302	Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930303	Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930366	Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
931065	Acrylic attachment for Can		€ 3.95




CAN MIX'N MATCH

The new CAN series is the all-round solution for both private and commercial use – more extensive than ever before! Whether pendant light, ceiling light, wall light, reading light, track light, table and floor lamp, or outdoor luminaire – CAN is available in numerous variants and feels at home almost anywhere: living rooms, hotel rooms, restaurants, or garden areas.

With the new Mix'n Match variant – available for almost every type of luminaire – CAN can now be designed even more individually and adapted to different environments. The modular principle includes base, cylinder housing, and reflector ring as well as individual accessories, which, however, do not affect the look of the luminaire itself.

- 1 **choose BASE**
Define the CAN luminaire type:
ceiling light, wall light, floor lamp, etc.
- 2 **select CYLINDER HOUSING**
The cylinder housing is available in six different colours:
black, white, dark grey, brass, bronze, rose gold.
- 3 **add REFLECTOR RING**
Combine the reflector ring colour-matched to the cylinder housing
or create a deliberate contrast.
- 4 **ACCESSORIES [optional]**
If desired, the CAN can be complemented with a honeycomb filter
or a special lens.



Onlineshop

You can find more information about the products in the onlineshop:
Detailed images, videos, project reports, LDT files, EPREL data sheets and more.



CAN TILT SQUARE BASE MIX'N MATCH 1/3

- flat and discreet luminaire base
- can be customised with cylinder housing in 6 different colours

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Width	90 mm	Control	Dimmable via optional light source
Height	58 mm		
Base Width	90 mm	Rotation Angle	350 Degree
Base Height	15 mm	Swivelling Angle	90 Degree

Article	Housing Color	Length	Base Length	Max. Power	Price
348264	White	110 mm	110 mm	1x max. 7.5 W	€ 29.95
348265	Black	110 mm	110 mm	1x max. 7.5 W	€ 29.95
348266	White	305 mm	305 mm	2x max. 7.5 W	€ 55.95
348267	Black	305 mm	305 mm	2x max. 7.5 W	€ 55.95
348268	White	480 mm	480 mm	3x max. 7.5 W	€ 79.95
348269	Black	480 mm	480 mm	3x max. 7.5 W	€ 79.95



CAN TILT ROUND BASE MIX'N MATCH 1/3

Housing	Aluminium	Control	Dimmable via optional light source
Height	58 mm		
Base Height	15 mm	Rotation Angle	350 Degree
Rated Input Voltage	220-240 V/AC	Swivelling Angle	90 Degree

Article	Housing Color	Ø	Base Ø	Max. Power	Price
348270	White	80 mm	80 mm	1x max. 7.5 W	€ 29.95
348271	Black	80 mm	80 mm	1x max. 7.5 W	€ 29.95
348272	White	200 mm	200 mm	2x max. 7.5 W	€ 54.95
348273	Black	200 mm	200 mm	2x max. 7.5 W	€ 54.95
348274	White	250 mm	250 mm	3x max. 7.5 W	€ 79.95
348275	Black	250 mm	250 mm	3x max. 7.5 W	€ 79.95





CYLINDER HOOUSING FOR CAN MIX'N MATCH 2/3

Housing Aluminium Ø 60 mm
Height 98 mm

Article	Housing Color	Price
931053	 White	€ 6.45
931054	 Black	€ 6.45
931055	 Bronze	€ 14.95
931056	 Brass	€ 14.95
931057	 Black grey	€ 14.95
931058	 Rosé	€ 14.95

IP20



REFLECTOR RING FOR CAN MIX'N MATCH 3/3

Housing Plastic Ø 57 mm
Height 28 mm

Article	Housing Color	Price
930301	 White	€ 3.95
930302	 Black	€ 3.95
930303	 Gold	€ 3.95
930366	 Silver	€ 3.95

IP20



BENGALA ROUND

- Exchangeable lamp
- Can be rotated and swivelled

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, House wall / facade / front door, Home / Living

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Height	120 mm	Control	Dimmable via optional light source
Ø	96 mm	Swivelling Angle	30 Degree
Base Ø	96 mm		
Max. Power	1x max. 50 W		

Article	Housing Color	Price
122416	 Silver	€ 35.95
348022	 Black	€ 35.95
348023	 White	€ 35.95





BENGALA SQUARE

- Exchangeable lamp
- Can be rotated and swivelled

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, House wall / facade / front door, Home / Living

Housing	Aluminium	Max. Power	1x max. 50 W
Length	96 mm	Rated Input Voltage	220-240 V/AC
Width	96 mm	Control	Dimmable via optional light source
Height	120 mm	Swivelling Angle	30 Degree
Base Length	96 mm		
Base Width	96 mm		

Article	Housing Color	Price
122417	 Silver	€ 35.95
348024	 Black	€ 35.95
348025	 White	€ 35.95

GU10















PRO OFFICE SANO

PRO OFFICE SANO series ceiling lights are an efficient solution for renovating and modernising old T5/T8 louver lights. Due to slightly larger dimensions, the lights cover the old installations and so do not require the ceiling to be repainted.

Arrestor cables, plug connectors and mounting brackets make installation so easy that it can be performed by one person. In addition to ease of installation, the series offers impressive technical highlights: It provides flexible light control via CCT switch (3,000 K / 3,500 K / 4,000 K), dimmable variants (leading-edge/trailing-edge or DALI) and output adjustment in four stages (TRIAC variants only). They are also eligible for BEG German federal funding for energy-efficient buildings and emergency power capable.






PRO OFFICE SANO

- Renovation solution for T5/T8 louver lights
- Uniform illumination
- Covers the old installation, therefore no repainting necessary
- Easy to install due to plug connector, arrestor cables and mounting bracket
- Light colour adjustable in three levels
- Output adjustable in four levels [TRIAC variants only]
- Microprismatic surface structure
- Eligible for BEG German federal funding for energy-efficient buildings
- Emergency power capable [176-280 V/DC EOFI: 95 %]
- Suitable for workplaces with screens in accordance with EN 12464-1 BAP65 [L65 ≤ 3,000 cd/m²]

Application Area

Office / conference, Health / care / hospital / practice, Education / school / lecture theatre, Refurbishment

Housing	Aluminium, Stainless steel	Light Beam Angle	90 Degree
Colour Temperature	3000/3500/4000 K	Control	Trailing-edge dimmer, Leading-edge dimmer
Height	48 mm	CRI (Ra)	90
Rated Input Voltage	198-264 V/AC	IK Protection Class	IK03
Power Supply Unit incl.	Yes		




Article	Housing Color		Luminous Flux	Length	Width	Power Selectable	EEL	Price
348258	☐ White	 	4200/4500/4400 lm	625 mm	625 mm	27.0 / 30.0 / 33.0 / 35.0 W		€ 151.95
348259	☐ White	 	4350/4600/4500 lm	1225 mm	325 mm	27.0 / 30.0 / 32.0 / 35.0 W		€ 167.95
348260	☐ White	 	5200/5500/5400 lm	1525 mm	325 mm	32.0 / 35.5 / 38.0 / 42.0 W		€ 183.95



Lighting design

Interested in our lighting design service?

Your contact person will be happy to answer any questions you may have.






PRO OFFICE SANO DALI

- Renovation solution for T5/T8 louver lights
- uniform illumination
- Covers the old installation, therefore no repainting necessary
- Easy to install due to plug connector, arrestor cables and mounting bracket
- Light colour adjustable in three levels
- Output adjustable in four levels [TRIAC variants only]
- Microprismatic surface structure
- Eligible for BEG German federal funding for energy-efficient buildings
- Emergency power capable [176-280 V/DC EOFI: 95 %]
- Suitable for workplaces with screens in accordance with EN 12464-1 BAP65 [L65 ≤ 3,000 cd/m²]

Application Area

Office / conference, Health / care / hospital / practice, Education / school / lecture theatre, Refurbishment

Housing	Aluminium, Stainless steel	Light Beam Angle	90 Degree
Colour Temperature	3000/3500/4000 K	Control	DALI 2 / DT6, Intelli Push-Dim
Height	48 mm	CRI (Ra)	90
Rated Input Voltage	198-264 V/AC	IK Protection Class	IK03
Power Supply Unit incl.	Yes		



348261

Article	Housing Color		Luminous Flux	Length	Width	Power	Price
348261	☐ White	WW NW	4400/4700/4600 lm	625 mm	625 mm	35.0 W	€ 191.95
348262	☐ White	WW NW	4200/4500/4400 lm	1225 mm	325 mm	34.0 W	€ 175.95
348263	☐ White	WW NW	5300/5600/5500 lm	1525 mm	325 mm	42.0 W	€ 207.95



Onlineshop

You can find more information about the products in the onlineshop:
Detailed images, videos, project reports, LDT files, EPREL data sheets and more.

built in ceiling lights



page 86



page 87



page 88



page 89



page 92



page 98



page 104



page 105



page 106



page 108



page 113



page 120



□ ■
page 122



SAMSOLA ROUND

- Suitable for GU10/GU5.3 sockets [sold separately]
- Lamps are easy to install due to click lock

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Cut Out Ø	68 mm
Height	23 mm	Control	Dimmable via optional light source
Ø	82 mm	Swivelling Angle	30 Degree
Installation Depth	100 mm		

Article	Housing Color	Surface	Price
110039	 White	Matt	€ 7.95
110042	 Aluminium	Matt	€ 7.95
110041	 Silver	Shiny	€ 7.95
110040	 Silver	Brushed	€ 7.95
110038	 Copper	Brushed	€ 7.95
110043	 Black	Matt	€ 7.95




Accessories

100204	Socket GU10 with spacer		€ 3.25
100200	Socket GU5.3 with 15 cm cable		€ 0.75
829063	Safety spacer		€ 3.45
930967	Reducing ring round 130/70 mm, Traffic white		€ 7.95
931043	Reducing ring round 130/70 mm, Signal white		€ 7.95



Light sources
For all lights and bases:
You can find the right light sources in the »Light sources« section.



SAMSOLA SQUARE

- Suitable for GU10/GU5.3 sockets [sold separately]
- Lamps are easy to install due to click lock

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Cut Out Ø	68 mm
Length	85 mm	Control	Dimmable via optional light source
Width	85 mm	Swivelling Angle	30 Degree
Height	23 mm		
Installation Depth	100 mm		

Article	Housing Color	Surface	Price
110045	White	Matt	€ 7.95
110048	Aluminium	Matt	€ 7.95
110047	Silver	Shiny	€ 7.95
110046	Silver	Brushed	€ 7.95
110044	Copper	Brushed	€ 7.95
110049	Black	Matt	€ 7.95



Accessories

100204	Socket GU10 with spacer		€ 3.25
100200	Socket GU5.3 with 15 cm cable		€ 0.75
829063	Safety spacer		€ 3.45
930972	Reducing ring square 130/70 mm, Traffic white		€ 7.95
931048	Reducing ring square 130/70 mm, Signal white		€ 7.95



Onlineshop
You can find more information about the products in the onlineshop:
Detailed images, videos, project reports, LDT files, EPREL data sheets and more.



SAMSOLA MAX ROUND

- Suitable for GU10 / GU5.3 sockets [sold separately]
- Easy installation of the light sources thanks to click lock

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Cut Out Ø	68-80 mm
Height	23 mm	Control	Dimmable via optional light source
Ø	95 mm	Swivelling Angle	30 Degree
Installation Depth	100 mm		

Article	Housing Color	Surface	Price
110051	White	Brushed	€ 9.95
110054	Aluminium	Matt	€ 9.95
110053	Silver	Shiny	€ 9.95
110052	Silver	Brushed	€ 9.95
110050	Copper	Brushed	€ 9.95
110055	Black	Matt	€ 9.95




Accessories

100204	Socket GU10 with spacer		€ 3.25
100200	Socket GU5.3 with 15 cm cable		€ 0.75
829063	Safety spacer		€ 3.45
930967	Reducing ring round 130/70 mm, Traffic white		€ 7.95
931043	Reducing ring round 130/70 mm, Signal white		€ 7.95



Light sources
For all lights and bases:
You can find the right light sources in the »Light sources« section.



SAMSOLA MAX SQUARE

- Suitable for GU10 / GU5.3 sockets [sold separately]
- Easy installation of the light sources thanks to click lock

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Cut Out Ø	68-80 mm
Length	95 mm	Control	Dimmable via optional light source
Width	95 mm	Swivelling Angle	30 Degree
Height	23 mm		
Installation Depth	100 mm		

Article	Housing Color	Surface	Price
110057	White	Matt	€ 9.95
110060	Aluminium	Matt	€ 9.95
110059	Silver	Shiny	€ 9.95
110058	Silver	Brushed	€ 9.95
110056	Copper	Brushed	€ 9.95
110061	Black	Matt	€ 9.95



Accessories

100204	Socket GU10 with spacer		€ 3.25
100200	Socket GU5.3 with 15 cm cable		€ 0.75
829063	Safety spacer		€ 3.45
930972	Reducing ring square 130/70 mm, Traffic white		€ 7.95
931048	Reducing ring square 130/70 mm, Signal white		€ 7.95



5-year guarantee
Benefit from the maximum quality promise:
All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.



ARKTUR

- Replaceable lamp [GU5.3/MR16]
- Swivel-mounted
- Dimmable

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Cut Out Ø	85 mm
Height	43 mm	Control	Dimmable via optional light source
Ø	93 mm	Swivelling Angle	30 Degree
Max. Power	1x max. 35 W		
Rated Input Voltage	12 V/AC/DC		

Article	Housing Color	Price
110019	☐ White	€ 12.95





ALTAIR

- Replaceable lamp [GU5.3/MR16]
- Dimmable

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, Bathroom / WC


Housing	Aluminium	Rated Input Voltage	12 V/AC/DC
Height	35 mm	Cut Out Ø	68 mm
Ø	85 mm	Control	Dimmable via optional light source
Installation Depth	33 mm		
Max. Power	1x max. 35 W		

Article	Housing Color	Price
110017	☐ White	€ 9.95
		
		
		

Accessories


930967	Reducing ring round 130/70 mm, Traffic white		€ 7.95
931043	Reducing ring round 130/70 mm, Signal white		€ 7.95





CAN ROUND

The CAN recessed spotlight round offers a flexible lighting solution for commercial and private spaces. Available as a single and double-lamp version in black and white, it enables precise alignment of the light thanks to the rotatable and swiveling light body. The widely used GU10 base makes it easy to replace the light source quickly and the screw-on cylinder housing enables tool-free access. Thanks to the integrated plug-in terminals, installation for rigid and flexible cables is simple and efficient. The CAN surface-mounted ceiling luminaire is part of a versatile series that also includes pendant, wall, reading and outdoor luminaires.



CAN ROUND

- Customised lighting solution thanks to replaceable light source
- can be customised with cylinder housing in 5 different colours
- can be combined with the extensive product family of the CAN series

Application Area

Home / Living, Hotel / catering

Housing	Aluminium	Cut Out Ø	51 mm
Height	98 mm	Control	Dimmable via optional light source
Ø	60 mm	Rotation Angle	350 Degree
Installation Depth	40 mm	Swivelling Angle	90 Degree
Rated Input Voltage	220-240 V/AC		

Article	Housing Color	Length	Max. Power	Cut Out Length	Price
565755	White		1x max. 7.5 W		€ 26.95
565756	Black		1x max. 7.5 W		€ 26.95
565757	White	160 mm	2x max. 7.5 W	100 mm	€ 55.95
565758	Black	160 mm	2x max. 7.5 W	100 mm	€ 55.95



Accessories

930301	Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930302	Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930303	Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930366	Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
931065	Acrylic attachment for Can		€ 3.95



REDUCING RINGS

The renovation rings for recessed luminaires provide a practical solution for covering oversized ceiling cut-outs. Available in different sizes, they offer flexible adaptation to various cut-out dimensions and enable a clean retrofit of existing installations. The rings are suitable for suspended ceilings with a thickness of 3 to 30 mm and are ideal for recessed luminaires with mounting springs. Installation is quick and can often be carried out without tools.



REDUCING RINGS FOR RECESSED LIGHTS

- Renovation solution for excessively large ceiling cut-outs
- Flexible adaptation to ceiling cut-outs
- suitable for 3-30 mm thick hollow ceilings
- toolless installation possible

Housing		Metal	Installation Depth		41 mm		
Height		1.7 mm					
Article	Housing Color	Length	Width	Ø	Cut Out Ø	Inner diameter	Price
930967	☐ Traffic white			130 mm	95 mm	70 mm	€ 7.95
931043	☐ Signal white			130 mm	95 mm	70 mm	€ 7.95
930968	☐ Traffic white			155 mm	120 mm	95 mm	€ 9.95
931044	☐ Signal white			155 mm	120 mm	95 mm	€ 9.95
930969	☐ Traffic white			210 mm	175 mm	135 mm	€ 10.95
931045	☐ Signal white			210 mm	175 mm	135 mm	€ 10.95
930970	☐ Traffic white			240 mm	205 mm	180 mm	€ 13.95
931046	☐ Signal white			240 mm	205 mm	180 mm	€ 13.95
930971	☐ Traffic white			280 mm	245 mm	210 mm	€ 18.95
931047	☐ Signal white			280 mm	245 mm	210 mm	€ 18.95
930972	☐ Traffic white	130 mm	130 mm		95 mm	70 mm	€ 7.95
931048	☐ Signal white	130 mm	130 mm		95 mm	70 mm	€ 7.95
930973	☐ Traffic white	155 mm	155 mm		120 mm	95 mm	€ 9.95
931049	☐ Signal white	155 mm	155 mm		120 mm	95 mm	€ 9.45
930974	☐ Traffic white	210 mm	210 mm		175 mm	135 mm	€ 10.95
931050	☐ Signal white	210 mm	210 mm		175 mm	135 mm	€ 10.95
930975	☐ Traffic white	240 mm	240 mm		205 mm	180 mm	€ 13.95
931051	☐ Signal white	240 mm	240 mm		205 mm	180 mm	€ 13.95
930976	☐ Traffic white	280 mm	280 mm		245 mm	210 mm	€ 18.95
931052	☐ Signal white	280 mm	280 mm		245 mm	210 mm	€ 18.95

DIONE

The DIONE series comprises elegant recessed spotlights in aluminium housing with particularly shallow mounting depth - a real problem solver in the refurbishment sector.

The popular DIONE recessed ceiling luminaires with high-quality COB LED including reflector are housed in an aluminium casing and have a cut-out dimension of 68 mm. While the available colours white, silver, black, chrome and nickel harmonise with almost any type of ceiling, the actual special feature of the DIONE is not visible when installed: The recessed spotlights are extremely space-saving when installed and require only 25 or 27 mm of ceiling cavity. This is where the power supply unit and the Quick connection box are located, which allows 3-pole through-wiring of several DIONE models as well as retrofitting as part of renovations.

The plug-in connector between the spotlight and the power supply unit allows installers to conveniently install the lighting equipment and connect the spotlight once the ceiling work has been completed.

The DIONE recessed spotlights are available in the light colours 2,700K, 3,000 K, 4,000 K, as a dim-to-warm version [1,800- 3,000K] and RGBW. In addition to the IP20 version, an IP44 version is also available, making the DIONE suitable for bathrooms and other damp areas indoors.

With this variety, the DIONE series offers recessed spotlights for a wide range of applications - from private homes and exhibition areas to guest areas in hotels and restaurants. Thanks to the wide selection of light colours and IP classes, the DIONE can be flexibly integrated into any environment and covers all design requirements, from a feel-good character to functional lighting.



THAT'S HOW EASY IT IS



1 - Quick wiring / through-wiring on the Quick connection box due to screwless plug-in terminals



2 - quick connection box is placed over the 68 mm cut-out in the cavity



4 - connect the power supply unit to the spot using the connector



6 - The result: a compact installation with a swivelling spot, a dimmable power supply unit and the option of through-wiring in the ceiling cavity - ideal in refurbishment areas.




DIONE IP20

- Low installation depth
- Incl. dimmable power supply unit and connection box
- Feed-through wiring possible
- Ideal renovation solution
- Light and power supply unit with intermediate connector

Application Area


Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Required Installation Depth	25 mm
Height	41 mm	Light Beam Angle	36 Degree
Ø	82 mm	Swivelling Angle	30 Degree
Power	8.5 W	Cut Out Ø	68 mm
Rated Input Voltage	220-240 V/AC	Control	Leading-edge dimmer, Trailing-edge dimmer
Power Supply Unit incl.	Yes		
Installation Depth	38 mm		



565355

Article	Housing Color	Colour Temperature	Luminous Flux	CRI (Ra)	Price
565375	White	2700 K	750 lm	81	€ 47.95
565376	Silver	2700 K	750 lm	81	€ 47.95
565377	Black	2700 K	750 lm	81	€ 47.95
565378	Nickel	2700 K	750 lm	81	€ 47.95
565379	Chrome	2700 K	750 lm	81	€ 47.95
565355	White	3000 K	800 lm	81	€ 47.95
565356	Silver	3000 K	800 lm	81	€ 47.95
565357	Black	3000 K	800 lm	81	€ 47.95
565371	Nickel	3000 K	800 lm	81	€ 47.95
565372	Chrome	3000 K	800 lm	81	€ 47.95
565358	White	4000 K	800 lm	84	€ 47.95
565359	Silver	4000 K	800 lm	84	€ 47.95
565360	Black	4000 K	800 lm	84	€ 47.95
565373	Nickel	4000 K	800 lm	84	€ 47.95
565374	Chrome	4000 K	800 lm	84	€ 47.95



Accessories

- 930863 60° reflector for Dione
- 930864 Frosted diffusing lens for Dione
- 829063 Safety spacer
- 930967 Reducing ring round 130/70 mm, Traffic white
- 931043 Reducing ring round 130/70 mm, Signal white

- € 4.95
- € 2.25
- € 3.45
- € 7.95
- € 7.95




DIONE IP20 DTW

- Low installation depth
- Incl. dimmable power supply unit and connection box
- Feed-through wiring possible
- Ideal renovation solution
- Light and power supply unit with intermediate connector

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Installation Depth	38 mm
Colour Temperature	1800-3000 K	Required Installation Depth	25 mm
Luminous Flux	480 lm	Light Beam Angle	36 Degree
Height	41 mm	Swivelling Angle	30 Degree
Ø	82 mm	Cut Out Ø	68 mm
Power	8.5 W	Control	Leading-edge dimmer, Trailing-edge dimmer
Rated Input Voltage	220-240 V/AC		
Power Supply Unit incl.	Yes	CRI (Ra)	95




Article	Housing Color	Price
565380	White	€ 55.95
565381	Silver	€ 55.95
565382	Black	€ 55.95
565383	Chrome	€ 55.95
565384	Nickel	€ 55.95



Accessories

930863	60° reflector for Dione	€ 4.95
930864	Frosted diffusing lens for Dione	€ 2.25
829063	Safety spacer	€ 3.45
930967	Reducing ring round 130/70 mm, Traffic white	€ 7.95
931043	Reducing ring round 130/70 mm, Signal white	€ 7.95





DIONE IP44


- Low installation depth
- Splash-proof [downwards after installation]
- Incl. dimmable power supply unit and connection box
- Feed-through wiring possible
- Ideal renovation solution
- Light and power supply unit with intermediate connector



Application Area


Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, Bathroom / WC

Housing	Aluminium	Required Installation Depth	27 mm
Height	44 m	Light Beam Angle	36 Degree
Ø	82 mm	Swivelling Angle	30 Degree
Power	8.5 W	Cut Out Ø	68 mm
Rated Input Voltage	220-240 V/AC	Control	Leading-edge dimmer, Trailing-edge dimmer
Power Supply Unit incl.	Yes		
Installation Depth	41 mm		



565388


Article	Housing Color	Colour Temperature	Luminous Flux	CRI (Ra)	Price
565388	White	2700 K	750 lm	81	€ 51.95
565389	Silver	2700 K	750 lm	81	€ 51.95
565390	Black	2700 K	750 lm	81	€ 51.95
565391	Chrome	2700 K	750 lm	81	€ 51.95
565392	Nickel	2700 K	750 lm	81	€ 51.95
565393	White	3000 K	800 lm	81	€ 51.95
565394	Silver	3000 K	800 lm	81	€ 51.95
565395	Black	3000 K	800 lm	81	€ 51.95
565396	Chrome	3000 K	800 lm	81	€ 51.95
565397	Nickel	3000 K	800 lm	81	€ 51.95
565398	White	4000 K	800 lm	84	€ 51.95
565399	Silver	4000 K	800 lm	84	€ 51.95
565400	Black	4000 K	800 lm	84	€ 51.95
565401	Chrome	4000 K	800 lm	84	€ 51.95
565402	Nickel	4000 K	800 lm	84	€ 51.95



Accessories

- 930863** 60° reflector for Dione
- 930864** Frosted diffusing lens for Dione
- 829063** Safety spacer
- 930967** Reducing ring round 130/70 mm, Traffic white
- 931043** Reducing ring round 130/70 mm, Signal white

	€ 4.95
	€ 2.25
	€ 3.45
	€ 7.95
	€ 7.95




DIONE IP44 DTW


- Low installation depth
- Splash-proof [downwards after installation]
- Incl. dimmable power supply unit and connection box
- Feed-through wiring possible
- Ideal renovation solution
- Light and power supply unit with intermediate connector

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, Bathroom / WC

Housing	Aluminium	Installation Depth	41 mm
Colour Temperature	1800-3000 K	Required Installation Depth	27 mm
Luminous Flux	480 lm	Light Beam Angle	36 Degree
Height	44 mm	Swivelling Angle	30 Degree
Ø	82 mm	Cut Out Ø	68 mm
Power	8.5 W	Control	Leading-edge dimmer, Trailing-edge dimmer
Rated Input Voltage	220-240 V/AC		
Power Supply Unit incl.	Yes	CRI (Ra)	95




Article	Housing Color		Price
565403	White	WW	€ 59.95
565404	Silver	WW	€ 59.95
565405	Black	WW	€ 59.95
565406	Chrome	WW	€ 59.95
565407	Nickel	WW	€ 59.95



Accessories

930863	60° reflector for Dione	€ 4.95
930864	Frosted diffusing lens for Dione	€ 2.25
829063	Safety spacer	€ 3.45
930967	Reducing ring round 130/70 mm, Traffic white	€ 7.95
931043	Reducing ring round 130/70 mm, Signal white	€ 7.95







DIONE, IP44, RGBW

- Low installation depth
- splash-proof [downwards when installed]
- suitable for 24V colour controls
- can be combined with all Dione recessed spotlights
- high-quality RGBW COB technology
- RGB 3x 3W, WW 1x 6W, max. possible total output 9W
- homogeneous colour mixing

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, Bathroom / WC

Housing	Aluminium	Installation Depth	41 mm
Colour Temperature	3000 K	Required Installation Depth	27 mm
Luminous Flux	540 lm	Light Beam Angle	36 Degree
Height	41 mm	Swivelling Angle	30 Degree
Ø	82 mm	Cut Out Ø	68 mm
Power	9 W	Control	Dimmable via optional controller
Rated Input Voltage	24 V/DC	CRI (Ra)	90
Power Supply Unit incl.	No		

Article	Housing Color		Price
565450		White	€ 59.95
565451		Light grey	€ 59.95
565452		Black	€ 59.95
565453		Chrome	€ 59.95
565454		Nickel	€ 59.95




Accessories

843542	RF-smart, Starter-Set RGB/W/CCT, 12-48V, 20A incl. Remote, IP20
843037	Casambi BT Dimmer CBU-PWM4 (CV, 12-24V, 6A DC)
843502	RF-smart, starter set RGB/W/CCT, 12-48 V, 20 A incl. remote, IP20
843343	DALI 2 PWM dimmer CV 4CH 12-48V, 4A/CH, DT6
843344	DALI 2 PWM dimmer CV 4CH 12-48V, 4A/CH, DT8
843279	MULTI-LED dimmer 1-4 channels, DMX/auto/manual, 12-48 V, 20 A, flicker-free
862234	FLAT, CV, UT 24 V/20 W
862122	FLAT, CV, UT 24 V/50 W
862126	LONG-FLAT, CV, LT-100-24
930967	Reducing ring round 130/70 mm, Traffic white
931043	Reducing ring round 130/70 mm, Signal white



€ 91.95
€ 143.95
€ 79.95
€ 75.95
€ 75.95
€ 91.95
€ 20.95
€ 41.95
€ 77.95
€ 7.95
€ 7.95




SURTUR

- Integrated power supply unit
- through-wiring possible
- Light colour adjustable in 3 steps
- Very high colour rendering



Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Colour Temperature	2700/3000/4000 K	Control	Trailing-edge dimmer, Leading-edge dimmer
Rated Input Voltage	220-240 V/AC	CRI (Ra)	90
Power Supply Unit incl.	Yes	Accumulator/Battery Operated	No
Light Beam Angle	40 Degree	IK Protection Class	IK06
Swivelling Angle	30 Degree		



565455

Article	Housing Color	Luminous Flux	Housing	Ø cut out	Height	Ø	Power	Price
565455	White	520/600/510 lm	Polycarbonate	68-75 mm	44 mm	85 mm	6.0 W	€ 19.95
565456	Black	520/600/510 lm	Polycarbonate	68-75 mm	44 mm	85 mm	6.0 W	€ 19.95
565457	White	900/1000/1000 lm	Polycarbonate / PA - Polyamide	83-95 mm	72 mm	105 mm	9.0 W	€ 25.95
565458	Black	900/1000/1000 lm	Polycarbonate / PA - Polyamide	83-95 mm	72 mm	105 mm	9.0 W	€ 25.95



Accessories for 565455, 565456

930967	Reducing ring round 130/70 mm, Traffic white	2	€ 7.95
931043	Reducing ring round 130/70 mm, Signal white	2	€ 7.95

Accessories for 565457, 565458

930968	Reducing ring round 155/95 mm, Traffic white	2	€ 9.95
931044	Reducing ring round 155/95 mm, Signal white	2	€ 9.95



Onlineshop
You can find more information about the products in the onlineshop:
Detailed images, videos, project reports, LDT files, EPREL data sheets and more.



SURTUR DTW


- Integrated power supply unit
- Feed-through wiring possible
- Adjustable light colour - dim to warm
- Very high colour rendering



Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Colour Temperature	1800-2700 K	Control	Trailing-edge dimmer, Leading-edge dimmer
Rated Input Voltage	220-240 V/AC	CRI (Ra)	90
Power Supply Unit incl.	Yes	Accumulator/Battery	No
Light Beam Angle	40 Degree	Operated	
Swivelling Angle	30 Degree	IK Protection Class	IK06



565459

Article	Housing Color	Luminous Flux	Housing	Ø cut out	Height	Ø	Power	Price
565459	White	WW	230/430 lm Polycarbonate	68-75 mm	44 mm	85 mm	6.0 W	€ 22.95
565460	Black	WW	230/430 lm Polycarbonate	68-75 mm	44 mm	85 mm	6.0 W	€ 22.95
565461	White	WW	360/720 lm Polycarbonate / PA - Polyamide	83-95 mm	72 mm	105 mm	9.0 W	€ 29.95
565462	Black	WW	360/720 lm Polycarbonate / PA - Polyamide	83-95 mm	72 mm	105 mm	9.0 W	€ 29.95



Accessories for 565459, 565460

930967	Reducing ring round 130/70 mm, Traffic white	€ 7.95
931043	Reducing ring round 130/70 mm, Signal white	€ 7.95

Accessories for 565461, 565462

930968	Reducing ring round 155/95 mm, Traffic white	€ 9.95
931044	Reducing ring round 155/95 mm, Signal white	€ 9.95



Technical data sheet

New in the onlineshop: The technical data sheets offer even more information: Light and energy data, light distribution curves, dimensional drawings and more.



SMD-68-230V-ROUND

Plenty of power for less! SMD-68 series recessed lights deliver up to 550 lm and also have an integrated, dimmable power supply (230 V direct connection), which makes the use of GU10 holders and retrofitted equipment redundant.






SMD-68-230V-ROUND

- Integrated power supply unit
- Swivel-mounted
- Low installation depth

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Plastic	Light Beam Angle	45 Degree
Height	43.8 mm	Swivelling Angle	36 Degree
Ø	85 mm	Cut Out Ø	68 mm
Power	6.5 W	Control	Leading-edge dimmer, Trailing-edge dimmer
Rated Input Voltage	220-240 V/AC	CRI (Ra)	80
Power Supply Unit incl.	Yes		
Installation Depth	41.3 mm		




565337

Article	Housing Color	Colour Temperature	Luminous Flux	EEI	Price
565337	White	2700 K	510 lm	G	€ 15.95
565385	Black	2700 K	510 lm	G	€ 15.95
565338	White	3000 K	540 lm	F	€ 15.95
565386	Black	3000 K	540 lm	F	€ 15.95
565339	White	4000 K	550 lm	G	€ 15.95
565387	Black	4000 K	550 lm	G	€ 15.95



Accessories

930967	Reducing ring round 130/70 mm, Traffic white		€ 7.95
931043	Reducing ring round 130/70 mm, Signal white		€ 7.95




COB 68 HCL

- Suitable for 24 V HCL controllers
- Swivel-mounted

Application Area


Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Installation Depth	60 mm
Colour Temperature	2500-6500 K	Light Beam Angle	65 Degree
Luminous Flux	534 lm	Swivelling Angle	25 Degree
Height	46 mm	Cut Out Ø	68 mm
Ø	78 mm	Control	Dimmable via optional controller
Power	8 W	CRI (Ra)	80
Rated Input Voltage	24 V/DC		
Power Supply Unit incl.	No		



565193

Article	Housing Color	Colour Temperature	Price
565193	☐ White	☒ WW ☐ CW 2500-6500 K	€ 52.95




Accessories

- 829063** Safety spacer
- 862234** FLAT, CV, UT 24 V/20 W
- 862168** BASIC, CV, Q8H-24-150 W
- 843501** RF-smart, starter set LED single/CCT, 12-48 V, 20 A incl. remote control
- 930967** Reducing ring round 130/70 mm, Traffic white
- 931043** Reducing ring round 130/70 mm, Signal white

	€ 3.45
	€ 20.95
	€ 103.95
	€ 79.95
	€ 7.95
	€ 7.95






COB 95 HCL

- suitable for 24V HCL control
- swivelling

Application Area


Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Installation Depth	70 mm
Colour Temperature	2500-6500 K	Light Beam Angle	65 Degree
Luminous Flux	1118 lm	Swivelling Angle	25 Degree
Height	65 mm	Cut Out Ø	95 mm
Ø	108 mm	Control	Dimmable via optional controller
Power	16 W	CRI (Ra)	80
Rated Input Voltage	24 V/DC		
Power Supply Unit incl.	No		



565194

Article	Housing Color	Colour Temperature	Price
565194	☐ White	☒ WW ☒ CW 2500-6500 K	€ 87.95



Accessories

829063	Safety spacer
862233	FLAT, CV, UT 24 V/12 W
862166	BASIC, CV, Q8H-24-100 W
843501	RF-smart, starter set LED single/CCT, 12-48 V, 20 A incl. remote control
930968	Reducing ring round 155/95 mm, Traffic white
931044	Reducing ring round 155/95 mm, Signal white

	€ 3.45
	€ 17.95
	€ 77.95
	€ 79.95
	€ 9.95
	€ 9.95



TARVOS

The TARVOS series offers a well-designed LED downlight portfolio for professional indoor lighting solutions. The name of each luminaire directly refers to the cut-out diameter in millimeters – TARVOS 68, 100, 150, or 240. This allows the models to be planned quickly and precisely into existing or new ceiling cut-outs. All TARVOS recessed spotlights are suitable for emergency power operation, feature a round housing, and are available in several variants that differ in housing colour, light colour, beam angle, and control [see list]. This enables precise and individual adaptation of the lighting effect to the respective application – from pinpoint accentuation to wide, diffuse general lighting.




Overview of variants

- housing colour: black, light grey, white
- colour temperature: 2700K, 3000K, 4000K
- beam angle: 15°, 30°, 45°
- control: DALI 2.0, DT6, push dim

The TARVOS series meets the requirements for BEG funding (Federal Funding for Efficient Buildings). Combined with its high energy efficiency and long-lasting LED technology, the recessed spotlights thus present a future-proof solution from both economic and ecological perspectives – especially for refurbishment projects in existing buildings. The range covers offices, corridors and stairwells, retail and gastronomy areas, as well as public facilities.







TARVOS

The TARVOS series offers a well-designed LED downlight portfolio for professional indoor lighting solutions. The name of each luminaire directly refers to the cut-out diameter in millimeters – TARVOS 68, 100, 150, or 240. This allows the models to be planned quickly and precisely into existing or new ceiling cut-outs. All TARVOS recessed spotlights are suitable for emergency power operation, feature a round housing, and are available in several variants that differ in housing colour, light colour, beam angle, and control (see list). This enables precise and individual adaptation of the lighting effect to the respective application – from pinpoint accentuation to wide, diffuse general lighting.



Note: Please note that the TARVOS series are project items that are not available from stock. The delivery time is approx. 6 weeks.



TARVOS

- Through-wiring possible
- very high color rendering
- BEG eligible
- capable of emergency power supply
- incl. power supply unit and 230V direct connection

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	CRI (Ra)	90
Rated Input Voltage	220-240 V/AC	IK Protection Class	IK05



Lighting design

Interested in our lighting design service?

Your contact person will be happy to answer any questions you may have.

TARVOS 68

Ø x H					Cut Out Ø					Power rating	Colour temperature			Luminous flux	Dimmable	Housing Color			Light Beam Angle			Article	Price
85 x 86 mm	115 x 75 mm	165 x 113 mm	205 x 144 mm	255 x 160 mm	68 mm	100 mm	150 mm	190 mm	240 mm		2700 K	3000 K	4000 K		DALI 2.0 / D16 / Push-Dim	white	light grey	black	15°	30°	45°		
x					x					7.2 W	x			860 lm				x	x			565463	€ 136.95
x					x					7.2 W	x			860 lm				x		x		565464	€ 136.95
x					x					7.2 W	x			860 lm				x			x	565465	€ 136.95
x					x					7.2 W	x			860 lm			x		x			565466	€ 136.95
x					x					7.2 W	x			860 lm			x			x		565467	€ 136.95
x					x					7.2 W	x			860 lm			x				x	565468	€ 136.95
x					x					7.2 W	x			860 lm		x			x			565469	€ 136.95
x					x					7.2 W	x			860 lm		x				x		565470	€ 136.95
x					x					7.2 W	x			860 lm		x					x	565471	€ 136.95
x					x					7.2 W	x			860 lm	x			x	x			565472	€ 186.95
x					x					7.2 W	x			860 lm	x			x		x		565473	€ 186.95
x					x					7.2 W	x			860 lm	x			x			x	565474	€ 186.95
x					x					7.2 W	x			860 lm	x		x		x			565475	€ 186.95
x					x					7.2 W	x			860 lm	x		x			x		565476	€ 186.95
x					x					7.2 W	x			860 lm	x		x				x	565477	€ 186.95
x					x					7.2 W	x			860 lm	x	x			x			565478	€ 186.95
x					x					7.2 W	x			860 lm	x	x				x		565479	€ 186.95
x					x					7.2 W	x			860 lm	x	x					x	565480	€ 186.95
x					x					7.2 W		x		870 lm				x	x			565481	€ 136.95
x					x					7.2 W		x		870 lm				x		x		565482	€ 136.95
x					x					7.2 W		x		870 lm				x			x	565483	€ 136.95
x					x					7.2 W		x		870 lm			x		x			565484	€ 136.95
x					x					7.2 W		x		870 lm			x			x		565485	€ 136.95
x					x					7.2 W		x		870 lm			x				x	565486	€ 136.95
x					x					7.2 W		x		870 lm		x			x			565487	€ 136.95
x					x					7.2 W		x		870 lm		x				x		565488	€ 136.95
x					x					7.2 W		x		870 lm		x					x	565489	€ 136.95
x					x					7.2 W		x		870 lm	x			x	x			565490	€ 186.95
x					x					7.2 W		x		870 lm	x			x		x		565491	€ 186.95
x					x					7.2 W		x		870 lm	x			x			x	565492	€ 186.95
x					x					7.2 W		x		870 lm	x		x		x			565493	€ 186.95
x					x					7.2 W		x		870 lm	x		x			x		565494	€ 186.95
x					x					7.2 W		x		870 lm	x		x				x	565495	€ 186.95
x					x					7.2 W		x		870 lm	x	x			x			565496	€ 186.95
x					x					7.2 W		x		870 lm	x	x				x		565497	€ 186.95
x					x					7.2 W		x		870 lm	x	x					x	565498	€ 186.95
x					x					7.2 W			x	905 lm				x	x			565499	€ 136.95
x					x					7.2 W			x	905 lm				x		x		565500	€ 136.95
x					x					7.2 W			x	905 lm				x			x	565501	€ 136.95
x					x					7.2 W			x	905 lm			x		x			565502	€ 136.95
x					x					7.2 W			x	905 lm			x			x		565503	€ 136.95
x					x					7.2 W			x	905 lm			x				x	565504	€ 136.95
x					x					7.2 W			x	905 lm		x			x			565505	€ 136.95
x					x					7.2 W			x	905 lm		x				x		565506	€ 136.95
x					x					7.2 W			x	905 lm		x					x	565507	€ 136.95
x					x					7.2 W			x	905 lm	x			x	x			565508	€ 186.95
x					x					7.2 W			x	905 lm	x			x		x		565509	€ 186.95
x					x					7.2 W			x	905 lm	x			x			x	565510	€ 186.95
x					x					7.2 W			x	905 lm	x		x		x			565511	€ 186.95
x					x					7.2 W			x	905 lm	x		x			x		565512	€ 186.95
x					x					7.2 W			x	905 lm	x		x				x	565513	€ 186.95
x					x					7.2 W			x	905 lm	x	x			x			565514	€ 186.95
x					x					7.2 W			x	905 lm	x	x				x		565515	€ 186.95
x					x					7.2 W			x	905 lm	x	x					x	565516	€ 186.95

TARVOS 100

Ø x H					Cut Out Ø					Power rating	Colour temperature			Luminous flux	Dimmable	Housing Color			Light Beam Angle			Article	Price
85 x 86 mm	115 x 75 mm	165 x 113 mm	205 x 144 mm	255 x 160 mm	68 mm	100 mm	150 mm	190 mm	240 mm		2700 K	3000 K	4000 K			DALI 2.0 / DT6 / Push-Dim	white	light grey	black	15°	30°		
x	x				x	x				10.8 W	x			1290 lm			x	x			565517	€ 152.95	
	x					x				10.8 W	x			1290 lm			x		x		565518	€ 152.95	
	x					x				10.8 W	x			1290 lm			x			x	565519	€ 152.95	
	x					x				10.8 W	x			1290 lm		x		x			565520	€ 152.95	
	x					x				10.8 W	x			1290 lm		x			x		565521	€ 152.95	
	x					x				10.8 W	x			1290 lm		x				x	565522	€ 152.95	
	x					x				10.8 W	x			1290 lm		x		x			565523	€ 152.95	
	x					x				10.8 W	x			1290 lm		x			x		565524	€ 152.95	
	x					x				10.8 W	x			1290 lm		x				x	565525	€ 152.95	
	x					x				10.8 W	x			1290 lm	x		x	x			565526	€ 201.95	
	x					x				10.8 W	x			1290 lm	x		x		x		565527	€ 201.95	
	x					x				10.8 W	x			1290 lm	x		x			x	565528	€ 201.95	
	x					x				10.8 W	x			1290 lm	x	x		x			565529	€ 201.95	
	x					x				10.8 W	x			1290 lm	x	x			x		565530	€ 201.95	
	x					x				10.8 W	x			1290 lm	x	x				x	565531	€ 201.95	
	x					x				10.8 W	x			1290 lm	x	x					565532	€ 201.95	
	x					x				10.8 W	x			1290 lm	x	x			x		565533	€ 201.95	
	x					x				10.8 W	x			1290 lm	x	x				x	565534	€ 201.95	
	x					x				10.8 W		x		1310 lm			x	x			565535	€ 152.95	
	x					x				10.8 W		x		1310 lm			x		x		565536	€ 152.95	
	x					x				10.8 W		x		1310 lm			x			x	565537	€ 152.95	
	x					x				10.8 W		x		1310 lm			x				565538	€ 152.95	
	x					x				10.8 W		x		1310 lm			x			x	565539	€ 152.95	
	x					x				10.8 W		x		1310 lm			x			x	565540	€ 152.95	
	x					x				10.8 W		x		1310 lm		x					565541	€ 152.95	
	x					x				10.8 W		x		1310 lm		x				x	565542	€ 152.95	
	x					x				10.8 W		x		1310 lm		x					x	565543	€ 152.95
	x					x				10.8 W		x		1310 lm	x		x	x			565544	€ 201.95	
	x					x				10.8 W		x		1310 lm	x		x		x		565545	€ 201.95	
	x					x				10.8 W		x		1310 lm	x		x			x	565546	€ 201.95	
	x					x				10.8 W		x		1310 lm	x		x				565547	€ 201.95	
	x					x				10.8 W		x		1310 lm	x		x			x	565548	€ 201.95	
	x					x				10.8 W		x		1310 lm	x		x				x	565549	€ 201.95
	x					x				10.8 W		x		1310 lm	x	x			x		565550	€ 201.95	
	x					x				10.8 W		x		1310 lm	x	x				x	565551	€ 201.95	
	x					x				10.8 W		x		1310 lm	x	x					x	565552	€ 201.95
	x					x				10.8 W			x	1360 lm			x	x			565553	€ 152.95	
	x					x				10.8 W			x	1360 lm			x		x		565554	€ 152.95	
	x					x				10.8 W			x	1360 lm			x			x	565555	€ 152.95	
	x					x				10.8 W			x	1360 lm			x				565556	€ 152.95	
	x					x				10.8 W			x	1360 lm			x			x	565557	€ 152.95	
	x					x				10.8 W			x	1360 lm			x				x	565558	€ 152.95
	x					x				10.8 W			x	1360 lm		x					565559	€ 152.95	
	x					x				10.8 W			x	1360 lm		x				x	565560	€ 152.95	
	x					x				10.8 W			x	1360 lm		x					x	565561	€ 152.95
	x					x				10.8 W			x	1360 lm	x		x	x			565562	€ 201.95	
	x					x				10.8 W			x	1360 lm	x		x			x	565563	€ 201.95	
	x					x				10.8 W			x	1360 lm	x		x				x	565564	€ 201.95
	x					x				10.8 W			x	1360 lm	x		x				565565	€ 201.95	
	x					x				10.8 W			x	1360 lm	x		x				565566	€ 201.95	
	x					x				10.8 W			x	1360 lm	x		x				x	565567	€ 201.95
	x					x				10.8 W			x	1360 lm	x	x					565568	€ 201.95	
	x					x				10.8 W			x	1360 lm	x	x				x	565569	€ 201.95	
	x					x				10.8 W			x	1360 lm	x	x					x	565570	€ 201.95

TARVOS 150

Ø x H					Cut Out Ø					Power rating	Colour temperature			Luminous flux	Dimmable	Housing Color			Light Beam Angle			Article	Price
85 x 86 mm	115 x 75 mm	165 x 113 mm	205 x 144 mm	255 x 160 mm	68 mm	100 mm	150 mm	190 mm	240 mm		2700 K	3000 K	4000 K		DALI 2.0 / D16 / Push-Dim	white	light grey	black	15°	30°	45°		
		x					x			14.4 W	x			1720 lm				x	x			565571	€ 177.95
		x					x			14.4 W	x			1720 lm				x		x		565572	€ 177.95
		x					x			14.4 W	x			1720 lm				x			x	565573	€ 177.95
		x					x			14.4 W	x			1720 lm			x		x			565574	€ 177.95
		x					x			14.4 W	x			1720 lm			x			x		565575	€ 177.95
		x					x			14.4 W	x			1720 lm			x				x	565576	€ 177.95
		x					x			14.4 W	x			1720 lm		x			x			565577	€ 177.95
		x					x			14.4 W	x			1720 lm		x				x		565578	€ 177.95
		x					x			14.4 W	x			1720 lm		x					x	565579	€ 177.95
		x					x			14.4 W	x			1720 lm	x			x	x			565580	€ 226.95
		x					x			14.4 W	x			1720 lm	x			x		x		565581	€ 226.95
		x					x			14.4 W	x			1720 lm	x			x			x	565582	€ 226.95
		x					x			14.4 W	x			1720 lm	x		x		x			565583	€ 226.95
		x					x			14.4 W	x			1720 lm	x		x			x		565584	€ 226.95
		x					x			14.4 W	x			1720 lm	x		x				x	565585	€ 226.95
		x					x			14.4 W	x			1720 lm	x	x			x			565586	€ 226.95
		x					x			14.4 W	x			1720 lm	x	x				x		565587	€ 226.95
		x					x			14.4 W	x			1720 lm	x	x					x	565588	€ 226.95
		x					x			14.4 W		x		1750 lm				x	x			565589	€ 177.95
		x					x			14.4 W		x		1750 lm				x		x		565590	€ 177.95
		x					x			14.4 W		x		1750 lm				x			x	565591	€ 177.95
		x					x			14.4 W		x		1750 lm			x		x			565592	€ 177.95
		x					x			14.4 W		x		1750 lm			x			x		565593	€ 177.95
		x					x			14.4 W		x		1750 lm			x				x	565594	€ 177.95
		x					x			14.4 W		x		1750 lm		x			x			565595	€ 177.95
		x					x			14.4 W		x		1750 lm		x				x		565596	€ 177.95
		x					x			14.4 W		x		1750 lm		x					x	565597	€ 177.95
		x					x			14.4 W		x		1750 lm	x			x	x			565598	€ 226.95
		x					x			14.4 W		x		1750 lm	x			x		x		565599	€ 226.95
		x					x			14.4 W		x		1750 lm	x			x			x	565600	€ 226.95
		x					x			14.4 W		x		1750 lm	x		x		x			565601	€ 226.95
		x					x			14.4 W		x		1750 lm	x		x			x		565602	€ 226.95
		x					x			14.4 W		x		1750 lm	x		x				x	565603	€ 226.95
		x					x			14.4 W		x		1750 lm	x	x			x			565604	€ 226.95
		x					x			14.4 W		x		1750 lm	x	x				x		565605	€ 226.95
		x					x			14.4 W		x		1750 lm	x	x					x	565606	€ 226.95
		x					x			14.4 W			x	1810 lm				x	x			565607	€ 177.95
		x					x			14.4 W			x	1810 lm				x		x		565608	€ 177.95
		x					x			14.4 W			x	1810 lm				x			x	565609	€ 177.95
		x					x			14.4 W			x	1810 lm			x		x			565610	€ 177.95
		x					x			14.4 W			x	1810 lm			x			x		565611	€ 177.95
		x					x			14.4 W			x	1810 lm			x				x	565612	€ 177.95
		x					x			14.4 W			x	1810 lm		x			x			565613	€ 177.95
		x					x			14.4 W			x	1810 lm		x				x		565614	€ 177.95
		x					x			14.4 W			x	1810 lm		x					x	565615	€ 177.95
		x					x			14.4 W			x	1810 lm	x			x	x			565616	€ 226.95
		x					x			14.4 W			x	1810 lm	x			x		x		565617	€ 226.95
		x					x			14.4 W			x	1810 lm	x			x			x	565618	€ 226.95
		x					x			14.4 W			x	1810 lm	x		x		x			565619	€ 226.95
		x					x			14.4 W			x	1810 lm	x		x			x		565620	€ 226.95
		x					x			14.4 W			x	1810 lm	x		x				x	565621	€ 226.95
		x					x			14.4 W			x	1810 lm	x	x			x			565622	€ 226.95
		x					x			14.4 W			x	1810 lm	x	x				x		565623	€ 226.95
		x					x			14.4 W			x	1810 lm	x	x					x	565624	€ 226.95

TARVOS 190

Ø x H					Cut Out Ø					Power rating	Colour temperature			Luminous flux	Dimmable DALI 2.0 / DT6 / Push-Dim	Housing Color			Light Beam Angle			Article	Price
85 x 86 mm	115 x 75 mm	165 x 113 mm	205 x 144 mm	255 x 160 mm	68 mm	100 mm	150 mm	190 mm	240 mm		2700 K	3000 K	4000 K			white	light grey	black	15°	30°	45°		
			x					x		21.6 W	x			1590 lm				x	x			565625	€ 191.95
			x					x		21.6 W	x			1590 lm				x		x		565626	€ 191.95
			x					x		21.6 W	x			1590 lm				x			x	565627	€ 191.95
			x					x		21.6 W	x			1590 lm			x		x			565628	€ 191.95
			x					x		21.6 W	x			1590 lm			x			x		565629	€ 191.95
			x					x		21.6 W	x			1590 lm			x				x	565630	€ 191.95
			x					x		21.6 W	x			1590 lm		x			x			565631	€ 191.95
			x					x		21.6 W	x			1590 lm		x				x		565632	€ 191.95
			x					x		21.6 W	x			1590 lm		x					x	565633	€ 191.95
			x					x		21.6 W	x			1590 lm	x			x	x			565634	€ 242.95
			x					x		21.6 W	x			1590 lm	x			x		x		565635	€ 242.95
			x					x		21.6 W	x			1590 lm	x			x			x	565636	€ 242.95
			x					x		21.6 W	x			1590 lm	x		x		x			565637	€ 242.95
			x					x		21.6 W	x			1590 lm	x		x			x		565638	€ 242.95
			x					x		21.6 W	x			1590 lm	x		x				x	565639	€ 242.95
			x					x		21.6 W	x			1590 lm	x	x			x			565640	€ 242.95
			x					x		21.6 W	x			1590 lm	x	x				x		565641	€ 242.95
			x					x		21.6 W	x			1590 lm	x	x					x	565642	€ 242.95
			x					x		21.6 W		x		2630 lm				x	x			565643	€ 191.95
			x					x		21.6 W		x		2630 lm				x		x		565644	€ 191.95
			x					x		21.6 W		x		2630 lm				x			x	565645	€ 191.95
			x					x		21.6 W		x		2630 lm			x		x			565646	€ 191.95
			x					x		21.6 W		x		2630 lm			x			x		565647	€ 191.95
			x					x		21.6 W		x		2630 lm			x				x	565648	€ 191.95
			x					x		21.6 W		x		2630 lm		x			x			565649	€ 191.95
			x					x		21.6 W		x		2630 lm		x				x		565650	€ 191.95
			x					x		21.6 W		x		2630 lm		x					x	565651	€ 191.95
			x					x		21.6 W		x		2630 lm	x			x	x			565652	€ 242.95
			x					x		21.6 W		x		2630 lm	x			x		x		565653	€ 242.95
			x					x		21.6 W		x		2630 lm	x			x			x	565654	€ 242.95
			x					x		21.6 W		x		2630 lm	x		x		x			565655	€ 242.95
			x					x		21.6 W		x		2630 lm	x		x			x		565656	€ 242.95
			x					x		21.6 W		x		2630 lm	x		x				x	565657	€ 242.95
			x					x		21.6 W		x		2630 lm	x	x			x			565658	€ 242.95
			x					x		21.6 W		x		2630 lm	x	x				x		565659	€ 242.95
			x					x		21.6 W		x		2630 lm	x	x					x	565660	€ 242.95
			x					x		21.6 W			x	2720 lm				x	x			565661	€ 191.95
			x					x		21.6 W			x	2720 lm				x		x		565662	€ 191.95
			x					x		21.6 W			x	2720 lm				x			x	565663	€ 191.95
			x					x		21.6 W			x	2720 lm			x		x			565664	€ 191.95
			x					x		21.6 W			x	2720 lm			x			x		565665	€ 191.95
			x					x		21.6 W			x	2720 lm			x				x	565666	€ 191.95
			x					x		21.6 W			x	2720 lm		x			x			565667	€ 191.95
			x					x		21.6 W			x	2720 lm		x				x		565668	€ 191.95
			x					x		21.6 W			x	2720 lm		x					x	565669	€ 191.95
			x					x		21.6 W			x	2720 lm	x			x	x			565670	€ 242.95
			x					x		21.6 W			x	2720 lm	x			x		x		565671	€ 242.95
			x					x		21.6 W			x	2720 lm	x			x			x	565672	€ 242.95
			x					x		21.6 W			x	2720 lm	x		x		x			565673	€ 242.95
			x					x		21.6 W			x	2720 lm	x		x			x		565674	€ 242.95
			x					x		21.6 W			x	2720 lm	x		x				x	565675	€ 242.95
			x					x		21.6 W			x	2720 lm	x	x			x			565676	€ 242.95
			x					x		21.6 W			x	2720 lm	x	x				x		565677	€ 242.95
			x					x		21.6 W			x	2720 lm	x	x					x	565678	€ 242.95

TARVOS 240

Ø x H					Cut Out Ø					Power rating	Colour temperature			Luminous flux	Dimmable	Housing Color			Light Beam Angle			Article	Price	
85 x 86 mm	115 x 75 mm	165 x 113 mm	205 x 144 mm	255 x 160 mm	68 mm	100 mm	150 mm	190 mm	240 mm		2700 K	3000 K	4000 K			DALI 2.0 / DT6 / Push-Dim	white	light grey	black	15°	30°			45°
				x					x	25.2 W	x			3020 lm			x	x				565679	€ 226.95	
				x					x	25.2 W	x			3020 lm			x		x				565680	€ 226.95
				x					x	25.2 W	x			3020 lm			x			x			565681	€ 226.95
				x					x	25.2 W	x			3020 lm		x		x					565682	€ 226.95
				x					x	25.2 W	x			3020 lm		x			x				565683	€ 226.95
				x					x	25.2 W	x			3020 lm		x				x			565684	€ 226.95
				x					x	25.2 W	x			3020 lm		x		x					565685	€ 226.95
				x					x	25.2 W	x			3020 lm		x			x				565686	€ 226.95
				x					x	25.2 W	x			3020 lm		x				x			565687	€ 226.95
				x					x	25.2 W	x		x	3020 lm	x		x	x					565688	€ 290.95
				x					x	25.2 W	x		x	3020 lm	x		x		x				565689	€ 290.95
				x					x	25.2 W	x			3020 lm	x		x			x			565690	€ 290.95
				x					x	25.2 W	x			3020 lm	x	x		x					565691	€ 290.95
				x					x	25.2 W	x			3020 lm	x		x		x				565692	€ 290.95
				x					x	25.2 W	x			3020 lm	x		x			x			565693	€ 290.95
				x					x	25.2 W	x			3020 lm	x	x		x					565694	€ 290.95
				x					x	25.2 W	x			3020 lm	x	x			x				565695	€ 290.95
				x					x	25.2 W	x			3020 lm	x	x				x			565696	€ 290.95
				x					x	25.2 W		x		3070 lm				x	x				565697	€ 226.95
				x					x	25.2 W		x		3070 lm				x		x			565698	€ 226.95
				x					x	25.2 W		x		3070 lm				x			x		565699	€ 226.95
				x					x	25.2 W		x		3070 lm		x			x				565700	€ 226.95
				x					x	25.2 W		x		3070 lm			x		x				565701	€ 226.95
				x					x	25.2 W		x		3070 lm			x			x			565702	€ 226.95
				x					x	25.2 W		x		3070 lm		x			x				565703	€ 226.95
				x					x	25.2 W		x		3070 lm		x				x			565704	€ 226.95
				x					x	25.2 W		x		3070 lm		x					x		565705	€ 226.95
				x					x	25.2 W		x		3070 lm	x			x	x				565706	€ 290.95
				x					x	25.2 W		x		3070 lm	x			x		x			565707	€ 290.95
				x					x	25.2 W		x		3070 lm	x			x			x		565708	€ 290.95
				x					x	25.2 W		x		3070 lm	x		x		x				565709	€ 290.95
				x					x	25.2 W		x		3070 lm	x		x			x			565710	€ 290.95
				x					x	25.2 W		x		3070 lm	x		x				x		565711	€ 290.95
				x					x	25.2 W		x		3070 lm	x	x			x				565712	€ 290.95
				x					x	25.2 W		x		3070 lm	x	x				x			565713	€ 290.95
				x					x	25.2 W		x		3070 lm	x	x					x		565714	€ 290.95
				x					x	25.2 W			x	3170 lm				x	x				565715	€ 226.95
				x					x	25.2 W			x	3170 lm				x		x			565716	€ 226.95
				x					x	25.2 W			x	3170 lm				x			x		565717	€ 226.95
				x					x	25.2 W			x	3170 lm			x		x				565718	€ 226.95
				x					x	25.2 W			x	3170 lm			x			x			565719	€ 226.95
				x					x	25.2 W			x	3170 lm			x				x		565720	€ 226.95
				x					x	25.2 W			x	3170 lm		x			x				565721	€ 226.95
				x					x	25.2 W			x	3170 lm		x				x			565722	€ 226.95
				x					x	25.2 W			x	3170 lm		x					x		565723	€ 226.95
				x					x	25.2 W			x	3170 lm	x			x	x				565724	€ 290.95
				x					x	25.2 W			x	3170 lm	x			x		x			565725	€ 290.95
				x					x	25.2 W			x	3170 lm	x			x			x		565726	€ 290.95
				x					x	25.2 W			x	3170 lm	x		x		x				565727	€ 290.95
				x					x	25.2 W			x	3170 lm	x		x			x			565728	€ 290.95
				x					x	25.2 W			x	3170 lm	x		x				x		565729	€ 290.95
				x					x	25.2 W			x	3170 lm	x	x			x				565730	€ 290.95
				x					x	25.2 W			x	3170 lm	x	x				x			565731	€ 290.95
				x					x	25.2 W			x	3170 lm	x	x					x		565732	€ 290.95





SLIM

Matching recessed spotlights are available for our SLIM luminaire series. The die-cast aluminium luminaire body is always the same size [300 x 39 mm]. The SLIM recessed spotlights have the standard installation dimension of 68 mm. This makes the single-flame recessed spotlights particularly suitable for sales areas, reception areas or even hotels and restaurants.





SLIM

- Glare-free, due to low UGR value (<19)
- Slim design with only 39 mm diameter
- Incl. silver-coloured reflector ring
- Installation diameter 68 mm

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Installation Depth	25 mm
Colour Temperature	2700 K	Light Beam Angle	36 Degree
Luminous Flux	500 lm	Rotation Angle	300 Degree
Height	194 mm	Swivelling Angle	60 Degree
Ø	80 mm	Cut Out Ø	68 mm
Power	5 W	Control	Leading-edge dimmer, Trailing-edge dimmer
Rated Input Voltage	220-240 V/AC	CRI (Ra)	90
Power Supply Unit incl.	Yes		

Article	Housing Color	Price
565408	White	€ 47.95
565409	Black	€ 47.95



Accessories

930744	Reflector ring white for Slim series		€ 3.95
930745	Reflector ring black for Slim series		€ 3.95
930746	Reflector ring gold-coloured for Slim series		€ 4.75
930747	24° lens for Slim series		€ 3.95
930748	36° lens for Slim series		€ 3.95
930749	60° lens for Slim series		€ 3.95



5-year guarantee
Benefit from the maximum quality promise:
All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.




UNI 2

- „Glow“ effect on reflector ring
- Can be rotated and swivelled
- Can be combined with a power supply unit as desired [excl.]

Application Area


Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Light Beam Angle	36 Degree
Colour Temperature	3000 K	Swivelling Angle	85 Degree
Height	84 mm	Cut Out Ø	125 mm
Ø	139 mm	Control	Dimmable via optional power supply unit
Power	12 W	CRI (Ra)	90
Rated Input Voltage	33-34 V/DC	Rated Current	350 mA
Power Supply Unit incl.	No		
Installation Depth	90 mm		



565343

Article	Housing Color	Colour Temperature	Luminous Flux	EEL	Price
565343	White	3000 K	760 lm	F	€ 95.95
565361	Black	3000 K	1010 lm	F	€ 95.95



Accessories

930305	36° reflector for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 2.95
930306	48° reflector for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930334	Rear white cover for Uni II series		€ 2.95
930335	Rear black cover for Uni II series		€ 2.45
930336	White heat sink cover for Uni II series		€ 2.95
930337	Black heat sink cover for Uni II series		€ 6.45
930338	Reflector ring white for Uni II series		€ 9.95
930339	Reflector ring black for Uni II series		€ 8.95
930340	Reflector ring gold for Uni II series		€ 8.95
930341	Reflector ring chrome for Uni II series		€ 8.95
180512	BASIC, CC, CC35018/18 W		€ 18.95
862191	BASIC, DIM, Multi CC, IE-25D		€ 51.95
862204	BASIC, DIM, CC, D35020UF/20 W		€ 31.95
930969	Reducing ring round 210/135 mm, Traffic white		€ 10.95
931045	Reducing ring round 210/135 mm, Signal white		€ 10.95



page 54



page 389






UNI 2 MINI

- „Glow“ effect on reflector ring
- Can be rotated and swivelled
- Can be combined with a power supply unit as desired [excl.]



Application Area
 Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Light Beam Angle	36 Degree
Colour Temperature	3000 K	Swivelling Angle	75 Degree
Height	80 mm	Cut Out Ø	95 mm
Ø	103 mm	Control	Dimmable via optional power supply unit
Power	9 W	CRI (Ra)	90
Rated Input Voltage	18-19 V/DC	Rated Current	500 mA
Power Supply Unit incl.	No		
Installation Depth	85 mm		



565342

Article	Housing Color	Colour Temperature	Luminous Flux	Price
565342	White	3000 K	765 lm	€ 79.95
565354	Black	3000 K	825 lm	€ 79.95



Accessories

930328	White heat sink cover for Uni II Mini series
930329	Black heat sink cover for Uni II Mini series
930330	Reflector ring white for Uni II Mini series
930331	Reflector ring black for Uni II Mini series
930332	Reflector ring gold for Uni II Mini series
930333	Reflector ring chrome for Uni II Mini series
930770	Reflector 24° for Uni II Mini series
930771	Reflector 48° for Uni II Mini series
180513	BASIC, CC, CC50018/18 W
862190	BASIC, DIM, Multi CC, IE-12D
862236	OCTO, DIM, CC, RSM-12-500T/12 W
930968	Reducing ring round 155/95 mm, Traffic white
931044	Reducing ring round 155/95 mm, Signal white

	€ 2.95
	€ 2.45
	€ 8.95
	€ 8.95
	€ 8.95
	€ 8.95
	€ 8.95
	€ 8.95
	€ 18.95
	€ 47.95
	€ 23.95
	€ 9.95
	€ 9.95



Onlineshop
 You can find more information about the products in the onlineshop:
 Detailed images, videos, project reports, LDT files, EPREL data sheets and more.




UNI 2 MAX

- „Glow“ effect on reflector ring
- Can be rotated and swivelled
- Can be combined with a power supply unit as desired [excl.]

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Light Beam Angle	36 Degree
Colour Temperature	3000 K	Swivelling Angle	85 Degree
Height	97 mm	Cut Out Ø	155 mm
Ø	165 mm	Control	Dimmable via optional power supply unit
Power	24 W	CRI (Ra)	90
Rated Input Voltage	34-35 V/DC	Rated Current	700 mA
Power Supply Unit incl.	No		
Installation Depth	100 mm		



565344

Article	Housing Color		Luminous Flux	Price
565351	Black	ww	2260 lm	€ 119.95
565344	White	ww	2380 lm	€ 119.95



Accessories

930390	24° reflector for Uni II Max		€ 8.95
930391	36° reflector for Uni II Max		€ 9.95
930392	48° reflector for Uni II Max		€ 8.95
930395	White heat sink cover for Uni II Max series		€ 8.95
930396	Black heat sink cover for Uni II Max series		€ 8.95
930397	Reflector ring white for Uni II Max series		€ 9.95
930398	Reflector ring black for Uni II Max series		€ 8.95
930399	Reflector ring gold for Uni II Max series		€ 11.95
862192	BASIC, DIM, Multi CC, IE-45D		€ 55.95
862198	BASIC, CC, V8-30-700 mA/30 W		€ 21.95
862208	BASIC, DIM, CC, D70040NTF/40 W		€ 37.95



Technical data sheet

New in the onlineshop: The technical data sheets offer even more information: Light and energy data, light distribution curves, dimensional drawings and more.

downlights



page 129



page 130



page 132



page 133



page 134



page 135



page 136




page 138



page 140







ACRUX PRO CCT

- through-wiring possible
- Integrated power supply unit for 230V direct connection
- splash-proof [downwards when installed]
- light colour adjustable in three stages
- power adjustable in 3 stages (only Ø 120 / 145 / 190)
- BEG eligible

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium, PA - Polyamide	Control	Trailing-edge dimmer, Leading-edge dimmer
Surface	Shiny	CRI (Ra)	90
Colour Temperature	2700/3000/4000 K	Accumulator/Battery Operated	No
Rated Input Voltage	220-240 V/AC	IK Protection Class	IK05
Light Beam Angle	100 Degree		

Article	Housing Color		Luminous Flux	Height	Ø	Power	Ø cut out	Price
565745	White		800/840/840 lm	50 mm	90 mm	7,0 W	68-75 mm	€ 19.95
565746	Black		800/840/840 lm	50 mm	90 mm	7,0 W	68-75 mm	€ 19.95
565747	White		1080/1130/1180 lm	55 mm	110 mm	9,0 W	82-95 mm	€ 23.95
565748	Black		1080/1130/1180 lm	55 mm	110 mm	9,0 W	82-95 mm	€ 23.95
565749	White		1800/1950/1875 lm	60 mm	145 mm	9/12/15 W	120-130 mm	€ 27.95
565750	Black		1800/1950/1875 lm	60 mm	145 mm	9/12/15 W	120-130 mm	€ 27.95
565751	White		2400/2600/2500 lm	72 mm	180 mm	12/16/20 W	145-155 mm	€ 31.95
565752	Black		2400/2600/2500 lm	72 mm	180 mm	12/16/20 W	145-155 mm	€ 31.95
565753	White		3600/3900/3750 lm	85 mm	230 mm	18/24/30 W	190-205 mm	€ 43.95
565754	Black		3600/3900/3750 lm	85 mm	230 mm	18/24/30 W	190-205 mm	€ 43.95



Accessories for **565745, 565746**

930967 Reducing ring round 130/70 mm, Traffic white



€ 7.95

931043 Reducing ring round 130/70 mm, Signal white



€ 7.95

Accessories for **565747, 565748**

930968 Reducing ring round 155/95 mm, Traffic white



€ 9.95

931044 Reducing ring round 155/95 mm, Signal white



€ 9.95

Accessories for **565749, 565750**

930969 Reducing ring round 210/135 mm, Traffic white



€ 10.95

931045 Reducing ring round 210/135 mm, Signal white



€ 10.95

Accessories for **565753, 565754**

930971 Reducing ring round 280/210 mm, Traffic white



€ 18.95

931047 Reducing ring round 280/210 mm, Signal white




€ 18.95



ANIK ROUND

The ANIK ROUND LED downlight is a high-quality lighting solution for a wide range of applications - for example in reception areas, offices, conference rooms, shops, sales areas, hotels, the catering trade and in bathrooms and WCs. It impresses with its uniform, wide light distribution with a beam angle of 120° and very high colour rendering ($R_a \geq 90$). Thanks to its IP44 downward protection rating when installed, it is also suitable for damp environments. The luminaire can be combined with external power supply units and is therefore dimmable. The ANIK ROUND series covers a wide power spectrum from 9 W to 30 W and is available in the colour temperatures 2700 K, 3000 K and 4000 K. With its flat design (19-22 mm high) and various diameters (144-398 mm), it is suitable for both new buildings and refurbishment projects.





ANIK ROUND


- splash-proof [downwards when installed]
- very low installation depth [max. 36mm]
- uniform and wide light distribution
- very high colour rendering



Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, Bathroom / WC

Housing	Aluminium, Steel, PMMA - Polymethyl methacrylate	Light Beam Angle	120 Degree
Surface	Powder-coated, Fine structure, Matt	Control	Dimmable via optional power supply unit
Rated Input Voltage	32-37 V/DC	CRI (Ra)	90
Power Supply Unit incl.	No	Accumulator/Battery Operated	No
		IK Protection Class	IK05



565410

Article	Housing Color	Colour Temp.	Luminous Flux	Rated Current	Height	Ø	Ø cut out	Power	Price
565410	☐ White	2700 K	1070 lm	260 mA	19 mm	144 mm	130 mm	9.0 W	€ 26.95
565413	☐ White	2700 K	1540 lm	350 mA	22 mm	173 mm	165 mm	12.0 W	€ 38.95
565416	☐ White	2700 K	2050 lm	500 mA	20 mm	234 mm	220 mm	17.0 W	€ 55.95
565419	☐ White	2700 K	4130 lm	900 mA	20 mm	398 mm	380 mm	30.0 W	€ 78.95
565411	☐ White	3000 K	1100 lm	260 mA	19 mm	144 mm	130 mm	9.0 W	€ 26.95
565414	☐ White	3000 K	1580 lm	350 mA	22 mm	173 mm	165 mm	12.0 W	€ 38.95
565417	☐ White	3000 K	2080 lm	500 mA	20 mm	234 mm	220 mm	17.0 W	€ 55.95
565420	☐ White	3000 K	4180 lm	900 mA	20 mm	398 mm	380 mm	30.0 W	€ 78.95
565412	☐ White	4000 K	1150 lm	260 mA	19 mm	144 mm	130 mm	9.0 W	€ 26.95
565415	☐ White	4000 K	1620 lm	350 mA	22 mm	173 mm	165 mm	12.0 W	€ 38.95
565418	☐ White	4000 K	2130 lm	500 mA	20 mm	234 mm	220 mm	17.0 W	€ 55.95
565421	☐ White	4000 K	4230 lm	900 mA	20 mm	398 mm	380 mm	30.0 W	€ 78.95



Accessories for 565410, 565411, 565412

862285 BASIC, DIM, CC, D26012UF/12W

€ 25.95

Accessories for 565410, 565411, 565412, 565413, 565414, 565415

862190 BASIC, DIM, Multi CC, IE-12D

€ 47.95

Accessories for 565413, 565414, 565415

180512 BASIC, CC, CC35018/18 W

€ 18.95

862203 BASIC, DIM, CC, D350012UF/12 W

€ 29.95

Accessories for 565416, 565417, 565418

862191 BASIC, DIM, Multi CC, IE-25D

€ 51.95

862205 BASIC, DIM, CC, D50020UF/20 W

€ 31.95



Accessories for 565419, 565420, 565421

862157 BASIC, CC, V8-40-900/40 W

€ 23.95

862192 BASIC, DIM, Multi CC, IE-45D

€ 55.95




ANIK ROUND HCL

- splash-proof [downwards when installed]
- very low installation depth [max. 36mm]
- suitable for 24V HCL control
- uniform and wide light distribution
- very high colour rendering
- individually combinable and dimmable with power supply

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, Bathroom / WC

Housing	Aluminium, Steel, PMMA - Polymethyl methacrylate	Light Beam Angle	120 Degree
Surface	Powder-coated, Fine structure, Matt	Control	Dimmable via optional controller
Colour Temperature	2700-6500 K	CRI (Ra)	90
Rated Input Voltage	24 V/DC	Accumulator/Battery Operated	No
Power Supply Unit incl.	No	IK Protection Class	IK05



Article	Housing Color		Luminous Flux	Height	Ø	Ø cut out	Power	Installation Depth	Price
565422	☐ White	 	850 lm	19 mm	144 mm	130 mm	9.0 W	16.5 mm	€ 36.95
565423	☐ White	 	1310 lm	22 mm	173 mm	165 mm	12.0 W	19.5 mm	€ 46.95
565424	☐ White	 	1850 lm	20 mm	234 mm	220 mm	17.0 W	17.5 mm	€ 63.95
565425	☐ White	 	3220 lm	20 mm	398 mm	380 mm	30.0 W	17 mm	€ 87.95



Accessories

843501	RF-smart, starter set LED single/CCT, 12-48 V, 20 A incl. remote control		€ 79.95
862166	BASIC, CV, Q8H-24-100 W		€ 77.95
843341	DALI 2 PWM dimmer CV 2CH 12-48V, 8A/CH, DT6		€ 67.95
843342	DALI 2 PWM dimmer CV 2CH 12-48V, 8A/CH, DT8		€ 67.95
843037	Casambi BT Dimmer CBU-PWM4 (CV, 12-24V, 6A DC)		€ 143.95
843279	MULTI-LED dimmer 1-4 channels, DMX/auto/manual, 12-48 V, 20 A		€ 91.95

Accessories for 565422

930967	Reducing ring round 130/70 mm, Traffic white		€ 7.95
931043	Reducing ring round 130/70 mm, Signal white		€ 7.95

Accessories for 565422, 565423



862234	FLAT, CV, UT 24 V/20 W		€ 20.95
--------	------------------------	---	---------

Accessories for 565424

862163	BASIC, CV, Q8H-24-40 W		€ 37.95
--------	------------------------	---	---------

Accessories for 565425

862122	FLAT, CV, UT 24 V/50 W		€ 41.95
--------	------------------------	---	---------




ANIK ROUND RGBW

- splash-proof [downwards when installed]
- very low installation depth [max. 36mm]
- suitable for 24V colour control
- uniform and wide light distribution
- very high colour rendering
- individually combinable and dimmable with power supply unit

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, Bathroom / WC

Housing	Aluminium, Steel, PMMA - Polymethyl methacrylate	Light Beam Angle	120 Degree
Surface	Powder-coated, Fine structure, Matt	Control	Dimmable via optional controller
Colour Temperature	3000 K	CRI (Ra)	90
Rated Input Voltage	24 V/DC	Accumulator/Battery Operated	No
Power Supply Unit incl.	No	IK Protection Class	IK05



565426

Article	Housing Color		Luminous Flux	Height	Ø	Ø cut out	Power	Installation Depth	Price
565426	☐ White		780 lm	19 mm	144 mm	130 mm	12.0 W	16.5 mm	€ 43.95
565427	☐ White		1180 lm	22 mm	173 mm	165 mm	16.0 W	19.5 mm	€ 54.95
565428	☐ White		1580 lm	20 mm	234 mm	220 mm	22.0 W	17.5 mm	€ 71.95
565429	☐ White		2360 lm	20 mm	398 mm	380 mm	36.0 W	17 mm	€ 95.95



Accessories

843502	RF-smart, starter set RGB/W/CCT, 12-48 V, 20 A incl. remote, IP20		€ 79.95
862166	BASIC, CV, Q8H-24-100 W		€ 77.95
843343	DALI 2 PWM dimmer CV 4CH 12-48V, 4A/CH, DT6		€ 75.95
843344	DALI 2 PWM dimmer CV 4CH 12-48V, 4A/CH, DT8		€ 75.95
843037	Casambi BT Dimmer CBU-PWM4 (CV, 12-24V, 6A DC)		€ 143.95
843279	MULTI-LED dimmer 1-4 channels, DMX/auto/manual, 12-48 V, 20 A		€ 91.95

Accessories for 565426

930967	Reducing ring round 130/70 mm, Traffic white		€ 7.95
931043	Reducing ring round 130/70 mm, Signal white		€ 7.95

Accessories for 565426, 565427

862234	FLAT, CV, UT 24 V/20 W		€ 20.95
---------------	------------------------	--	----------------

Accessories for 565428

862163	BASIC, CV, Q8H-24-40 W		€ 37.95
---------------	------------------------	--	----------------

Accessories for 565429

862122	FLAT, CV, UT 24 V/50 W		€ 41.95
---------------	------------------------	--	----------------




ANIK SQUARE

- splash-proof [downwards when installed]
- very low installation depth [max. 36mm]
- uniform and wide light distribution
- very high colour rendering

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, Bathroom / WC

Housing	Aluminium, Steel, PMMA - Polymethyl methacrylate	Light Beam Angle	120 Degree
Surface	Powder-coated, Fine structure, Matt	Control	Dimmable via optional power supply unit
Rated Input Voltage	32-37 V/DC	CRI (Ra)	90
Power Supply Unit incl.	No	Accumulator/Battery Operated	No
		IK Protection Class	IK05



Article	Housing Color	Colour Temperature	Luminous Flux	Length	Width	Height	cut out	Price
565430	☐ White	2700 K	1020 lm	110 mm	110 mm	20.5 mm	90x90 mm	€ 26.95
565433	☐ White	2700 K	2060 lm	180 mm	180 mm	21 mm	155x155 mm	€ 38.95
565436	☐ White	2700 K	2860 lm	237 mm	237 mm	21 mm	215x215 mm	€ 55.95
565439	☐ White	2700 K	3850 lm	398 mm	398 mm	20 mm	380x380 mm	€ 78.95
565431	☐ White	3000 K	1050 lm	110 mm	110 mm	20.5 mm	90x90 mm	€ 26.95
565434	☐ White	3000 K	2100 lm	180 mm	180 mm	21 mm	155x155 mm	€ 38.95
565437	☐ White	3000 K	2910 lm	237 mm	237 mm	21 mm	215x215 mm	€ 55.95
565440	☐ White	3000 K	3900 lm	398 mm	398 mm	20 mm	380x380 mm	€ 78.95
565432	☐ White	4000 K	1100 lm	110 mm	110 mm	20.5 mm	90x90 mm	€ 26.95
565435	☐ White	4000 K	2150 lm	180 mm	180 mm	21 mm	155x155 mm	€ 38.95
565438	☐ White	4000 K	2950 lm	237 mm	237 mm	21 mm	215x215 mm	€ 55.95
565441	☐ White	4000 K	4170 lm	398 mm	398 mm	20 mm	380x380 mm	€ 78.95



Accessories for **565430, 565431, 565432**

862190	BASIC, DIM, Multi CC, IE-12D		€ 47.95
862285	BASIC, DIM, CC, D26012UF/12W		€ 25.95

Accessories for **565433, 565434, 565435**

862205	BASIC, DIM, CC, D50020UF/20 W		€ 31.95
862226	FLAT, CC, UT500 mA/20 W		€ 22.95

Accessories for **565433, 565434, 565435, 565436, 565437, 565438**



862191	BASIC, DIM, Multi CC, IE-25D		€ 51.95
--------	------------------------------	--	---------

Accessories for **565436, 565437, 565438**

862198	BASIC, CC, V8-30-700 mA/30 W		€ 21.95
862208	BASIC, DIM, CC, D70040NTF/40 W		€ 37.95

Accessories for **565439, 565440, 565441**

862157	BASIC, CC, V8-40-900/40 W		€ 23.95
862192	BASIC, DIM, Multi CC, IE-45D		€ 55.95




ANIK SQUARE HCL

- splash-proof [downwards when installed]
- very low installation depth [max. 36mm]
- suitable for 24V HCL control
- uniform and wide light distribution
- very high colour rendering
- individually combinable and dimmable with power supply

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, Bathroom / WC

Housing	Aluminium, Steel, PMMA - Polymethyl methacrylate	Light Beam Angle	120 Degree
Surface	Powder-coated, Fine structure, Matt	Control	Dimmable via optional controller
Colour Temperature	2700-6500 K	CRI (Ra)	90
Rated Input Voltage	24 V/DC	Accumulator/Battery Operated	No
Power Supply Unit incl.	No	IK Protection Class	IK05



565443

Article	Housing Color		Luminous Flux	Length	Width	Height	cut out	Power	Price
565442	☐ White	☒ WW ☒ CW	860 lm	110 mm	110 mm	20.5 mm	90x90 mm	9.0 W	€ 36.95
565443	☐ White	☒ WW ☒ CW	1860 lm	180 mm	180 mm	21 mm	155x155 mm	17.0 W	€ 46.95
565444	☐ White	☒ WW ☒ CW	2620 lm	237 mm	237 mm	21 mm	215x215 mm	24.0 W	€ 63.95
565445	☐ White	☒ WW ☒ CW	3290 lm	398 mm	398 mm	20 mm	380x380 mm	30.0 W	€ 87.95



Accessories

843501	RF-smart, starter set LED single/CCT, 12-48 V, 20 A incl. remote control		€ 79.95
862166	BASIC, CV, Q8H-24-100 W		€ 77.95
843341	DALI 2 PWM dimmer CV 2CH 12-48V, 8A/CH, DT6		€ 67.95
843342	DALI 2 PWM dimmer CV 2CH 12-48V, 8A/CH, DT8		€ 67.95
843037	Casambi BT Dimmer CBU-PWM4 (CV, 12-24V, 6A DC)		€ 143.95
843279	MULTI-LED dimmer 1-4 channels, DMX/auto/manual, 12-48 V, 20 A		€ 91.95

Accessories for 565442


862234	FLAT, CV, UT 24 V/20 W		€ 20.95
930967	Reducing ring round 130/70 mm, Traffic white		€ 7.95
931043	Reducing ring round 130/70 mm, Signal white		€ 7.95

Accessories for 565443, 565444

862163	BASIC, CV, Q8H-24-40 W		€ 37.95
--------	------------------------	--	---------

Accessories for 565445

862122	FLAT, CV, UT 24 V/50 W		€ 41.95
--------	------------------------	--	---------



ANIK SQUARE RGBW

- splash-proof [downwards when installed]
- suitable for 24V colour control
- uniform and wide light distribution
- very high colour rendering
- can be individually combined and dimmed with power supply unit

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, Bathroom / WC

Housing	Aluminium, Steel, PMMA - Polymethyl methacrylate	Light Beam Angle	120 Degree
Surface	Powder-coated, Fine structure, Matt	Control	Dimmable via optional controller
Colour Temperature	3000 K	CRI (Ra)	90
Rated Input Voltage	24 V/DC	Accumulator/Battery Operated	No
Power Supply Unit incl.	No	IK Protection Class	IK05

Article	Housing Color	Luminous Flux	Length	Width	Height	cut out	Power	Price
565446	☐ White	960 lm	110 mm	110 mm	20.5 mm	90x90 mm	14.0 W	€ 43.95
565447	☐ White	1510 lm	180 mm	180 mm	21 mm	155x155 mm	23.0 W	€ 54.95
565448	☐ White	2010 lm	237 mm	237 mm	21 mm	215x215 mm	30.0 W	€ 71.95
565449	☐ White	2410 lm	398 mm	398 mm	20 mm	380x380 mm	37.0 W	€ 95.95



Accessories

843502	RF-smart, starter set RGBW/CCT, 12-48 V, 20 A incl. remote, IP20		€ 79.95
862166	BASIC, CV, Q8H-24-100 W		€ 77.95
843343	DALI 2 PWM dimmer CV 4CH 12-48V, 4A/CH, DT6		€ 75.95
843344	DALI 2 PWM dimmer CV 4CH 12-48V, 4A/CH, DT8		€ 75.95
843037	Casambi BT Dimmer CBU-PWM4 (CV, 12-24V, 6A DC)		€ 143.95
843279	MULTI-LED dimmer 1-4 channels, DMX/auto/manual, 12-48 V, 20 A		€ 91.95

Accessories for 565446

862234	FLAT, CV, UT 24 V/20 W		€ 20.95
930967	Reducing ring round 130/70 mm, Traffic white		€ 7.95
931043	Reducing ring round 130/70 mm, Signal white		€ 7.95

Accessories for 565447, 565448

862163	BASIC, CV, Q8H-24-40 W		€ 37.95
--------	------------------------	--	---------

Accessories for 565449

862122	FLAT, CV, UT 24 V/50 W		€ 41.95
--------	------------------------	--	---------



REDUCING RINGS FOR RECESSED LIGHTS

- Renovation solution for excessively large ceiling cut-outs
- Flexible adaptation to ceiling cut-outs
- suitable for 3-30 mm thick hollow ceilings
- toolless installation possible

Housing Height	Metal 1.7 mm		Installation Depth		41 mm		
Article	Housing Color	Length	Width	Ø	Cut Out Ø	Inner diameter	Price
930967	☐ Traffic white			130 mm	95 mm	70 mm	€ 7.95
931043	☐ Signal white			130 mm	95 mm	70 mm	€ 7.95
930968	☐ Traffic white			155 mm	120 mm	95 mm	€ 9.95
931044	☐ Signal white			155 mm	120 mm	95 mm	€ 9.95
930969	☐ Traffic white			210 mm	175 mm	135 mm	€ 10.95
931045	☐ Signal white			210 mm	175 mm	135 mm	€ 10.95
930970	☐ Traffic white			240 mm	205 mm	180 mm	€ 13.95
931046	☐ Signal white			240 mm	205 mm	180 mm	€ 13.95
930971	☐ Traffic white			280 mm	245 mm	210 mm	€ 18.95
931047	☐ Signal white			280 mm	245 mm	210 mm	€ 18.95
930972	☐ Traffic white	130 mm	130 mm		95 mm	70 mm	€ 7.95
931048	☐ Signal white	130 mm	130 mm		95 mm	70 mm	€ 7.95
930973	☐ Traffic white	155 mm	155 mm		120 mm	95 mm	€ 9.95
931049	☐ Signal white	155 mm	155 mm		120 mm	95 mm	€ 9.45
930974	☐ Traffic white	210 mm	210 mm		175 mm	135 mm	€ 10.95
931050	☐ Signal white	210 mm	210 mm		175 mm	135 mm	€ 10.95
930975	☐ Traffic white	240 mm	240 mm		205 mm	180 mm	€ 13.95
931051	☐ Signal white	240 mm	240 mm		205 mm	180 mm	€ 13.95
930976	☐ Traffic white	280 mm	280 mm		245 mm	210 mm	€ 18.95
931052	☐ Signal white	280 mm	280 mm		245 mm	210 mm	€ 18.95



MODULAR SYSTEM COB 31 W

The MODULAR recessed ceiling light range offers a wide range of possible applications. Whether virtually invisible or with a prominent frame - these modules are as flexible as you want them to be. By replacing the reflectors, different light beams can be created and by using filters / diffusers, you can individually select or retrofit your lighting mood. We offer the LED modules in warm and neutral white. This gives you the option of adapting the individual elements to local requirements in order to create your perfect lighting situation.






MODULAR SYSTEM COB 31 W

· Lamp can be customised with comprehensive accessories

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Power Supply Unit incl.	No
Height	103 mm	Light Beam Angle	60 Degree
Ø	85 mm	CRI (Ra)	90
Power	31 W	Rated Current	900 mA
Rated Input Voltage	35-36 V/DC		



565352

Article	Housing Color	Colour Temperature	Luminous Flux	Price
565352	Grey	3000 K	3660 lm	€ 99.95
565353	Grey	4000 K	3850 lm	€ 99.95



Accessories

930084	17° reflector for modular system COB		€ 15.95
930085	40° reflector for modular system COB		€ 15.95
930087	Frosted glass diffuser for modular system COB		€ 0.95
930088	Honeycomb filter for modular system COB		€ 4.95
930089	170 mm mounting ring for modular system COB, 150 mm		€ 17.95
930090	230 mm mounting ring for modular system COB, 220 mm		€ 23.95
930091	Swivel mounting ring for modular system COB, 115 mm		€ 25.95
930092	Cardan frame 1-fold for modular system COB, 130x130 mm		€ 29.95
930093	Cardan frame 2-fold for modular system COB, 130x240 mm		€ 53.95
930094	Cardan insert without frame for modular system COB		€ 71.95
930095	Cardan insert without frame for modular system COB		€ 71.95
930096	Cardan insert without frame for modular system COB		€ 92.95
930097	Cardan insert without frame for modular system COB		€ 92.95
862157	BASIC, CC, V8-40-900/40 W		€ 23.95
862264	BASIC, DIM, CC, D090040NTF/40 W		€ 37.95
862192	BASIC, DIM, Multi CC, IE-45D		€ 55.95



Lighting design

Interested in our lighting design service?


Your contact person will be happy to answer any questions you may have.



ZAURAK

Recessed ceiling lights can be subtly integrated into private and commercial spaces, yet when it comes to replacing, the existing ceiling cut-out can present a problem. The ZAURAK series comes with an adjustable mounting clip, which can be used with larger and smaller ceiling cut-outs. In addition, the ZAURAK has a low installation depth for universal use. Two exchangeable cover rings in silver and black are included in the scope of delivery.






ZAURAK

- Light colour adjustable in three stages
- Output adjustable in two stages
- Adjustable recess dimension 65-270 mm [model-dependent]
- Ideal renovation solution for ceiling recesses
- Incl. two colour rings [black/silver]

Application Area

Bathroom / WC, Corridor / stairwell, Home / Living, Refurbishment

Housing	Plastic	Light Beam Angle	110 Degree
Colour Temperature	3000/4000/5700 K	CRI (Ra)	80
Rated Input Voltage	220-240 V/AC	IK Protection Class	IK03
Power Supply Unit incl.	Yes		



565327


Article	Housing Color		Luminous Flux	Height	Ø	Power Selectable	Cut Out Ø	Price
565327	☐ White	WW NW CW	900/960/840 lm	20.5 mm	180 mm	8.0 W / 12.0 W	65-160 mm	€ 37.95
565328	☐ White	WW NW CW	1440/1710/1530 lm	21.5 mm	220 mm	12.0 W / 18.0 W	120-200 mm	€ 45.95
565329	☐ White	WW NW CW	2125/2375/2250 lm	25 mm	300 mm	18.0 W / 25.0 W	150-270 mm	€ 63.95




Onlineshop

You can find more information about the products in the onlineshop:
Detailed images, videos, project reports, LDT files, EPREL data sheets and more.


insert panels



☐ page 146




☐ page 147




☐ page 148



☐ page 149



☐ page 152




☐ page 153




☐ page 154




☐ page 156



☐ page 157



☐ page 158



☐ page 159



BACKLIGHT PANELS [SERIES: BASIC AND PRO] – TECHNOLOGY AND ADVANTAGES

Not every LED panel is built the same! There are technologies exist to produce homogeneous, flat and glare-free light. Each method has its own advantages and disadvantages and depends on the individual user requirements and budget needs. For example, the LED panels from our BASIC and PRO series rely on backlight technology.

In LED panels with backlight technology, the LEDs - behind the diffuser - are evenly spread over the entire panel surface and shine directly downwards. This design has a decisive advantage: no other components are required to direct the light in the desired direction [downwards], because the LEDs are already in the »right« position. The simpler design results above all in better efficiency and a lower price as well as a longer lifetime. At the same time you do not have to worry about possible yellowing of the light guide plate, which is often used in some cheaper sidelight panels.

The disadvantages: Due to their design, the LED elements require more space, which is why backlight panels are curved towards the backside and therefore have a higher thickness with it. For this [optical] reason, backlight panels are only suitable to a limited extent for suspension from the ceiling. Their smaller beam angle [approx. 90°] results in a smaller illuminated area.

advantages

- better efficiency
- longer lifetime
- lower costs
- much more attractive price/performance ratio
- no light guide plates that are prone to yellowing

disadvantages

- higher thickness
- lower beam angle [approx. 90°]
- less suitable for suspension
- thicker packaging

In the following picture you can see the typical structure of a backlight LED panel.






BASIC

- BEG-eligible
- cost-effective, ready-to-connect solution
- for insertion into grid ceilings
- Mounting in surface-mounted and recessed frames possible
- Refurbishment solution for T5/T8 louvre luminaires
- Incl. power supply unit CC, 900mA, 33-38V, 36W

Application Area


Reception / Communication, Corridor / stairwell, Shop / Retail / Sales area, Health / care / hospital / practice, Education / school / lecture theatre, Refurbishment

Housing	Aluminium	Light Beam Angle	120 Degree
Height	32 mm	CRI (Ra)	80
Rated Input Voltage	220-240 V/AC	IK Protection Class	IK03
Power Supply Unit incl.	Yes	UGR	22



100140

Article	Housing Color	Colour Temperature	Luminous Flux	Length	Width	Power	Price
100143	☐ White	3000 K	3900 lm	1195 mm	295 mm	30.5 W	€ 39.95
100149	☐ White	3000 K	3900 lm	595 mm	595 mm	30.5 W	€ 34.95
100140	☐ White	3000 K	3900 lm	620 mm	620 mm	30.5 W	€ 35.95
100144	☐ White	4000 K	4320 lm	1195 mm	295 mm	30.5 W	€ 39.95
100150	☐ White	4000 K	4320 lm	595 mm	595 mm	30.5 W	€ 34.95
100141	☐ White	4000 K	4320 lm	620 mm	620 mm	33.0 W	€ 35.95



Accessories

930674	Safety cable		€ 3.95
930676	Mounting brackets for 600x600/300x1,200 mm backlit panel		€ 3.95
862192	BASIC, DIM, Multi CC, IE-45D		€ 55.95

Accessories for 100140, 100141


930665	Surface-mounted frame for 620x620 mm panel		€ 47.95
930668	Recessed frame for 620x620 mm panel		€ 45.95

Accessories for 100143, 100144

930666	Surface-mounted frame for 300x1,200 mm panel		€ 55.95
930669	Recessed frame for 300x1,200 mm panel		€ 53.95

Accessories for 100149, 100150

930664	Surface-mounted frame for 595x595 mm panel		€ 43.95
930667	Recessed frame for 595x595 mm panel		€ 41.95




BASIC FLEX

- Eligible for BEG German federal funding for energy-efficient buildings
- Light colour adjustable in three stages
- For insertion into grid ceilings
- Can be installed in surface-mount or flush-mount frames
- Renovation solution for T5/T8 louver lights
- Incl. CC power supply, 900mA, 33-38 V, 36 W

Application Area


Reception / Communication, Corridor / stairwell, Shop / Retail / Sales area, Health / care / hospital / practice, Education / school / lecture theatre, Refurbishment

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000/4000/6000 K	Light Beam Angle	120 Degree
Luminous Flux	3900/4320/4140 lm	CRI (Ra)	80
Power	30.5 W	IK Protection Class	IK03
Rated Input Voltage	220-240 V/AC	UGR	22



100142

Article	Housing Color		Length	Width	Height	Power	Power Selectable	Price
100145	☐ White	WW NW CW	295 mm	1195 mm	32 mm	30.5 W		€ 43.95
100142	☐ White	WW NW CW	620 mm	620 mm	25 mm		30.5 W	€ 38.95



Accessories


930674	Safety cable		€ 3.95
930676	Mounting brackets for 600x600/300x1,200 mm backlit panel		€ 3.95
862264	BASIC, DIM, CC, D090040NTF/40 W		€ 37.95
862192	BASIC, DIM, Multi CC, IE-45D		€ 55.95

Accessories for 100142

930665	Surface-mounted frame for 620x620 mm panel		€ 47.95
930668	Recessed frame for 620x620 mm panel		€ 45.95

Accessories for 100145

930666	Surface-mounted frame for 300x1,200 mm panel		€ 55.95
930669	Recessed frame for 300x1,200 mm panel		€ 53.95




BASIC OFFICE

- For insertion into grid ceilings
- Can be installed in surface-mount or flush-mount frames
- Suitable for workplaces with screens in accordance with EN 12464-1 BAP65
- Microprismatic surface structure
- Suitable for office spaces, reception rooms and hallways
- Good value, ready-to-install solution
- Incl. CC power supply, 900mA, 33-38 V, 36 W

Application Area


Office / conference, Reception / Communication, Corridor / stairwell, Shop / Retail / Sales area, Health / care / hospital / practice, Education / school / lecture theatre, Refurbishment

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	4000 K	Light Beam Angle	90 Degree
Luminous Flux	4000 lm	CRI (Ra)	80
Height	32 mm	IK Protection Class	IK03
Power	30.5 W	UGR	19
Rated Input Voltage	220-240 V/AC		



100146

Article	Housing Color		Length	Width	Height	Power	Power Selectable	Price
100147	☐ White	NW	295 mm	1195 mm	32 mm	30.5 W		€ 42.95
100151	☐ White	NW	595 mm	595 mm	25 mm		30.5 W	€ 37.95
100146	☐ White	NW	620 mm	620 mm	25 mm		30.5 W	€ 39.95



Accessories

930674	Safety cable		€ 3.95
930676	Mounting brackets for 600x600/300x1,200 mm backlit panel		€ 3.95
862264	BASIC, DIM, CC, D090040NTF/40 W		€ 37.95
862192	BASIC, DIM, Multi CC, IE-45D		€ 55.95

Accessories for 100146

930665	Surface-mounted frame for 620x620 mm panel		€ 47.95
930668	Recessed frame for 620x620 mm panel		€ 45.95

Accessories for 100147

930666	Surface-mounted frame for 300x1,200 mm panel		€ 55.95
930669	Recessed frame for 300x1,200 mm panel		€ 53.95

Accessories for 100151

930664	Surface-mounted frame for 595x595 mm panel		€ 43.95
930667	Recessed frame for 595x595 mm panel		€ 41.95




PRO OFFICE

- Eligible for BEG German federal funding for energy-efficient buildings
- For insertion into grid ceilings
- Can be installed in surface-mount or flush-mount frames
- Highly efficient solution
- Renovation solution for T5/T8 louver lights
- Suitable for office spaces/reception rooms/hallways
- Suitable for workplaces with screens in accordance with EN 12464-1 BAP65
- Microprismatic surface structure
- Can be combined with a power supply unit as desired [excl.]

Application Area

Office / conference, Reception / Communication, Corridor / stairwell, Shop / Retail / Sales area, Health / care / hospital / practice, Education / school / lecture theatre, Refurbishment

Housing	Aluminium	Control	Dimmable via optional power supply unit
Height	32 mm	CRI (Ra)	80
Power	17 W	Rated Current	450 mA
Rated Input Voltage	35-40 V/DC	IK Protection Class	IK03
Power Supply Unit incl.	No	UGR	19
Light Beam Angle	90 Degree		



100084

Article	Housing Color	Colour Temperature	Luminous Flux	Length	Width	EEI	Price
100084	☐ White	3000 K	2880 lm	620 mm	620 mm	D	€ 54.95
100089	☐ White	3000 K	2880 lm	1195 mm	295 mm	E	€ 56.95
100122	☐ White	4000 K	3200 lm	295 mm	1195 mm	D	€ 55.95
100148	☐ White	4000 K	3200 lm	595 mm	595 mm	C	€ 49.95
100088	☐ White	4000 K	3200 lm	620 mm	620 mm	D	€ 54.95



Accessories

930674	Safety cable		€ 3.95
930676	Mounting brackets for 600x600/300x1,200 mm backlit panel		€ 3.95
862257	QUICK, CC, 450 mA, 30-40 V, 20 W		€ 29.95
862191	BASIC, DIM, Multi CC, IE-25D		€ 51.95

Accessories for 100084, 100088

930665	Surface-mounted frame for 620x620 mm panel		€ 47.95
930668	Recessed frame for 620x620 mm panel		€ 45.95

Accessories for 100089, 100122

930666	Surface-mounted frame for 300x1,200 mm panel		€ 55.95
930669	Recessed frame for 300x1,200 mm panel		€ 53.95

Accessories for 100148

930664	Surface-mounted frame for 595x595 mm panel		€ 43.95
930667	Recessed frame for 595x595 mm panel		€ 41.95

SIDELIGHT-PANELS [SERIES: STANDARD] – TECHNOLOGY AND ADVANTAGES

Not every LED panel is built the same! There are technologies exist to produce homogeneous, flat light. Each method has its own advantages and disadvantages and depends on the individual user requirements and budget needs. For example LED panels from our standard series use sidelight technology.

Unlike backlight panels, the LEDs are not spread over the entire panel surface, but are located on the side of the aluminum frame of the luminaire. Depending on the model and version, only one, two or all four sides are equipped with LED stripes. What all edgelit or sidelight panels have in common is that the LEDs shine into the center of the panel. The light must therefore still be redirected in order to radiate downwards.

The most important element here is the light guide plate. This is usually made of acrylic glass [also PMMA (polymethyl methacrylate), a transparent thermoplastic material], which distributes the light evenly over the entire surface and deflects it downwards. In addition, acrylic glass does not yellow with age. In addition to the light guide plate, which deflects the light by means of small laser-engraved dots, the additional reflector, similar to the one the backlight panel, and the diffuser also contribute to the significantly more complex structure of a sidelight panel [see picture to the right].

The great advantage is the lower construction thickness, which is why edgelit panels can be integrated more discreetly in rooms and are better suited as pendant variants. At the same time, the panels allow a higher beam angle [approx. 120°] what results in a larger illuminated area. The disadvantages: Edgelit panels are more expensive and offer less efficiency and lifetime compared to backlight panels.


advantages

- lower thickness
- higher beam angle [approx. 120°]
- more suitable for suspension
- thinner packing

disadvantages

- higher costs
- worse price/performance ratio
- average lifetime
- lower efficiency

In the following picture you can see the typical structure of a sidelight LED panel.






STANDARD FLEX

- Light colour adjustable in three stages
- For insertion into grid ceilings
- Can be installed in surface-mount or flush-mount frames
- Suitable for pendant mounting
- Suitable for reception rooms and hallways
- Can be combined with a power supply unit as desired [excl.]

Application Area

Reception / Communication, Corridor / stairwell, Shop / Retail / Sales area, Health / care / hospital / practice, Education / school / lecture theatre, Refurbishment

Housing	Aluminium	Control	Dimmable via optional power supply unit
Colour Temperature	3000/4000/6000 K	CRI (Ra)	90
Height	10 mm	IK Protection Class	IK03
Rated Input Voltage	33-38 V/DC	UGR	22
Power Supply Unit incl.	No		
Light Beam Angle	120 Degree		



100123

Article	Housing Color		Luminous Flux	Length	Width	Power	Rated Current	Price
100125	☐ White		3570/3990/3780 lm	1195 mm	295 mm	36.0 W	1050 mA	€ 66.95
100123	☐ White		3780/4200/4000 lm	620 mm	620 mm	36.0 W	1050 mA	€ 63.95
100139	☐ White		5300/6000/5700 lm	1195 mm	595 mm	51.5 W	1500 mA	€ 131.95
100154	☐ White		5300/6000/5700 lm	1240 mm	620 mm	51.5 W	1500 mA	€ 135.95



Accessories

930674	Safety cable		€ 3.95
--------	--------------	--	--------

Accessories for 100123

930665	Surface-mounted frame for 620x620 mm panel		€ 47.95
930670	Recessed frame for 620x620 mm backlit panel		€ 47.95

Accessories for 100123, 100125

930672	Cable suspension for 620x620/300x1,200 mm panel		€ 17.95
862193	BASIC, DIM, Multi CC, IE-45HD		€ 55.95
862258	QUICK, CC, 1,050 mA, 25-40 V, 42 W		€ 37.95

Accessories for 100125

930666	Surface-mounted frame for 300x1,200 mm panel		€ 55.95
930671	Recessed frame for 300x1,200 mm backlit panel		€ 55.95

Accessories for 100139

930675	Surface-mounted frame for 600x1,200 mm panel		€ 55.95
930688	Recessed frame for 600x1,200 mm backlit panel		€ 67.95

Accessories for 100139, 100154

930673	Cable suspension for 600x1,200 mm panel		€ 25.95
862194	BASIC, DIM, Multi CC, IE-75D		€ 67.95
862259	QUICK, CC, 1,500 mA, 27-42 V, 60 W		€ 45.95




STANDARD OFFICE

- For insertion into grid ceilings
- Can be installed in surface-mount or flush-mount frames
- Suitable for pendant mounting
- Suitable for office spaces, reception rooms, hallways
- Suitable for workplaces with screens in accordance with EN 12464-1 BAP65
- Microprismatic surface structure

Application Area

Office / conference, Reception / Communication, Corridor / stairwell, Shop / Retail / Sales area, Health / care / hospital / practice, Education / school / lecture theatre, Refurbishment

Housing	Aluminium	Light Beam Angle	90 Degree
Colour Temperature	4000 K	Control	Dimmable via optional power supply unit
Luminous Flux	4200 lm	CRI (Ra)	90
Height	9 mm	Rated Current	1050 mA
Power	36 W	IK Protection Class	IK03
Rated Input Voltage	33-38 V/DC	UGR	19
Power Supply Unit incl.	No		



100124

Article	Housing Color	Length	Width	EEI	Price
100138	White	1195 mm	295 mm	G	€ 66.95
100124	White	620 mm	620 mm	F	€ 63.95



Accessories

930672	Cable suspension for 620x620/300x1,200 mm panel		€ 17.95
930674	Safety cable		€ 3.95
862258	QUICK, CC, 1,050 mA, 25-40 V, 42 W		€ 37.95
862193	BASIC, DIM, Multi CC, IE-45HD		€ 55.95

Accessories for 100124

930665	Surface-mounted frame for 620x620 mm panel		€ 47.95
930670	Recessed frame for 620x620 mm backlit panel		€ 47.95

Accessories for 100138

930666	Surface-mounted frame for 300x1,200 mm panel		€ 55.95
930671	Recessed frame for 300x1,200 mm backlit panel		€ 55.95




STANDARD SANO

The SANO LED panel is a simple and cost-effective solution for renovating old T5/T8 louver lights. Its slim design enables seamless integration into existing installations without the need for additional adjustments.

Due to its eligibility for BEG German federal funding for energy-efficient buildings, the SANO insert panel is a sustainable and economically attractive solution. The panel provides uniform illumination with high colour reproduction values and minimises glare, which is particularly important in commercial environments.





STANDARD SANO

- Eligible for BEG German federal funding for energy-efficient buildings
- For insertion into grid ceilings
- Can be installed in surface-mount or flush-mount frames
- Suitable for pendant mounting
- Renovation solution for T5/T8 louver lights
- Can be combined with a power supply unit as desired [excl.]

Application Area

Reception / Communication, Corridor / stairwell, Shop / Retail / Sales area, Health / care / hospital / practice, Education / school / lecture theatre, Refurbishment

Housing	Aluminium, Polycarbonate	Rated Input Voltage	35-40 V/DC
Colour Temperature	4000 K	Power Supply Unit incl.	No
Luminous Flux	4900 lm	Light Beam Angle	120 Degree
Length	1495 mm	Control	Dimmable via optional power supply unit
Width	295 mm	CRI (Ra)	90
Height	10 mm	Rated Current	1050 mA
Power	33 W	UGR	22

Article	Housing Color	Price
100158	☐ White NW	€ 107.95




Accessories

930795	Surface-mounted frame for 1,500x300 mm panel
930796	Recessed frame for 1,500x300 mm panel
930673	Cable suspension for 600x1,200 mm panel
930674	Safety cable
862258	QUICK, CC, 1,050 mA, 25-40 V, 42 W

	€ 63.95
	€ 55.95
	€ 25.95
	€ 3.95
	€ 37.95



Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.



OFFICE FLEX


- For insertion into grid ceilings
- Can be installed in surface-mount or flush-mount frames
- Suitable for pendant mounting
- Suitable for office spaces, reception rooms, hallways
- Light colour adjustable in three stages
- Suitable for workplaces with screens in accordance with EN 12464-1 BAP65
- Microprismatic surface structure



Application Area


Office / conference, Reception / Communication, Corridor / stairwell, Shop / Retail / Sales area, Health / care / hospital / practice, Education / school / lecture theatre, Refurbishment

Housing	Aluminium	Light Beam Angle	100 Degree
Colour Temperature	3000/4000/5700 K	Control	Leading-edge dimmer, Trailing-edge dimmer
Height	10 mm	CRI (Ra)	90
Power	40 W	IK Protection Class	IK08
Rated Input Voltage	220-240 V/AC	UGR	19
Power Supply Unit incl.	Yes		



100078

Article	Housing Color	Luminous Flux	Length	Width	Price
100078	☐ White WW NW CW	3300 lm	620 mm	620 mm	€ 143.95
100079	☐ White WW NW CW	3500 lm	1195 mm	295 mm	€ 175.95



Accessories

862193 BASIC, DIM, Multi CC, IE-45HD



€ 55.95

Accessories for 100078

930665 Surface-mounted frame for 620x620 mm panel



€ 47.95

930670 Recessed frame for 620x620 mm backlit panel



€ 47.95

Accessories for 100079

930666 Surface-mounted frame for 300x1,200 mm panel



€ 55.95

930671 Recessed frame for 300x1,200 mm backlit panel




€ 55.95



Technical data sheet

New in the onlineshop: The technical data sheets offer even more information: Light and energy data, light distribution curves, dimensional drawings and more.




HCL

- For insertion into grid ceilings
- Can be installed in surface-mount or flush-mount frames
- Suitable for 24 V HCL controllers
- Suitable for event spaces/reception rooms, hallways
- Low housing depth

Application Area

Reception / Communication, Corridor / stairwell, Shop / Retail / Sales area, Health / care / hospital / practice, Education / school / lecture theatre, Refurbishment

Housing	Aluminium	Rated Input Voltage	24 V/DC
Colour Temperature	3000-5500 K	Power Supply Unit incl.	No
Luminous Flux	3551 lm	Light Beam Angle	120 Degree
Length	620 mm	Control	Dimmable via optional controller
Width	620 mm		
Height	10 mm	CRI (Ra)	80
Power	49.5 W		



100032

Article	Housing Color	Colour Temperature	Price
100032	☐ White	☒ WW ☒ CW 3000-5500 K	€ 135.95





Accessories

930665	Surface-mounted frame for 620x620 mm panel
930670	Recessed frame for 620x620 mm backlit panel
862122	FLAT, CV, UT 24 V/50 W
862166	BASIC, CV, Q8H-24-100 W
843501	RF-smart, starter set LED single/CCT, 12-48 V, 20 A incl. remote control

	€ 47.95
	€ 47.95
	€ 41.95
	€ 77.95
	€ 79.95



5-year guarantee
Benefit from the maximum quality promise:
All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.




STANDARD RGB CCT

- For insertion into grid ceilings
- Can be installed in surface-mount or flush-mount frames
- Suitable for event spaces, reception rooms, hallways
- Suitable for 24 V colour and HCL controllers

Application Area

Reception / Communication, Object lighting / architecture, Wellness / Spa / Gym, Advertising lighting, Hotel / catering, Theatre / event, Refurbishment

Housing	Aluminium	Light Beam Angle	110 Degree
Colour Temperature	2700-6500 K	Control	Dimmable via optional controller
Luminous Flux	5000 lm	CRI (Ra)	90
Height	12.5 mm	IK Protection Class	IK05
Power	88 W	UGR	19
Rated Input Voltage	24 V/DC		
Power Supply Unit incl.	No		



Article	Housing Color	Length	Width	Price
100160	☐ White ☐ RGB ☐ WW ☐ CW	595 mm	595 mm	€ 164.95
100159	☐ White ☐ RGB ☐ WW ☐ CW	620 mm	620 mm	€ 167.95



Accessories for 100159



- 930665** Surface-mounted frame for 620x620 mm panel
- 930668** Recessed frame for 620x620 mm panel



Accessories for 100160

- 930664** Surface-mounted frame for 595x595 mm panel
- 930667** Recessed frame for 595x595 mm panel
- 930907** Recessed frame 600x600 for standard panels






STANDARD RGBW

- For insertion into grid ceilings
- Can be installed in surface-mount or flush-mount frames
- Powerful and intense colours, incl. pastel tones
- Suitable for 24 V colour controllers
- Suitable for event spaces, reception rooms, hallways

Application Area


Reception / Communication, Object lighting / architecture, Wellness / Spa / Gym, Advertising lighting, Hotel / catering, Theatre / event, Refurbishment

Housing	Aluminium	Light Beam Angle	110 Degree
Height	11 mm	Control	Dimmable via optional controller
Power	94 W	CRI (Ra)	90
Rated Input Voltage	24 V/DC		
Power Supply Unit incl.	No		



100152

Article	Housing Color	Colour Temperature	Luminous Flux	Length	Width	Price
100156	☐ White	3000 K	4000 lm	595 mm	595 mm	€ 147.95
100152	☐ White	3000 K	4000 lm	620 mm	620 mm	€ 151.95
100157	☐ White	4000 K	4200 lm	595 mm	595 mm	€ 147.95
100153	☐ White	4000 K	4200 lm	620 mm	620 mm	€ 151.95



Accessories

862166	BASIC, CV, Q8H-24-100 W		€ 77.95
872091	IP, CV, V6-320-24		€ 175.95
843502	RF-smart, starter set RGB/W/CCT, 12-48 V, 20 A incl. remote, IP20		€ 79.95
843037	Casambi BT Dimmer CBU-PWM4 (CV, 12-24V, 6A DC)		€ 143.95
843279	MULTI-LED dimmer 1-4 channels, DMX/auto/manual, 12-48 V, 20 A, flicker-free		€ 91.95

Accessories for 100152, 100153

930665	Surface-mounted frame for 620x620 mm panel		€ 47.95
930668	Recessed frame for 620x620 mm panel		€ 45.95

Accessories for 100156, 100157

930664	Surface-mounted frame for 595x595 mm panel		€ 43.95
930667	Recessed frame for 595x595 mm panel		€ 41.95

Accessories for 100157

930907	Recessed frame 600x600 for standard panels		€ 43.95
---------------	--	--	---------

surface mounted wall lights



page 162



page 163



page 164



page 167



page 168






ACAMAR

Application Area
Reception / Communication, Object lighting / architecture, Home / Living, Hotel / catering

Housing	Aluminium	Base Height	33 mm
Colour Temperature	3000 K	Power	6.5 W
Length	170 mm	Rated Input Voltage	220-240 V/AC
Width	100 mm	Power Supply Unit incl.	Yes
Height	80 mm	Light Beam Angle	105 Degree
Base Length	120 mm	Control	Trailing-edge dimmer
Base Width	60 mm	CRI (Ra)	92



341194

Article	Housing Color	Luminous Flux	Price
341196	Black, Gold	300 lm	€ 123.95
341194	White	390 lm	€ 123.95
341195	Silver, White	500 lm	€ 123.95






APODIS

Application Area
Home / Living, Reception / Communication, Home office / study, Hotel / catering

Housing	Aluminium	Base Height	100 mm
Colour Temperature	3000 K	Rated Input Voltage	220-240 V/AC
Length	76 mm	Power Supply Unit incl.	Yes
Width	61 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Base Length	60 mm	CRI (Ra)	80
Base Width	18 mm		



341200


Article	Housing Color		Luminous Flux	Height	Power	Light Beam Angle	Price
341200	■ Gold, Black	ww	350 lm	500 mm	10.8 W	40 Degree	€ 184.95
341202	■ Gold, Black	ww	450 lm	800 mm	14.7 W	30 Degree	€ 224.95





CUBE

Little cube, big effect: The cube emits its light up and down in equal measure, drawing the eye to spacial elements and bringing structure. The compact cube made from concrete or plaster [available in the colour tones beige, grey, dark grey, white and black] with its subdued design has the essentials in focus, assuming a back seat presence.



CUBE

- Exchangeable lamp
- A variety of concrete/plaster colour variants
- Can be painted over [white variant only]

Application Area

Home / Living, Hotel / catering

Length	115 mm	Max. Power	1x max. 25 W
Width	115 mm	Rated Input Voltage	220-240 V/AC
Height	115 mm	Control	Dimmable via optional light source
Base Length	57 mm	Colour of Light Output	White
Base Width	57 mm		
Base Height	63 mm		

Article	Housing Color	Housing	Paintable	Price
341183	 Grey	Concrete		€ 55.95
341184	 Dark grey	Concrete		€ 55.95
341250	 Black	Plaster		€ 57.95
341249	 White	Plaster	Yes	€ 57.95



Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.





CAN IP20

- Customised lighting solution thanks to replaceable light source
- combinable with the extensive product family of the CAN series

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Base Height	77 mm
Length	72 mm	Max. Power	1x max. 7.5 W
Height	125 mm	Rated Input Voltage	220-240 V/AC
Ø	60 mm	Control	Dimmable via optional light source
Base Length	12.6 mm		
Base Width	40 mm		

Article	Housing Color	Price
341341	White	€ 35.95
341342	Black	€ 35.95



Accessories

930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930301	Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930302	Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930366	Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930303	Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
931065	Acrylic attachment for Can		€ 3.95



page 30

page 68

page 70

page 72

page 383



Light sources

For all lights and bases:

You can find the right light sources in the »Light sources« section.



CAN UP & DOWN IP20

The CAN wall light provides versatile lighting options for various commercial and private projects. The up/down variant with light emission on both sides can be adapted perfectly to individual room concepts. The GU10 base enables simple replacement of the lamp, while the screw-on cylinder allows tool-free access. Installation for rigid and flexible conductors is particularly easy due to the integrated push terminals. Individual accents can be created with the optional, interchangeable decorative rings. The CAN wall light is part of a comprehensive series and is also available as a pendant, ceiling, reading and outdoor light.





CAN UP & DOWN IP20

- Customised lighting solution thanks to replaceable light source
- combinable with the extensive product family of the CAN series

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Base Height	77 mm
Length	72 mm	Max. Power	2x max. 7.5 W
Height	230 mm	Rated Input Voltage	220-240 V/AC
Ø	60 mm	Control	Dimmable via optional light source
Base Length	12.6 mm		
Base Width	40 mm		

Article	Housing Color	Price
341343	☐ White	€ 43.95
341344	☒ Black	€ 43.95



Accessories

930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930301	Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930302	Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930366	Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930303	Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
931065	Acrylic attachment for Can		€ 3.95



Light sources

For all lights and bases:

You can find the right light sources in the »Light sources« section.

built in wall lights






☐ page 174



☐ page 176






ALWAID PRO

The new ALWAID PRO series combines functional wall-mounted recessed luminaires with a compact design, elegant appearance, and practical features. With a mounting depth of only 39 mm, the luminaires fit into all common 68 mm switch boxes – whether standard or deep versions. This makes the ALWAID PRO ideal for renovations and new constructions with limited space.

The ALWAID PRO series offers maximum design freedom: all luminaires are available with both round and square covers. Two colour options are available for the housing – white and black – as well as two high-quality material finishes: aluminium and glass/polycarbonate. Additionally, a selection of geometric light exit openings provides individual lighting moods depending on the application and architectural requirements. Furthermore, the recessed spots [2,700 K or 3,000 K] are available as dimmable versions or as ALWAID PRO MOTION with integrated motion sensor. The latter additionally offers a two-stage power switch [2 W / 4 W] for individual adjustment of light output.

All variants are equipped with an integrated power supply for 230V direct connection and can be easily through-wired – ideal for series installations in corridors or staircases.





ALWAID PRO

- integrated power supply unit for 230V direct connection
- through-wiring possible
- dimmable via leading edge/trailing edge phase
- suitable for 68 mm switch boxes of normal and deep design




Housing	Aluminium, Polycarbonate	Installation Depth	39 mm
Height	41 mm	Cut Out Ø	68 mm
Ø	71.5 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Power	4 W	CRI (Ra)	80
Rated Input Voltage	220-240 V/AC	IK Protection Class	IK05
Power Supply Unit incl.	Yes	Light Direction	Front

Article	Housing Color	Colour Temperature	Luminous Flux	Price
565733	☐ White	2700 K	610 lm	€ 47.95
565734	☐ White	3000 K	630 lm	€ 47.95



Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.



ALWAID PRO

Article	Housing Color	Housing	housing shape	light cone	L x W x H	Ø x H	Price
931013	White	Aluminium	round	wide		75 x 18 mm	€ 9.95
931015	Black	Aluminium	round	wide		75 x 18 mm	€ 9.95
931025	White	Aluminium	angular	wide	75 x 75 x 18 mm		€ 9.95
931027	Black	Aluminium	angular	wide	75 x 75 x 18 mm		€ 9.95
931007	White	Aluminium	round	narrow		75 x 18 mm	€ 9.95
931009	Black	Aluminium	round	narrow		75 x 18 mm	€ 9.95
931019	White	Aluminium	angular	narrow	75 x 75 x 18 mm		€ 9.95
931021	Black	Aluminium	angular	narrow	75 x 75 x 18 mm		€ 9.95
931037	White	Glass / Polycarbonate	round	soft		78 x 23 mm	€ 14.95
931039	Black	Glass / Polycarbonate	round	soft		78 x 23 mm	€ 14.95
931031	White	Glass / Polycarbonate	angular	soft	78 mm		€ 14.95
931033	Black	Glass / Polycarbonate	angular	soft	78 mm		€ 14.95

IP20




ALWAID PRO MOTION

- integrated power supply unit for 230V direct connection
- with motion detector
- through-wiring possible
- power adjustable in 2 stages
- suitable for 68 mm switch boxes of normal and deep design




Housing	Aluminium, Polycarbonate	Power Supply Unit incl.	Yes
Height	41 mm	Installation Depth	39 mm
Ø	71.5 mm	Cut Out Ø	68 mm
Power Selectable	2 W, 4 W	CRI (Ra)	80
Rated Input Voltage	220-240 V/AC	IK Protection Class	IK05
		Light Direction	Front

Article	Housing Color	Colour Temperature	Luminous Flux	Price
565736	☐ White	2700 K	610 lm	€ 51.95
565737	☐ White	3000 K	630 lm	€ 51.95



5-year guarantee
Benefit from the maximum quality promise:
All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.



ALWAID PRO MOTION

Article	Housing Color	Housing	housing shape	light cone	L x W x H	Ø x H	Price
931016	☐ White	Aluminium	round	wide		75 x 18 mm	€ 12.95
931018	☒ Black	Aluminium	round	wide		75 x 18 mm	€ 12.95
931028	☐ White	Aluminium	angular	wide	75 x 75 x 18 mm		€ 12.95
931030	☒ Black	Aluminium	angular	wide	75 x 75 x 18 mm		€ 12.95
931010	☐ White	Aluminium	round	narrow		75 x 18 mm	€ 12.95
931012	☒ Black	Aluminium	round	narrow		75 x 18 mm	€ 12.95
931022	☐ White	Aluminium	angular	narrow	75 x 75 x 18 mm		€ 12.95
931024	☒ Black	Aluminium	angular	narrow	75 x 75 x 18 mm		€ 12.95
931040	☐ White	Glass / Polycarbonate	round	soft		75 x 18 mm	€ 17.95
931042	☒ Black	Glass / Polycarbonate	round	soft		75 x 18 mm	€ 17.95
931034	☐ White	Glass / Polycarbonate	angular	soft	75 x 75 x 18 mm		€ 17.95
931036	☒ Black	Glass / Polycarbonate	angular	soft	75 x 75 x 18 mm		€ 17.95

IP20

reading lights



page 180



page 181



page 182



page 184





BRAHE ROUND

The BRAHE wall light with indirect lighting and narrow light emission angle of 25° means anyone else in the bed can sleep peacefully while the person on the other side is still reading. The simple design of the BRAHE also impresses in other areas, such as reading nooks.



page 194



page 195




BRAHE ROUND

·Direct and indirect lighting can be switched on separately

Application Area


Home / Living, Hotel / catering

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Colour Temperature	3000 K	Power Supply Unit incl.	Yes
Height	110 mm	Light Beam Angle	25 Degree
Ø	150 mm	Swivelling Angle	360 Degree
Power	8.5 W	CRI (Ra)	80



341242

Article	Housing Color		Luminous Flux	Price
341243	Black	WW	395 lm	€ 83.95
341242	White	WW	490 lm	€ 83.95




BRAHE SQUARE

- High-quality, flexible gooseneck
- Gooseneck with silicone sleeve for easy cleaning
- Individually adjustable via flexible gooseneck

Application Area


Home / Living, Hotel / catering

Housing	Aluminium	Base Height	25 mm
Colour Temperature	3000 K	Power	3.3 W
Length	310 mm	Rated Input Voltage	100-240 V/AC
Height	80 mm	Power Supply Unit incl.	Yes
Ø	25 mm	Light Beam Angle	25 Degree
Base Length	80 mm	Swivelling Angle	360 Degree
Base Width	80 mm	CRI (Ra)	80



341236

Article	Housing Color		Luminous Flux	Price
341237	Black	WW	165 lm	€ 53.95
341236	White	WW	175 lm	€ 53.95





CANTILT SQUARE

The square CAN reading light is the ideal choice for modern hotel rooms and sophisticated living spaces. It offers a convenient charging option for smartphones and other devices via USB-C and USB-A (article no. 341339 and 341340 only). The widely used GU10 base enables the quick replacement of the lamp, while the screw-on cylinder housing allows tool-free access. Individual accents can be set with the optional, replaceable decorative rings. The CAN reading light is part of a versatile lighting family, which is also available as a pendant, ceiling, wall and outdoor light.



page 30



page 68



page 70



page 72





CAN TILT SQUARE

- Flat and discreet lamp base
- Replaceable lamp to offer an individual lighting solution
- Can be customised with a wide range of accessories
- Can be combined with the comprehensive product family of the CAN series
- Can be charged via USB-C/USB-A [art. nos. 341339 and 341340 only]

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Max. Power	1x max. 7.5 W
Length	102 mm	Rated Input Voltage	220-240 V/AC
Height	105 mm	Control	Dimmable via optional light source
Ø	60 mm	Rotation Angle	355 Degree
Base Width	100 mm	Swivelling Angle	90 Degree
Base Height	100 mm		

Article	Housing Color	Charging connection	Price
341337	☐ White		€ 39.95
341338	☒ Black		€ 39.95
341339	☐ White	1 x USB type A / 1 x USB type C	€ 55.95
341340	☒ Black	1 x USB type A / 1 x USB type C	€ 55.95



Accessories

930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930301	Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930302	Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930366	Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930303	Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
931065	Acrylic attachment for Can		€ 3.95



Light sources

For all lights and bases:

You can find the right light sources in the »Light sources« section.



CANTILT ROUND

The round CAN reading light is the ideal choice for modern hotel rooms and sophisticated living spaces. It offers a convenient charging option for smartphones and other devices via USB-C and USB-A (article no. 341335 and 341336 only). The widely used GU10 base enables the quick replacement of the lamp, while the screw-on cylinder housing allows tool-free access. Individual accents can be set with the optional, replaceable decorative rings. The CAN reading light is part of a versatile lighting family, which is also available as a pendant, ceiling, wall and outdoor light.



page 30



page 69



page 70



page 72





CAN TILT ROUND

- Flat and discreet lamp base
- Can be customised with a wide range of accessories
- Replaceable lamp to offer an individual lighting solution
- Can be combined with the comprehensive product family of the CAN series
- Can be charged via USB-C/USB-A [art. nos. 341335 and 341336 only]

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Length	102 mm	Control	Dimmable via optional light source
Height	105 mm	Rotation Angle	355 Degree
Ø	60 mm	Swivelling Angle	90 Degree
Base Ø	100 mm		
Max. Power	1x max. 7.5 W		

Article	Housing Color	Charging connection	Price
341333	White		€ 39.95
341334	Black		€ 39.95
341335	White	1 x USB type A / 1 x USB type C	€ 55.95
341336	Black	1 x USB type A / 1 x USB type C	€ 55.95



Accessories

930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930301	Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930302	Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930366	Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930303	Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
931065	Acrylic attachment for Can		€ 3.95



Light sources

For all lights and bases:

You can find the right light sources in the »Light sources« section.



CAN TILT SQUARE BASE MIX'N MATCH 1/3

- flat and discreet luminaire base
- charging option via USB-C / USB-A [only item no. 341347 and 341348]

Application Area
 Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Height	105 mm	Control	Dimmable via optional light source
Ø	60 mm	Rotation Angle	340 Degree
Base Length	100 mm	Swivelling Angle	90 Degree
Base Width	100 mm		
Max. Power	1x max. 7.5 W		

Article	Housing Color	Charging connection	Price
341345	White		€ 33.95
341346	Black		€ 33.95
341347	White	1 x USB type A / 1 x USB type C	€ 49.95
341348	Black	1 x USB type A / 1 x USB type C	€ 49.95



CAN TILT ROUND BASE MIX'N MATCH 1/3

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Height	105 mm	Control	Dimmable via optional light source
Ø	60 mm	Rotation Angle	340 Degree
Base Ø	100 mm	Swivelling Angle	90 Degree
Max. Power	1x max. 7.5 W		

Article	Housing Color	Charging connection	Price
341349	White		€ 33.95
341350	Black		€ 33.95
341351	White	1 x USB type A / 1 x USB type C	€ 49.95
341352	Black	1 x USB type A / 1 x USB type C	€ 49.95





CYLINDER HOUSING FUR CAN MIX'N MATCH 2/3

Housing Aluminium Ø 60 mm
Height 95 mm

Article	Housing Color	Price
931059	 White	€ 6.45
931060	 Black	€ 6.45
931061	 Bronze	€ 14.95
931062	 Brass	€ 14.95
931063	 Black grey	€ 14.95
931064	 Rosé	€ 14.95

IP20



REFLECTOR RING FOR CAN MIX'N MATCH 3/3

Housing Plastic Ø 57 mm
Height 28 mm

Article	Housing Color	Price
930301	 White	€ 3.95
930302	 Black	€ 3.95
930303	 Gold	€ 3.95
930366	 Silver	€ 3.95

IP20

table and floor lights



page 190



page 191



page 192



page 192



page 194



page 195



page 196





CAN

- customisable with extensive accessories
- customised lighting solution thanks to replaceable light source
- combinable with the extensive product family of the CAN series

Application Area

Home / Living, Hotel / catering

Housing	Aluminium	Primary Cable Length	2 m
Height	1115 mm	Primary Connection End	Safety plug
Ø	60 mm	Control	Dimmable via optional light source
Base Ø	252 mm	Rotation Angle	340 Degree
Max. Power	1x max. 7.5 W	Swivelling Angle	90 Degree
Rated Input Voltage	220-240 V/AC		

Article	Housing Color	Price
343037	 White	€ 103.95
343038	 Black	€ 103.95



Accessories

930301	Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930302	Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930303	Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930366	Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
931065	Acrylic attachment for Can		€ 3.95



Light sources

For all lights and bases:
You can find the right light sources in the »Light sources« section.



CAN

- customisable with extensive accessories
- customised lighting solution thanks to replaceable light source
- combinable with the extensive product family of the CAN series

Application Area

Home / Living, Hotel / catering

Housing	Aluminium	Primary Cable Length	2 m
Height	400 mm	Primary Connection End	Safety plug
Ø	60 mm	Control	Dimmable via optional light source
Base Ø	182 mm	Rotation Angle	340 Degree
Max. Power	1x max. 7.5 W	Swivelling Angle	90 Degree
Rated Input Voltage	220-240 V/AC		

Article	Housing Color	Price
346086	☐ White	€ 76.95
346087	☒ Black	€ 76.95



Accessories

930301	Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930302	Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930303	Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930366	Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
931065	Acrylic attachment for Can		€ 3.95



5-year guarantee

Benefit from the maximum quality promise:

All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.



CAN BASE MIX'N MATCH 1/3

- customisable with extensive accessories
- individual lighting solution thanks to interchangeable light source
- can be customised with cylinder housing in 6 different colours
- can be combined with the extensive product family of the CAN series

Application Area
Home / Living, Hotel / catering

Housing	Aluminium	Primary Cable Length	2 m
Length	252 mm	Primary Connection End	Safety plug
Width	240 mm	Control	Dimmable via optional light source
Height	1115 mm	Rotation Angle	340 Degree
Base Ø	240 mm	Swivelling Angle	90 Degree
Max. Power	1x max. 7.5 W		
Rated Input Voltage	220-240 V/AC		

Article	Housing Color	Price
343039	 White	€ 97.95
343040	 Black	€ 97.95



CAN BASE MIX'N MATCH 1/3

Housing	Aluminium	Primary Cable Length	2 m
Length	182 mm	Primary Connection End	Safety plug
Width	170 mm	Control	Dimmable via optional light source
Height	400 mm	Rotation Angle	340 Degree
Base Ø	170 mm	Swivelling Angle	90 Degree
Max. Power	1x max. 7.5 W		
Rated Input Voltage	220-240 V/AC		

Article	Housing Color	Price
346088	 White	€ 69.95
346089	 Black	€ 69.95





CYLINDER HOOUSING FOR CAN MIX'N MATCH 2/3

Housing Aluminium Ø 60 mm
Height 95 mm

Article	Housing Color	Price
931059	 White	€ 6.45
931060	 Black	€ 6.45
931061	 Bronze	€ 14.95
931062	 Brass	€ 14.95
931063	 Black grey	€ 14.95
931064	 Rosé	€ 14.95

IP20



REFLECTOR RING FOR CAN MIX'N MATCH 3/3

Housing Plastic Ø 57 mm
Height 28 mm

Article	Housing Color	Price
930301	 White	€ 3.95
930302	 Black	€ 3.95
930303	 Gold	€ 3.95
930366	 Silver	€ 3.95

IP20




BRAHE


- Can be rotated and swivelled
- Direct and indirect lighting can be switched on separately

Application Area
 Home / Living, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000 K	Light Beam Angle	25 Degree
Height	455 mm	Swivelling Angle	90 Degree
Ø	150 mm	Primary Connection End	Power plug IP20
Power	8.5 W	CRI (Ra)	80
Rated Input Voltage	220-240 V/AC		

Article	Housing Color		Luminous Flux	Price
346016		Black 	370 lm	€ 124.95
346015		White 	470 lm	€ 124.95





BRAHE


- Can be rotated and swivelled
- Direct and indirect lighting can be switched on separately

Application Area

Home / Living, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000 K	Light Beam Angle	25 Degree
Height	1387 mm	Swivelling Angle	90 Degree
Ø	305 mm	Primary Connection End	Power plug IP20
Power Selectable	3 W, 8 W	CRI (Ra)	80
Rated Input Voltage	220-240 V/AC		

Article	Housing Color		Luminous Flux	Price
343026	Black	WW	555 lm	€ 207.95
343025	White	WW	735 lm	€ 207.95





ADHARA

Classic design interpreted in a modern way - the ADHARA made from aluminium captivates with its classic lines, ultra-modern materials and high degree of flexibility. The ADHARA can be optimally adjusted to any situation via its two or three joints. Its powerful LED module delivers 950 lumens and can also be dimmed thanks to a touch sensor. Whether for the boss's office or for a child's desk, the ADHARA looks great anywhere.



ADHARA

- Can be rotated and swivelled via joints
- Dimmable in three stages using touch sensor

Application Area

Home / Living, Reception / Communication, Home office / study

Housing	Aluminium	Power	12 W
Colour Temperature	3000 K	Rated Input Voltage	100-240 V/AC
Luminous Flux	950 lm	Power Supply Unit incl.	Yes
Length	498 mm	Light Beam Angle	120 Degree
Height	480 mm	Swivelling Angle	180 Degree
Ø	150 mm	Primary Cable Length	1.6 m
Base Height	21.5 mm	Primary Connection End	Power plug
Base Ø	180 mm	CRI (Ra)	80

Article	Housing Color		Price
346026		Black	 € 159.95
346027		White	 € 159.95
346028		Silver	 € 159.95



Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.

office lights



□ ■ □
page 200



■ □ □
page 202



□ □ ■
page 204



□ □ ■
page 205



■
page 206



□ □ ■
page 212



□ □ ■
page 213



□ □ ■
page 214



□ □ ■
page 215





ROUND TRANSPARENT LED PANEL

The LED pendant light is equipped with a transparent acrylic glass pane for soft direct and indirect light distribution, which is almost transparent when switched off. When switched on, the pane distributes the light almost entirely without glare.

With a glare rating [UGR] of under 22, this pendant light is suitable for various communal or even conference rooms. Bright, efficient and with a sophisticated design, this light not only stands out from all other office equipment, but can also be integrated into any other modern interior.






ROUND TRANSPARENT LED PANEL

- Eligible for BEG German federal funding for energy-efficient buildings
- Light colour adjustable in three stages
- Particularly delicate frame
- Low glare value
- Transparent luminous element

Application Area

Reception / Communication, Office / conference, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Base Ø	215 mm
Colour Temperature	3000/3500/4000 K	Power Supply Unit incl.	Yes
Power	50 W	Light Beam Angle	140 Degree
Rated Input Voltage	200-240 V/AC	Light Beam Angle 2	150 Degree
Height	12 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	633 mm	CRI (Ra)	90
Pendulum Length	1800 mm	IK Protection Class	IK04
Base Height	43 mm		



342251

Article	Housing Color		Luminous Flux	Price
342252	Black	WW NW	6000/6100/6100 lm	€ 339.95
342253	Light grey	WW NW	6100/6200/6200 lm	€ 339.95
342251	White	WW NW	6200/6400/6400 lm	€ 339.95



Accessories

843340	DALI, Triac dimmer, 100-240 V, 400 W, IP20		€ 59.95
843503	RF-smart, Triac dimmer, 230 V, 300 W, IP20		€ 55.95



Lighting design

Interested in our lighting design service?

Your contact person will be happy to answer any questions you may have.



LED PANEL TRANSPARENT ANGULAR

The LED pendant lamp has transparent glass for direct and indirect light distribution that is almost see-through when switched off. When the light is switched on, the pane distributes the light almost entirely without glare.

This pendant lamp is fully office-compatible with a glare value [UGR] of under 19. Bright, efficient and with a sophisticated design, this light not only stands out in any type of office environment.






LED PANEL TRANSPARENT ANGULAR

- Very low glare value
- Light colour adjustable in 2 stages
- Transparent luminous element
- Max. suspended mounting 1,800 mm

Application Area

Reception / Communication, Office / conference, Home / Living, Home office / study, Hotel / catering

Housing	Aluminium	Base Length	570 mm
Colour Temperature	3000/4000 K	Base Width	80 mm
Luminous Flux	5600/6100 lm	Base Height	50 mm
Power	53 W	Power Supply Unit incl.	Yes
Rated Input Voltage	220-240 V/AC	Light Beam Angle	360 Degree
Length	295 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Width	1195 mm	CRI (Ra)	90
Height	12 mm		
Pendulum Length	1800 mm		



342221

Article	Housing Color	Price
342219	Black	€ 239.95
342220	Light grey	€ 239.95
342221	White	€ 239.95



Technical data sheet

New in the onlineshop: The technical data sheets offer even more information: Light and energy data, light distribution curves, dimensional drawings and more.




OFFICE THREE STANDARD

- Suitable for VDU workstations (according to EN 12464-1 BAP65 [L65 = 3000cd/m²])
- BEG-eligible
- CRI>95 for direct light component
- Indirect light component 85%

Application Area

Reception / Communication, Office / conference, Home office / study, Education / school / lecture theatre

Housing	Aluminium	Base Width	52 mm
Colour Temperature	4000 K	Base Height	35 mm
Luminous Flux	8300 lm	Power Supply Unit incl.	Yes
Power	56 W	Light Beam Angle	115 Degree
Rated Input Voltage	180-264 V/AC	Light Beam Angle 2	50 Degree
Length	1179 mm	Control	DALI 2 / DT6, Intelli Push-Dim
Width	64 mm	CRI (Ra)	95
Height	35 mm	IK Protection Class	IK03
Pendulum Length	2500 mm		
Base Length	603 mm		



342258

Article	Housing Color	Price
342258	White	€ 439.95
342259	Light grey	€ 439.95
342260	Black	€ 439.95






OFFICE THREE PRO

- Suitable for VDU workstations (according to EN 12464-1 BAP65 [L65 = 3000cd/m²])
- BEG-eligible
- CRI>95 for direct light component
- Indirect light component 85%
- D4i power supply unit for direct coupling with DALI sensor

Application Area

Reception / Communication, Office / conference, Home office / study, Education / school / lecture theatre

Housing	Aluminium	Base Width	52 mm
Colour Temperature	4000 K	Base Height	35 mm
Luminous Flux	10900 lm	Power Supply Unit incl.	Yes
Power	77 W	Light Beam Angle	115 Degree
Rated Input Voltage	220-240 V/AC	Light Beam Angle 2	50 Degree
Length	1391 mm	Control	DALI 2 / DT6 D4i, Intelli Push-Dim
Width	64 mm	CRI (Ra)	95
Height	35 mm	IK Protection Class	IK03
Pendulum Length	2500 mm		
Base Length	603 mm		



342261

Article	Housing Color		Price
342261	White	NW	€ 559.95
342262	Light grey	NW	€ 559.95
342263	Black	NW	€ 559.95






OFFICE ONE

- Very low glare value
- Service life 50,000 h L80B10
- Dimmable using touch sensor
- Ready to use

Application Area

Reception / Communication, Office / conference, Home office / study, Education / school / lecture theatre

Housing	Aluminium	Power	80 W
Colour Temperature	4000 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	7400 lm	Power Supply Unit incl.	Yes
Length	610 mm	Light Beam Angle	110 Degree
Width	310 mm	Light Beam Angle 2	90 Degree
Height	1950 mm	Primary Cable Length	1.5 m
Base Length	460 mm	Primary Connection End	Power plug
Base Width	300 mm	CRI (Ra)	80
Base Height	8 mm		



343030

Article	Housing Color	Price
343030	Silver	€ 655.95





OFFICE ONE MOTION

- Very low glare value
- Service life 50,000 h L80B10
- Dimmable using touch sensor
- Motion sensor
- Ready to use

Application Area


Reception / Communication, Office / conference, Home office / study, Education / school / lecture theatre

Housing	Aluminium	Power	80 W
Colour Temperature	4000 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	7400 lm	Power Supply Unit incl.	Yes
Length	610 mm	Light Beam Angle	110 Degree
Width	310 mm	Light Beam Angle 2	90 Degree
Height	1950 mm	Primary Cable Length	1.5 m
Base Length	460 mm	Primary Connection End	Power plug
Base Width	300 mm	CRI (Ra)	80
Base Height	8 mm	Motion Detector	Yes

Article	Housing Color	Price
343032	Silver	€ 759.95








OFFICE ONE TRANSPARENT

Application Area
Reception / Communication, Office / conference, Home office / study, Education / school / lecture theatre

Housing	Aluminium	Power	55 W
Colour Temperature	4000 K	Rated Input Voltage	200-240 V/AC
Luminous Flux	6245 lm	Power Supply Unit incl.	No
Length	610 mm	Light Beam Angle	150 Degree
Width	310 mm	Light Beam Angle 2	150 Degree
Height	1950 mm	Primary Cable Length	2.5 m
Base Length	500 mm	Primary Connection End	Power plug
Base Width	225 mm	CRI (Ra)	80
Base Height	8 mm		



343022

Article	Housing Color	Price
343022	Silver	€ 655.95





OFFICE THREE

The OFFICE THREE series is our bestseller and problem solver for lighting individual workstations. Available as a free-standing or table lamp, the OFFICE THREE impresses with excellent light quality [Ra95] and glare-free [UGR<6] and ensures fatigue-free working in any situation. Thanks to the individually adjustable brightness for direct and indirect light, OFFICE THREE enables high-quality and flexible illumination of individual workstations. Optimised for tables with standard dimensions of 160 x 80 cm, the series is also suitable for other table sizes.



High-precision radar presence detector

- The 24Ghz presence sensor recognises even the smallest movements on the desk - such as movements of the computer mouse - and switches the light on automatically. Faulty switch-offs are effectively prevented despite the short run-on time.
- Without movement, the brightness is reduced to 30% after 5*/15/30 minutes [*default setting].
- If there is no movement, the light switches off after a further 5*/15/30 minutes [*default setting].

Daylight sensor

- Switch on the light and dim to the desired brightness [this setting is saved by the daylight sensor as the default].
- As soon as the ambient light changes, the sensor adjusts the brightness according to the stored standard [10% tolerance].



Touch panel

- Brightness of direct and indirect light separately or synchronised, infinitely adjustable
- Direct and indirect light can be switched separately
- Continuously adjustable light colour [PRO models only]
- Adjustable run-on time of the presence sensor




Universal table clamp

- table clamp can be used for table tops with a total thickness of 15-65 mm [incl. substructure] as required
- If part of the frame construction runs in the clamping area of the luminaire, the hard rubber buffers supplied must be used to compensate for the unevenness and create a flush clamping area.
- The universal design of the table clamp allows it to be mounted on almost all table tops.



Optional mounting kit

- For larger table tops or for free positioning on the table, the optional mounting kit can be used instead of the pre-installed table clamp. This is simply mounted through a drill hole in the table.
- suitable for table tops with a total thickness of 15-35 mm
- suitable for hole diameters from 22-30 mm




OFFICE THREE STANDARD FLOOR

- Suitable for workstations with screens (in accordance with EN 12464-1 BAP65 [L65 <=3,000 cd/m²])
- Eligible for BEG German federal funding for energy-efficient buildings
- Ideal for high-quality illumination of individual workstations
- Redesigned and extended lamp head for ideal illumination of 160 x 80 cm tables
- Direct and indirect light can be dimmed and switched separately using touch panel
- Adjustable switch-off delay of the sensor [5/15/30 mins]
- High-precision radar presence detector detects the smallest movements
- Daylight sensor for dynamic brightness adjustment

Application Area

Reception / Communication, Office / conference, Home office / study, Education / school / lecture theatre

Housing	Aluminium	Power	80 W
Colour Temperature	4000 K	Rated Input Voltage	180-264 V/AC
Luminous Flux	10100 lm	Power Supply Unit incl.	Yes
Length	1240 mm	Light Beam Angle	120 Degree
Width	64 mm	Light Beam Angle 2	50 Degree
Height	1950 mm	Primary Cable Length	2.5 m
Base Length	530 mm	Primary Connection End	Safety plug
Base Width	225 mm	CRI (Ra)	95
Base Height	10 mm	Motion Detector	Yes



342228

Article	Housing Color		Price
342228	White	NW	€ 999.95
342229	Light grey	NW	€ 999.95
342230	Black	NW	€ 999.95






OFFICE THREE STANDARD TABLE

- Suitable for workstations with screens (in accordance with EN 12464-1 BAP65 [$L_{65} \leq 3,000 \text{ cd/m}^2$])
- Eligible for BEG German federal funding for energy-efficient buildings
- Ideal for high-quality illumination of height-adjustable individual workstations
- Redesigned and extended lamp head for ideal illumination of 160x80 cm tables
- Suitable for table designs with 15-65 mm thickness
- Direct and indirect light can be dimmed and switched separately using touch panel
- High-precision radar presence detector detects the smallest movements
- Adjustable switch-off delay of the sensor [5/15/30 mins]
- Daylight sensor for dynamic brightness adjustment
- Incl. 2.5 m connecting cable with safety plug and C21 mains plug
- Incl. hard rubber buffers for use with table designs that run close to the edge

Application Area

Reception / Communication, Office / conference, Home office / study, Education / school / lecture theatre

Housing	Aluminium	Power	80 W
Colour Temperature	4000 K	Rated Input Voltage	180-264 V/AC
Luminous Flux	10100 lm	Power Supply Unit incl.	Yes
Length	1240 mm	Light Beam Angle	120 Degree
Width	64 mm	Light Beam Angle 2	50 Degree
Height	1194 mm	Primary Cable Length	2.5 m
Base Length	115 mm	Primary Connection End	Safety plug
Base Width	80 mm	CRI (Ra)	95
Base Height	120 mm	Motion Detector	Yes



346063

Article	Housing Color		Price
346063	☐ White	NW	€ 839.95
346064	☐ Light grey	NW	€ 839.95
346065	☒ Black	NW	€ 839.95



Accessories for 346063

930727 Assembly kit for table lamp Office Three

 € 31.95

Accessories for 346064

930728 Assembly kit for table lamp Office Three, light grey

 € 31.95

Accessories for 346065

930729 Assembly kit for table lamp Office Three

 € 31.95




OFFICE THREE PRO FLOOR

- Suitable for workstations with screens (in accordance with EN 12464-1 BAP65 [L65 <=3,000 cd/m²])
- Eligible for BEG German federal funding for energy-efficient buildings
- Ideal for high-quality illumination of individual workstations
- Redesigned and extended lamp head for ideal illumination of 160 x 80 cm tables
- Direct and indirect light can be dimmed and switched separately using touch panel
- Light colour adjustable via touch panel
- High-precision radar presence detector detects the smallest movements
- Adjustable switch-off delay of the sensor [5/15/30 mins]
- Daylight sensor for dynamic brightness adjustment

Application Area


Reception / Communication, Office / conference, Home office / study, Education / school / lecture theatre

Housing	Aluminium	Power	80 W
Colour Temperature	2700-6500 K	Rated Input Voltage	180-264 V/AC
Luminous Flux	9000/9800 lm	Power Supply Unit incl.	Yes
Length	1240 mm	Light Beam Angle	120 Degree
Width	64 mm	Light Beam Angle 2	50 Degree
Height	1950 mm	Primary Cable Length	2.5 m
Base Length	530 mm	Primary Connection End	Safety plug
Base Width	225 mm	CRI (Ra)	95
Base Height	10 mm	Motion Detector	Yes



Article	Housing Color		Price
342231	White	CW	€ 1167.95
342232	Light grey	CW	€ 1167.95
342233	Black	CW	€ 1167.95






OFFICE THREE PRO TABLE

- Suitable for workstations with screens (in accordance with EN 12464-1 BAP65 [$L65 \leq 3,000 \text{ cd/m}^2$])
- Eligible for BEG German federal funding for energy-efficient buildings
- Ideal for high-quality illumination of height-adjustable individual workstations
- Redesigned and extended lamp head for ideal illumination of $160 \times 80 \text{ cm}$ tables
- Suitable for table designs with 15-65 mm thickness
- Direct and indirect light can be dimmed and switched separately using touch panel
- Light colour adjustable via touch panel
- High-precision radar presence detector detects the smallest movements
- Daylight sensor for dynamic brightness adjustment

Application Area


Reception / Communication, Office / conference, Home office / study, Education / school / lecture theatre

Housing	Aluminium	Power	80 W
Colour Temperature	2700-6500 K	Rated Input Voltage	180-264 V/AC
Luminous Flux	9000/9800 lm	Power Supply Unit incl.	Yes
Length	1240 mm	Light Beam Angle	120 Degree
Width	64 mm	Light Beam Angle 2	50 Degree
Height	1194 mm	Primary Cable Length	2.5 m
Base Length	115 mm	Primary Connection End	Safety plug
Base Width	80 mm	CRI (Ra)	95
Base Height	120 mm	Motion Detector	Yes



346066

Article	Housing Color	Price
346066	☐ White WW CW	€ 999.95
346067	☐ Light grey WW CW	€ 999.95
346068	☐ Black WW CW	€ 999.95



Accessories for 346066

930727 Assembly kit for table lamp Office Three

 € 31.95

Accessories for 346067

930728 Assembly kit for table lamp Office Three, light grey

 € 31.95

Accessories for 346068

930729 Assembly kit for table lamp Office Three

 € 31.95

hall floodlights



■
page 219



■
page 220



■
page 222



■
page 225








HIGHBAY BASIC

- cost-effective and powerful
- particularly energy-efficient and economical
- power adjustable in three stages
- light colour adjustable in three stages

Application Area

Workshop / Craft / Warehouse, DIY store / discount store / supermarket / car dealership, Industry / production / high-bay warehouse

Housing	Aluminium, Polycarbonate, Steel	Power Selectable	210 W, 160 W, 110 W
Colour Temperature	4000/4500/5700 K	Rated Input Voltage	100-277 V/AC
Luminous Flux	33500/34500/33500 lm	Power Supply Unit incl.	Yes
Height	111 mm	Light Beam Angle	90 Degree
Ø	302 mm	CRI (Ra)	80
		IK Protection Class	IK08



732162

Article	Housing Color	Price
732162	Black	€ 140.95



Accessories

930977	60° Lens for Highbay Basic	€ 15.95
930978	120° Lens for Highbay Basic	€ 15.95
930641	Chain suspension 1 m for Alludra / Highbay Basic / Vega	€ 11.95
930685	Chain suspension 3 m for Alludra / Highbay Basic / Vega	€ 19.95
930742	Wall assembly arm for Vega OnOff, Highbay Basic	€ 31.95
930571	Outdoor cable conn. 2 cables 4-14 mm, 2-5 strands 0.5-4 mm², 450 V AC/24 A	€ 7.95
930573	Outdoor Y connector for 3 cables 4-14 mm, 3 strands, 0.5-4 mm², 450 V AC/24 A	€ 8.95



Lighting design

Interested in our lighting design service?

Your contact person will be happy to answer any questions you may have.



HIGHBAY BASIC DALI

The Highbay Basic DALI high-bay spotlight combines high light output with economic efficiency and flexible adaptability. Thanks to selectable output and switchable light color in three levels, the high bay spotlight is ideal for industrial halls, storage areas and production areas. The DALI-2/D4i control system enables modern lighting management including Intelli-Data function for luminaire, energy and maintenance data.






HIGHBAY BASIC DALI

- cost-effective and high-performance
- particularly energy-efficient and economical
- output adjustable in three stages
- light colour adjustable in three stages
- with Intelli-Data: Dali parts 251, 252, 253 for lighting, energy and maintenance data
- with D4i driver for direct connection to DALI sensors

Application Area

Workshop / Craft / Warehouse, DIY store / discount store / supermarket / car dealership, Industry / production / high-bay warehouse

Housing	Aluminium, Polycarbonate, Steel	Power Selectable	210 W, 160 W, 110 W
Colour Temperature	4000/4500/5700 K	Rated Input Voltage	100-277 V/AC
Luminous Flux	33500/34500/33500 lm	Power Supply Unit incl.	Yes
Height	111 mm	Light Beam Angle	90 Degree
Ø	302 mm	Control	DALI 2 / DT6 D4i
		CRI (Ra)	80
		IK Protection Class	IK08



732163

Article	Housing Color	Price
732163	Black NW CW	€ 167.95



Accessories

930977	60° Lens for Highbay Basic	€ 15.95
930978	120° Lens for Highbay Basic	€ 15.95
930641	Chain suspension 1 m for Alludra / Highbay Basic / Vega	€ 11.95
930685	Chain suspension 3 m for Alludra / Highbay Basic / Vega	€ 19.95
930742	Wall assembly arm for Vega OnOff, Highbay Basic	€ 31.95
930571	Outdoor cable conn. 2 cables 4-14 mm, 2-5 strands 0.5-4 mm², 450 V AC/24 A	€ 7.95




Technical data sheet

New in the onlineshop: The technical data sheets offer even more information: Light and energy data, light distribution curves, dimensional drawings and more.



VEGA

The VEGA high-bay light - quality that shines through. The high-bay light is the perfect solution for industrial halls/warehouses where first-class lighting is required. The variant with three selectable output levels can adapt to your requirements. The spotlights are also very energy efficient, which has a positive effect on your operating costs. A long service life of 50,000 hours (L80B20) ensures reliable, no-compromise lighting for a long time to come. With optional lenses, the VEGA spotlights can achieve a UGR value below 19, ensuring glare-free light. We also offer variants with DALI control capability for those wanting precise lighting control. The high-bay lights are also eligible for BEG German federal funding for energy-efficient buildings.






VEGA

- High-quality, flexible and powerful high-bay lights
- Suitable for fire-prone facilities (EN60598-2-24)
- Output adjustable in three stages
- UGR <19 with optional lens
- Particularly energy efficient

Application Area

Workshop / Craft / Warehouse, DIY store / discount store / supermarket / car dealership, Industry / production / high-bay warehouse

Housing	Aluminium	Rated Input Voltage	100-277 V/AC
Surface	Powder-coated	Power Supply Unit incl.	Yes
Luminous Flux	28800 lm	Light Beam Angle	120 Degree
Height	120 mm	Primary Cable Length	1.5 m
Ø	400 mm	CRI (Ra)	80
Power Selectable	90 W, 130 W, 160 W	IK Protection Class	IK09



732156

Article	Housing Color	Colour Temperature	Price
732156	Black	4000 K	€ 255.95
732158	Black	5700 K	€ 255.95



Accessories

930742	Wall assembly arm for Vega OnOff, Highbay Basic	€ 31.95
930743	60° lens for Vega	€ 39.95
930641	Chain suspension 1 m for Alludra / Highbay Basic / Vega	€ 11.95
930685	Chain suspension 3 m for Alludra / Highbay Basic / Vega	€ 19.95



5-year guarantee
Benefit from the maximum quality promise:
All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.






VEGA DALI

- High-quality, flexible and powerful high-bay lights
- Suitable for fire-prone facilities (EN60598-2-24)
- UGR <19 with optional lens
- Particularly energy efficient

Application Area

Workshop / Craft / Warehouse, DIY store / discount store / supermarket / car dealership, Industry / production / high-bay warehouse

Housing	Aluminium	Power Supply Unit incl.	Yes
Surface	Powder-coated	Light Beam Angle	120 Degree
Luminous Flux	28800 lm	Control	DALI 2 / DT6
Height	122 mm	Primary Cable Length	1.5 m
Ø	400 mm	CRI (Ra)	80
Power	160 W	IK Protection Class	IK09
Rated Input Voltage	100-277 V/AC		



732157

Article	Housing Color	Colour Temperature	Price
732157	Black	NW 4000 K	€ 295.95
732159	Black	CW 5700 K	€ 295.95



Accessories

930743	60° lens for Vega
930775	Wall assembly arm for Vega DALI
930641	Chain suspension 1 m for Alludra / Highbay Basic / Vega
930685	Chain suspension 3 m for Alludra / Highbay Basic / Vega



Onlineshop

You can find more information about the products in the onlineshop:
Detailed images, videos, project reports, LDT files, EPREL data sheets and more.

damp-proof luminaires



■
page 229



■
page 230



■
page 231



□ ■ ■
page 232




□ ■ ■
page 234



□ ■ ■
page 235








TRI PROOF BASIC

- Eligible for BEG German federal funding for energy-efficient buildings
- Particularly energy efficient
- Long service life of 50,000 hours L80B50
- Pre-installed feed-through wiring 3x1.5 mm²
- Cable entry point on the back
- Stainless steel clips on the cover can be locked with screws
- Robust polycarbonate [PC] plastic housing

Application Area

Garage / carport / car park, Workshop / Craft / Warehouse, Industry / production / high-bay warehouse, Basement / damp room, Multi-storey car park / underground car park, Retrofit / Refurbishment

Housing	Polycarbonate, Steel	Number in Row max.	15
Colour Temperature	4000 K	Power Supply Unit incl.	Yes
Width	82 mm	Light Beam Angle	120 Degree
Height	75 mm	CRI (Ra)	80
Rated Input Voltage	220-240 V/AC	IK Protection Class	IK08



730489

Article	Housing Color	Luminous Flux	Length	Power	Price
730509	Light grey	1400 lm	610 mm	10.0 W	€ 39.95
730483	Light grey	2520 lm	610 mm	18.0 W	€ 43.95
730510	Light grey	2800 lm	1210 mm	20.0 W	€ 55.95
730511	Light grey	4200 lm	1510 mm	30.0 W	€ 63.95
730486	Light grey	5040 lm	1210 mm	36.0 W	€ 63.95
730489	Light grey	7700 lm	1510 mm	55.0 W	€ 75.95




Accessories

930713	Cable suspension for Tri Proof Basic		€ 15.95
931098	Cable gland PG/M20 incl. locknut + sealing ring, IP68		€ 1.75



Lighting design

Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.




TRI PROOF BASIC MOTION

- Eligible for German BEG federal funding
- Particularly energy efficient
- Long service life of 50,000 hours (L80B50)
- Continuous 3x1.5 mm² wiring pre-installed
- Cable entry point on the back
- Stainless steel clips on the cover can be locked with screws
- Robust polycarbonate (PC) plastic housing
- Adjustable radar motion sensor

Application Area

Garage / carport / car park, Workshop / Craft / Warehouse, Industry / production / high-bay warehouse, Basement / damp room, Multi-storey car park / underground car park, Retrofit / Refurbishment

Housing	Polycarbonate (PC)/iron	Number in Row max.	15
Colour Temperature	4000 K	Power Supply Unit incl.	Yes
Width	82 mm	Light Beam Angle	120 Degree
Height	75 mm	CRI (Ra)	80
Rated Input Voltage	220-240 V/AC	Motion Detector	Yes
		IK Protection Class	IK08



730490

Article	Housing Color	Luminous Flux	Length	Power	Price
730484	Light grey	2520 lm	610 mm	18.0 W	€ 59.95
730487	Light grey	5040 lm	1210 mm	36.0 W	€ 79.95
730490	Light grey	7700 lm	1510 mm	55.0 W	€ 91.95



Accessories

930713	Cable suspension for Tri Proof Basic		€ 15.95
931098	Cable gland PG/M20 incl. locknut + sealing ring, IP68		€ 1.75



5-year guarantee
Benefit from the maximum quality promise:
All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.




TRI PROOF BASIC DALI

- Eligible for BEG German federal funding for energy-efficient buildings
- Emergency power capable [180-264 V/DC EOFI: 15 %]
- Particularly energy efficient
- Long service life of 50,000 hours L80B50
- Pre-installed feed-through wiring 5x 1.5 mm²
- Cable entry point on the back
- Stainless steel clips on the cover can be locked with screws
- Robust plastic housing

Application Area

Garage / carport / car park, Workshop / Craft / Warehouse, Industry / production / high-bay warehouse, Basement / damp room, Multi-storey car park / underground car park, Safety lighting / emergency lighting, Retrofit / Refurbishment

Housing	Polycarbonate (PC)/ iron	Power Supply Unit incl.	Yes
Colour Temperature	4000 K	Light Beam Angle	120 Degree
Width	82 mm	Control	DALI 2 / DT6, Intelli Push-Dim
Height	75 mm	CRI (Ra)	80
Rated Input Voltage	220-240 V/AC	IK Protection Class	IK08
Number in Row max.	15		



730491

Article	Housing Color	Luminous Flux	Length	Power	Price
730485	Light grey	2520 lm	610 mm	18.0 W	€ 83.95
730488	Light grey	5040 lm	1210 mm	36.0 W	€ 103.95
730491	Light grey	7700 lm	1510 mm	55.0 W	€ 127.95



Accessories


930713	Cable suspension for Tri Proof Basic		€ 15.95
931098	Cable gland PG/M20 incl. locknut + sealing ring, IP68		€ 1.75



Lighting design

Interested in our lighting design service?

Your contact person will be happy to answer any questions you may have.






SOTANO

- Classic cellar light with modern LED technology
- Colour temperature adjustable (3,000/4,000 K) via slide switch
- Output adjustable in two stages (4.5/7.5 W) via slide switch
- Six cable entry points on multiple sides
- Flexible installation

Application Area

Garage / carport / car park, Workshop / Craft / Warehouse, Basement / damp room, Multi-storey car park / underground car park, Refurbishment

Housing	Polycarbonate	Power Selectable	4.5 W, 7.5 W
Colour Temperature	3000/4000 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	450/750 lm	Power Supply Unit incl.	Yes
Length	165 mm	Light Beam Angle	120 Degree
Width	120 mm	Light Direction	Front
Height	65 mm	IK Protection Class	IK08



731160

Article	Housing Color		Price
731160	White	WW NW	€ 13.95
731161	Grey	WW NW	€ 13.95
731162	Black	WW NW	€ 13.95



5-year guarantee

Benefit from the maximum quality promise:

All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.



SOTANO RETRO ROUND

- Classic, low-cost cellar lamp
- Replaceable lamp [E27]
- Cable entry on multiple sides
- Several mounting points for flexible installation

Application Area

Garage / carport / car park, Workshop / Craft / Warehouse, Basement / damp room

Housing	PP - Polypropylene	Rated Input Voltage	220-240 V/AC
Height	100 mm	Control	Dimmable via optional light source
Ø	180 mm	IK Protection Class	IK06
Max. Power	1x max. 60 W		

Article	Housing Color	Price
731163	 White	€ 10.95
731164	 Grey	€ 10.95
731165	 Black	€ 10.95



Light sources
For all lights and bases:
You can find the right light sources in the »Light sources« section.



SOTANO RETRO OVAL


- Classic, low-cost cellar lamp
- Replaceable lamp [E27]
- Cable entry on multiple sides
- Several mounting points for flexible installation

Application Area

Garage / carport / car park, Workshop / Craft / Warehouse, Basement / damp room

Housing	PP - Polypropylene	Rated Input Voltage	220-240 V/AC
Length	186 mm	Control	Dimmable via optional light source
Width	122 mm	IK Protection Class	IK06
Height	108 mm		
Max. Power	1x max. 60 W		

Article	Housing Color	Price
731166	White	€ 8.95
731167	Grey	€ 8.95
731168	Black	€ 8.95



Onlineshop

You can find more information about the products in the onlineshop:
Detailed images, videos, project reports, LDT files, EPREL data sheets and more.



TRUNKING SYSTEMS

240 trunking systems

Trunking systems



☐ page 244



☐ page 247



☐ page 248



☐ page 249



☐ page 250



☐ page 251



☐ page 257



☐ page 257



☐ page 258



☐ page 259



☐ page 260



☐ page 261



SANOTRUNK UNIVERSAL – THE SMART SOLUTION FOR MODERN LIGHTING REFURBISHMENTS

Want to modernize old T5 and T8 trunking systems efficiently and sustainably? With SANOTRUNK UNIVERSAL, you can make almost any trunking system fit for the future.

SANOTRUNK UNIVERSAL sets new standards in terms of compatibility. Thanks to quick-fit clips and tool-free installation, the system can be integrated into almost all standard trunking systems - whether from Philips, RIDI, Trilux, Zumtobel or other manufacturers. The continuous halogen-free 5 or 7-core through-wiring, the integrated plug connectors and a selection of interchangeable lens optics [including 30°, 90°, 25° asymmetrical on one or both sides] make adaptation to any application child's play. The conversion is carried out in five simple steps:



1 - old light inserts removed [wiring remains in]



2 - hang new LED modules in old mounting rail



3 - connect modules and adjust power if necessary



4 - click in the modules



5 - finished

COMPATIBILITY OVERVIEW

brand	trunk name	shape
AEG	Gealux-TS XX	
AEG/PHILIPS	Maxos	
Antaris	Antaris	
Antaris	trunking system	
ClickLUX Tragschiene	701501880016/ 703002880017/ 704503880018	
Fluolite	TRX / TRZ	
Fluora	Mini-Fix	
Kandem	SV70 / SV75	
Lite Licht	E-STN	
Lite Licht	Q-EMMS	
Lite Licht	Q-Rail Q-TS	
Lite Licht	Q-STN***	
Litec		
Ludwig	TR50W	
Lunix	Q-STN***	
MOLTOMX	Prestige	
Newlec	HSDT	
Norton	NSL	
OMS	Prestige	
Philips	Maxos TL5 / Maxos TL-D	
Philips	TTX150	
Philips	TTX200	
Philips	TTX400	
Philips	TTX400 T5 / TTX400 T8	
Regent	Traq	


brand	trunk name	shape
Regent	ICE**	
Regiolux	SDT	
Regiolux	SDT XX	
Regiolux	SMT / SPT	
RIDI	VLG XX	
RIDI, new trunking system	VLT***	
RIDI, new trunking system	VLT XX	
RZB	Planos	
Siemens	5LJ80XX	
Siemens	5LJ9*	
Siemens	5LS8..	
Siteco	DUS*	
Siteco	Modario	
Thron	090554 / 098287	
Trilux	07650XX	
Trilux	07690XX	
Trilux	218120 (7761/7861)	
Trilux	7910X** / 7920X**	
Trilux	7770	
VEKO	PRN	
Zumtobel	PNR	
Zumtobel	Tecton	
Zumtobel	ZX1	
Zumtobel	ZX2 T8 / ZX2 T5	

with optional mounting bracket

* 930931 | ** 930932 | *** 930933

BENEFITS FOR EVERY APPLICATION

The SANOTRUNK UNIVERSAL refurbishment insert offers a wide range of possible applications and enables sustainable modernisation of your lighting.



Supermarket / Sales Area

Optic: 25° asymmetric, single- or double-sided

Benefit: The asymmetric light distribution illuminates shelf areas precisely, avoids stray light in the aisles, and creates a pleasant, sales-promoting atmosphere.

Promotional displays or end caps can be illuminated using the spot-light modules.



Industrial and Production Halls

Optic: 90° beam angle

Benefit: Uniform, standard-compliant illumination of work areas. Ideal for precision tasks and safety-relevant activities.



Warehouse / High-Bay Storage

Optics: 30°, 60° or 90°

Benefit: Deep shelving aisles and varying storage heights can be illuminated with pinpoint accuracy. The light reaches the lowest and highest levels – without shadows or isolated light spots.

The shelving areas are also illuminated evenly, ensuring that shelf spaces remain clearly visible.




Workshops / Assembly Areas

Optic: 120° beam angle

Benefit: Broad, low-shadow illumination of entire rooms. Perfect for fine assembly work, inspections, or manual tasks with high lighting requirements.

The homogeneous light-line appearance fully meets even the highest aesthetic demands.



SANOTRUNK UNIVERSAL

The SANOTRUNK trunking system is a specially developed retrofit solution for the fast and cost-effective modernisation of existing T5 and T8 trunking systems. By reusing existing trunking rails, installation effort is minimised and tool-free mounting is enabled. Thanks to its compatible system architecture, SANOTRUNK UNIVERSAL can be integrated into trunking systems from leading manufacturers such as Philips, Trilux, Siteco, Zumtobel, Regiolux, Ridi, Fluolite and many others.

In addition to retrofit projects, SANOTRUNK trunking rails are also suitable for extending existing installations and for creating completely new lighting systems.

The pre-wired through-wiring with 2.5 mm² conductor cross-section ensures reliable power distribution across long trunking runs and multiple circuits. Existing wiring can continue to be used as a power supply if required.

Power-switch technology or DALI control [depending on the model] allow flexible adaptation of the lighting system. Optional blank covers and connectors provide maximum flexibility when designing lighting layouts.






SANOTRUNK UNIVERSAL

- Renovation solution for T5/T8 light strip systems
- Continued use of existing mounting rails possible
- Easy, quick and reliable installation
- Compatible with common manufacturers
- Eligible for BEG German federal funding for energy-efficient buildings
- Can run on emergency power
- Can be individually adapted to the lighting circumstances

Application Area

Shop / Retail / Sales area, DIY store / discount store / supermarket / car dealership, Industry / production / high-bay warehouse, Refurbishment, Safety lighting / emergency lighting

Housing	Aluminium	Height	31 mm
Colour Temperature	4000 K	Rated Input Voltage	198-264 V/AC
Length	1528 mm	CRI (Ra)	80
Width	65.6 mm	IK Protection Class	IK04




707228

Article	Housing Color	Luminous Flux	Power Selectable	Light Beam Angle	Price
707228	☐ White	NW 11600 lm	75 / 68 / 59 / 52 / 42 / 36 / 27 / 21 W	120 Degree	€ 179.95
707227	☐ White	NW 12200 lm	70 / 64 / 55 / 49 / 39 / 34 / 26 / 20 W	90 Degree	€ 179.95
707226	☐ White	NW 12400 lm	70 / 64 / 55 / 49 / 39 / 34 / 26 / 20 W	30 Degree	€ 179.95




Accessories


930915	Sanotrunk Universal Lense, Set 5 pcs, 30 degree		€ 23.95
930916	Sanotrunk Universal Lense, Set 5 pcs, 60 degree		€ 23.95
930917	Sanotrunk Universal Lense, Set 5 pcs, 90 degree		€ 23.95
930918	Sanotrunk Universal Lense, Set 5 pcs, 25 degree, single side asymmetrical		€ 23.95
930919	Sanotrunk Universal Lense, Set 5 pcs, 25 degree, double side asymmetrical		€ 23.95
930920	Sanotrunk universal dummy cover, shortenable, PC		€ 15.95
930922	Sanotrunk Universal Blind Cover Aluminium		€ 31.95
930921	Sanotrunk universal mounting clips for blind cover, can be shortened 2 pcs.		€ 3.95
930931	Sanotrunk universal mounting clips Siteco DUS / Simens 5LJ9 2 pcs.		€ 3.95
930932	Sanotrunk universal mounting clamps Regent ICE 2 pcs.		€ 3.95
930933	Sanotrunk universal mounting clips RIDI VLT(old) / Lite-Light Q-STN / Lunux Q-STN 2 pcs.		€ 3.95
930923	Sanotrunk Universal Power feed socket WAGO 267-501		€ 9.95
930924	Sanotrunk Universal Power supply plug WAGO 267-510		€ 9.95
930925	Sanotrunk Universal Power supply socket On/Off wired WAGO 267-501		€ 11.95
930927	Sanotrunk Universal Power supply plug On/Off wired WAGO 267-510		€ 13.95
930929	Connector, Sanotrunk Universal		€ 35.95




30°




90°




120°



60°



25°, asymmetrical on one side



25°, double-sided asymmetrical






SANOTRUNK UNIVERSAL DALI

- Renovation solution for T5/T8 light strip systems
- Continued use of existing mounting rails possible
- Easy, quick and reliable installation
- Compatible with common manufacturers
- Eligible for BEG German federal funding for energy-efficient buildings
- Can run on emergency power
- DALI versions with Intelli-Data: Dali parts 251, 252, 253 for lighting, energy and maintenance data
- Can be individually adapted to the lighting circumstances

Application Area

Shop / Retail / Sales area, DIY store / discount store / supermarket / car dealership, Industry / production / high-bay warehouse, Refurbishment, Safety lighting / emergency lighting

Housing	Aluminium	Rated Input Voltage	198-264 V/AC
Colour Temperature	4000 K	Control	DALI 2 / DT6, Push-Dim
Length	1528 mm	CRI (Ra)	80
Width	65.6 mm	IK Protection Class	IK04
Height	31 mm		



707229

Article	Housing Color	Luminous Flux	Power	Light Beam Angle	Price
707231	☐ White 	11600 lm	75.0 W	120 Degree	€ 219.95
707230	☐ White 	12200 lm	70.0 W	90 Degree	€ 219.95
707229	☐ White 	12400 lm	70.0 W	30 Degree	€ 219.95



Accessories

930915	Sanotrunk Universal Lense, Set 5 pcs, 30 degree		€ 23.95
930916	Sanotrunk Universal Lense, Set 5 pcs, 60 degree		€ 23.95
930917	Sanotrunk Universal Lense, Set 5 pcs, 90 degree		€ 23.95
930918	Sanotrunk Universal Lense, Set 5 pcs, 25 degree, single side asymmetrical		€ 23.95
930919	Sanotrunk Universal Lense, Set 5 pcs, 25 degree, double side asymmetrical		€ 23.95
930920	Sanotrunk universal dummy cover, shortenable, PC		€ 15.95
930922	Sanotrunk Universal Blind Cover Aluminium		€ 31.95
930921	Sanotrunk universal mounting clips for blind cover, can be shortened 2 pcs.		€ 3.95
930931	Sanotrunk universal mounting clips Siteco DUS / Simens 5LJ9 2 pcs.		€ 3.95
930932	Sanotrunk universal mounting clamps Regent ICE 2 pcs.		€ 3.95
930933	Sanotrunk universal mounting clips RIDI VLT(old) / Lite-Light Q-STN / Lunux Q-STN 2 pcs.		€ 3.95
930923	Sanotrunk Universal Power feed socket WAGO 267-501		€ 9.95
930924	Sanotrunk Universal Power supply plug WAGO 267-510		€ 9.95
930926	Sanotrunk Universal Power supply socket DALI wired WAGO 267-501		€ 11.95
930928	Sanotrunk Universal Power supply plug DALI wired WAGO 267-510		€ 13.95
930930	Connector, Sanotrunk Universal		€ 39.95




SANOTRUNK UNIVERSAL SPOT

- Refurbishment solution for T5/T8 trunking systems
- Further use of existing trunking possible
- Simple, quick and safe installation
- Compatible with leading manufacturers
- BEG eligible
- Emergency power capable
- Can be customised to lighting scenarios
- Reflector can be replaced
- ideal for promotional displays or shelf end caps

Application Area

Shop / Retail / Sales area, DIY store / discount store / supermarket / car dealership, Industry / production / high-bay warehouse, Refurbishment, Safety lighting / emergency lighting

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	4000 K	Light Beam Angle	36 Degree
Length	764 mm	Rotation Angle	355 Degree
Width	65 mm	Swivelling Angle	90 Degree
Height	144 mm	CRI (Ra)	90
Rated Input Voltage	198-264 V/AC	IK Protection Class	IK04



707274

Article	Housing Color	Luminous Flux	Power Selectable	Price
707274	☐ White	4260 lm	30 / 28 / 26 / 24 / 22 / 20 / 18 / 16 / 14 / 12 W	€ 143.95
707277	☐ White	8580 lm	60 / 58, / 56 / 54 / 52 / 50 / 48 / 46 / 44 / 42 / 40 / 38 / 30 W	€ 231.95



Accessories

931170	Sanotrunk Universal Spot, reflector 15 degrees
931171	Sanotrunk Universal Spot, reflector 24 degrees
931172	Sanotrunk Universal Spot, reflector 36 degrees
930923	Sanotrunk Universal Power feed socket WAGO 267-501
930924	Sanotrunk Universal Power supply plug WAGO 267-510
930925	Sanotrunk Universal Power supply socket On/Off wired WAGO 267-501
930927	Sanotrunk Universal Power supply plug On/Off wired WAGO 267-510
930931	Sanotrunk universal mounting clips Siteco DUS / Simens 5LJ9 2 pcs.
930932	Sanotrunk universal mounting clamps Regent ICE 2 pcs.
930933	Sanotrunk universal mounting clips RIDI VLT(old) / Lite-Light Q-STN / Lunux Q-STN 2 pcs.

	€ 5.45
	€ 5.45
	€ 5.45
	€ 9.95
	€ 9.95
	€ 11.95
	€ 13.95
	€ 3.95
	€ 3.95
	€ 3.95




SANOTRUNK UNIVERSAL SPOT DALI

- Refurbishment solution for T5/T8 trunking systems
- Further use of existing trunking possible
- Simple, quick and safe installation
- Compatible with leading manufacturers
- BEG eligible
- Emergency power capable
- Can be customised to lighting scenarios
- Reflector can be replaced
- with Intelli-Data: Dali Parts 251, 252, 253 for luminaire, energy and maintenance data
- ideal for promotional displays or shelf end caps

Application Area

Shop / Retail / Sales area, DIY store / discount store / supermarket / car dealership, Industry / production / high-bay warehouse, Refurbishment, Safety lighting / emergency lighting

Housing	Aluminium	Rotation Angle	355 Degree
Colour Temperature	4000 K	Swivelling Angle	90 Degree
Length	764 mm	Control	DALI 2 / DT6, Intelli Push-Dim
Width	65 mm	CRI (Ra)	90
Height	144 mm	IK Protection Class	IK04
Power Supply Unit incl.	Yes		
Light Beam Angle	36 Degree		




707280

Article	Housing Color	Lum. Flux	Power Selectable	Rated Input Voltage	Price
707280	☐ White	4260 lm	30 / 28 / 26 / 24 / 22 / 20 / 18 / 16 / 14 / 12 W	198-264 V/AC	€ 175.95
707283	☐ White	8580 lm	60 / 58 / 56 / 54 / 52 / 50 / 48 / 46 / 44 / 42 / 40 / 38 / 36 W	180-264 V/AC	€ 263.95



Accessories

931170	Sanotrunk Universal Spot, reflector 15 degrees		€ 5.45
931171	Sanotrunk Universal Spot, reflector 24 degrees		€ 5.45
931172	Sanotrunk Universal Spot, reflector 36 degrees		€ 5.45
930923	Sanotrunk Universal Power feed socket WAGO 267-501		€ 9.95
930924	Sanotrunk Universal Power supply plug WAGO 267-510		€ 9.95
930926	Sanotrunk Universal Power supply socket DALI wired WAGO 267-501		€ 11.95
930928	Sanotrunk Universal Power supply plug DALI wired WAGO 267-510		€ 13.95
930931	Sanotrunk universal mounting clips Siteco DUS / Simens 5LJ9 2 pcs.		€ 3.95
930932	Sanotrunk universal mounting clamps Regent ICE 2 pcs.		€ 3.95
930933	Sanotrunk universal mounting clips RIDI VLT(old) / Lite-Light Q-STN / Lunux Q-STN 2 pcs.		€ 3.95



SANOTRUNK UNIVERSAL SENSOR AND DEVICE CARRIER

- Accessory mounting up to 9kg [sensor, camera, shield]
- for electrical or mechanical accessories
- Integrated connection terminals for electrical accessories
- compatible with common motion, presence and daylight sensors [not included]

Housing	Aluminium	Height	0.3 mm
Length	51 mm	Rated Input Voltage	180-264 V/AC
Width	6.6 mm	IK Protection Class	IK04

Article	Housing Color	Price
931168	☐ White	€ 59.95




Accessories

930931	Sanotrunk universal mounting clips Siteco DUS / Simens 5LJ9 2 pcs.		€ 3.95
930932	Sanotrunk universal mounting clamps Regent ICE 2 pcs.		€ 3.95
930933	Sanotrunk universal mounting clips RIDI VLT(old) / Lite-Light Q-STN / Lunux Q-STN 2 pcs.		€ 3.95
930923	Sanotrunk Universal Power feed socket WAGO 267-501		€ 9.95
930924	Sanotrunk Universal Power supply plug WAGO 267-510		€ 9.95
930925	Sanotrunk Universal Power supply socket On/Off wired WAGO 267-501		€ 11.95
930927	Sanotrunk Universal Power supply plug On/Off wired WAGO 267-510		€ 13.95



Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.



SANOTRUNK UNIVERSAL DALI SENSOR AND DEVICE CARRIER

- Accessory mounting up to 9kg [sensor, camera, shield]
- for electrical or mechanical accessories
- Integrated connection terminals for electrical accessories
- compatible with common motion, presence and daylight sensors [not included]

Housing	Aluminium	Control	DALI 1 / DT6, DALI 1 / DT8, DALI 2 / DT6, DALI 2 / DT6 D4i, DALI 2 / DT8, DALI 2 / DT8 D4i
Length	51 mm		
Width	6.6 mm		
Height	0.3 mm		
Rated Input Voltage	180-264 V/AC	IK Protection Class	IK04

Article	Housing Color	Price
931169	☐ White	€ 63.95



Accessories

930931	Sanotrunk universal mounting clips Siteco DUS / Siemens 5LJ9 2 pcs.		€ 3.95
930932	Sanotrunk universal mounting clamps Regent ICE 2 pcs.		€ 3.95
930933	Sanotrunk universal mounting clips RIDI VLT(old) / Lite-Light Q-STN / Lunux Q-STN 2 pcs.		€ 3.95
930923	Sanotrunk Universal Power feed socket WAGO 267-501		€ 9.95
930924	Sanotrunk Universal Power supply plug WAGO 267-510		€ 9.95
930926	Sanotrunk Universal Power supply socket DALI wired WAGO 267-501		€ 11.95
930928	Sanotrunk Universal Power supply plug DALI wired WAGO 267-510		€ 13.95




5-year guarantee
Benefit from the maximum quality promise:
All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.

SANOTRUNKTRUNKING SYSTEM



components	illust.	item	page
mounting rail L: 1500 mm	01	930946	257
mounting rail L: 3000 mm	01	930947	257
feed-in box	02	931088	258
end piece	03	931089	258
end cap [2 pcs.]	04	930950	257
mounting clips for blind cover [2 pcs.]	05	930921	257
L-connector left	06	930954	259
L-connector right	07	930955	259
T-connector left	08	931090	260
T-connector right type A	09	930957	260
T-connector right type B	10	931091	260
T-connector double	11	930956	260
X-connector straight	12	930958	261
X-connector threefold	13	930959	261
cable gland M20	14	931098	257
mountg bracket for mounting rail [10 pcs.]	15	930951	257
suspension kit 5000 mm for mounting rail [10 pcs.]	16	930952	257
bracket chain suspension for mounting rail [10 pcs.]	17	930953	257
chain suspension 3000 mm	17	931087	257
holder for chain suspension for connector [10 pcs.]	18	931086	259

ILLUSTRATION OF THE COMPONENTS




MOUNTING POINTS

1528 mm INSTALLATION




1 Before assembly, join two 1.5-metre mounting rails securely and treat them as a single 3-metre support rail from then on.


3056 mm INSTALLATION



INSTALLATION OF THE LIGHT FITTINGS





PLANNING GUIDE



Lighting design

Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.





SANOTRUNK MOUNTING RAILS

Housing	Steel	Height	45 mm
Width	65 mm		

Article	Housing Color	Length	Price
930946	White	1528 mm	€ 19.95
930947	White	3056 mm	€ 33.95

Accessories

930951	Sanotrunk, mounting Bracket for Trunking Rail, Set 10 Pcs.		€ 13.95
930952	Sanotrunk, Suspension Kit 5,0 m for Trunking Rail, Set 10 Pcs.		€ 71.95
930953	Sanotrunk, Bracket Chain Suspension for Trunking Rail, Set 10 Pcs.		€ 23.95
930950	Sanotrunk, Endcap for Trunking Rail, Set 2 Pcs.		€ 4.95
930948	Sanotrunk, Cover for Trunking Rail 1,5 m		€ 7.95
930949	Sanotrunk, Cover for Trunking Rail 3,0 m		€ 15.95
931087	Sanotrunk, chain suspension, 3m		€ 7.95
931098	Cable gland PG/M20 incl. locknut + sealing ring, IP68		€ 1.75



SANOTRUNK UNIVERSAL BLIND COVER

Length	1528 mm
--------	---------

Article	Housing Color	Housing	Width	Height	Price
930922	White	Aluminium	65.6 mm	26 mm	€ 31.95
930920	White	Polycarbonate	can be shortened 62 mm	19.2 mm	€ 15.95

Accessories for 930920

930921	Sanotrunk universal mounting clips for blind cover, can be shortened 2 pcs.		€ 3.95
--------	---	--	--------



SANOTRUNK FEED-IN BOX + END PIECE

Housing	Aluminium	Control	DALI 1 / DT6, DALI 1 / DT8, DALI 2 / DT6, DALI 2 / DT6 D4i, DALI 2 / DT8, DALI 2 / DT8 D4i
Width	64.7 mm		
Height	65.5 mm		

Article	Housing Color	Type	Length	Price
931088	☐ White	feed piece including integrated connection block	383.1 mm	€ 33.95
931089	☐ White	end piece	237.1 mm	€ 15.95




Accessories

930951	Sanotrunk, mounting Bracket for Trunking Rail, Set 10 Pcs.		€ 13.95
930952	Sanotrunk, Suspension Kit 5,0 m for Trunking Rail, Set 10 Pcs.		€ 71.95
930953	Sanotrunk, Bracket Chain Suspension for Trunking Rail, Set 10 Pcs.		€ 23.95
931087	Sanotrunk, chain suspension, 3m		€ 7.95
931098	Cable gland PG/M20 incl. locknut + sealing ring, IP68		€ 1.75



Onlineshop
You can find more information about the products in the onlineshop:
Detailed images, videos, project reports, LDT files, EPREL data sheets and more.



SANOTRUNK L-CONNECTOR

- Pre-wiring with 7 cores, incl. DALI cables
- suitable for DALI and ON / OFF

Housing	Aluminium	Control	DALI 1 / DT6, DALI 1 / DT8, DALI 2 / DT6, DALI 2 / DT6 D4i, DALI 2 / DT8, DALI 2 / DT8 D4i
Length	304.3 mm		
Width	304.3 mm		
Height	73 mm		

Article	Housing Color	Type	Price
930954	White	left	€ 63.95
930955	White	right	€ 65.95



Accessories

930951	Sanotrunk, mounting Bracket for Trunking Rail, Set 10 Pcs.		€ 13.95
930952	Sanotrunk, Suspension Kit 5,0 m for Trunking Rail, Set 10 Pcs.		€ 71.95
930953	Sanotrunk, Bracket Chain Suspension for Trunking Rail, Set 10 Pcs.		€ 23.95
931086	Sanotrunk, set of 10 pcs. Holder for chain suspension for connector		€ 9.95
931087	Sanotrunk, chain suspension, 3m		€ 7.95



Technical data sheet
New in the onlineshop: The technical data sheets offer even more information: Light and energy data, light distribution curves, dimensional drawings and more.



SANOTRUNK T-CONNECTOR

- Pre-wiring with 7 cores, incl. DALI cables
- suitable for DALI and ON / OFF

Housing	Aluminium	Control	DALI 1 / DT6, DALI 1 / DT8, DALI 2 / DT6, DALI 2 / DT6 D4i, DALI 2 / DT8, DALI 2 / DT8 D4i
Length	515.4 mm		
Width	304.3 mm		
Height	73 mm		

Article	Housing Color	Type	Price
931090	☐ White	left	€ 83.95
930957	☐ White	right type A	€ 93.95
931091	☐ White	right type B	€ 83.95
930956	☐ White	double	€ 91.95




Accessories

930951	Sanotrunk, mounting Bracket for Trunking Rail, Set 10 Pcs.
930952	Sanotrunk, Suspension Kit 5,0 m for Trunking Rail, Set 10 Pcs.
930953	Sanotrunk, Bracket Chain Suspension for Trunking Rail, Set 10 Pcs.
931086	Sanotrunk, set of 10 pcs. Holder for chain suspension for connector
931087	Sanotrunk, chain suspension, 3m

	€ 13.95
	€ 71.95
	€ 23.95
	€ 9.95
	€ 7.95



Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.



SANOTRUNK X-CONNECTOR

- Pre-wiring with 7 cores, incl. DALI cables
- suitable for DALI and ON / OFF

Housing	Aluminium	Control	DALI 1 / DT6, DALI 1 / DT8, DALI 2 / DT6, DALI 2 / DT6 D4i, DALI 2 / DT8, DALI 2 / DT8 D4i
Length	515.4 mm		
Width	515.4 mm		
Height	73 mm		

Article	Housing Color	Type	Price
930958	☐ White	straight	€ 119.95
930959	☐ White	dreifach	€ 123.95



Accessories

930951	Sanotrunk, mounting Bracket for Trunking Rail, Set 10 Pcs.
930952	Sanotrunk, Suspension Kit 5,0 m for Trunking Rail, Set 10 Pcs.
930953	Sanotrunk, Bracket Chain Suspension for Trunking Rail, Set 10 Pcs.
931086	Sanotrunk, set of 10 pcs. Holder for chain suspension for connector
931087	Sanotrunk, chain suspension, 3m

	€ 13.95
	€ 71.95
	€ 23.95
	€ 9.95
	€ 7.95



5-year guarantee
Benefit from the maximum quality promise:
All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.



POWER RAILS

- 266 D ONE 1-phase power rail system
- 286 1-phase power rail luminaires
- 302 D LINE 3-phase power rail system
- 334 D LINE DALI 3-phase power rail system
- 364 power rail luminaires

D ONE system



page 270



page 273



page 274



page 274



page 275



page 275



page 276



page 276



page 277



page 277




page 278



page 278



☐ ☒
page 279



☐ ☒
page 280



☐ ☒
page 280



☐ ☒
page 281



☐ ☒
page 282



☐ ☒
page 282



☐ ☒
page 283




☐ ☒
page 283

D ONE MOUNTING POWER RAIL SYSTEM 1-PHASE 230V

mounting modules	illust.	white	black	page
mounting power rail L: 1000 mm	01	720000	720003	271
mounting power rail L: 2000 mm	01	720001	720004	271
mounting power rail L: 3000 mm	01	720002	720005	271
mounting power rail curved 90° left	01	720042	720044	273
mounting power rail curved 90° right	01	720043	720045	273
feeder left	02	720006	720007	274
feeder right	03	720008	720009	274
flex feeder with ceiling canopy	04	720010	720011	275
electrical straight connector with center feed option	05	720012	720013	275
electrical connector	06	720014	720015	276
90°-joint left	07	720016	720017	276
90°-joint right	08	720018	720019	277
T-joint left-right-right	09	720020	720021	277
T-joint right-right-left	10	720022	720023	278
T-joint left-left-right	11	720024	720025	279
T-joint right-left-left	12	720026	720027	278
X-joint left-left-right-right	13	720028	720029	279
endcap	14	720030	720031	280
cover panel	15	720038	720039	280
ceiling mounting bracket flex	16	720032	720033	282
wall bracket	17	720040	720041	282
wire suspension bracket 3000 mm	18	720034	720035	283
wire suspension bracket curved 3000 mm	19	720046	720047	283
1-phase adapter for light installation	20	720036	720037	281

ILLUSTRATIONS WITH PLANNING-RELEVANT DIMENSIONS

01




02




03



04




05




06




07




08




09




10




11



12



13



14




15




16




17




18



19




20




FIXING POINTS

power rail	a	b	c	d
1000 mm	125 mm			
2000 mm	125 mm	870 mm		
3000 mm	125 mm		790 mm	1160 mm




MECHANICAL LOAD TRACK POWER RAIL 1000 MM

10 N ± 1,02 kg
dimension in mm




MECHANICAL LOAD TRACK POWER RAIL 2000MM

10 N ± 1,02 kg
dimension in mm




MECHANICAL LOAD TRACK POWER RAIL 3000MM

10 N ± 1,02 kg
dimension in mm



PLANNING GUIDE D ONE TRACK SYSTEM 1-PHASE 230V





D ONE SURFACE-MOUNTED POWER TRACK

D ONE is the single-phase, 230 V busbar system from DEKO-LIGHT. This extremely compact and sophisticated system combines the benefits of 48 V low-voltage busbars [slim design] with the practical advantages of fully fledged 230 V systems [no transformer required for operation]. Their small size allows all D ONE components to integrate seamlessly into an extremely wide variety of environments, adding a timeless, understated, premium look to private dwellings and commercial facilities like shops and bars. All D ONE components are available in the universally suitable colours black and white, allowing a wide variety of installation options for flexible and universal use. The flexible infeed with ceiling canopy even allows D ONE busbars to be installed in places where there is no power supply available in the immediate vicinity.



D ONE SURFACE-MOUNTED POWER TRACK

- elegant and compact mini design
- easy to install
- many different designs available
- Mini design with one current phase

Application Area

Home / Living, Shop / Retail / Sales area

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Width	26.2 mm	Output Current	16 A
Height	22.2 mm		

Article	Housing Color	Length	Price
720000	☐ White	1000 mm	€ 31.95
720003	☒ Black	1000 mm	€ 31.95
720001	☐ White	2000 mm	€ 55.95
720004	☒ Black	2000 mm	€ 55.95
720002	☐ White	3000 mm	€ 79.95
720005	☒ Black	3000 mm	€ 79.95



Accessories for 720000, 720001, 720002
720038 D One cover panel for integrated busbar, white


 € 4.95

Accessories for 720003, 720004, 720005
720039 D One cover panel for integrated busbar, black


 € 4.95




Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.



720042, 720044



720043, 720045



examples of designs



D ONE SURFACE-MOUNTED POWER TRACK CURVED

- Curved track 90° (radius 0.8m)
- Enables completely new design shapes (corner, semicircle, circle, wave)
- Segment length 1.26m
- Only suitable for standard track adapters (max. length 8cm)
- Mini design with one power phase

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Aluminium	Height	26.2 mm
Length	1260 mm	Rated Input Voltage	220-240 V/AC
Width	22.2 mm	Output Current	16 A

Article	Housing Color		Price
720042	White	left	€ 67.95
720044	Black	left	€ 67.95
720043	White	right	€ 67.95
720045	Black	right	€ 67.95



Accessories for 720042, 720043

- 720032 D One ceiling mounting bracket Flex, white
- 720046 D One CURVED suspension bracket with 3 m cable, white

	€ 4.95
	€ 13.95

Accessories for 720044, 720045

- 720033 D One ceiling mounting bracket Flex, black
- 720047 D One CURVED suspension bracket with 3 m cable, black

	€ 4.95
	€ 13.95



D ONE ELECTRIC FEEDER LEFT

- Power can be fed in from above (ceiling) or from the side
- Elegant and compact mini design
- Simple installation
- Enables flexible installation options

Application Area

Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	22.2 mm
Length	71 mm	Rated Input Voltage	220-240 V/AC
Width	26 mm	Output Current	16 A

Article	Housing Color	Price
720006	 White	€ 10.95
720007	 Black	€ 10.95



D ONE ELECTRIC FEEDER RIGHT

- Power can be fed in from above (ceiling) or from the side
- elegant and compact mini design
- easy to install
- enables flexible installation options

Application Area

Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	22.2 mm
Length	71 mm	Rated Input Voltage	220-240 V/AC
Width	26 mm	Output Current	16 A

Article	Housing Color	Price
720008	 White	€ 10.95
720009	 Black	€ 10.95





D ONE FLEX FEEDER WITH CEILING CANOPY

- Elegant and compact mini design
- Easy to install
- Power supply via ceiling baldachin/current track adapter (200-1,000 mm)
- Enables various installation options

Application Area

Home / Living, Shop / Retail / Sales area

Housing	Plastic, Metal	Rated Input Voltage	220-240 V/AC
Length	1000 mm	Output Current	6 A
Width	120 mm	Connected Load max.	1320 W
Height	28 mm		

Article	Housing Color	Price
720010	 White	€ 31.95
720011	 Black	€ 31.95



D ONE ELECTRICAL STRAIGHT CONNECTOR WITH FEED OPTION

- Elegant and compact mini design
- Easy to install
- Power supply from above (from ceiling)

Application Area

Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	22.2 mm
Length	121 mm	Rated Input Voltage	220-240 V/AC
Width	26 mm	Output Current	16 A

Article	Housing Color	Price
720012	 White	€ 19.95
720013	 Black	€ 19.95





D ONE MINI-STRAIGHT CONNECTOR


- elegant and compact mini design
- easy to install

Application Area

Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	22 mm
Length	62 mm	Rated Input Voltage	220-240 V/AC
Width	26 mm	Output Current	16 A

Article	Housing Color	Price
720014	 White	€ 7.45
720015	 Black	€ 7.45



D ONE 90°-CONNECTOR LEFT

- Optional power supply from above (from ceiling)
- Elegant and compact mini design
- Easy to install
- Many different design shapes possible


Application Area

Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	22.2 mm
Length	73 mm	Rated Input Voltage	220-240 V/AC
Width	73 mm	Output Current	16 A

Article	Housing Color	Price
720016	 White	€ 19.95
720017	 Black	€ 19.95





D ONE 90°-CONNECTOR RIGHT


- Optional power supply from above (from ceiling)
- Elegant and compact mini design
- Easy to install
- Many different design shapes possible

Application Area

Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	22.2 mm
Length	73 mm	Rated Input Voltage	220-240 V/AC
Width	73 mm	Output Current	16 A

Article	Housing Color	Price
720018	 White	€ 19.95
720019	 Black	€ 19.95



D ONE T-CONNECTOR RIGHT-LEFT-LEFT

- Optional power supply from above (from ceiling)
- Elegant and compact mini design
- Easy to install
- Many different design shapes possible


Application Area

Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	22.2 mm
Length	121 mm	Rated Input Voltage	220-240 V/AC
Width	73 mm	Output Current	16 A

Article	Housing Color	Price
720026	 White	€ 27.95
720027	 Black	€ 27.95





D ONE T-CONNECTOR RIGHT-RIGHT-LEFT


- Optional power supply from above (from ceiling)
- Elegant and compact mini design
- Easy to install
- Many different design shapes possible

Application Area

Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	22.2 mm
Length	121 mm	Rated Input Voltage	220-240 V/AC
Width	73 mm	Output Current	16 A

Article	Housing Color	Price
720022	 White	€ 27.95
720023	 Black	€ 27.95



D ONE T-CONNECTOR LEFT-RIGHT-RIGHT

- Power can be fed in from above [via ceiling]
- Elegant and compact mini design
- Easy to install
- Enables many different design shapes


Application Area

Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	22.2 mm
Length	121 mm	Rated Input Voltage	220-240 V/AC
Width	73 mm	Output Current	16 A

Article	Housing Color	Price
720020	 White	€ 27.95
720021	 Black	€ 27.95





D ONE T-CONNECTOR LEFT-LEFT-RIGHT


- Power can be fed in from above [via ceiling]
- Elegant and compact mini design
- Easy to install
- Enables many different design shapes

Application Area

Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	22.2 mm
Length	121 mm	Rated Input Voltage	220-240 V/AC
Width	73 mm	Output Current	16 A

Article	Housing Color	Price
720024	 White	€ 27.95
720025	 Black	€ 27.95



D ONE X-CONNECTOR

- Power can be fed in from above [via ceiling]
- Easy to install

Application Area

Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	22.2 mm
Length	121 mm	Rated Input Voltage	220-240 V/AC
Width	121 mm	Output Current	16 A

Article	Housing Color	Price
720028	 White	€ 37.95
720029	 Black	€ 37.95





D ONE COVER PANEL

- suitable for D-One surface-mounted system
- for covering live busbars < 2.30 m high (contact zone)

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic	Width	16.5 mm
Length	1000 mm	Height	6.8 mm

Article	Housing Color	Price
720038	 White	€ 4.95
720039	 Black	€ 4.95



D ONE END CAP

- Current touch protection
- For closing open current track ends

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic	Width	26 mm
Length	15 mm	Height	22.2 mm

Article	Housing Color	Price
720030	 White	€ 3.45
720031	 Black	€ 3.45





D ONE 1-PHASE ADAPTER FOR LIGHT INSTALLATION

- Elegant and compact mini design
- Easy to install
- 230 V adapter for converting lights
- Delivery incl. mounting material (reduction bush, flat M10 nut, strain relief)

Application Area

Home / Living, Shop / Retail / Sales area

Housing	Plastic, Metal	Rated Input Voltage	220-240 V/AC
Length	70 mm	Output Current	6 A
Width	26 mm	Loading Weight max.	10 kg
Height	30 mm	Load Force max.	100 N

Article	Housing Color	Price
720036	 White	€ 13.95
720037	 Black	€ 13.95





D ONE MOUNTING BRACKET FLEX

- Simplifies the installation of more complex track shapes
- Enables numerous design forms
- Expands options for installation

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Metal	Height	10.5 mm
Length	30 mm	Loading Weight max.	25 kg
Width	28 mm		

Article	Housing Color	Price
720032	 White	€ 4.95
720033	 Black	€ 4.95



D ONE WALL BRACKET

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Aluminium	Height	80 mm
Length	91.9 mm	Loading Weight max.	10 kg
Width	25 mm		

Article	Housing Color	Price
720040	 White	€ 11.95
720041	 Black	€ 11.95





D ONE ROPE SUSPENSION BRACKET

- Stylish and sophisticated suspended mounting
- Enables numerous design forms
- Expands options for installation
- Can be cut to length for hanger lengths: 70-3,020 mm

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Metal	Height	3020 mm
Length	120 mm	Loading Weight max.	25 kg
Width	28 mm		

Article	Housing Color	Price
720034	☐ White	€ 15.95
720035	☒ Black	€ 15.95



D ONE ROPE SUSPENSION BRACKET CURVED

Housing	Metal	Height	3020 mm
Length	30 mm	Loading Weight max.	8 kg
Width	28 mm		

Article	Housing Color	Price
720046	☐ White	€ 13.95
720047	☒ Black	€ 13.95



1-phase power rail luminaires



page 287



page 289



page 292



page 294



page 295



page 296



page 297







CAN

- Replaceable light source to offer an individual lighting solution
- Can be combined with the comprehensive CAN series product family

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium, Polycarbonate	Rated Input Voltage	220-240 V/AC
Height	134 mm	Control	Dimmable via optional light source
Ø	60 mm	Rotation Angle	350 Degree
Max. Power	1 x max. 7.5 W	Swivelling Angle	90 Degree

Article	Housing Color	Price
707155	White	€ 33.95
707156	Black	€ 33.95

GU10

IP20

Accessories

930301	Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930302	Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930303	Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930366	Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
931065	Acrylic attachment for Can		€ 3.95



page 30

page 68

page 72


page 167

page 184

page 382

page 467





CAN

- customisable with extensive accessories
- customised lighting solution thanks to replaceable light source
- combinable with the extensive product family of the CAN series

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Ø	60 mm	Control	Dimmable via optional light source
Pendulum Length	1500 mm		
Max. Power	1x max. 7.5 W		

Article	Housing Color	Height	Price
707253	White	150 mm	€ 61.95
707254	Black	150 mm	€ 61.95
707257	White	350 mm	€ 73.95
707258	Black	350 mm	€ 73.95



Accessories

930301	Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series	€ 3.95
930302	Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series	€ 3.95
930303	Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series	€ 3.95
930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series	€ 6.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series	€ 6.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series	€ 6.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series	€ 6.95
930366	Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series	€ 3.95
931065	Acrylic attachment for Can	€ 3.95



CAN BASE MIX'N MATCH 1/3

- customised lighting solution thanks to interchangeable light source
- can be customised with cylinder housing in 6 different colours
- can be combined with the extensive product family of the CAN series

Housing	Aluminium	Control	Dimmable via optional light source
Height	74 mm	Rotation Angle	350 Degree
Ø	70 mm	Swivelling Angle	90 Degree
Max. Power	1x max. 7.5 W		
Rated Input Voltage	220-240 V/AC		

Article	Housing Color	Price
707249	☐ White	€ 28.95
707250	☒ Black	€ 28.95





CYLINDER HOOUSING FOR CAN MIX'N MATCH 2/3

Housing Aluminium Ø 60 mm
Height 98 mm

Article	Housing Color	Price
931053	 White	€ 6.45
931054	 Black	€ 6.45
931055	 Bronze	€ 14.95
931056	 Brass	€ 14.95
931057	 Black grey	€ 14.95
931058	 Rosé	€ 14.95

IP20



REFLECTOR RING FOR CAN MIX'N MATCH 3/3

Housing Plastic Ø 57 mm
Height 28 mm

Article	Housing Color	Price
930301	 White	€ 3.95
930302	 Black	€ 3.95
930303	 Gold	€ 3.95
930366	 Silver	€ 3.95

IP20



UNI 2 MINI

The UNI 2 MINI is a compact and flexibly customisable single-circuit track luminaire for professional lighting concepts. The rotatable and swivelling LED spot impresses with its decorative "glow" effect on the reflector ring and numerous customisation options using interchangeable reflectors, lenses, reflector rings and accessories. Ideal for living areas, reception areas, hotels and the catering trade.






UNI 2 MINI

- „Glow“ effect on the reflector ring
- Rotatable and swivelling
- Can be customised with a wide range of accessories

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium, Steel, Polycarbonate	Power Supply Unit incl.	Yes
Colour Temperature	2700 K	Light Beam Angle	36 Degree
Height	128 mm	Rotation Angle	350 Degree
Ø	75 mm	Swivelling Angle	90 Degree
Power	11.3 W	Control	Leading-edge dimmer, Trailing-edge dimmer
Rated Input Voltage	220-240 V/AC	CRI (Ra)	90



707187

Article	Housing Color		Luminous Flux	Price
707188			700 lm	€ 110.95
707187			730 lm	€ 110.95




Accessories

930327	Rear black cover for Uni II Mini series		€ 2.95
930328	White heat sink cover for Uni II Mini series		€ 2.95
930329	Black heat sink cover for Uni II Mini series		€ 2.45
930330	Reflector ring white for Uni II Mini series		€ 8.95
930331	Reflector ring black for Uni II Mini series		€ 8.95
930332	Reflector ring gold for Uni II Mini series		€ 8.95
930333	Reflector ring chrome for Uni II Mini series		€ 8.95
930770	Reflector 24° for Uni II Mini series		€ 8.95
930771	Reflector 48° for Uni II Mini series		€ 8.95



Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.




SLIM

- glare-free thanks to low UGR value (<19)
- slim design with just 39 mm diameter
- incl. silver-coloured reflector ring

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	2700 K	Light Beam Angle	36 Degree
Luminous Flux	500 lm	Rotation Angle	330 Degree
Height	197 mm	Swivelling Angle	60 Degree
Ø	39 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Power	5 W	CRI (Ra)	90
Rated Input Voltage	220-240 V/AC		



707201

Article	Housing Color	Price
707201	White	€ 66.95
707202	Black	€ 66.95



Accessories

930744	Reflector ring white for Slim series		€ 3.95
930745	Reflector ring black for Slim series		€ 3.95
930746	Reflector ring gold-coloured for Slim series		€ 4.75
930747	24° lens for Slim series		€ 3.95
930748	36° lens for Slim series		€ 3.95
930749	60° lens for Slim series		€ 3.95



page 24

page 295

page 408




SLIM

- Extra-soft fabric cable
- Glare-free, due to low UGR value [<19]
- Slim design at just 39 mm in diameter
- Max. suspended mounting: 1,800 mm

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Colour Temperature	2700 K	Power Supply Unit incl.	Yes
Luminous Flux	500 lm	Light Beam Angle	24 Degree
Height	300 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	39 mm	CRI (Ra)	90
Pendulum Length	1800 mm		
Power	5 W		




707163

Article	Housing Color		Price
707163	Black	WW	€ 74.95
707164	White	WW	€ 74.95




Accessories

930744	Reflector ring white for Slim series		€ 3.95
930745	Reflector ring black for Slim series		€ 3.95
930746	Reflector ring gold-coloured for Slim series		€ 4.75
930747	24° lens for Slim series		€ 3.95
930749	60° lens for Slim series		€ 3.95
930748	36° lens for Slim series		€ 3.95



page 24

page 408




LUCEA

- incl. black reflector ring
- Can be customised with a wide range of accessories

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium	Rotation Angle	350 Degree
Colour Temperature	2700 K	Swivelling Angle	90 Degree
Height	157 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	65 mm	CRI (Ra)	90
Rated Input Voltage	200-240 V/AC	IK Protection Class	IK03
Power Supply Unit incl.	Yes		
Light Beam Angle	36 Degree		



707165

Article	Housing Color		Luminous Flux	Power	Price
707165		White	800 lm	6.0 W	€ 72.95
707166		Black	800 lm	6.0 W	€ 72.95
707167		White	1300 lm	10.0 W	€ 77.95
707168		Black	1300 lm	10.0 W	€ 77.95



Accessories

930679	Lens 24° for Lucea 6/10		€ 7.95
930752	Door panel for Lucea 6/10 white		€ 17.95
930753	Door panel for Lucea 6/10 black		€ 17.95
930756	Reflector ring for Lucea 6/10 white		€ 3.95
930757	Reflector ring for Lucea 6/10 black		€ 3.95
930758	Reflector ring for Lucea 6/10 gold		€ 3.95



page 28

page 64

page 65

page 297




LUCEA

- Particularly soft textile cable
- incl. black reflector ring

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	2700 K	Light Beam Angle	36 Degree
Height	157 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	65 mm	CRI (Ra)	90
Pendulum Length	1600 mm	IK Protection Class	IK03
Rated Input Voltage	200-240 V/AC		



707175

Article	Housing Color		Luminous Flux	Power	Price
707175	☐ White		800 lm	6.0 W	€ 96.95
707176	☒ Black		800 lm	6.0 W	€ 96.95
707177	☐ White		1300 lm	10.0 W	€ 99.95
707178	☒ Black		1300 lm	10.0 W	€ 99.95



Accessories

930679	Lens 24° for Lucea 6/10		€ 7.95
930752	Door panel for Lucea 6/10 white		€ 17.95
930753	Door panel for Lucea 6/10 black		€ 17.95
930756	Reflector ring for Lucea 6/10 white		€ 3.95
930757	Reflector ring for Lucea 6/10 black		€ 3.95
930758	Reflector ring for Lucea 6/10 gold		€ 3.95



page 28





page 64



page 65



page 296




LUCEA DTW

- Dim-to-warm 1,800K - 2,700K
- incl. black reflector ring
- Can be customised with a wide range of accessories

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium	Light Beam Angle	36 Degree
Colour Temperature	1800-2700 K	Rotation Angle	350 Degree
Luminous Flux	750 lm	Swivelling Angle	90 Degree
Height	249 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	65 mm	CRI (Ra)	90
Power	10 W	IK Protection Class	IK03
Rated Input Voltage	200-240 V/AC		
Power Supply Unit incl.	Yes		



707211


Article	Housing Color		Price
707211	White	ww	€ 83.95
707212	Black	ww	€ 83.95



Accessories

930752	Door panel for Lucea 6/10 white		€ 17.95
930753	Door panel for Lucea 6/10 black		€ 17.95
930756	Reflector ring for Lucea 6/10 white		€ 3.95
930757	Reflector ring for Lucea 6/10 black		€ 3.95
930758	Reflector ring for Lucea 6/10 gold		€ 3.95






LUCEA DTW

- high colour rendering
- Dim-to-warm 1,800K-2,700K
- incl. black reflector ring

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium	Rated Input Voltage	200-240 V/AC
Colour Temperature	1800-2700 K	Power Supply Unit incl.	Yes
Luminous Flux	750 lm	Light Beam Angle	36 Degree
Height	157 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	65 mm	CRI (Ra)	90
Pendulum Length	1800 mm	IK Protection Class	IK03
Power	10 W		



707215

Article	Housing Color		Price
707215	White	WW	€ 108.95
707216	Black	WW	€ 108.95



Accessories

930752	Door panel for Lucea 6/10 white		€ 17.95
930753	Door panel for Lucea 6/10 black		€ 17.95
930756	Reflector ring for Lucea 6/10 white		€ 3.95
930757	Reflector ring for Lucea 6/10 black		€ 3.95
930758	Reflector ring for Lucea 6/10 gold		€ 3.95



page 26



page 60



page 62



page 400



page 404

D LINE system



page 310



page 312



page 313



page 314



page 314



page 315



page 315



page 316



page 316



page 317



page 318



page 318



 
page 319



  
page 320



 
page 320



 
page 321



 
page 321



 
page 322



 
page 322



 
page 323



 
page 323



 
page 324



 
page 324



 
page 325



 
page 325




page 326




page 326



 
page 327



 
page 328



 
page 329



 
page 330



 
page 331



 
page 331




page 333


D LINE MOUNTING POWER RAIL SYSTEM 3-PHASE 220-440V

mounting modules	illust.	white	black	page
mounting power rail L: 1000 mm	01	710000	710002	311
mounting power rail L: 2000 mm	01	710003	710005	311
mounting power rail L: 3000 mm	01	710006	710008	311
mounting power rail curved 90° left	01	710113	710115	312
mounting power rail curved 90° right	01	710114	710116	213
mounting adapter for lights	02	710045	710047	313
live end feeder left	03	710009	710011	314
live end feeder right side	04	710012	710014	314
electrical straight connector with center feed option	05	710042	710044	315
flexible-connector left-right side	06	710039	710041	315
electrical joint	07	710015	710017	316
mechanical joint	08	710018	710020	316
90°-joint left-right with exchange mechanism	09	710036	710038	317
T-joint left-left-right with exchange mechanism	10	710027	710029	318
T-joint right-right-left with exchange mechanism	11	710030	710032	318
X-joint left-left-right-right	12	710033	710035	319
cover plate built in track	13	710077	710079	320
endcap	14	710066	710068	320
ceiling mounting bracket flex	15	710063	710065	321
suspension clamp for track connection	16	710057	710059	322
ceiling suspension rigid [635 mm] with canopy	17	710078	710084	323
extension for ceiling suspension [300 mm]	17	710086	710087	323
wire suspension bracket with ceiling rosette 1500 mm	18	710048	710050	324
rope suspension bracket Mini mit Abhängeseil 5000 mm	19	710094	710096	324
curved suspension cable bracket	20	710117	710118	325
suspension cable bracket with adjustment crossbar	21	710110	710112	325
quick mounting bracket for grid ceilings	22	710051	710053	327
quick mounting bracket for grid ceilings for or mini cable suspension	23	710108	710109	321
wall bracket	24	710104	710106	322
truss adapter silver coloured	25	-	-	327
quick mounting clamp for exhibition stand construction	26	-	710082	326
3-circuits adapter for light installation	27	710097	710099	328
3-circuits adapter with Multi CC power supply 250/350/450/500 mA 6,30 - 21,00 W 25-42V	28	862180	862183	329
3-circuits adapter with Multi CC power supply 600/700/750/800 mA 15,00 - 33,60 W 25-42V	28	862181	862184	329
3-circuits adapter with Multi CC power supply 850/900/950/1050 mA 23,00 - 44,10 W 27-42V	28	862182	862185	329
electrical outlet adapter	29	710024	710026	330
mounting adapter for additional components max. 10kg	30	710054	710056	330
signs hook, max. load 5kg	31	710060	710062	331




Note: Recessed track systems can be found in the D LINE DALI 3-phase power rail luminaires chapter.

ILLUSTRATIONS WITH PLANNING-WRELEVANT DIMENSIONS




FIXING POINTS

power rail	a	b	c	d
1000 mm	125 mm			
2000 mm	125 mm	998 mm		
3000 mm	125 mm		914 mm	1167 mm




MECHANICAL LOAD TRACK POWER RAIL 1000 MM

50 N $\triangleq$ 5,09 kg
dimension in mm







MECHANICAL LOAD TRACK POWER RAIL 2000/3000 MM

50 N $\triangleq$ 5,09 kg
dimension in mm




PLANNING GUIDE D LINE MOUNTING POWER RAIL SYSTEM 3-PHASE 220-440V






710113, 710115



710114, 710116



examples of designs



D LINE CURVED


The D LINE CURVED track enables completely new design possibilities for modern lighting concepts. Featuring a 90° curve with a 1 m radius, it allows the creation of semicircles, circles and wave-shaped layouts. The 1.57 m segments can be used as either D LINE DALI or D LINE Standard tracks. A variety of mounting options ensures maximum installation flexibility.




D LINE POWER RAIL SYSTEM 3-PHASE 220-440V

The D LINE track system is available exclusively from DEKO-LIGHT and is extremely easy to plan and install thanks to its components, some of which have been completely redesigned. It is also compatible with all common track adapters and luminaires. The elegant and timeless design is available in white, black and grey, and the wide range

of accessories and mounting components means that there are no limits to its use and installation. Thanks to the interchangeable mechanism of the 90° and T connectors, planning is easier than ever before and the installation of even complex shapes will be child's play in the future.



COMPATIBILITY OVERVIEW



D LINE 3-phase track is compatible with the following track lights / adapters:

manufacturer	system name
DEKO-LIGHT	all 3-phase spotlights
Molto Luce	3-Phase-Track*
Global / Nordic	Trac Pro 3*
Ivela	LKM Square / Quadro*
Erco	3-Phasen*
Hoffmeister	3-Phasen*
Zumtobel / Staff	3-Phasen*
Eutrac	One Track*
SLV	S-Track

*compatible with all DEKO-LIGHT 3-circuit spotlights, except 3-circuit adapters with integrated Multi-CC driver [p. 329]

All information is provided without guarantee. Technical data and dimensions are subject to change without prior notice. To ensure proper functionality, compatibility should be verified using a sample during the project planning phase.



On request, all D LINE busbars can be supplied ready-made and cut to size according to your specifications for a small surcharge. This allows you to start installation directly on site at the customer's premises. Please contact



D LINE SURFACE-MOUNTED POWER TRACK

The D LINE busbar system is available exclusively from DEKO-LIGHT and is now extremely easy to plan and install thanks to a complete redesign of several components. It is also compatible with all common busbar adapters and lights. The elegant and timeless design is available in white, black and grey, and with a huge range of accessories and assembly components available, the possibilities are almost endless when it comes to application and installation. The reversal mechanism of the 90° and T-connectors makes planning easier than ever before, and in the future installing even complex shapes will be a breeze.



Note: Recessed track systems can be found in the D LINE DALI 3-phase power rail luminaires chapter.



D LINE SURFACE-MOUNTED POWER TRACK

- Up to three phases (3x 16 A) can be fed in
- Numerous attachment options

Application Area

Home / Living, Shop / Retail / Sales area

Housing	Aluminium	Height	35.5 mm
Mounting Type	Top mounting	Rated Input Voltage	220-440 V/AC
Width	35.2 mm	Output Current	16 A

Article	Housing Color	Length	Price
710000	☐ White	1000 mm	€ 35.95
710002	☒ Black	1000 mm	€ 35.95
710003	☐ White	2000 mm	€ 71.95
710005	☒ Black	2000 mm	€ 71.95
710006	☐ White	3000 mm	€ 103.95
710008	☒ Black	3000 mm	€ 103.95



Accessories for 710000, 710003, 710006

710077 D Line/Dali cover panel for integrated busbar, white

 € 4.95

Accessories for 710002, 710005, 710008

710079 D Line/Dali cover panel for integrated busbar, black

 € 4.95




Lighting design

Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.



D LINE/DALI SURFACE-MOUNTED POWER TRACK CURVED

- Curved track 90° (radius 1m)
- Enables completely new design forms (corner, semicircle, circle, wave)
- Segment length 1.57m
- Can be used as D-Line DALI or D-Line standard track
- only suitable for standard track adapters (max. length 12cm)
- up to 3 phases [3x 16A] can be fed in
- cutting tool required for Dali customised assembly
- Many different mounting options



examples of designs

Application Area

Home / Living, Shop / Retail / Sales area

Housing	Aluminium	Height	35.5 mm
Mounting Type	Top mounting	Rated Input Voltage	220-440 V/AC
Length	1570 mm	Output Current	16 A
Width	35.2 mm		

Article	Housing Color		Price
710113	☐ White	left	€ 211.95
710115	☒ Black	left	€ 211.95
710114	☐ White	right	€ 211.95
710116	☒ Black	right	€ 211.95





D LINE SURFACE-MOUNTED ADAPTER

- Surface-mounted housing for converting busbar spotlights
- Single phase (1x 16 A) feed
- Easy to install

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic	Rated Input Voltage	220-240 V/AC
Height	35 mm	Output Current	16 A
Ø	110 mm		

Article	Housing Color	Price
710045	☐ White	€ 23.95
710047	☒ Black	€ 23.95





D LINE ELECTRIC FEEDER LEFT

- Up to three phases (3x 16 A) can be fed in
- Power can be fed in from above (ceiling) or from the side
- Suitable for surface-mounted and recessed systems

Application Area
 Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	35.5 mm
Length	98.5 mm	Rated Input Voltage	220-440 V/AC
Width	35.2 mm	Output Current	16 A

Article	Housing Color	Price
710009	 White	€ 12.95
710011	 Black	€ 12.95



D LINE ELECTRIC FEEDER RIGHT

- Up to three phases (3x 16 A) can be fed in
- Power can be fed in from above (ceiling) or from the side
- Suitable for surface-mounted and recessed systems

Application Area
 Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	35.5 mm
Length	98.5 mm	Rated Input Voltage	220-440 V/AC
Width	35.2 mm	Output Current	16 A

Article	Housing Color	Price
710012	 White	€ 12.95
710014	 Black	€ 12.95




Accessories
710089 D Line cover panel feed left/right



€ 3.45



D LINE ELECTRICAL LONGITUDINAL CONNECTOR WITH FEED OPTION



- Up to three phases (3x 16 A) can be fed in
- Power supply from above (from ceiling)
- Suitable for surface-mounted and recessed systems

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	35.5 mm
Length	166 mm	Rated Input Voltage	220-440 V/AC
Width	35 mm	Output Current	16 A


Article	Housing Color	Price
710042	White	€ 26.95
710044	Black	€ 26.95



Accessories
710090 D Line/Dali cover panel for longitudinal connector, white



€ 3.45



D LINE FLEXIBLE CONNECTOR, LEFT-RIGHT

- Compensates for height or angle differences
- Suitable for surface-mounted systems

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	35.5 mm
Length	248 mm	Rated Input Voltage	220-440 V/AC
Width	35 mm	Output Current	16 A

Article	Housing Color	Price
710039	White	€ 34.95
710041	Black	€ 34.95





D LINE ELECTRIC CONNECTOR

·suitable for surface-mounted and recessed systems

Application Area

Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	26.5 mm
Length	68 mm	Rated Input Voltage	220-440 V/AC
Width	20.5 mm	Output Current	16 A

Article	Housing Color	Price
710015	 White	€ 7.95
710017	 Black	€ 7.95



D LINE MECHANICAL CONNECTOR

- Mechanical connector without electrical contacts
- For electrical separation of two different power circuits within one track system
- Suitable for surface-mounted and recessed systems


Application Area

Home / Living, Shop / Retail / Sales area

Housing	Plastic	Width	20 mm
Length	66.4 mm	Height	27 mm

Article	Housing Color	Price
710018	 White	€ 5.95
710020	 Black	€ 5.95





D LINE 90° CONNECTOR LEFT-RIGHT WITH REVERSAL MECHANISM

- With reversal mechanism for switching the orientation between left and right
- Suitable for surface-mounted and recessed systems

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	35.5 mm
Length	100.7 mm	Rated Input Voltage	220-440 V/AC
Width	100.7 mm	Output Current	16 A

Article	Housing Color	Price
710036	White	€ 28.95
710038	Black	€ 28.95



Accessories
710091 D Line/Dali cover panel for 90° connector, white



€ 3.45



D LINE T-CONNECTOR LEFT-LEFT-RIGHT WITH REVERSAL MECHANISM

- with reversal mechanism for switching the orientation between left / right
- suitable for surface-mounted and recessed systems

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	35.5 mm
Length	166 mm	Rated Input Voltage	220-440 V/AC
Width	101 mm	Output Current	16 A

Article	Housing Color	Price
710027	 White	€ 40.95
710029	 Black	€ 40.95



D LINE T-CONNECTOR RIGHT/RIGHT/LEFT WITH EXCHANGE MECHANICS

- with reversal mechanism for switching the orientation between left / right
- suitable for surface-mounted and recessed systems

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	35.5 mm
Length	166 mm	Rated Input Voltage	220-440 V/AC
Width	101 mm	Output Current	16 A



Article	Housing Color	Price
710030	 White	€ 40.95
710032	 Black	€ 40.95



Accessories
710093 D Line/Dali cover panel for T-connector, white



€ 3.45



D LINE X-CONNECTOR LEFT-LEFT-RIGHT-RIGHT

- Easy to install
- Suitable for surface-mounted and recessed systems

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	35.5 mm
Length	166 mm	Rated Input Voltage	220-440 V/AC
Width	166 mm	Output Current	16 A

Article	Housing Color	Price
710033	White	€ 52.95
710035	Black	€ 52.95



Accessories
710092 D Line/Dali cover panel for X-connector, white



€ 3.95



D LINE COVER PANEL

- Suitable for surface-mounted and recessed systems
- For sealing publicly accessible busbars within a contact zone of less than 2.30 m

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic	Width	21.5 mm
Length	1000 mm	Height	7.5 mm

Article	Housing Color	Price
710077	 White	€ 4.95
710079	 Black	€ 4.95



D LINE END CAP

- For closing open current track ends (touch protection)
- Easy to install
- Suitable for surface-mounted systems

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	32.5 mm
---------	---------	--------	---------

Article	Housing Color	Length	Width	Price
710066	 White	31.3 mm	35.2 mm	€ 2.45
710068	 Black	31.3 mm	35.2 mm	€ 2.45
710103	 White	56 mm	47.9 mm	€ 2.45
710538	 Black	56 mm	47.9 mm	€ 2.45





D LINE MOUNTING BRACKET FLEX

- Suitable for surface-mounted systems
- Simplifies installation of complex shapes
- Current track can still be slid during installation

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Metal	Width	33.8 mm
Length	40 mm	Height	12.5 mm

Article	Housing Color	Price
710063	 White	€ 4.95
710065	 Black	€ 4.95



D LINE/DALI GRID-CEILING QUICK-MOUNTING BRACKET FOR MINI CABLE SUSPENSION

- Suitable for surface-mounted systems
- For universal use for mounting other components using M6 thread stud bolts on grid ceilings
- Suitable for 22-24 mm grid-ceiling support rails
- Suitable for steel cables up to 2.6 mm
- Mechanical load up to 7 kg/70 N

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Steel	Width	39 mm
Length	25 mm	Height	27 mm

Article	Housing Color	Price
710108	 White	€ 3.45
710109	 Black	€ 3.45






D LINE WALL BRACKET

- Suitable for surface-mounted systems
- Simplifies installation of current tracks near walls
- Ideal for illuminating pictures and objects, for example in exhibitions, collections and museums

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Aluminium	Width	25 mm
Length	91.9 mm	Height	80 mm

Article	Housing Color	Price
710104	 White	€ 11.95
710106	 Black	€ 11.95



D LINE SUSPENSION CONNECTION BRACKET

- Suitable for surface-mounted systems
- For chain installation or similar (chain not included in the scope of delivery)

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Metal	Width	32 mm
Length	181 mm	Height	20 mm

Article	Housing Color	Price
710057	 White	€ 7.95
710059	 Black	€ 7.95





D LINE CEILING SUSPENSION RIGID

- Sturdy, elegant ceiling hanger
- Suitable for surface-mounted systems
- Hanger dimension 635 mm (can be shortened to 335 mm)
- Hanger can be extended with accessories

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Aluminium	Width	60 mm
Length	635 mm		

Article	Housing Color	Price
710078	☐ White	€ 24.95
710084	☒ Black	€ 24.95



D LINE EXTENSION FOR CEILING SUSPENSION RIGID

- Suitable for rigid ceiling hangers
- Extends the hanger length by 300 mm

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Aluminium	Width	10 mm
Length	310 mm		

Article	Housing Color	Price
710086	☐ White	€ 4.95
710087	☒ Black	€ 4.95





D LINE ROPE SUSPENSION BRACKET

- Can be cut to length for suspension dimension: 120-1,500 mm
- suitable for surface-mounted systems

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Metal	Width	31 mm
Length	120 mm	Height	52 mm

Article	Housing Color	Price
710048	 White	€ 11.95
710050	 Black	€ 11.95



Accessories
710081 D Line/Dali cable for cable suspension 4.0 m



€ 6.95



D LINE ROPE SUSPENSION BRACKET MINI

- Stylish and sophisticated suspended mounting
- Can be cut to length for hanger lengths: 90-4,960 mm
- Suitable for surface-mounted systems

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Metal	Width	31 mm
Length	120 mm	Height	58 mm

Article	Housing Color	Price
710094	 White	€ 15.95
710096	 Black	€ 15.95




Accessories
710108 D Line/Dali grid ceiling quick-mounting clip for wire suspension Mini white
710109 D Line/Dali grid ceiling quick-mounting clip for wire suspension Mini black



€ 3.45



€ 3.45



D LINE/DALI ROPE SUSPENSION BRACKET

- special wire suspension for D-Line/DALI Curved tracks
- enables and extends the mounting options
- Suspension dimension can be individually shortened: 90 - 4960 mm

Housing	Metal	Height	59 mm
Length	62 mm	Loading Weight max.	10 kg
Width	35 mm	Load Force max.	100 N

Article	Housing Color	Price
710117	White	€ 14.95
710118	Black	€ 14.95



D LINE/DALI CABLE SUSPENSION BRACKET WITH ADJUSTMENT TRAVERSE

- Set consisting of wire suspension with ceiling attachment and adjustment traverse
- Compensation of asymmetrical weight loads in the track system through one-sided spotlight mounting
- Easy and quick adjustment
- Suspension dimension can be individually shortened: 160-4960 mm
- Suitable for D Line/Dali mounting system

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Metal	Width	32 mm
Length	120 mm	Height	120 mm

Article	Housing Color	Price
710110	White	€ 20.95
710112	Black	€ 20.95





D LINE FAST-MOUNTING BRACKET

- Suitable for surface-mounted systems
- Current track can be installed without tools using knurled thumb screw and spring clamps
- Quick installation and removal for e.g. trade fair construction

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Aluminium	Width	30 mm
Length	40 mm	Height	11.9 mm

Article	Housing Color	Price
710082	 Black	€ 8.95



D LINE TRUSS ADAPTER

- Suitable for surface-mounted systems
- Quick-action couplers for fast mounting of current tracks on cross rail structures
- Fits all 50 mm aluminium cross rails in event/trade fair construction

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Aluminium	Width	30 mm
Length	40 mm	Height	11.9 mm

Article	Housing Color	Price
710083	 Silver	€ 25.95



This little »jack-of-all-trades« makes mounting a track on an existing grid ceiling child's play. The installation time is only a fraction of what it used to be. In the first step, the clip is simply clicked into the visible metal strips of the grid ceiling and is held bomb-proof on the ceiling by means of a safety spring clip. After that, the conductor rail is simply pushed onto it and the installation is finished.



D LINE GRID CEILING FAST-MOUNTING BRACKET

- Suitable for surface-mounted systems
- Quick and easy to install on grid ceilings
- Mechanical load up to 15.0 kg/150 N
- Suitable for 22-24 mm ceiling grid support rails

Application Area

Home / Living, Shop / Retail / Sales area

Housing	Metal	Width	31 mm
Length	120 mm	Height	11 mm

Article	Housing Color	Price
710051	☐ White	€ 9.95
710053	☒ Black	€ 9.95





D LINE 3-PHASE ADAPTER FOR LIGHT INSTALLATION

- Suitable for surface-mounted and recessed systems
- Includes reduction bush, M10 flat nut and strain relief grommet
- Easy to install
- Integrated secondary drop protection
- Max. load 10 kg/100 N

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	54 mm
Length	84 mm	Rated Input Voltage	220-240 V/AC
Width	32 mm	Output Current	10 A

Article	Housing Color	Price
710097	☐ White	€ 15.95
710099	☒ Black	€ 15.95






D LINE THREE-PHASE ADAPTER WITH INTEGRATED MULTI CC POWER SUPPLY

- Suitable for surface-mounted and recessed systems
- Integrated secondary drop protection
- Supplied with trumpet nipple and M10 flat nut
- Stable integrated adjustable power supply [CC]
- Check suitability of the intended lamp
- Max. 10 kg/100 N
- Exclusively for D LINE, Ivela and Hoffmeister three-phase current tracks

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	41 mm
Length	162 mm	Rated Input Voltage	220-240 V/AC
Width	31 mm		

Article		Output Current Selectable	Power	Output Voltage	Price
862180	☐	250 mA / 350 mA / 450 mA / 500 mA	6.2-21.0 W	25-42 V/DC	€ 25.95
862183	☒	250 mA / 350 mA / 450 mA / 500 mA	6.2-21.0 W	25-42 V/DC	€ 25.95
862181	☐	600 mA / 700 mA / 750 mA / 800 mA	15.0-33.0 W	25-42 V/DC	€ 27.95
862184	☒	600 mA / 700 mA / 750 mA / 800 mA	15.0-33.0 W	25-42 V/DC	€ 27.95
862182	☐	850 mA / 900 mA / 950 mA / 1050 mA	22.0-44.0 W	27-42 V/DC	€ 29.95
862185	☒	850 mA / 900 mA / 950 mA / 1050 mA	22.0-44.0 W	27-42 V/DC	€ 29.95





D LINE SOCKET ADAPTER

- easy to install
- suitable for surface-mounted and recessed systems
- as power distribution system in current tracks
- max. 1,380 W
- integrated plug fuse

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic	Rated Input Voltage	230 V/AC
Length	58.5 mm	Output Current	6 A
Width	53.5 mm	Connected Load max.	1380 W
Height	103 mm		

Article	Housing Color	Price
710024	White	€ 22.95
710026	Black	€ 22.95





D LINE MOUNTING ADAPTER FOR ADDITIONAL COMPONENTS

- Suitable for surface-mounted and recessed systems
- Mounting adapter (M6 thread) for holding additional devices and lights
- Ideal for use with optional D Line socket adapter
- Load max. 10 kg/100 N

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Metal, Plastic	Width	31.5 mm
Length	66.5 mm	Height	84 mm

Article	Housing Color	Price
710054	 White	€ 8.95
710056	 Black	€ 8.95



D LINE SIGN HOOK

- Suitable for surface-mounted and recessed systems
- Hook for attaching information signs etc.
- Load max. 5kg / 50N

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic, Steel	Ø	25 mm
Height	52 mm		

Article	Housing Color	Price
710060	 White	€ 2.45
710062	 Black	€ 2.45



D LINE DALI system



page 340



page 341



page 343



page 344



page 345



page 346



page 347



page 347



page 348



page 348



page 349



page 350



☐ ☒
page 351



☐ ☒
page 353



☐ ☒
page 353



☐ ☒
page 354



☐ ☒
page 354



☐ ☒
page 355



☐ ☒
page 355



☐ ☒
page 356



☐ ☒
page 356



☐ ☒
page 357



☐ ☒
page 357



☐ ☒
page 359



☐ ☒
page 360



☐ ☒
page 361




☐ ☒
page 361

D LINE DALI MOUNTING POWER RAIL SYSTEM 3-PHASE 220-440V


mounting modules	illustr.	white	black	page
mounting power rail L: 1000 mm	01	710500	710501	340
mounting power rail L: 2000 mm	01	710502	710503	340
mounting power rail L: 3000 mm	01	710504	710505	340
mounting power rail curved 90° left	01	710113	710115	343
mounting power rail curved 90° right	01	710114	710116	343
mounting adapter for lights	02	710512	710513	341
live end feeder left	03	710514	710515	346
live end feeder right side	04	710516	710517	346
electrical straight connector with center feed option	05	710520	710521	347
flexible-connector left-right side	06	710523	710524	347
electrical joint	07	710525	710526	348
mechanical joint	08	710018	710020	348
90°-joint left-right with exchange mechanism	09	710527	710528	349
T-joint left-left-right with exchange mechanism	10	710530	710531	350
T-joint right-right-left with exchange mechanism	11	710532	710533	350
X-joint left-left-right-right	12	710535	710536	351
cover plate	13	710077	710079	352
endcap	14	710066	710068	352
ceiling mounting bracket flex	15	710063	710065	353
suspension clamp for track connection	16	710057	710059	354
ceiling suspension rigid [635 mm] with canopy	17	710078	710084	355
extension for ceiling suspension [300 mm]	17	710086	710087	355
wire suspension bracket with ceiling rosette 1500 mm	18	710048	710050	356
rope suspension bracket Mini mit Abhängeseil 5000 mm	19	710094	710096	356
curved suspension cable bracket	20	710117	710118	357
suspension cable bracket with adjustment crossbar	21	710110	710112	357
quick mounting bracket for grid ceilings	22	710051	710053	359
quick mounting bracket for grid ceilings for or mini cable suspension	23	710108	710109	353
wall bracket	24	710104	710106	354
truss adapter silver coloured	25	710083	710083	358
quick mounting clamp for exhibition stand construction	26	-	710082	358
3-circuits adapter for light installation	27	710539	710540	360
electrical outlet adapter	28	710024	710026	360
mounting adapter for additional components max. 10kg	29	710054	710056	361
signs hook, max. load 5kg	30	710060	710062	361

ILLUSTRATIONS WITH PLANNING RELEVANT DIMENSIONS

01



02




03




04



05



06




07




08




09




10



11



12



13




14




15




16




17




18




19




20




21




22




23



24




25




26



27



28



29




30

























D LINE DALI BUILT IN POWER RAL SYSTEM 3-PHASE 220-440V

built in modules	illust.	white	cover	black	cover	page
built in power rail L:1000 mm	01	710506	-	710507	-	344
built in power rail L: 2000 mm	01	710508	-	710509	-	344
built in power rail L: 3000 mm	01	710510	-	710511	-	344
electric feeder left side	02+18	710514	710518	710515	710519	346
electric feeder right side	03+18	710516	710518	710517	710519	346
electrical straight connector with center feed option	04+19	710520	710090	710521	710522	347
electrical joint	05	710525	-	710526	-	348
mechanical joint	06	710018	-	710020	-	348
90°-joint left-right	07+20	710527	710091	710528	710529	349
T-joint left-left-right	08+21	710530	710093	710531	710534	350
T-joint right-right-left	09+21	710532	710093	710533	710534	350
X-joint left-left-right-right	10+22	710535	710092	710536	710537	351
cover plate	11	710077	-	710079	-	352
endcap	12	710103	-	710538	-	352
quick-mounting bracket for installation rail	13	710107	-	-	-	345
3-circuits adapter for light installation	14	710539	-	710540	-	360
electrical outlet adapter	15	710024	-	710026	-	360
mounting adapter for additional components max. 10kg	16	710054	-	710056	-	361
signs hook, max. load 5kg	17	710060	-	710062	-	361




Unlike other Dali systems, you do not need any additional or special electrical components such as feeders, connectors, corners or T-connectors for the recessed tracks, corners or T-connectors. All the standard components of the system are used and only the matching plastic cover is replaced; the recessed version is ready. This simplifies stock-keeping and also provides significantly more flexibility.

ILLUSTRATIONS WITH PLANNING RELEVANT DIMENSIONS




FIXING POINTS




MECHANICAL LOAD TRACK POWER RAIL 1000 MM

60 N $\triangleq$ 6,12 kg
dimension in mm







MECHANICAL LOAD TRACK POWER RAIL 2000/3000 MM

30 N $\triangleq$ 3,06 kg
dimension in mm



PLANNING GUIDE D LINE DALI MOUNTING POWER RAIL SYSTEM 220-440V





D LINE DALI SURFACE-MOUNTED TRACK RAIL

- Can be controlled with DALI
- Up to three phases [3x 16 A] can be fed in
- Cutting tool required for in-house assembly
- Numerous attachment options

Application Area

Reception / Communication, Corridor / stairwell, Home / Living, Office / conference, Shop / Retail / Sales area

Housing	Aluminium	Rated Input Voltage	220-440 V/AC
Width	35.2 mm	Output Current	16 A
Height	35.5 mm		

Article	Housing Color	Length	Price
710500	White	1000 mm	€ 38.95
710501	Black	1000 mm	€ 38.95
710502	White	2000 mm	€ 73.95
710503	Black	2000 mm	€ 73.95
710504	White	3000 mm	€ 107.95
710505	Black	3000 mm	€ 107.95



Accessories

931066 D LINE DALI, cut-back tool for shortening the DALI wires  € 154.95

Accessories for 710500, 710502, 710504

710077 D Line/Dali cover panel for integrated busbar, white  € 4.95

Accessories for 710501, 710503, 710505

710079 D Line/Dali cover panel for integrated busbar, black  € 4.95



Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.



D LINE DALI SURFACE-MOUNTED ADAPTER


- Can be controlled with DALI
- Surface-mounted housing for converting busbar spotlights
- Single phase (1x 16 A) feed
- Easy to install

Application Area
Reception / Communication, Corridor / stairwell, Home / Living, Office / conference, Shop / Retail / Sales area


Housing	Plastic	Rated Input Voltage	220-240 V/AC
Height	35 mm	Output Current	16 A
Ø	143 mm		

Article	Housing Color	Price
710512	 White	€ 26.95
710513	 Black	€ 26.95






710113, 710115



710114, 710116



examples of designs



D LINE/DALI SURFACE-MOUNTED POWERTRACK CURVED

- Curved track 90° (radius 1m)
- Enables completely new design forms (corner, semicircle, circle, wave)
- Segment length 1.57m
- Can be used as D-Line DALI or D-Line standard track
- only suitable for standard track adapters (max. length 12cm)
- up to 3 phases [3x 16A] can be fed in
- cutting tool required for Dali customised assembly
- Many different mounting options

Application Area

Home / Living, Shop / Retail / Sales area

Housing	Aluminium	Height	35.5 mm
Mounting Type	Top mounting	Rated Input Voltage	220-440 V/AC
Length	1570 mm	Output Current	16 A
Width	35.2 mm		

Article	Housing Color		Price
710113	☐ White	left	€ 211.95
710115	☒ Black	left	€ 211.95
710114	☐ White	right	€ 211.95
710116	☒ Black	right	€ 211.95





D LINE DALI RECESSED TRACK RAIL

- Can be controlled with DALI
- Up to three phases [3x 16 A] can be fed in
- Cutting tool required for in-house assembly
- Numerous attachment options

Application Area

Reception / Communication, Corridor / stairwell, Home / Living, Office / conference, Shop / Retail / Sales area

Housing	Aluminium	Rated Input Voltage	220-440 V/AC
Width	56 mm	Output Current	16 A
Height	35.5 mm		

Article	Housing Color	Length	Price
710506	White	1000 mm	€ 45.95
710507	Black	1000 mm	€ 45.95
710508	White	2000 mm	€ 83.95
710509	Black	2000 mm	€ 83.95
710510	White	3000 mm	€ 119.95
710511	Black	3000 mm	€ 119.95



Accessories

931066 D LINE DALI, cut-back tool for shortening the DALI wires  € 154.95

Accessories for 710506, 710508, 710510

710077 D Line/Dali cover panel for integrated busbar, white  € 4.95

Accessories for 710507, 710509, 710511

710079 D Line/Dali cover panel for integrated busbar, black  € 4.95



Onlineshop
You can find more information about the products in the onlineshop:
Detailed images, videos, project reports, LDT files, EPREL data sheets and more.



D LINE QUICK-MOUNTING BRACKET FOR INSTALLATION RAIL

- Suitable for recessed systems
- Simplifies installation of recessed current tracks
- No additional substructure is required for mounting (check admissible load of ceiling construction)

Application Area

Home / Living, Shop / Retail / Sales area

Housing	Steel	Width	45 mm
Length	70 mm	Height	25 mm

Article	Housing Color	Price
710107	 Silver	€ 3.95



Lighting design


Interested in our lighting design service?

Your contact person will be happy to answer any questions you may have.



D LINE DALI ELECTRIC FEEDER LEFT

- Can be controlled using DALI
- Up to three phases (3x 16 A) can be fed in
- Power can be fed in from above (ceiling) or from the side
- Suitable for surface-mounted and recessed systems



Application Area

Reception / Communication, Corridor / stairwell, Home / Living, Office / conference, Shop / Retail / Sales area


Housing	Plastic	Height	35.5 mm
Length	139 mm	Rated Input Voltage	220-440 V/AC
Width	35.2 mm	Output Current	16 A

Article	Housing Color	Price
710514	White	€ 14.95
710515	Black	€ 14.95



D LINE DALI ELECTRIC FEEDER RIGHT

- Can be controlled using DALI
- Up to three phases (3x 16 A) can be fed in
- Power can be fed in from above (ceiling) or from the side
- Suitable for surface-mounted and recessed systems



Application Area

Reception / Communication, Corridor / stairwell, Home / Living, Office / conference, Shop / Retail / Sales area

Housing	Plastic	Height	35.5 mm
Length	139 mm	Rated Input Voltage	220-440 V/AC
Width	35.2 mm	Output Current	16 A

Article	Housing Color	Price
710516	White	€ 14.95
710517	Black	€ 14.95




- Accessories for 710516
- 710518 D Line DALI cover panel feed left/right, white
- Accessories for 710517
- 710519 D Line DALI cover panel feed left/right, black





D LINE DALI STRAIGHT CONNECTOR WITH FEED OPTION

- Can be controlled using DALI
- Up to three phases (3x 16 A) can be fed in
- Power supply from above (ceiling)
- Suitable for surface-mounted and recessed systems



Application Area

Reception / Communication, Corridor / stairwell, Home / Living, Office / conference, Shop / Retail / Sales area

Housing	Plastic	Height	35.5 mm
Length	203 mm	Rated Input Voltage	220-440 V/AC
Width	35.2 mm	Output Current	16 A

Article	Housing Color	Price
710520	White	€ 28.95
710521	Black	€ 28.95



Accessories for 710520

710090 D Line/Dali cover panel for longitudinal connector, white



€ 3.45

Accessories for 710521

710522 D Line DALI cover panel for longitudinal connector, black




€ 3.45



D LINE DALI FLEX CONNECTOR

- Can be controlled using DALI
- Easy to install
- Compensates for height or angle differences within a track system
- Suitable for surface-mounted systems



Application Area

Reception / Communication, Corridor / stairwell, Home / Living, Office / conference, Shop / Retail / Sales area

Housing	Plastic	Height	35.5 mm
Length	285 mm	Rated Input Voltage	220-440 V/AC
Width	35.2 mm	Output Current	16 A

Article	Housing Color	Price
710523	White	€ 37.95
710524	Black	€ 37.95





D LINE DALI ELECTRIC CONNECTOR


- easy to install
- suitable for surface-mounted and recessed systems

Application Area

Reception / Communication, Corridor / stairwell, Home / Living, Office / conference, Shop / Retail / Sales area

Housing	Plastic	Height	26.5 mm
Length	107 mm	Rated Input Voltage	220-440 V/AC
Width	20.5 mm	Output Current	16 A

Article	Housing Color	Price
710525	White	€ 9.95
710526	Black	€ 9.95



D LINE MECHANICAL CONNECTOR

- Mechanical connector without electrical contacts
- For electrical separation of two different power circuits within one track system
- Suitable for surface-mounted and recessed systems

Application Area

Home / Living, Shop / Retail / Sales area

Housing	Plastic	Width	20 mm
Length	66.4 mm	Height	27 mm

Article	Housing Color	Price
710018	White	€ 5.95
710020	Black	€ 5.95





D LINE DALI 90°-CONNECTOR


- with reversal mechanism for switching the orientation between left and right
- easy to install
- suitable for surface-mounted and recessed systems

Application Area

Reception / Communication, Corridor / stairwell, Home / Living, Office / conference, Shop / Retail / Sales area

Housing	Plastic	Height	35.5 mm
Length	119 mm	Rated Input Voltage	220-440 V/AC
Width	119 mm	Output Current	16 A

Article	Housing Color	Price
710527	 White	€ 31.95
710528	 Black	€ 31.95



Accessories for 710527

710091 D Line/Dali cover panel for 90° connector, white

 € 3.45

Accessories for 710528


710529 D Line DALI cover panel for 90° connector, black

 € 3.45



D LINE DALI T-CONNECTOR LEFT-LEFT-RIGHT

- with reversal mechanism for switching the orientation between left and right
- easy to install
- suitable for surface-mounted and recessed systems



Application Area

Reception / Communication, Corridor / stairwell, Home / Living, Office / conference, Shop / Retail / Sales area


Housing	Plastic	Height	35.5 mm
Length	203 mm	Rated Input Voltage	220-440 V/AC
Width	119 mm	Output Current	16 A

Article	Housing Color	Price
710530	White	€ 44.95
710531	Black	€ 44.95



D LINE DALI T-CONNECTOR RIGHT-RIGHT-LEFT

- with reversal mechanism for switching the orientation between left and right
- easy to install
- suitable for surface-mounted and recessed systems



Application Area

Reception / Communication, Corridor / stairwell, Home / Living, Office / conference, Shop / Retail / Sales area

Housing	Plastic	Height	35.5 mm
Length	203 mm	Rated Input Voltage	220-440 V/AC
Width	119 mm	Output Current	16 A

Article	Housing Color	Price
710532	White	€ 44.95
710533	Black	€ 44.95



Accessories for 710532


710093 D Line/Dali cover panel for T-connector, white

€ 3.45

Accessories for 710533

710534 D Line DALI cover panel for T-connector, black

€ 3.45




D LINE DALI X-CONNECTOR

- easy to install
- suitable for surface-mounted and recessed systems


Application Area

Reception / Communication, Corridor / stairwell, Home / Living, Office / conference, Shop / Retail / Sales area



Housing	Plastic	Height	35.5 mm
Length	203 mm	Rated Input Voltage	220-440 V/AC
Width	203 mm	Output Current	16 A

Article	Housing Color	Price
710535	White	€ 56.95
710536	Black	€ 56.95



Accessories for 710535

710092 D Line/Dali cover panel for X-connector, white



€ 3.95

Accessories for 710536

710537 D Line DALI cover panel for X-connector, black



€ 3.95



D LINE COVER PANEL

- Suitable for surface-mounted and recessed systems
- For sealing publicly accessible busbars within a contact zone of less than 2.30 m

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic	Width	21.5 mm
Length	1000 mm	Height	7.5 mm

Article	Housing Color	Price
710077	 White	€ 4.95
710079	 Black	€ 4.95



D LINE END CAP

- For closing open current track ends (touch protection)
- Easy to install
- Suitable for surface-mounted systems

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic	Height	32.5 mm
---------	---------	--------	---------

Article	Housing Color	Length	Width	Price
710066	 White	31.3 mm	35.2 mm	€ 2.45
710068	 Black	31.3 mm	35.2 mm	€ 2.45
710103	 White	56 mm	47.9 mm	€ 2.45
710538	 Black	56 mm	47.9 mm	€ 2.45





D LINE MOUNTING BRACKET FLEX

- Suitable for surface-mounted systems
- Simplifies installation of complex shapes
- Current track can still be slid during installation

Application Area

Home / Living, Shop / Retail / Sales area

Housing	Metal	Width	33.8 mm
Length	40 mm	Height	12.5 mm

Article	Housing Color	Price
710063	 White	€ 4.95
710065	 Black	€ 4.95



D LINE/DALI GRID-CEILING QUICK-MOUNTING BRACKET FOR MINI CABLE SUSPENSION

- Suitable for surface-mounted systems
- For universal use for mounting other components using M6 thread stud bolts on grid ceilings
- Suitable for 22-24 mm grid-ceiling support rails
- Suitable for steel cables up to 2.6 mm
- Mechanical load up to 7 kg/70 N

Application Area

Home / Living, Shop / Retail / Sales area

Housing	Steel	Width	39 mm
Length	25 mm	Height	27 mm

Article	Housing Color	Price
710108	 White	€ 3.45
710109	 Black	€ 3.45






D LINE WALL BRACKET

- Suitable for surface-mounted systems
- Simplifies installation of current tracks near walls
- Ideal for illuminating pictures and objects, for example in exhibitions, collections and museums

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Aluminium	Width	25 mm
Length	91.9 mm	Height	80 mm

Article	Housing Color	Price
710104	 White	€ 11.95
710106	 Black	€ 11.95



D LINE SUSPENSION CONNECTION BRACKET


- Suitable for surface-mounted systems
- For chain installation or similar (chain not included in the scope of delivery)

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Metal	Width	32 mm
Length	181 mm	Height	20 mm

Article	Housing Color	Price
710057	 White	€ 7.95
710059	 Black	€ 7.95





D LINE CEILING SUSPENSION RIGID

- Sturdy, elegant ceiling hanger
- Suitable for surface-mounted systems
- Hanger dimension 635 mm (can be shortened to 335 mm)
- Hanger can be extended with accessories

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Aluminium	Width	60 mm
Length	635 mm		

Article	Housing Color	Price
710078	☐ White	€ 24.95
710084	☒ Black	€ 24.95



D LINE EXTENSION FOR CEILING SUSPENSION RIGID

- Suitable for rigid ceiling hangers
- Extends the hanger length by 300 mm

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Aluminium	Width	10 mm
Length	310 mm		

Article	Housing Color	Price
710086	☐ White	€ 4.95
710087	☒ Black	€ 4.95





D LINE ROPE SUSPENSION BRACKET

- Can be cut to length for suspension dimension: 120-1,500 mm
- suitable for surface-mounted systems

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Metal	Width	31 mm
Length	120 mm	Height	52 mm

Article	Housing Color	Price
710048	White	€ 11.95
710050	Black	€ 11.95



Accessories
710081 D Line/Dali cable for cable suspension 4.0 m



€ 6.95



D LINE ROPE SUSPENSION BRACKET MINI

- Stylish and sophisticated suspended mounting
- Can be cut to length for hanger lengths: 90-4,960 mm
- Suitable for surface-mounted systems

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Metal	Width	31 mm
Length	120 mm	Height	58 mm

Article	Housing Color	Price
710094	White	€ 15.95
710096	Black	€ 15.95



Accessories
710108 D Line/Dali grid ceiling quick-mounting clip for wire suspension Mini white
710109 D Line/Dali grid ceiling quick-mounting clip for wire suspension Mini black



€ 3.45



€ 3.45





D LINE/DALI CABLE SUSPENSION BRACKET WITH ADJUSTMENT TRAVERSE

- Set consisting of wire suspension with ceiling attachment and adjustment traverse
- Compensation of asymmetrical weight loads in the track system through one-sided spotlight mounting
- Easy and quick adjustment
- Suspension dimension can be individually shortened: 160-4960 mm
- Suitable for D Line/Dali mounting system



Application Area

Home / Living, Shop / Retail / Sales area

Housing	Metal	Width	32 mm
Length	120 mm	Height	120 mm

Article	Housing Color	Price
710110	White	€ 20.95
710112	Black	€ 20.95




D LINE/DALI ROPE SUSPENSION BRACKET

- special wire suspension for D-Line/DALI Curved tracks
- enables and extends the mounting options
- Suspension dimension can be individually shortened: 90 - 4960 mm

Housing	Metal	Height	59 mm
Length	62 mm	Loading Weight max.	10 kg
Width	35 mm	Load Force max.	100 N

Article	Housing Color	Price
710117	White	€ 14.95
710118	Black	€ 14.95





D LINE FAST-MOUNTING BRACKET

- Suitable for surface-mounted systems
- Current track can be installed without tools using knurled thumb screw and spring clamps
- Quick installation and removal for e.g. trade fair construction

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Aluminium	Width	30 mm
Length	40 mm	Height	11.9 mm

Article	Housing Color	Price
710082	 Black	€ 8.95



D LINE TRUSS ADAPTER

- Suitable for surface-mounted systems
- Quick-action couplers for fast mounting of current tracks on cross rail structures
- Fits all 50 mm aluminium cross rails in event/trade fair construction

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Aluminium	Width	30 mm
Length	40 mm	Height	11.9 mm

Article	Housing Color	Price
710083	 Silver	€ 25.95



This little »jack-of-all-trades« makes mounting a track on an existing grid ceiling child's play. The installation time is only a fraction of what it used to be. In the first step, the clip is simply clicked into the visible metal strips of the grid ceiling and is held bomb-proof on the ceiling by means of a safety spring clip. After that, the conductor rail is simply pushed onto it and the installation is finished.



D LINE GRID CEILING FAST-MOUNTING BRACKET

- Suitable for surface-mounted systems
- Quick and easy to install on grid ceilings
- Mechanical load up to 15.0 kg/150 N
- Suitable for 22-24 mm ceiling grid support rails

Application Area

Home / Living, Shop / Retail / Sales area

Housing	Metal	Width	31 mm
Length	120 mm	Height	11 mm

Article	Housing Color	Price
710051	☐ White	€ 9.95
710053	☒ Black	€ 9.95





D LINE DALI THREE-PHASE ADAPTER FOR INSTALLING LAMPS


- can be controlled with DALI, up to three phases can be fed in
- easy to install
- suitable for surface-mounted and recessed systems

Application Area

Reception / Communication, Corridor / stairwell, Home / Living, Office / conference, Shop / Retail / Sales area

Housing	Plastic	Height	51 mm
Length	113 mm	Rated Input Voltage	220-240 V/AC
Width	32 mm	Output Current	10 A

Article	Housing Color	Price
710539	White	€ 19.95
710540	Black	€ 19.95



D LINE SOCKET ADAPTER

- easy to install
- suitable for surface-mounted and recessed systems
- as power distribution system in current tracks
- max. 1,380 W
- integrated plug fuse

Application Area

Home / Living, Shop / Retail / Sales area

Housing	Plastic	Rated Input Voltage	230 V/AC
Length	58.5 mm	Output Current	6 A
Width	53.5 mm	Connected Load max.	1380 W
Height	103 mm		

Article	Housing Color	Price
710024	White	€ 22.95
710026	Black	€ 22.95





D LINE MOUNTING ADAPTER FOR ADDITIONAL COMPONENTS

- Suitable for surface-mounted and recessed systems
- Mounting adapter (M6 thread) for holding additional devices and lights
- Ideal for use with optional D Line socket adapter
- Load max. 10 kg/100 N

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Metal, Plastic	Width	31.5 mm
Length	66.5 mm	Height	84 mm

Article	Housing Color	Price
710054	☐ White	€ 8.95
710056	☒ Black	€ 8.95



D LINE SIGN HOOK

- Suitable for surface-mounted and recessed systems
- Hook for attaching information signs etc.
- Load max. 5kg / 50N

Application Area
Home / Living, Shop / Retail / Sales area

Housing	Plastic, Steel	Ø	25 mm
Height	52 mm		

Article	Housing Color	Price
710060	☐ White	€ 2.45
710062	☒ Black	€ 2.45



3-phases power luminaires



page 364



page 365



page 366



page 367



page 368



page 369



page 369



page 372



page 373



page 375



page 376



page 377



□ ■
page 378



□ ■
page 379



□ ■
page 381



□ ■ ■
page 383



□ ■ ■
page 384



■ □
page 386



□ ■
page 389



□ ■ ■
page 390



□ ■ ■
page 391



□ ■
page 392



□ ■
page 398



□ ■
page 399



□ ■
page 400



□ ■
page 401



□ ■
page 404



□ ■
page 406



□ ■
page 407



■ □
page 408




□ ■
page 409



FOCARIS DIM

- Infinitely adjustable beam angle
- no reflector change necessary
- Homogeneous light image
- opt. honeycomb filter available

Housing	Aluminium, Polycarbonate	Rotation Angle	355 Degree
Colour Temperature	2700/3000/4000 K	Swivelling Angle	90 Degree
Length	158 mm	Control	Trailing-edge dimmer
Rated Input Voltage	198-264 V/AC	CRI (Ra)	90
Power Supply Unit incl.	Yes	Light Direction	Front
Light Beam Angle	15 Degree	IK Protection Class	IK04



707268

Article	Housing Color		Luminous Flux	W x H	Power	Light Beam Angle 2	Price
707268	White		1210/1350/1350 lm	80 x 142 mm	15.0 W	50 Degree	€ 111.95
707269	Black		1100/1250/1250 lm	80 x 142 mm	15.0 W	50 Degree	€ 111.95
707270	White		3015/3450/3450 lm	118 x 181 mm	37.0 W	60 Degree	€ 175.95
707271	Black		3015/3450/3450 lm	118 x 181 mm	37.0 W	60 Degree	€ 175.95



Accessories for **707268, 707269**

931166 Focar, Honeycomb filter 80 mm

€ 3.95

Accessories for **707270, 707271**

931167 Focar, Honeycomb filter 118 mm

€ 4.95



Lighting design

Interested in our lighting design service?


Your contact person will be happy to answer any questions you may have.



FOCARIS DALI

- Infinitely adjustable beam angle
- no reflector change necessary
- Homogeneous light image
- opt. honeycomb filter available

Housing	Aluminium, Polycarbonate	Swivelling Angle	90 Degree
Colour Temperature	2700/3000/4000 K	Control	DALI 2 / DT6, Intelli Push-Dim
Rated Input Voltage	198-264 V/AC	CRI (Ra)	90
Power Supply Unit incl.	Yes	Light Direction	Front
Light Beam Angle	15 Degree	IK Protection Class	IK04
Rotation Angle	355 Degree		



707264

Article	Housing Color		Luminous Flux	L x W x H	Light Beam Angle 2	Power	Price
707264	White	WW NW	1210/1350/1350 lm	198 x 80 x 144 mm	50 Grad	15.0 W	€ 135.95
707265	Black	WW NW	1100/1250/1250 lm	198 x 80 x 144 mm	50 Grad	15.0 W	€ 135.95
707266	White	WW NW	3015/3450/3450 lm	238 x 118 x 180 mm	60 Grad	37.0 W	€ 191.95
707267	Black	WW NW	3015/3450/3450 lm	238 x 118 x 180 mm	60 Grad	37.0 W	€ 191.95



Accessories for 707264, 707265
931166 Focaris, Honeycomb filter 80 mm

€ 3.95

Accessories for 707266, 707267
931167 Focaris, Honeycomb filter 118 mm

€ 4.95




5-year guarantee
Benefit from the maximum quality promise:
All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.



CERES ON/OFF

- particularly energy efficient
- high-quality light image
- can be customised with a wide range of accessories

Housing	Aluminium	Rotation Angle	355 Degree
Surface	Matt	Swivelling Angle	90 Degree
Rated Input Voltage	198-264 V/AC	CRI (Ra)	90
Power Supply Unit incl.	Yes	IK Protection Class	IK04
Light Beam Angle	36 Degree		



707284

Article	Housing Color	Colour Temperature	Luminous Flux	Height	Ø	Power	Price
707284	White	3000 K	2500 lm	60 mm	90 mm	19.0 W	€ 59.95
707285	Black	3000 K	2500 lm	60 mm	90 mm	19.0 W	€ 59.95
707292	White	3000 K	4400 lm	69 mm	118 mm	31.0 W	€ 75.95
707293	Black	3000 K	4400 lm	69 mm	118 mm	31.0 W	€ 75.95
707286	White	4000 K	2600 lm	60 mm	90 mm	19.0 W	€ 59.95
707287	Black	4000 K	2600 lm	60 mm	90 mm	19.0 W	€ 59.95
707294	White	4000 K	4600 lm	69 mm	118 mm	31.0 W	€ 75.95
707295	Black	4000 K	4600 lm	69 mm	118 mm	31.0 W	€ 75.95



Accessories for **707284, 707285, 707286, 707287**

931174	Lens 24 degrees for Ceres 90	€ 7.95
931175	Lens 60 degrees for Ceres 90	€ 7.95
931176	Honeycomb filter for Ceres 90, black	€ 3.95
931177	Cross for Ceres 90, black	€ 7.95
931178	Wall Washer for Ceres 90, black	€ 9.95
931179	Barndoor for Ceres 90, black	€ 25.95

Accessories for **707292, 707293, 707294, 707295**

931186	Lens 24 degrees for Ceres 118	€ 7.95
931187	Lens 60 degrees for Ceres 118	€ 7.95
931188	Honeycomb filter for Ceres 118, black	€ 3.95
931189	Cross for Ceres 118, black	€ 7.95
931190	Wall Washer for Ceres 118, black	€ 9.95
931191	Barndoor for Ceres 118, black	€ 29.95






CERES DALI

- particularly energy efficient
- high-quality light image
- can be customised with a wide range of accessories

Housing	Aluminium	Swivelling Angle	90 Degree
Surface	Matt	Control	DALI 2 / DT6, Intelli Push-Dim
Rated Input Voltage	198-264 V/AC	CRI (Ra)	90
Power Supply Unit incl.	Yes	IK Protection Class	IK04
Light Beam Angle	36 Degree		
Rotation Angle	355 Degree		



707296

Article	Housing Color	Colour Temperature	Luminous Flux	Height	Ø	Power	Price
707296	White	3000 K	2500 lm	60 mm	90 mm	19.0 W	€ 91.95
707297	Black	3000 K	2500 lm	60 mm	90 mm	19.0 W	€ 91.95
707304	White	3000 K	4400 lm	69 mm	118 mm	31.0 W	€ 107.95
707305	Black	3000 K	4400 lm	69 mm	118 mm	31.0 W	€ 107.95
707298	White	4000 K	2600 lm	60 mm	90 mm	19.0 W	€ 91.95
707299	Black	4000 K	2600 lm	60 mm	90 mm	19.0 W	€ 91.95
707306	White	4000 K	4600 lm	69 mm	118 mm	31.0 W	€ 107.95
707307	Black	4000 K	4600 lm	69 mm	118 mm	31.0 W	€ 107.95



Accessories for **707296, 707297, 707298, 707299**

931174	Lens 24 degrees for Ceres 90	€ 7.95
931175	Lens 60 degrees for Ceres 90	€ 7.95
931176	Honeycomb filter for Ceres 90, black	€ 3.95
931177	Cross for Ceres 90, black	€ 7.95
931178	Wall Washer for Ceres 90, black	€ 9.95
931179	Barndoor for Ceres 90, black	€ 25.95

Accessories for **707304, 707305, 707306, 707307**

931186	Lens 24 degrees for Ceres 118	€ 7.95
931187	Lens 60 degrees for Ceres 118	€ 7.95
931188	Honeycomb filter for Ceres 118, black	€ 3.95
931189	Cross for Ceres 118, black	€ 7.95
931190	Wall Washer for Ceres 118, black	€ 9.95
931191	Barndoor for Ceres 118, black	€ 29.95






PANEL TRACK LIGHT

- Ideal for homogeneous basic lighting
- Can be rotated and swivelled
- High luminous flux

Application Area

Shop / Retail / Sales area, DIY store / discount store / supermarket / car dealership, Trade fair construction / shop fitting

Housing	Aluminium	Rated Input Voltage	110-240 V/AC
Length	300 mm	Power Supply Unit incl.	Yes
Width	110 mm	Light Beam Angle	110 Degree
Height	8.5 mm	Swivelling Angle	90 Degree
Power	20 W	CRI (Ra)	80



707134

Article	Housing Color	Colour Temperature	Luminous Flux	Price
707134	White	3000 K	2000 lm	€ 91.95
707135	Black	3000 K	2000 lm	€ 91.95
707136	White	4000 K	2200 lm	€ 87.95
707137	Black	4000 K	2200 lm	€ 87.95





LINEAR 60


- low height
- homogeneous illumination



Application Area


Shop / Retail / Sales area, Home / Living, Trade fair construction / shop fitting, Hotel / catering

Housing	Aluminium	Power	18 W
Surface	Matt	Rated Input Voltage	200-240 V/AC
Length	687 mm	Power Supply Unit incl.	Yes
Width	32 mm	Light Beam Angle	110 Degree
Height	62 mm	CRI (Ra)	80



707147

Article	Housing Color	Colour Temperature	Luminous Flux	Price
707148	Black	3000 K	1950 lm	€ 114.95
707147	White	3000 K	2100 lm	€ 114.95
707150	Black	4000 K	2100 lm	€ 114.95
707149	White	4000 K	2300 lm	€ 114.95




LINEAR 100

- low height
- homogeneous illumination

Application Area


Shop / Retail / Sales area, Home / Living, Trade fair construction / shop fitting, Hotel / catering

Housing	Aluminium	Power	28 W
Surface	Matt	Rated Input Voltage	200-240 V/AC
Length	1087 mm	Power Supply Unit incl.	Yes
Width	32 mm	Light Beam Angle	110 Degree
Height	62 mm	CRI (Ra)	80



707151

Article	Housing Color	Colour Temperature	Luminous Flux	Price
707152	Black	3000 K	3100 lm	€ 147.95
707151	White	3000 K	3200 lm	€ 147.95
707154	Black	4000 K	3200 lm	€ 147.95
707153	White	4000 K	3400 lm	€ 147.95





LINEAR PRO SOFT

LINEAR PRO 3-circuit track luminaires are the ideal solution for illuminating retail shelving, aisles in supermarkets and many other applications.

The LINEAR PRO is available as a 3-circuit track luminaire in four versions: FOLD, TILT, SOFT and OFFICE. Each version offers specific advantages for lighting design and enables precise illumination of products and other objects. While the SOFT version features an extra-wide fixed beam angle of 120°, the LINEAR PRO TILT and LINEAR PRO FOLD can be flexibly adjusted to suit the respective sales areas.


LINEAR PRO SOFT



LINEAR PRO TILT



LINEAR PRO FOLD



TILT or FOLD?

The LINEAR PRO TILT can either illuminate straight downwards or be individually tilted sideways by up to 30°. In contrast, the LINEAR PRO FOLD features a three-part design with two LED wings complemented by a diffuse light line in the centre.

This makes the LINEAR PRO FOLD particularly suitable for the uniform illumination of complete aisles with shelving on both sides, while the LINEAR PRO TILT can be flexibly directed towards individual shelving units.

For optimum retail lighting, the SOFT, TILT and FOLD series can ideally be combined with additional spotlight modules. These are particularly suitable for highlighting promotional displays and shelf end caps.

3 ADVANTAGES

ADJUSTABLE POWER


The power of the LINEAR PRO 3-circuit track lights can be adjusted in four stages. The luminaires are also DC-capable and can be integrated into emergency power systems.

BEG SUBSIDY

The LINEAR PRO luminaires fulfil the requirements of the BEG subsidy for efficient LED luminaires and are subsidised by the Federal Ministry for Economic Affairs and Climate Protection with 15%.

SEAMLESSLY COMBINABLE

The 1500 mm versions of the LINEAR PRO have a sliding track adapter and are each available in a 50% mirrored A/B version to allow for seamless side-by-side installation, even across track connectors.






LINEAR PRO SOFT DALI

- Eligible for BEG German federal funding for energy-efficient buildings
- Emergency power capable [198-264 V/DC EOFI: 15 %]
- Long service life of 60,000 hours [L80B50]
- Particularly energy efficient

Application Area

Reception / Communication, Shop / Retail / Sales area, Workshop / Craft / Warehouse, DIY store / discount store / supermarket / car dealership, Trade fair construction / shop fitting, Industry / production / high-bay warehouse, Safety lighting / emergency lighting

Housing	Aluminium	Rated Input Voltage	198-264 V/AC
Length	602 mm	Power Supply Unit incl.	Yes
Width	61.1 mm	Light Beam Angle	120 Degree
Height	58 mm	Control	DALI 2 / DT6
Power Selectable	14 W, 16 W, 18 W, 20 W	CRI (Ra)	90
		IK Protection Class	IK03



707219

Article	Housing Color	Colour Temperature	Luminous Flux	Price
707220	Black	3000 K	2800 lm	€ 114.95
707219	White	3000 K	2850 lm	€ 114.95
707222	Black	4000 K	2850 lm	€ 114.95
707221	White	4000 K	2900 lm	€ 114.95



Lighting design

Interested in our lighting design service?

Your contact person will be happy to answer any questions you may have.




LINEAR PRO SOFT DALI CCT

- Eligible for German BEG federal funding
- Can run on emergency power
- Long service life of 60,000 hours (L80B50)
- Particularly energy efficient

Application Area

Reception / Communication, Shop / Retail / Sales area, Workshop / Craft / Warehouse, DIY store / discount store / supermarket / car dealers-hip, Trade fair construction / shop fitting, Industry / production / high-bay warehouse, Safety lighting / emergency lighting

Housing	Aluminium	Rated Input Voltage	198-264 V/AC
Colour Temperature	3000/3500/4000 K	Power Supply Unit incl.	Yes
Length	1196 mm	Light Beam Angle	120 Degree
Width	61.1 mm	Control	DALI 2 / DT6
Height	58 mm	CRI (Ra)	90
Power Selectable	28 W, 32 W, 36 W, 40 W	IK Protection Class	IK03




707223

Article	Housing Color	Luminous Flux	Price
707224	Black	4800/5000/4900 lm	€ 147.95
707223	White	4900/5100/5000 lm	€ 147.95



5-year guarantee
Benefit from the maximum quality promise:
All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.






LINEAR PRO OFFICE DALI

- Suitable for VDU workstations (in accordance with EN 12464-1 BAP65 [L65 = 3000cd/m²])
- BEG eligible
- Seamless baying
- Emergency current capable [198-264 V/DC EOFI: 100%]
- Output adjustable in 4 levels

Application Area

Reception / Communication, Office / conference, Home office / study, Education / school / lecture theatre, Shop / Retail / Sales area, DIY store / discount store / supermarket / car dealership, Trade fair construction / shop fitting, Safety lighting / emergency lighting

Housing	Steel	Light Beam Angle	60 Degree
Width	62 mm	Control	DALI 2 / DT6, Intelli Push-Dim
Height	58 mm	CRI (Ra)	90
Rated Input Voltage	220-240 V/AC	IK Protection Class	IK03
Power Supply Unit incl.	Yes		



707335

Article	Housing Color	Colour Temperature	Luminous Flux	Length	Power Selectable	Price
707329	Black	3000 K	3600 lm	600 mm	24.0 W / 22.0 W / 20.0 W / 18.0 W	€ 151.95
707328	White	3000 K	3850 lm	600 mm	24.0 W / 22.0 W / 20.0 W / 18.0 W	€ 151.95
707333	Black	3000 K	8750 lm	1493 mm	60.0 W / 55.0 W / 50.0 W / 45.0 W	€ 183.95
707332	White	3000 K	9300 lm	1493 mm	60.0 W / 55.0 W / 50.0 W / 45.0 W	€ 183.95
707331	Black	4000 K	3600 lm	600 mm	24.0 W / 22.0 W / 20.0 W / 18.0 W	€ 151.95
707330	White	4000 K	3850 lm	600 mm	24.0 W / 22.0 W / 20.0 W / 18.0 W	€ 151.95
707335	Black	4000 K	8750 lm	1493 mm	60.0 W / 55.0 W / 50.0 W / 45.0 W	€ 183.95
707334	White	4000 K	9300 lm	1493 mm	60.0 W / 55.0 W / 50.0 W / 45.0 W	€ 183.95






LINEAR PRO TILT

- Eligible for BEG German federal funding for energy-efficient buildings
- Emergency power capable [198-264 V/DC EOFI: 100 %]
- Can be locked shining downwards
- Can be swivelled up to 30° to each side
- Long service life of 60,000 hours [L80B50]
- Particularly energy efficient
- Output adjustable in three stages

Application Area

Reception / Communication, Shop / Retail / Sales area, Workshop / Craft / Warehouse, DIY store / discount store / supermarket / car dealership, Trade fair construction / shop fitting, Industry / production / high-bay warehouse, Safety lighting / emergency lighting

Housing	Steel	Light Beam Angle	60 Degree
Width	60 mm	Swivelling Angle	60 Degree
Height	54 mm	CRI (Ra)	90
Rated Input Voltage	198-264 V/AC	IK Protection Class	IK03
Power Supply Unit incl.	Yes		



707141

Article	Housing Color	Colour Temperature	Luminous Flux	Length	Power Selectable	Price
707195	White	3000 K	3200 lm	600 mm	14.0 W / 16.0 W / 18.0 W / 20.0 W	€ 122.95
707196	Black	3000 K	3200 lm	600 mm	14.0 W / 16.0 W / 18.0 W / 20.0 W	€ 122.95
707197	White	3000 K	8000 lm	1493 mm	35.0 W / 40.0 W / 45.0 W / 50.0 W	€ 151.95
707198	Black	3000 K	8000 lm	1493 mm	35.0 W / 40.0 W / 45.0 W / 50.0 W	€ 151.95
707141	White	4000 K	3200 lm	600 mm	14.0 W / 16.0 W / 18.0 W / 20.0 W	€ 122.95
707142	Black	4000 K	3200 lm	600 mm	14.0 W / 16.0 W / 18.0 W / 20.0 W	€ 122.95
707143	White	4000 K	8000 lm	1493 mm	35.0 W / 40.0 W / 45.0 W / 50.0 W	€ 151.95
707144	Black	4000 K	8000 lm	1493 mm	35.0 W / 40.0 W / 45.0 W / 50.0 W	€ 151.95






LINEAR PRO TILT DALI

- Eligible for BEG German federal funding for energy-efficient buildings
- Emergency power capable [198-264 V/DC EOFI: 15 %]
- Can be locked shining downwards
- Can be swivelled up to 30° to each side
- Long service life of 60,000 hours [L80B50]
- Particularly energy efficient

Application Area

Reception / Communication, Shop / Retail / Sales area, Workshop / Craft / Warehouse, DIY store / discount store / supermarket / car dealership, Trade fair construction / shop fitting, Industry / production / high-bay warehouse, Safety lighting / emergency lighting

Housing	Steel	Rated Input Voltage	198-264 V/AC
Luminous Flux	8000 lm	Power Supply Unit incl.	Yes
Length	1493 mm	Light Beam Angle	60 Degree
Width	60 mm	Swivelling Angle	60 Degree
Height	54 mm	Control	DALI 2 / DT6
Power Selectable	50 W, 45 W, 40 W, 35 W	CRI (Ra)	90
		IK Protection Class	IK03



Article	Housing Color	Colour Temperature	Price
707199	White	3000 K	€ 175.95
707200	Black	3000 K	€ 175.95
707145	White	4000 K	€ 175.95
707146	Black	4000 K	€ 175.95






LINEAR PRO FOLD

- Eligible for BEG German federal funding for energy-efficient buildings
- Emergency power capable [198-264 V/DC EOFI: 100 %]
- Long service life of 60,000 hours [L80B50]
- Can be swivelled up to 30° to each side
- Particularly energy efficient
- Output adjustable in four steps

Application Area

Reception / Communication, Shop / Retail / Sales area, Workshop / Craft / Warehouse, DIY store / discount store / supermarket / car dealership, Trade fair construction / shop fitting, Industry / production / high-bay warehouse, Safety lighting / emergency lighting

Housing	Aluminium	Light Beam Angle	30 Degree
Width	120 mm	Light Beam Angle 2	90 Degree
Height	68 mm	CRI (Ra)	90
Rated Input Voltage	198-264 V/AC	IK Protection Class	IK03
Power Supply Unit incl.	Yes		



707189

Article	Housing Color	Colour Temperature	Luminous Flux	Length	Power Selectable	Price
707205	White	3000 K	2900 lm	600 mm	14.0 W / 16.0 W / 18.0 W / 20.0 W	€ 139.95
707206	Black	3000 K	2900 lm	600 mm	14.0 W / 16.0 W / 18.0 W / 20.0 W	€ 139.95
707207	White	3000 K	7250 lm	1493 mm	35.0 W / 40.0 W / 45.0 W / 50.0 W	€ 167.95
707208	Black	3000 K	7250 lm	1493 mm	35.0 W / 40.0 W / 45.0 W / 50.0 W	€ 167.95
707189	White	4000 K	2900 lm	600 mm	14.0 W / 16.0 W / 18.0 W / 20.0 W	€ 139.95
707190	Black	4000 K	2900 lm	600 mm	14.0 W / 16.0 W / 18.0 W / 20.0 W	€ 139.95
707191	White	4000 K	7250 lm	1493 mm	35.0 W / 40.0 W / 45.0 W / 50.0 W	€ 167.95
707192	Black	4000 K	7250 lm	1493 mm	35.0 W / 40.0 W / 45.0 W / 50.0 W	€ 167.95






LINEAR PRO FOLD DALI

- Eligible for BEG German federal funding for energy-efficient buildings
- Emergency power capable [198-264 V/DC EOFI: 15 %]
- Long service life of 60,000 hours [L80B50]
- Particularly energy efficient

Application Area

Reception / Communication, Shop / Retail / Sales area, Workshop / Craft / Warehouse, DIY store / discount store / supermarket / car dealership, Trade fair construction / shop fitting, Industry / production / high-bay warehouse, Safety lighting / emergency lighting

Housing	Aluminium	Power Supply Unit incl.	Yes
Length	1493 mm	Light Beam Angle	30 Degree
Width	120 mm	Light Beam Angle 2	90 Degree
Height	68 mm	Control	DALI 2 / DT6
Power Selectable	50 W, 45 W, 40 W, 35 W	CRI (Ra)	90
Rated Input Voltage	198-264 V/AC	IK Protection Class	IK03



707193

Article	Housing Color	Colour Temperature	Luminous Flux	Price
707210	Black	3000 K	7000 lm	€ 191.95
707209	White	3000 K	7250 lm	€ 191.95
707194	Black	4000 K	7000 lm	€ 191.95
707193	White	4000 K	7250 lm	€ 191.95







CAN

- customisable with extensive accessories
- customised lighting solution thanks to replaceable light source
- combinable with the extensive product family of the CAN series

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Ø	60 mm	Control	Dimmable via optional light source
Pendulum Length	1500 mm		
Max. Power	1x max. 7.5 W		

Article	Housing Color	Height	Price
707251	 White	150 mm	€ 55.95
707252	 Black	150 mm	€ 55.95
707255	 White	350 mm	€ 67.95
707256	 Black	350 mm	€ 67.95



Accessories

930301	Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930302	Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930303	Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930366	Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
931065	Acrylic attachment for Can		€ 3.95





CAN

- customised lighting solution thanks to replaceable light source
- can be combined with the product family of the CAN series

Application Area

Home / Living, Reception / Communication, Hotel / catering, Trade fair construction / shop fitting

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Height	134 mm	Control	Dimmable via optional light source
Ø	60 mm	Swivelling Angle	90 Degree
Max. Power	1x max. 7.5 W		

Article	Housing Color	Price
707079	White	€ 39.95
707080	Silver	€ 39.95
707081	Black	€ 39.95

GU10

Accessories

930301	Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930302	Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930303	Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930366	Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
931065	Acrylic attachment for Can		€ 3.95





CAN BASE MIX'N MATCH 1/3

- customised lighting solution thanks to replaceable light source
- can be customised with cylinder housing in 6 different colours
- can be combined with the extensive product family of the CAN series

Housing	Aluminium	Control	Dimmable via optional light source
Height	91 mm	Rotation Angle	350 Degree
Ø	76 mm	Swivelling Angle	90 Degree
Max. Power	1x max. 7.5 W		
Rated Input Voltage	220-240 V/AC		

Article	Housing Color	Price
707246	White	€ 33.95
707247	Black	€ 33.95
707248	Silver	€ 33.95





CYLINDER HOOUSING FOR CAN MIX'N MATCH 2/3

Housing Aluminium Ø 60 mm
Height 98 mm

Article	Housing Color	Price
931053	 White	€ 6.45
931054	 Black	€ 6.45
931055	 Bronze	€ 14.95
931056	 Brass	€ 14.95
931057	 Black grey	€ 14.95
931058	 Rosé	€ 14.95

IP20



REFLECTOR RING FOR CAN MIX'N MATCH 3/3

Housing Plastic Ø 57 mm
Height 28 mm

Article	Housing Color	Price
930301	 White	€ 3.95
930302	 Black	€ 3.95
930303	 Gold	€ 3.95
930366	 Silver	€ 3.95

IP20



HORUS

If you're looking for a slim, powerful and flexible three-phase spotlight, look no further than the Horus. The slimline housing and matt surface finish combined with the powerful chip for all wattages make the Horus a true jack-of-all-trades.




HORUS

- low glare value
- can be rotated and swivelled

Application Area

Shop / Retail / Sales area, Office / conference, Office / conference

Housing	Plastic	Light Beam Angle	40 Degree
Surface	Matt	Swivelling Angle	350 Degree
Rated Input Voltage	220-240 V/AC	CRI (Ra)	80
Power Supply Unit incl.	Yes		



707094

Article	Housing Color	Colour Temperature	Luminous Flux	Height	Ø	Power	EEI	Price
707094	Black	WW 3000 K	625 lm	125 mm	60 mm	7.0 W	A E	€ 55.95
707095	White	WW 3000 K	625 lm	125 mm	60 mm	7.0 W	A E	€ 55.95
707098	Black	WW 3000 K	915 lm	140 mm	70 mm	10.0 W	A E	€ 63.95
707099	White	WW 3000 K	915 lm	140 mm	70 mm	10.0 W	A E	€ 63.95
707102	Black	WW 3000 K	1705 lm	185 mm	80 mm	20.0 W	A F	€ 71.95
707103	White	WW 3000 K	1705 lm	185 mm	80 mm	20.0 W	A F	€ 71.95
707106	Black	WW 3000 K	2525 lm	210 mm	90 mm	30.0 W	A F	€ 87.95
707107	White	WW 3000 K	2525 lm	210 mm	90 mm	30.0 W	A F	€ 87.95
707096	Black	NW 4000 K	635 lm	125 mm	60 mm	7.0 W	A E	€ 55.95
707097	White	NW 4000 K	635 lm	125 mm	60 mm	7.0 W	A E	€ 55.95
707100	Black	NW 4000 K	1030 lm	140 mm	70 mm	10.0 W	A E	€ 63.95
707101	White	NW 4000 K	1030 lm	140 mm	70 mm	10.0 W	A E	€ 63.95
707104	Black	NW 4000 K	1785 lm	185 mm	80 mm	20.0 W	A F	€ 71.95
707105	White	NW 4000 K	1785 lm	185 mm	80 mm	20.0 W	A F	€ 71.95
707108	Black	NW 4000 K	2605 lm	210 mm	90 mm	30.0 W	A F	€ 87.95
707109	White	NW 4000 K	2605 lm	210 mm	90 mm	30.0 W	A F	€ 87.95








UNI 2

- „Glow“ effect on reflector ring
- Can be rotated and swivelled
- Can be customised with a comprehensive range of accessories

Application Area


Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Trade fair construction / shop fitting

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000 K	Light Beam Angle	36 Degree
Height	167 mm	Swivelling Angle	90 Degree
Ø	100 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Power	17 W	CRI (Ra)	90
Rated Input Voltage	220-240 V/AC		



707044

Article	Housing Color		Luminous Flux	Price
707131	Black	WW	1080 lm	€ 148.95
707044	White	WW	1110 lm	€ 148.95



Accessories

930339	Reflector ring black for Uni II series		€ 8.95
930340	Reflector ring gold for Uni II series		€ 8.95
930341	Reflector ring chrome for Uni II series		€ 8.95
930335	Rear black cover for Uni II series		€ 2.45
930337	Black heat sink cover for Uni II series		€ 6.45
930306	48° reflector for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95






NIHAL

- can be rotated and swivelled
- large tilt angle

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Trade fair construction / shop fitting

Housing	Aluminium	Power Supply Unit incl.	Yes
Length	135 mm	Light Beam Angle	33 Degree
Width	138 mm	Swivelling Angle	180 Degree
Height	188 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	86 mm	CRI (Ra)	90
Rated Input Voltage	220-240 V/AC		



707040

Article	Housing Color	Colour Temperature	Luminous Flux	Power	Price
707056	Silver	3000 K	2470 lm	33.0 W	€ 183.95
707041	Black	3000 K	2580 lm	33.0 W	€ 183.95
707040	White	3000 K	2880 lm	33.0 W	€ 183.95
707043	Black	4000 K	2660 lm	33.0 W	€ 183.95
707057	Silver	4000 K	2700 lm	33.0 W	€ 183.95
707042	White	4000 K	3100 lm	34.0 W	€ 183.95



Accessories

930315	Reflector ring white for Nihal series
930316	Reflector ring black for Nihal series
930365	Reflector ring silver for Nihal series
930317	Reflector ring gold for Nihal series
930311	Side cover white for Nihal series
930312	Side cover black for Nihal series
930363	Side cover silver for Nihal series
930313	Side cover gold for Nihal series
930314	Side cover walnut wood look for Nihal series
930769	Side cover natural oak wood look for Nihal series
930318	15° reflector for Nihal series
930320	50° reflector for Nihal series
930321	Honeycomb filter for Nihal series
930322	Spread lens for Nihal 37° series
930323	Softening lens for Nihal 37° series
930324	Linear spread lens for Nihal 40°/80° series

	€ 3.95
	€ 3.95
	€ 3.95
	€ 3.95
	€ 4.95
	€ 4.95
	€ 4.45
	€ 4.95
	€ 6.45
	€ 6.45
	€ 13.95
	€ 13.95
	€ 8.95
	€ 8.95
	€ 8.95
	€ 8.95




NIHAL MINI

- Can be rotated and swivelled
- Large tilt angle

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Trade fair construction / shop fitting

Housing	Aluminium	Power Supply Unit incl.	Yes
Length	94 mm	Light Beam Angle	35 Degree
Width	102 mm	Swivelling Angle	180 Degree
Height	139 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	60 mm	CRI (Ra)	90
Power	15 W		
Rated Input Voltage	220-240 V/AC		



707036

Article	Housing Color	Colour Temperature	Luminous Flux	Price
707037	Black	3000 K	1080 lm	€ 141.95
707054	Silver	3000 K	1100 lm	€ 141.95
707036	White	3000 K	1240 lm	€ 141.95
707039	Black	4000 K	1160 lm	€ 141.95
707055	Silver	4000 K	1190 lm	€ 141.95
707038	White	4000 K	1330 lm	€ 141.95



Accessories

930301	Reflector ring white for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930302	Reflector ring black for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930303	Reflector ring gold for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930297	Side cover white for Nihal Mini series		€ 3.25
930298	Side cover black for Nihal Mini series		€ 3.25
930364	Side cover silver for Nihal Mini series		€ 2.95
930299	Side cover gold for Nihal Mini series		€ 3.25
930300	Side cover walnut wood look for Nihal Mini series		€ 4.95
930768	Side cover natural oak wood look for Nihal Mini series		€ 4.75
930306	48° reflector for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930307	Honeycomb filter for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930308	Spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930309	Softening lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930310	Linear spread lens for Klara/Nihal Mini/Rigel Mini/Uni II series		€ 6.95
930366	Reflector ring silver for Klara/Nihal Mini/Rigel Mini/Can series		€ 3.95
930767	12° lens for Nihal Mini series		€ 8.95



RF-SMART EVENTUS THREE-PHASE SPOT RGB+CCT

The RF-SMART EVENTUS 3-PHASE SPOT RGB+CCT is an intelligent LED spotlight for 3-phase track that combines coloured accent light and precise white light control in a single luminaire. With RGB+CCT technology, ZigBee 3.0, RF-SMART control and up to 16 million colours, it is ideal for modern lighting scenarios in commercial, hospitality and event areas.





RF-SMART EVENTUS THREE-PHASE SPOT RGB+CCT

- rotatable and swivelling
- brightness and colour saturation dimmable
- RGB 3x 6W (max. 18W), CW/WW 2x 30W (max. 30W), max. total output 30W
- 16 million colours and colour temperature adjustable
- 18 automatic programmes pre-installed
- program and remote control synchronisation when operating multiple RF-smart components [repeater function]
- opt. controllable with RF-smart radio remote controls [2.4Ghz, range approx. 30 m]
- controllable with all Zigbee 3.0 compatible controllers / apps such as Amazon Echo [Alexa], Google Assistant, Tuya [corresponding gateway required, outdoor range up to 100 m]

Housing	Plastic, Metal	Rated Input Voltage	100-240 V/AC
Surface	Powder-coated, Fine structure, Matt	Power Supply Unit incl.	Yes
Colour Temperature	2700-6000 K	Light Beam Angle	36 Degree
Luminous Flux	1800 lm	Rotation Angle	350 Degree
Length	205 mm	Swivelling Angle	90 Degree
Width	76 mm	Control	RF-Smart, ZigBee 3.0
Height	246 mm	CRI (Ra)	90
Power	30 W	Light Direction	Front

Article	Housing Color		Price
843530	White	RGB WW CW	€ 159.95
843531	Black	RGB WW CW	€ 159.95



Accessories

843510	RF-smart, remote control, white, 1 zone, RGB/RGBW/RGB+CCT, IP20		€ 30.95
843511	RF-smart, remote control, black, 1 zone, RGB/RGBW/RGB+CCT, IP20		€ 30.95
843512	RF-smart, remote control, black, 8 zones, single/CCT/RGB/RGBW/RGB+CCT		€ 39.95
843525	RF-smart, Standard Remote, black, 3 zones, Single/CCT/RGB/RGBW/RGB+CCT		€ 39.95
843513	RF-smart, wall remote control, white, 3 V, 4 zones, single/CCT/RGB/W/+CCT		€ 55.95
843522	RF-smart, wall remote control, white, 230 V, 4 zones, single/CCT/RGB/W/+CCT		€ 59.95
843514	RF-smart, wall remote control, white, 8 zones, single/CCT/RGB/RGBW/RGB+CCT		€ 87.95
843527	RF-smart, PIR motion detector, white, 120deg/7m, 3V		€ 30.95
843529	RF-smart, DMX-Gateway, 5V DC, 16 Zonen Single/CCT/RGB/W+CCT		€ 47.95

LUCEA

The LUCEA series includes pendant, ceiling and track luminaires and impresses with its timeless design and flexible customisation options.



lenses

Depending on the model, you can narrow or widen the beam angle of the LUCEA luminaires using the easily replaceable lenses.

reflector rings

With the reflector rings [available for all models in black, white and gold], you can set colourful accents depending on the surroundings and atmosphere.

door panels

With the optional barn door trim, you can limit the light emission of the LUCEA luminaires with particular precision using four individually adjustable wings.

LUCEA-VARIETY

surface-mounted lights

The LUCEA surface-mounted luminaires are available as pendant luminaires, as swivelling and tilting ceiling luminaires with a base and as fixed spotlights.




1-phase luminaires

The pendant luminaires with a particularly soft textile cable and the spotlights for use on single-circuit track systems are primarily aimed at private users looking for a slim and versatile solution for the home.




3-phase luminaires

The LUCEA luminaires for 3-phase 230V track systems are available as ceiling and pendant versions and, thanks to the CCT dip switch, are particularly suitable for commercial use in bars, restaurants or offices.



FLEXIBLE COLOUR TEMPERATURE


The colour temperature has a decisive influence on the lighting effect in the room. For this reason, the LUCEA series is available in different colour temperatures, depending on the model and intended use. With an Ra value >90, the LUCEA luminaires also guarantee true-to-life colour rendering of walls, ceilings and objects. Using the LUCEA ceiling light as an example, you can see in the illustrations below how the light colour and lighting mood change depending on the model version - from warm white to neutral white and as a flexible dim-to-warm version.



dim-to-warm


[1,800K - 2.700K]

In the dim-to-warm version, the colour temperature adjusts automatically when dimming [the lower the light intensity, the warmer the colour temperature].




2,700 K

For private users: the lights with extra warm white 2,700K.



3,000 K

For commercial applications: The surface-mounted and 3-phase luminaires offer a CCT dip switch to switch between 3,000K [warm white] and 4,000K [neutral white].




4,000 K



In addition to the CCT versions, the 3-phase spotlights with 40W are also available as a pure 4,000K [neutral white] version.

FLEXIBLE BEAM ANGLE


Wide, soft light or a precise, focussed spot – with the LUCEA series you have the choice, even retrospectively. In addition to the standard beam angle of 36°, the luminaires can be narrowed or widened in all versions (surface-mounted, pendant, track) using optionally available lenses. You are even more flexible with the optional, colour-matching barn door cover. With its four wings, the light emission can be adapted to different room and object geometries. The illustrations below show how the light emission of the LUCEA changes through the use of different lenses and the barn door.





24°
narrow beam angle with optional 24° lens



36°
standard beam angle with 36° lens [standard]



60°
wide beam angle with optional 60° lens



door panels

individual limitation of the beam angle with the wings of the barn door panel




LUCEA DALI

- emergency current capable [176-280V/DC EOFI: 100%]
- incl. black reflector ring

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Trade fair construction / shop fitting

Housing	Aluminium	EOFI	100 %
Colour Temperature	2700 K	Power Supply Unit incl.	Yes
Luminous Flux	1300 lm	Pendulum Length	1600 mm
Length	65 mm	Light Beam Angle	36 Degree
Width	65 mm	Control	DALI 2 / DT6, Push-Dim
Height	157 mm	CRI (Ra)	90
Power	10 W	IK Protection Class	IK03
Rated Input Voltage	200-240 V/AC		
Voltage range emergency lighting	176-280 V/DC		



Article	Housing Color	Price
707244	White	€ 119.95
707245	Black	€ 119.95



Accessories

930679	Lens 24° for Lucea 6/10	€ 7.95
930756	Reflector ring for Lucea 6/10 white	€ 3.95
930757	Reflector ring for Lucea 6/10 black	€ 3.95
930758	Reflector ring for Lucea 6/10 gold	€ 3.95






LUCEA CCT DALI

- emergency current capable [176-280V/DC EOFI: 100%]
- light colour adjustable in two stages
- incl. black reflector ring

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Trade fair construction / shop fitting

Housing	Aluminium	Pendulum Length	1600 mm
Colour Temperature	3000/4000 K	Light Beam Angle	36 Degree
Rated Input Voltage	200-240 V/AC	Control	DALI 2 / DT6, Push-Dim
Voltage range emergency lighting	176-280 V/DC	CRI (Ra)	90
EOFI	100 %	IK Protection Class	IK03
Power Supply Unit incl.	Yes		



707234

Article	Housing Color		Luminous Flux	Length	Width	Height	Power	Price
707234	White		930/1000 lm	65 mm	65 mm	157 mm	11.0 W	€ 123.95
707235	Black		930/1000 lm	65 mm	65 mm	157 mm	11.0 W	€ 123.95
707238	White		1930/2000 lm	85 mm	85 mm	178 mm	20.0 W	€ 159.95
707239	Black		1930/2000 lm	85 mm	85 mm	178 mm	20.0 W	€ 159.95



Accessories for 707234, 707235

930679	Lens 24° for Lucea 6/10		€ 7.95
930756	Reflector ring for Lucea 6/10 white		€ 3.95
930757	Reflector ring for Lucea 6/10 black		€ 3.95
930758	Reflector ring for Lucea 6/10 gold		€ 3.95

Accessories for 707238, 707239

930680	Lens 24° for Lucea 15/20		€ 9.95
930681	Lens 60° for Lucea 15/20		€ 9.95
930759	Reflector ring for Lucea 15/20 white		€ 4.75
930760	Reflector ring for Lucea 15/20 black		€ 4.75
930761	Reflector ring for Lucea 15/20 gold		€ 4.75




LUCEA CCT

- Light colour adjustable in two stages
- Incl. black reflector ring

Application Area
 Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Trade fair construction / shop fitting

Housing	Aluminium	Light Beam Angle	36 Degree
Colour Temperature	3000/4000 K	Control	Leading-edge dimmer, Trailing-edge dimmer
Rated Input Voltage	220-240 V/AC	CRI (Ra)	90
Power Supply Unit incl.	Yes	IK Protection Class	IK03
Pendulum Length	1800 mm		



707124

Article	Housing Color	Luminous Flux	Height	Ø	Power	Price
707124	White	930/1000 lm	157 mm	65 mm	10.0 W	€ 119.95
707125	Black	930/1000 lm	157 mm	65 mm	10.0 W	€ 119.95
707128	White	1930/2000 lm	178 mm	85 mm	20.0 W	€ 151.95
707129	Black	1930/2000 lm	178 mm	85 mm	20.0 W	€ 151.95



Accessories for 707124, 707125		
930679	Lens 24° for Lucea 6/10	€ 7.95
930756	Reflector ring for Lucea 6/10 white	€ 3.95
930757	Reflector ring for Lucea 6/10 black	€ 3.95
930758	Reflector ring for Lucea 6/10 gold	€ 3.95
Accessories for 707128, 707129		
930680	Lens 24° for Lucea 15/20	€ 9.95
930681	Lens 60° for Lucea 15/20	€ 9.95
930759	Reflector ring for Lucea 15/20 white	€ 4.75
930760	Reflector ring for Lucea 15/20 black	€ 4.75
930761	Reflector ring for Lucea 15/20 gold	€ 4.75






LUCEA DTW

- high colour rendering
- Dim-to-warm 1,800K-2,700K
- incl. black reflector ring

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	1800-2700 K	Pendulum Length	1800 mm
Luminous Flux	750 lm	Light Beam Angle	36 Degree
Height	157 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	65 mm	CRI (Ra)	90
Power	10 W	IK Protection Class	IK03
Rated Input Voltage	200-240 V/AC		



707217

Article	Housing Color	Price
707217	White	€ 108.95
707218	Black	€ 108.95



Accessories

930756	Reflector ring for Lucea 6/10 white	€ 3.95
930757	Reflector ring for Lucea 6/10 black	€ 3.95
930758	Reflector ring for Lucea 6/10 gold	€ 3.95



5-year guarantee

Benefit from the maximum quality promise:

All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.




LUCEA DALI

- emergency current capable [176-280V/DC EOFI: 100%]
- incl. black reflector ring
- can be customised with a wide range of accessories

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Trade fair construction / shop fitting

Housing	Aluminium	Swivelling Angle	90 Degree
Length	113 mm	Control	DALI 2 / DT6, Intelli Push-Dim
Rated Input Voltage	200-240 V/AC	CRI (Ra)	90
Power Supply Unit incl.	Yes	IK Protection Class	IK03
Light Beam Angle	36 Degree		
Rotation Angle	350 Degree		



707240

Article	Housing Color	Colour Temperature	Luminous Flux	Width	Height	Power	Price
707240	White	2700 K	1950 lm	85 mm	269 mm	15.0 W	€ 127.95
707241	Black	2700 K	1950 lm	85 mm	269 mm	15.0 W	€ 127.95
707242	White	4000 K	4480 lm	100 mm	315 mm	40.0 W	€ 171.95
707243	Black	4000 K	4480 lm	100 mm	315 mm	40.0 W	€ 171.95



Accessories for **707240, 707241**

930680	Lens 24° for Lucea 15/20		€ 9.95
930681	Lens 60° for Lucea 15/20		€ 9.95
930754	Door panel for Lucea 15/20 white		€ 18.95
930755	Door panel for Lucea 15/20 black		€ 18.95
930759	Reflector ring for Lucea 15/20 white		€ 4.75
930760	Reflector ring for Lucea 15/20 black		€ 4.75
930761	Reflector ring for Lucea 15/20 gold		€ 4.75

Accessories for **707242, 707243**

930677	Door panel for Lucea 30/40 white		€ 19.95
930678	Door panel for Lucea 30/40 black		€ 19.95
930682	Lens 24° for Lucea 30/40		€ 12.95
930684	Lens 60° for Lucea 30/40		€ 12.95
930762	Reflector ring for Lucea 30/40 white		€ 5.45
930763	Reflector ring for Lucea 30/40 black		€ 5.45
930764	Reflector ring for Lucea 30/40 gold		€ 5.45




LUCEA CCT DALI

- emergency current capable [176-280V/DC EOFI: 100%]
- light colour adjustable in 2 shades
- incl. black reflector ring
- can be customised with a wide range of accessories

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Trade fair construction / shop fitting

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000/4000 K	Light Beam Angle	36 Degree
Luminous Flux	2700/2900 lm	Rotation Angle	350 Degree
Length	113 mm	Swivelling Angle	90 Degree
Width	100 mm	Control	DALI 2 / DT6, Intelli Push-Dim
Height	302 mm	CRI (Ra)	90
Power	33 W	IK Protection Class	IK03
Rated Input Voltage	200-240 V/AC		



707232

Article	Housing Color		Price
707232	White	WW NW	€ 171.95
707233	Black	WW NW	€ 171.95



Accessories

- 930677 Door panel for Lucea 30/40 white
- 930678 Door panel for Lucea 30/40 black
- 930682 Lens 24° for Lucea 30/40
- 930684 Lens 60° for Lucea 30/40
- 930762 Reflector ring for Lucea 30/40 white
- 930763 Reflector ring for Lucea 30/40 black
- 930764 Reflector ring for Lucea 30/40 gold

	€ 19.95
	€ 19.95
	€ 12.95
	€ 12.95
	€ 5.45
	€ 5.45
	€ 5.45




LUCEA CCT

- Incl. black reflector ring
- Can be customised with a comprehensive range of accessories
- Light colour adjustable in two stages

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Trade fair construction / shop fitting

Housing	Aluminium	Swivelling Angle	90 Degree
Colour Temperature	3000/4000 K	Control	Leading-edge dimmer, Trailing-edge dimmer
Rated Input Voltage	220-240 V/AC	CRI (Ra)	90
Power Supply Unit incl.	Yes	IK Protection Class	IK03
Light Beam Angle	36 Degree		
Rotation Angle	350 Degree		



707116

Article	Housing Color		Luminous Flux	Height	Ø	Power	Price
707116	 White		930/1000 lm	249 mm	65 mm	10.0 W	€ 111.95
707117	 Black		930/1000 lm	249 mm	65 mm	10.0 W	€ 111.95
707118	 White		1460/1500 lm	269 mm	85 mm	15.0 W	€ 127.95
707119	 Black		1460/1500 lm	269 mm	85 mm	15.0 W	€ 127.95
707120	 White		1930/2000 lm	269 mm	85 mm	20.0 W	€ 143.95
707121	 Black		1930/2000 lm	269 mm	85 mm	20.0 W	€ 143.95
707122	 White		2700/2900 lm	302 mm	100 mm	30.0 W	€ 159.95
707123	 Black		2700/2900 lm	302 mm	100 mm	30.0 W	€ 159.95



Technical data sheet

New in the onlineshop: The technical data sheets offer even more information: Light and energy data, light distribution curves, dimensional drawings and more.

Accessories for **707116, 707117**

- 930679** Lens 24° for Lucea 6/10
930752 Door panel for Lucea 6/10 white
930753 Door panel for Lucea 6/10 black
930756 Reflector ring for Lucea 6/10 white
930757 Reflector ring for Lucea 6/10 black
930758 Reflector ring for Lucea 6/10 gold

	€ 7.95
	€ 17.95
	€ 17.95
	€ 3.95
	€ 3.95
	€ 3.95

Accessories for **707118, 707119, 707120, 707121**

- 930680** Lens 24° for Lucea 15/20
930681 Lens 60° for Lucea 15/20
930754 Door panel for Lucea 15/20 white
930755 Door panel for Lucea 15/20 black
930759 Reflector ring for Lucea 15/20 white
930760 Reflector ring for Lucea 15/20 black
930761 Reflector ring for Lucea 15/20 gold

	€ 9.95
	€ 9.95
	€ 18.95
	€ 18.95
	€ 4.75
	€ 4.75
	€ 4.75

Accessories for **707122, 707123**

- 930677** Door panel for Lucea 30/40 white
930678 Door panel for Lucea 30/40 black
930682 Lens 24° for Lucea 30/40
930684 Lens 60° for Lucea 30/40
930762 Reflector ring for Lucea 30/40 white

	€ 19.95
	€ 19.95
	€ 12.95
	€ 12.95
	€ 5.45



page 26



page 60



page 62



page 296



page 400






LUCEA

- Incl. black reflector ring
- Can be customised with a comprehensive range of accessories

Application Area
Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Trade fair construction / shop fitting

Housing	Aluminium	Light Beam Angle	36 Degree
Colour Temperature	4000 K	Rotation Angle	350 Degree
Luminous Flux	4480 lm	Swivelling Angle	90 Degree
Height	211 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	100 mm	CRI (Ra)	90
Power	40 W	IK Protection Class	IK03
Rated Input Voltage	200-240 V/AC		
Power Supply Unit incl.	Yes		



707183

Article	Housing Color	Price
707183	White	€ 159.95
707184	Black	€ 159.95



Accessories

930682	Lens 24° for Lucea 30	€ 12.95
930684	Lens 60° for Lucea 30	€ 12.95
930677	Door panel for Lucea 30/40 white	€ 19.95
930678	Door panel for Lucea 30/40 black	€ 19.95
930762	Reflector ring for Lucea 30/40 white	€ 5.45
930763	Reflector ring for Lucea 30/40 black	€ 5.45
930764	Reflector ring for Lucea 30/40 gold	€ 5.45




LUCEA DTW

- Dim-to-warm 1,800K - 2,700K
- incl. black reflector ring
- Can be customised with a wide range of accessories

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	1800-2700 K	Light Beam Angle	36 Degree
Luminous Flux	750 lm	Control	Leading-edge dimmer, Trailing-edge dimmer
Height	249 mm	CRI (Ra)	90
Ø	65 mm	IK Protection Class	IK03
Power	10 W		
Rated Input Voltage	200-240 V/AC		



Article	Housing Color		Price
707213	White	ww	€ 87.95
707214	Black	ww	€ 87.95



Accessories

930752	Door panel for Lucea 6/10 white		€ 17.95
930753	Door panel for Lucea 6/10 black		€ 17.95
930756	Reflector ring for Lucea 6/10 white		€ 3.95
930757	Reflector ring for Lucea 6/10 black		€ 3.95
930758	Reflector ring for Lucea 6/10 gold		€ 3.95



page 26

page 60

page 62

page 400




SLIM

- Extra-soft fabric cable
- Glare-free due to low UGR value [<19]
- Suspended mounting up to 1,800 mm
- Slim design at just 39 mm in diameter

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	2700 K	Pendulum Length	1500 mm
Luminous Flux	500 lm	Light Beam Angle	24 Degree
Height	300 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	39 mm	CRI (Ra)	90
Power	5 W		
Rated Input Voltage	220-240 V/AC		



707162

Article	Housing Color	Price
707161	Black	€ 74.95
707162	White	€ 74.95



Accessories

930744	Reflector ring white for Slim series		€ 3.95
930745	Reflector ring black for Slim series		€ 3.95
930746	Reflector ring gold-coloured for Slim series		€ 4.75
930747	24° lens for Slim series		€ 3.95
930749	60° lens for Slim series		€ 3.95
930748	36° lens for Slim series		€ 3.95






SLIM

- glare-free, thanks to low UGR value [<19]
- slim design with a diameter of only 39 mm
- incl. silver-coloured reflector ring

Application Area

Home / Living, Reception / Communication, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	2700 K	Light Beam Angle	36 Degree
Luminous Flux	500 lm	Rotation Angle	330 Degree
Height	213 mm	Swivelling Angle	60 Degree
Ø	39 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Power	5 W	CRI (Ra)	90
Rated Input Voltage	220-240 V/AC		



707203

Article	Housing Color		Price
707203	White	WW	€ 65.95
707204	Black	WW	€ 65.95



Accessories


930744	Reflector ring white for Slim series		€ 3.95
930745	Reflector ring black for Slim series		€ 3.95
930746	Reflector ring gold-coloured for Slim series		€ 4.75
930747	24° lens for Slim series		€ 3.95
930748	36° lens for Slim series		€ 3.95
930749	60° lens for Slim series		€ 3.95






414 battery lights

BATTERY LIGHTS



battery and solar lights



page 414



page 416





CANIS SET

Discover our portable cordless LED lamps from the CANIS series. With a 3.5 W output and 270 lm of brightness, our lamps provide a particularly wide and pleasant light distribution. And the infinitely variable dimming function allows you to set the perfect illumination using the practical touch sensor. Choose from two light colour levels to create the perfect atmosphere. And the best part? One battery charge is enough for more than eight hours of lighting. You can charge up to six lamps at the same time with the optional charging dock, so you always have enough lights to hand. Choose from eight colours, including trendy pastel tones, to reflect your personal style.

Note: Includes USB charging base





CANIS SET


- Pleasant and wide light distribution
- More than eight hours of light after charging
- Infinitely dimmable via touch sensor
- Light colour adjustable in two stages
- Charge up to six cordless lamps using the stackable charging dock [optional]
- Includes USB charging base

Application Area

Garden / Terrace / Balcony / Walkways, Reception / Communication, Home / Living, Hotel / catering

Housing	Aluminium	Ø	112 mm
Surface	Matt	Power	3.5 W
Colour Temperature	2200/3000 K	Rated Input Voltage	3.7 V/DC
Luminous Flux	270 lm	Light Beam Angle	100 Degree
Height	370 mm	CRI (Ra)	80

Article	Housing Color		Price
620194	 Sand		€ 87.95
620195	 Green		€ 87.95
620196	 Terracotta		€ 87.95
620197	 Blue		€ 87.95
620198	 Rust		€ 87.95
620199	 White		€ 87.95
620200	 Black		€ 87.95
620201	 Dark grey		€ 87.95



Accessories

- 930716** 6-way charging station incl. power supply for Canis light
- 930887** USB-A plug-in power supply 5 V DC, 1,000 mA, black



€ 159.95

€ 6.95



CANIS MINI SET

Discover our portable cordless LED lamps from the CANIS series. With a 2.3 W output and 110 lm of brightness, our lamps provide a particularly wide and pleasant light distribution. And the infinitely variable dimming function allows you to set the perfect illumination using the practical touch sensor. Choose from two light colour levels to create the perfect atmosphere. And the best part? One battery charge is enough for more than eight hours of lighting. You can charge up to 15 lamps at the same time with the optional charging station, so you always have enough lights to hand. Choose from eight colours, including trendy pastel tones, to reflect your personal style.

Note: Includes USB charging base





CANIS MINI SET


- Pleasant and wide light distribution
- More than eight hours of light after charging
- Infinitely dimmable using touch sensor
- Light colour adjustable in two stages
- Charge up to 15 cordless lamps using the stackable charging dock [optional]
- Includes USB charging base

Application Area

Garden / Terrace / Balcony / Walkways, Reception / Communication, Home / Living, Hotel / catering

Housing	Aluminium	Ø	76 mm
Surface	Matt	Power	2.3 W
Colour Temperature	2200/3000 K	Rated Input Voltage	3.7 V/DC
Luminous Flux	110 lm	Light Beam Angle	100 Degree
Height	208 mm	CRI (Ra)	80

Article	Housing Color	Price
620202	Sand	€ 79.95
620203	Green	€ 79.95
620204	Terracotta	€ 79.95
620205	Blue	€ 79.95
620206	Rust	€ 79.95
620207	White	€ 79.95
620208	Black	€ 79.95
620209	Dark grey	€ 79.95



Accessories

- 930734** 15-way charging station incl. power supply unit for Canis Mini light
- 930887** USB-A plug-in power supply 5 V DC, 1,000 mA, black




€ 239.95

€ 6.95




OUTDOOR LIGHTS

- 422 bollard lights
- 442 surface mounted wall lights
- 484 ceiling and wall lights
- 488 built in wall lights
- 494 spherical lamps
- 498 energy distributor
- 508 surface mounted / ground spike lights
- 520 wall washer
- 524 ground recessed lights
- 540 floodlight
- 544 display lights



bollard lights



page 422



page 424



page 427



page 428



page 430



page 432



page 434



page 436



page 438





FACADO 2 ROUND

Our FACADO series bollard lights feature IP65 degree of protection for excellent weather resistance. Choose between an opal diffuser or a transparent diffuser with smoked glass to suit your requirements. The series is available in two different sizes (650 mm/1,000 mm) and features an E27 socket for replaceable lamps. The newly designed lamp head provides significantly improved illumination. The FACADO light is made of high-quality, die-cast aluminium and is available in dark grey or rust and in square or round designs. The IP67 connection box features a double M20 cable gland suitable for e.g. buried cables in sizes 3x1.5 mm², 5x1.5 mm² or 3x2.5 mm².





FACADO 2 ROUND

- IP65 weather resistance
- IP67 connection box suitable for e.g. buried cables 3x1.5 mm²/5x1.5 mm²/3x2.5 mm²
- Newly designed lamp head for improved illumination
- Available with an opal diffuser or a transparent diffuser with smoked glass
- Ideal for e.g. ST64 bulbs and A60/70 bulbs

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Home / Living, Hotel / catering

Housing	Aluminium, Polycarbonate	Rated Input Voltage	220-240 V/AC
Surface	Matt	Control	Dimmable via optional light source
Ø	108 mm	IK Protection Class	IK05
Max. Power	1x max. 20 W		

Article	Housing Color	Height	Colour of Light Output	Price
730499	 Dark grey	650 mm	Smoke-coloured	€ 119.95
730501	 Rust	650 mm	Smoke-coloured	€ 119.95
730500	 Dark grey	650 mm	White	€ 119.95
730502	 Rust	650 mm	White	€ 119.95
730503	 Dark grey	1000 mm	Smoke-coloured	€ 159.95
730505	 Rust	1000 mm	Smoke-coloured	€ 159.95
730504	 Dark grey	1000 mm	White	€ 159.95
730506	 Rust	1000 mm	White	€ 159.95



Accessories

931098 Cable gland PG/M20 incl. locknut + sealing ring, IP68



€ 1.75



FACADO 2 SQUARE

Our FACADO series bollard lights feature IP65 degree of protection for excellent weather resistance. Choose between an opal diffuser or a transparent diffuser with smoked glass to suit your requirements. The series is available in two different sizes (650 mm/1,000 mm) and features an E27 socket for replaceable lamps. The newly designed lamp head provides even better illumination. The FACADO light is made from high-quality die-cast aluminium and available in dark grey and in square or rounded designs.

The IP67 connection box features a double M20 cable gland suitable for buried cables in sizes 3 × 1.5 mm², 5 × 1.5 mm² or 3 × 2.5 mm², and more.





FACADO 2 SQUARE

- IP65 weather resistance
- IP67 connection box suitable for e.g. buried cables 3x1.5 mm²/5x1.5 mm²/3x2.5 mm²
- Newly designed lamp head for improved illumination
- Available with an opal diffuser or a transparent diffuser with smoked glass
- Ideal for e.g. ST64 bulbs and A60/70 bulbs

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Home / Living, Hotel / catering

Housing	Aluminium, Polycarbonate	Max. Power	1x max. 20 W
Surface	Matt	Rated Input Voltage	220-240 V/AC
Length	108 mm	Control	Dimmable via optional light source
Width	108 mm	IK Protection Class	IK05

Article	Housing Color	Height	Colour of Light Output	Price
730496	Dark grey	650 mm	Smoke-coloured	€ 119.95
730495	Dark grey	650 mm	White	€ 119.95
730497	Dark grey	1000 mm	Smoke-coloured	€ 159.95
730498	Dark grey	1000 mm	White	€ 159.95



Accessories

931098 Cable gland PG/M20 incl. locknut + sealing ring, IP68




€ 1.75



FARO – POWERFUL, ROBUST AND EFFICIENT

FARO features a specially developed optical system that provides exceptionally wide and uniform light distribution. This minimizes shadows directly beneath the luminaire and allows large areas to be illuminated efficiently with fewer fixtures. Its robust, impact-resistant and seawater-resistant construction makes FARO the ideal solution for parks, coastal areas and other demanding environments. An optional ground spike enables flexible installation wherever permanent cabling or concrete foundations are not possible or desired. The highly shielded optical system directs more than 98% of the light downward, reducing light pollution while ensuring highly efficient area illumination.






FARO ON/OFF

- Glare-free, downward-directed light [>98 %]
- Lens optics for wide homogeneous illumination with a diameter of up to 6 / 8 / 12 m
- IP68 connection box with through-wiring
- Particularly high-quality and solid construction
- Dirt-repellent powder coating in DB703
- Suitable for emergency lighting [180–264 V/DC EOFI: 100%]
- Seawater-resistant


Application Area

Garden / Terrace / Balcony / Walkways, Park / public outdoor area, Object lighting / architecture

Housing	Aluminium	Power	12 W
Colour Temperature	3000 K	Rated Input Voltage	180-264 V/AC
Luminous Flux	570 lm	Power Supply Unit incl.	Yes
Ø	100 mm	CRI (Ra)	80
Base Height	60 mm	IK Protection Class	IK10
Base Ø	90 mm		



Article	Housing Color		730519	Price
			Height	
730519	Dark grey WW		330 mm	€ 219.95
730520	Dark grey WW		600 mm	€ 239.95
730521	Dark grey WW		1000 mm	€ 279.95



Accessories

- 931192 Concrete anchor for Faro 100mm series
- 931193 Ground spike for Faro 100mm series
- 931099 Cable gland PG/M25 incl. locknut + sealing ring, IP68



- € 15.95
- € 21.95
- € 2.25



FARO DALI

The solid FARO bollard lights made from die-cast aluminium are available in the sizes 25, 60 and 100 cm. Their design [more than 98 % of light directed downwards] and lens optics allow glare-free light distribution and a particularly large light beam of up to 10 metres in diameter. All variants are also DALI2 DT6 compatible. The FARO models can be equipped with an optional screening shade to illuminate surfaces on one side only. The IP68 connection box with possible feed-through wiring and the dirt-repellent powder coating in DB703 make the FARO bollard lights a long-lasting and high-quality choice for your outdoor lighting.






FARO DALI

- Glare-free, light directed downwards [>98 %]
- Lens optics for wide homogeneous illumination with up to 5 / 8 / 12 m diameter
- Optional screening shade for darkening on one side
- IP68 connection box with feed-through wiring
- Particularly high-quality and solid construction
- Dirt-repellent powder coating in DB703
- Emergency power capable [180-264 V/DC EOFI: 100 %]
- Seawater-resistant

Application Area


Garden / Terrace / Balcony / Walkways, Park / public outdoor area, Object lighting / architecture

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000 K	Light Beam Angle	360 Degree
Luminous Flux	1030 lm	Light Beam Angle 2	180 Degree
Ø	180 mm	Control	DALI 2 / DT6
Power	24 W	CRI (Ra)	80
Rated Input Voltage	180-264 V/AC	IK Protection Class	IK10



730492

Article	Housing Color		Height	Price
730492	Dark grey	WW	250 mm	€ 351.95
730493	Dark grey	WW	600 mm	€ 407.95
730494	Dark grey	WW	1000 mm	€ 471.95



Accessories

- 930731 Concrete anchor for Faro 180mm series
- 930776 Screening shade 180 degrees for Faro 180mm series
- 931099 Cable gland PG/M25 incl. locknut + sealing ring, IP68

	€ 19.95
	€ 7.95
	€ 2.25



LERNA

LERNA series bollard lights offer a number of advantages. The ability to adjust the light colour in 2 stages (3,000 K/4,000 K) allows you to choose the colour temperature that sets the perfect ambience. The downward orientation of the lighting also fully guarantees efficient illumination without creating light pollution. LERNA series bollard lights are available in two different sizes (600 mm and 1,000 mm). With a power rating of 7.4 W and up to 256 lm, the light itself is incredibly bright.






LERNA

- Light colour adjustable in two stages
- Light directed fully downwards to prevent light pollution

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Home / Living, Hotel / catering

Housing	Aluminium	Rated Input Voltage	200-240 V/AC
Colour Temperature	3000/4000 K	Power Supply Unit incl.	Yes
Luminous Flux	237/256 lm	Light Beam Angle	50 Degree
Length	120 mm	Light Beam Angle 2	100 Degree
Width	100 mm	CRI (Ra)	80
Power	7.4 W	IK Protection Class	IK06



733072

Article	Housing Color		Height	Price
733073	Dark grey		600 mm	€ 167.95
733072	Dark grey		1000 mm	€ 207.95



Accessories

931098 Cable gland PG/M20 incl. locknut + sealing ring, IP68



€ 1.75




Lighting design


Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.



CATA

The CATA series impresses not only as a modern path light, but also as a standalone lighting and design feature when creating outdoor spaces. The LEDs not only ensure full-surface illumination of paths and entrance areas but also inevitably draw attention to the striking frame construction. Available in three sizes, the CATA IV models can also be combined really well.






CATA

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Home / Living, Hotel / catering

Housing	Aluminium	Base Height	20 mm
Colour Temperature	3000 K	Power	4 W
Luminous Flux	350 lm	Rated Input Voltage	100-240 V/AC
Length	151 mm	Power Supply Unit incl.	Yes
Width	61 mm	Light Beam Angle	120 Degree
Base Length	145 mm	Primary Connection End	Connection box IP65
Base Width	55 mm	CRI (Ra)	80



733040

Article	Housing Color		Height	Price
733040	Dark grey		500 mm	€ 159.95
733041	Dark grey		700 mm	€ 175.95
733042	Dark grey		1000 mm	€ 191.95



5-year guarantee
Benefit from the maximum quality promise:
All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.



CHERTAN

With its extraordinary mix of materials consisting of die-cast aluminium housing and base made of weather-resistant, fibreglass-reinforced concrete, the CHERTAN outdoor standing light certainly stands apart from other models just on looks alone. With its pleasantly warm white light and light emission angle of 120°, the outdoor light is perfectly suited for decorative use in entrance areas, on paths or in the garden.

Note: As concrete is a natural product, every surface is unique and forms a distinct patina over time, depending on local conditions. It is therefore normal in wet conditions for a blotchy surface to form that disappears again when dried, yet produces an individual patina over the long-term.






CHERTAN

·Fibreglass-reinforced and weather-resistant concrete base

Application Area

Garden / Terrace / Balcony / Walkways, Hotel / catering

Housing	Aluminium	Power	13 W
Colour Temperature	3000 K	Rated Input Voltage	100-240 V/AC
Length	170 mm	Power Supply Unit incl.	Yes
Width	72 mm	Light Beam Angle	120 Degree
Base Length	160 mm	Primary Connection End	Connection box IP54
Base Width	30 mm	CRI (Ra)	90
Base Height	40 mm		



733043

Article	Housing Color	Luminous Flux	Height	Price
733043	Dark grey 	480 lm	450 mm	€ 159.95
733044	Dark grey 	530 lm	600 mm	€ 175.95
733045	Dark grey 	640 lm	1000 mm	€ 191.95



Onlineshop

You can find more information about the products in the onlineshop:
Detailed images, videos, project reports, LDT files, EPREL data sheets and more.



ORTIS

The Ortis LED bollard light cuts an excellent figure anywhere with its dark grey aluminium housing and, thanks to its IP54 certification, is suitable for flexible outdoor use in gardens, entrances and as path lighting. In addition, the Ortis has an internal slatted insert in the lamp head, which ensures a pleasant dimmed light that is directed downwards (warm white, 3,000 K).






ORTIS

·Light directed downwards, dimmed by the slatted insert

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Home / Living, Hotel / catering

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Colour Temperature	3000 K	Power Supply Unit incl.	Yes
Luminous Flux	510 lm	Light Beam Angle	360 Degree
Height	1000 mm	Primary Connection End	Connection box
Ø	120 mm	CRI (Ra)	80
Power	15.9 W	IK Protection Class	IK05



733004

Article	Housing Color		Price
733004	Dark grey	WW	€ 175.95



Technical data sheet
New in the onlineshop: The technical data sheets offer even more information: Light and energy data, light distribution curves, dimensional drawings and more.



TUCANAE

With its slim, unfussy housing design, the TUCANAE is a modern outdoor light that can be integrated almost anywhere. The 100-cm-high bollard light emits its warm white light diagonally downwards onto paths and other surfaces and, in the MOTION variant, has an integrated twilight switch with adjustable brightness threshold and operating time.






TUCANAE

- Powerful and energy saving
- Uniform illumination
- Adjustable brightness threshold and operating time [733068]

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Home / Living, Hotel / catering

Housing	Aluminium	Base Height	10 mm
Colour Temperature	3000 K	Power	18 W
Luminous Flux	2150 lm	Rated Input Voltage	110-240 V/AC
Length	206 mm	Power Supply Unit incl.	Yes
Width	180 mm	Light Beam Angle	120 Degree
Height	1000 mm	Primary Connection End	Connection box
Base Length	120 mm	CRI (Ra)	80
Base Width	180 mm		



733068

Article	Housing Color	IP Protection Type	Motion Detector	Type of Motion Detector	Price
733068	Dark grey	IP 54	Yes	Infrared	€ 234.95
733069	Dark grey	IP 65	No		€ 207.95



Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.

surface mounted wall lights



■ ■ □
page 444



■ ■ □
page 445



■ ■ □
page 446



■ ■ □
page 447



■ ■ □
page 448



■ ■ □
page 449



■ ■ □
page 450



■ ■ □
page 451



■ ■ □
page 452



■ ■ □
page 453



■ ■ □
page 454



■ ■ □
page 455



■ ■ ■
page 456



■ ■ ■
page 457



■
page 458



■
page 459



■ ■
page 460



■
page 461



■ ■ ■ ■
page 462



■ ■ ■ ■
page 463



■ ■ ■
page 464



■ ■ ■
page 464



■
page 465



■
page 465



■ ■
page 466



■ ■
page 467



■
page 468



■
page 471



■
page 472



■
page 472



■
page 474



■
page 476



■
page 477



■
page 478





■ ■
page 480

SHORELINE

The SHORELINE PRO series comprises high-quality surface-mounted wall luminaires for outdoor applications and offers maximum design flexibility for modern façade and architectural lighting. With more than a dozen versions in round or square designs, available as downlight or up/down versions, as well as selected models with replaceable GU10 light sources, the series covers a wide range of applications – from residential and commercial buildings to hotels and hospitality projects.



All luminaires are made from robust die-cast aluminium, are sea-water-resistant, and feature IP65 protection and IK08 impact resistance. The integrated technology allows the colour temperature [3,000 K / 4,000 K] to be switched directly on the luminaire, while the high-quality optics ensure precise and uniform light distribution.



These luminaires have been developed for use in coastal regions and can withstand the increased salt and humidity in the environment - ideal for outdoor areas near the sea.



The integrated CCT function enables flexible selection of the light colour between warm white and neutral white light. This allows the lighting to be optimised for different applications and environments.

SIMPLE INSTALLATION



The SHORELINE PRO series has been specifically designed for quick and safe installation and impresses with several well thought-out mounting details:

- separable mounting plate with plug-in connection for easy pre-assembly
- angled fixing screws ensure better accessibility during screw connection
- through-wiring for series mounting
- optionally available spacers enable elegant and clean surface mounting - even on uneven surfaces



ACCESSORIES FOR SHORELINE PRO

- reflector inserts: 24°, 30°, 36°, 60° [depending on model]
- covers: Slot: very narrow beam for accent lighting on the façade
Triangle: narrow beam for accent lighting and additional light in the walkway area
- spacers: for clean surface mounting on uneven surfaces







SHORELINE PRO ROUND

- continuous wiring possible
- seawater-resistant
- easy and quick installation
- separable mounting plate with plug-in connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Max. Power	1x max. 7.5 W
Height	140 mm	Rated Input Voltage	220-240 V/AC
Ø	68 mm	Control	Dimmable via optional light source
Base Length	43 mm	IK Protection Class	IK08
Base Width	55 mm	Colour of Light Output	Clear
Base Height	130 mm		

Article	Housing Color	Price
731211	Light grey	€ 71.95
731212	Dark grey	€ 71.95
731213	White	€ 71.95



Accessories

930874	Spacer for ShoreLine Pro series, light grey	****	€ 4.95
930877	Spacer for ShoreLine Pro series, dark grey	****	€ 4.95
930880	Spacer for ShoreLine Pro series, white	****	€ 4.95



SHORELINE PRO ROUND UP+DOWN

- continuous wiring possible
- seawater-resistant
- easy and quick installation
- separable mounting plate with plug-in connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Max. Power	2x max. 7.5 W
Height	158 mm	Rated Input Voltage	220-240 V/AC
Ø	68 mm	Control	Dimmable via optional light source
Base Length	43 mm	IK Protection Class	IK08
Base Width	55 mm	Colour of Light Output	Clear
Base Height	130 mm		

Article	Housing Color	Price
731214	 Light grey	€ 79.95
731215	 Dark grey	€ 79.95
731216	 White	€ 79.95



Accessories

930874	Spacer for ShoreLine Pro series, light grey	----	€ 4.95
930877	Spacer for ShoreLine Pro series, dark grey	----	€ 4.95
930880	Spacer for ShoreLine Pro series, white	----	€ 4.95




SHORELINE PRO ROUND 68

- light colour adjustable in 2 stages
- through-wiring possible
- seawater resistant
- separable mounting plate through plug connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Power	6 W
Colour Temperature	3000/4000 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	480/550 lm	Power Supply Unit incl.	Yes
Height	150 mm	Light Beam Angle	30 Degree
Ø	68 mm	Control	Trailing-edge dimmer
Base Length	43 mm	CRI (Ra)	90
Base Width	55 mm	IK Protection Class	IK08
Base Height	130 mm		



731217

Article	Housing Color	Price
731217	Light grey	€ 135.95
731218	Dark grey	€ 135.95
731219	White	€ 135.95



Accessories

930980	Cover, 68/70, line, ShoreLine Pro Series, dark grey		€ 6.45
930981	Cover, 68/70, triangular, ShoreLine Pro Series, dark grey		€ 6.45
930878	Reflector, 68/70, ShoreLine Pro Series, 30 degrees, chrome		€ 6.45
930879	Reflector, 68/70, ShoreLine Pro Series, 60 degrees, chrome		€ 6.45
930874	Spacer for ShoreLine Pro series, light grey		€ 4.95
930877	Spacer for ShoreLine Pro series, dark grey		€ 4.95
930880	Spacer for ShoreLine Pro series, white		€ 4.95




SHORELINE PRO ROUND UP+DOWN 68

- light colour adjustable in 2 stages
- through-wiring possible
- seawater resistant
- separable mounting plate through plug connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors

Application Area


Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Power	7.5 W
Colour Temperature	3000/4000 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	700/780 lm	Power Supply Unit incl.	Yes
Height	186 mm	Light Beam Angle	30 Degree
Ø	68 mm	Control	Trailing-edge dimmer
Base Length	43 mm	CRI (Ra)	90
Base Width	55 mm	IK Protection Class	IK08
Base Height	130 mm		




731220

Article	Housing Color	Price
731220	Light grey	€ 159.95
731221	Dark grey	€ 159.95
731222	White	€ 159.95



Accessories

930980	Cover, 68/70, line, ShoreLine Pro Series, dark grey	€ 6.45
930981	Cover, 68/70, triangular, ShoreLine Pro Series, dark grey	€ 6.45
930878	Reflector, 68/70, ShoreLine Pro Series, 30 degrees, chrome	€ 6.45
930879	Reflector, 68/70, ShoreLine Pro Series, 60 degrees, chrome	€ 6.45
930874	Spacer for ShoreLine Pro series, light grey	€ 4.95
930877	Spacer for ShoreLine Pro series, dark grey	€ 4.95
930880	Spacer for ShoreLine Pro series, white	€ 4.95




SHORELINE PRO ROUND 100

- light colour adjustable in 2 stages
- through-wiring possible
- seawater-resistant
- easy and quick installation
- separable mounting plate with plug-in connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Power	12 W
Colour Temperature	3000/4000 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	900/1000 lm	Power Supply Unit incl.	Yes
Height	163 mm	Light Beam Angle	36 Degree
Ø	100 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Base Length	40 mm	CRI (Ra)	92
Base Width	80 mm	IK Protection Class	IK08
Base Height	130 mm		



731196

Article	Housing Color	Price
731196	Light grey	€ 151.95
731197	Dark grey	€ 151.95
731198	White	€ 151.95



Accessories

930867	Cover, 100, line, ShoreLine Pro Series, dark grey	€ 7.95
930868	Cover, 100, triangular, ShoreLine Pro Series, dark grey	€ 7.95
930875	Reflector, 100, ShoreLine Pro Series, 36 degrees, chrome	€ 11.95
930876	Reflector, 100, ShoreLine Pro Series, 60 degrees, chrome	€ 11.95
930874	Spacer for ShoreLine Pro series, light grey	€ 4.95
930877	Spacer for ShoreLine Pro series, dark grey	€ 4.95
930880	Spacer for ShoreLine Pro series, white	€ 4.95




SHORELINE PRO ROUND UP+DOWN 100

- light colour adjustable in 2 stages
- through-wiring possible
- seawater resistant
- separable mounting plate through plug connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors

Application Area


Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Power	20 W
Colour Temperature	3000/4000 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	1700/1900 lm	Power Supply Unit incl.	Yes
Height	238 mm	Light Beam Angle	36 Degree
Ø	100 mm	Control	Trailing-edge dimmer
Base Length	40 mm	CRI (Ra)	92
Base Width	80 mm	IK Protection Class	IK08
Base Height	130 mm		



731193

Article	Housing Color	Price
731193	Light grey	€ 207.95
731194	Dark grey	€ 207.95
731195	White	€ 207.95




Accessories

930867	Cover, 100, line, ShoreLine Pro Series, dark grey	€ 7.95
930868	Cover, 100, triangular, ShoreLine Pro Series, dark grey	€ 7.95
930875	Reflector, 100, ShoreLine Pro Series, 36 degrees, chrome	€ 11.95
930876	Reflector, 100, ShoreLine Pro Series, 60 degrees, chrome	€ 11.95
930874	Spacer for ShoreLine Pro series, light grey	€ 4.95
930877	Spacer for ShoreLine Pro series, dark grey	€ 4.95
930880	Spacer for ShoreLine Pro series, white	€ 4.95



SHORELINE PRO ROUND 140


- light colour adjustable in 2 stages
- through-wiring possible
- seawater resistant
- separable mounting plate through plug connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors



Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Colour Temperature	3000/4000 K	Power Supply Unit incl.	Yes
Height	218 mm	Light Beam Angle	36 Degree
Ø	140 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Base Length	40 mm	CRI (Ra)	92
Base Width	80 mm	IK Protection Class	IK08
Base Height	130 mm		



731169

Article	Housing Color	Luminous Flux	Power	Price
731169	Light grey	2000/2200 lm	20.0 W	€ 207.95
731170	Dark grey	2000/2200 lm	20.0 W	€ 207.95
731171	White	2000/2200 lm	20.0 W	€ 207.95
731172	Light grey	3100/3400 lm	33.0 W	€ 239.95
731173	Dark grey	3100/3400 lm	33.0 W	€ 239.95
731174	White	3100/3400 lm	33.0 W	€ 239.95



Accessories

930869	Cover, 140, line, ShoreLine Pro Series, dark grey		€ 9.95
930870	Cover, 140, triangular, ShoreLine Pro Series, dark grey		€ 9.95
930871	Reflector, 140, ShoreLine Pro Series, 24 degrees, chrome		€ 13.95
930872	Reflector, 140, ShoreLine Pro Series, 36 degrees, chrome		€ 13.95
930873	Reflector, 140, ShoreLine Pro Series, 60 degrees, chrome		€ 13.95
930874	Spacer for ShoreLine Pro series, light grey		€ 4.95
930877	Spacer for ShoreLine Pro series, dark grey		€ 4.95
930880	Spacer for ShoreLine Pro series, white		€ 4.95



SHORELINE PRO ROUND UP+DOWN 140


- light colour adjustable in 2 stages
- through-wiring possible
- seawater resistant
- separable mounting plate through plug connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors



Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Colour Temperature	3000/4000 K	Power Supply Unit incl.	Yes
Height	332 mm	Light Beam Angle	36 Degree
Ø	140 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Base Length	40 mm	CRI (Ra)	92
Base Width	80 mm	IK Protection Class	IK08
Base Height	130 mm		





731175

Article	Housing Color	Luminous Flux	Power	Price
731175	Light grey	3100/3400 lm	31.0 W	€ 287.95
731176	Dark grey	3100/3400 lm	31.0 W	€ 287.95
731177	White	3100/3400 lm	31.0 W	€ 287.95
731178	Light grey	5100/5600 lm	54.0 W	€ 367.95
731179	Dark grey	5100/5600 lm	54.0 W	€ 367.95
731180	White	5100/5600 lm	54.0 W	€ 367.95



Accessories

930869	Cover, 140, line, ShoreLine Pro Series, dark grey	€ 9.95
930870	Cover, 140, triangular, ShoreLine Pro Series, dark grey	€ 9.95
930871	Reflector, 140, ShoreLine Pro Series, 24 degrees, chrome	€ 13.95
930872	Reflector, 140, ShoreLine Pro Series, 36 degrees, chrome	€ 13.95
930873	Reflector, 140, ShoreLine Pro Series, 60 degrees, chrome	€ 13.95
930874	Spacer for ShoreLine Pro series, light grey	€ 4.95
930877	Spacer for ShoreLine Pro series, dark grey	€ 4.95
930880	Spacer for ShoreLine Pro series, white	€ 4.95




SHORELINE PRO SQUARE 70

- light colour adjustable in 2 stages
- through-wiring possible
- seawater resistant
- separable mounting plate through plug connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Base Height	130 mm
Colour Temperature	3000/4000 K	Power	6 W
Luminous Flux	480/550 lm	Rated Input Voltage	220-240 V/AC
Length	70 mm	Power Supply Unit incl.	Yes
Width	70 mm	Light Beam Angle	30 Degree
Height	150 mm	Control	Trailing-edge dimmer
Base Length	43 mm	CRI (Ra)	90
Base Width	55 mm	IK Protection Class	IK08



731205

Article	Housing Color	Price
731205	Light grey	€ 143.95
731206	Dark grey	€ 143.95
731207	White	€ 143.95



Accessories

930980	Cover, 68/70, line, ShoreLine Pro Series, dark grey	€ 6.45
930981	Cover, 68/70, triangular, ShoreLine Pro Series, dark grey	€ 6.45
930878	Reflector, 68/70, ShoreLine Pro Series, 30 degrees, chrome	€ 6.45
930879	Reflector, 68/70, ShoreLine Pro Series, 60 degrees, chrome	€ 6.45
930874	Spacer for ShoreLine Pro series, light grey	€ 4.95
930877	Spacer for ShoreLine Pro series, dark grey	€ 4.95
930880	Spacer for ShoreLine Pro series, white	€ 4.95




SHORELINE PRO SQUARE UP+DOWN 70

- light colour adjustable in 2 stages
- through-wiring possible
- seawater resistant
- separable mounting plate through plug connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors

Application Area


Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Base Height	130 mm
Colour Temperature	3000/4000 K	Power	7.5 W
Luminous Flux	700/780 lm	Rated Input Voltage	220-240 V/AC
Length	70 mm	Power Supply Unit incl.	Yes
Width	70 mm	Light Beam Angle	30 Degree
Height	186 mm	Control	Trailing-edge dimmer
Base Length	43 mm	CRI (Ra)	90
Base Width	55 mm	IK Protection Class	IK08





731208

Article	Housing Color	Price
731208	Light grey	€ 167.95
731209	Dark grey	€ 167.95
731210	White	€ 167.95



Accessories

930980	Cover, 68/70, line, ShoreLine Pro Series, dark grey	€ 6.45
930981	Cover, 68/70, triangular, ShoreLine Pro Series, dark grey	€ 6.45
930878	Reflector, 68/70, ShoreLine Pro Series, 30 degrees, chrome	€ 6.45
930879	Reflector, 68/70, ShoreLine Pro Series, 60 degrees, chrome	€ 6.45
930874	Spacer for ShoreLine Pro series, light grey	€ 4.95
930877	Spacer for ShoreLine Pro series, dark grey	€ 4.95
930880	Spacer for ShoreLine Pro series, white	€ 4.95




SHORELINE PRO SQUARE 100

- Light colour adjustable in 2 stages
- through-wiring possible
- Seawater resistant
- separable mounting plate through plug connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Power	12 W
Colour Temperature	3000/4000 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	900/1000 lm	Power Supply Unit incl.	Yes
Length	100 mm	Light Beam Angle	36 Degree
Width	100 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Height	163 mm	CRI (Ra)	90
Base Length	40 mm	IK Protection Class	IK08
Base Width	80 mm		
Base Height	130 mm		





731202

Article	Housing Color	Price
731202	Light grey	€ 151.95
731203	Dark grey	€ 151.95
731204	White	€ 151.95



Accessories

930867	Cover, 100, line, ShoreLine Pro Series, dark grey		€ 7.95
930868	Cover, 100, triangular, ShoreLine Pro Series, dark grey		€ 7.95
930875	Reflector, 100, ShoreLine Pro Series, 36 degrees, chrome		€ 11.95
930876	Reflector, 100, ShoreLine Pro Series, 60 degrees, chrome		€ 11.95
930874	Spacer for ShoreLine Pro series, light grey		€ 4.95
930877	Spacer for ShoreLine Pro series, dark grey		€ 4.95
930880	Spacer for ShoreLine Pro series, white		€ 4.95




SHORELINE PRO SQUARE UP+DOWN 100

- light colour adjustable in 2 stages
- through-wiring possible
- seawater resistant
- separable mounting plate through plug connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors

Application Area


Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Base Height	130 mm
Colour Temperature	3000/4000 K	Power	21 W
Luminous Flux	1800/2000 lm	Rated Input Voltage	220-240 V/AC
Length	100 mm	Power Supply Unit incl.	Yes
Width	100 mm	Light Beam Angle	36 Degree
Height	238 mm	Control	Trailing-edge dimmer
Base Length	40 mm	CRI (Ra)	92
Base Width	80 mm	IK Protection Class	IK08



731199

Article	Housing Color	Price
731199	Light grey	€ 207.95
731200	Dark grey	€ 207.95
731201	White	€ 207.95





Accessories

930867	Cover, 100, line, ShoreLine Pro Series, dark grey	€ 7.95
930868	Cover, 100, triangular, ShoreLine Pro Series, dark grey	€ 7.95
930875	Reflector, 100, ShoreLine Pro Series, 36 degrees, chrome	€ 11.95
930876	Reflector, 100, ShoreLine Pro Series, 60 degrees, chrome	€ 11.95
930874	Spacer for ShoreLine Pro series, light grey	€ 4.95
930877	Spacer for ShoreLine Pro series, dark grey	€ 4.95
930880	Spacer for ShoreLine Pro series, white	€ 4.95



SHORELINE PRO SQUARE 140


- light colour adjustable in 2 stages
- through-wiring possible
- seawater resistant
- separable mounting plate through plug connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors



Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Colour Temperature	3000/4000 K	Power Supply Unit incl.	Yes
Length	140 mm	Light Beam Angle	36 Degree
Width	140 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Height	218 mm	CRI (Ra)	90
Base Length	44,5 mm	IK Protection Class	IK08
Base Width	80 mm		
Base Height	130 mm		




731181

Article	Housing Color	Luminous Flux	Power	Price
731181	Light grey	2000/2300 lm	20.5 W	€ 215.95
731182	Dark grey	2000/2300 lm	20.5 W	€ 215.95
731183	White	2000/2300 lm	20.5 W	€ 215.95
731184	Light grey	3100/3400 lm	33.0 W	€ 239.95
731185	Dark grey	3100/3400 lm	33.0 W	€ 239.95
731186	White	3100/3400 lm	33.0 W	€ 239.95




Accessories

930869	Cover, 140, line, ShoreLine Pro Series, dark grey		€ 9.95
930870	Cover, 140, triangular, ShoreLine Pro Series, dark grey		€ 9.95
930871	Reflector, 140, ShoreLine Pro Series, 24 degrees, chrome		€ 13.95
930872	Reflector, 140, ShoreLine Pro Series, 36 degrees, chrome		€ 13.95
930873	Reflector, 140, ShoreLine Pro Series, 60 degrees, chrome		€ 13.95
930874	Spacer for ShoreLine Pro series, light grey		€ 4.95
930877	Spacer for ShoreLine Pro series, dark grey		€ 4.95
930880	Spacer for ShoreLine Pro series, white		€ 4.95



SHORELINE PRO SQUARE UP+DOWN 140


- light colour adjustable in 2 stages
- through-wiring possible
- seawater resistant
- separable mounting plate through plug connection
- angled fixing screw for better installation
- opt. Spacer for surface mounting
- opt. interchangeable reflector inserts / reflectors



Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Colour Temperature	3000/4000 K	Power Supply Unit incl.	Yes
Length	140 mm	Light Beam Angle	36 Degree
Width	140 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Height	332 mm	CRI (Ra)	90
Base Length	44.5 mm	IK Protection Class	IK08
Base Width	80 mm		
Base Height	130 mm		



731187

Article	Housing Color	Luminous Flux	Power	Price
731187	Light grey	3200/3400 lm	31.5 W	€ 295.95
731188	Dark grey	3200/3400 lm	31.5 W	€ 295.95
731189	White	3200/3400 lm	31.5 W	€ 295.95
731190	Light grey	5400/5800 lm	55.0 W	€ 367.95
731191	Dark grey	5400/5800 lm	55.0 W	€ 367.95
731192	White	5400/5800 lm	55.0 W	€ 367.95



Accessories

930869	Cover, 140, line, ShoreLine Pro Series, dark grey	€ 9.95
930870	Cover, 140, triangular, ShoreLine Pro Series, dark grey	€ 9.95
930871	Reflector, 140, ShoreLine Pro Series, 24 degrees, chrome	€ 13.95
930872	Reflector, 140, ShoreLine Pro Series, 36 degrees, chrome	€ 13.95
930873	Reflector, 140, ShoreLine Pro Series, 60 degrees, chrome	€ 13.95
930874	Spacer for ShoreLine Pro series, light grey	€ 4.95
930877	Spacer for ShoreLine Pro series, dark grey	€ 4.95
930880	Spacer for ShoreLine Pro series, white	€ 4.95




ORTIS

·downward-directed light, dimmed by the louvre insert]

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, House wall / facade / front door, Home / Living, Hotel / catering

Housing	Aluminium	Base Width	77 mm
Colour Temperature	3000 K	Base Height	67 mm
Luminous Flux	510 lm	Power	15.9 W
Length	260 mm	Rated Input Voltage	220-240 V/AC
Width	120 mm	Power Supply Unit incl.	Yes
Height	181 mm	Light Beam Angle	360 Degree
Ø	120 mm	CRI (Ra)	80
Base Length	100 mm		



731031

Article	Housing Color	Price
731031	Dark grey	€ 159.95

IP54

1 CH

A
↑
G

G






TUCANAE

- Modern minimalist design
- Powerful and energy saving
- Uniform illumination
- Adjustable brightness threshold and operating time [model-dependent]

Application Area


Garden / Terrace / Balcony / Walkways, Garage / carport / car park, House wall / facade / front door, Home / Living, Hotel / catering


Housing	Aluminium	Base Width	135 mm
Colour Temperature	3000 K	Base Height	15 mm
Luminous Flux	2150 lm	Power	18 W
Length	140 mm	Rated Input Voltage	110-240 V/AC
Width	172 mm	Power Supply Unit incl.	Yes
Height	219 mm	Light Beam Angle	110 Degree
Base Length	125 mm	CRI (Ra)	80



731133

Article	Housing Color	IP Protection Type	Motion Detector	Price
731133	Dark grey	IP 54	Yes	€ 158.95
731144	Dark grey	IP 65	No	€ 148.95





FACADO 2 ROUND

- Feed-through wiring possible
- Mounting plate can be disconnected via plug
- Quick and secure installation
- IP65 weather resistance
- Newly designed lamp head for improved illumination

Application Area

Garden /Terrace / Balcony / Walkways, Garage / carport / car park, House wall / facade / front door, Home / Living, Hotel / catering

Housing	Aluminium, Polycarbonate	Base Height	104 mm
Surface	Matt	Max. Power	1x max. 20 W
Height	262 mm	Rated Input Voltage	220-240 V/AC
Ø	108 mm	Control	Dimmable via optional light source
Base Length	46 mm	IK Protection Class	IK05
Base Width	64 mm		

Article	Housing Color	Colour of Light Output	Price
731153	 Dark grey	Smoke-coloured	€ 99.95
731155	 Rust	Smoke-coloured	€ 99.95
731154	 Dark grey	White	€ 99.95
731156	 Rust	White	€ 99.95





FACADO 2 SQUARE

- Feed-through wiring possible
- Mounting plate can be disconnected via plug
- Quick and secure installation
- IP65 weather resistance
- Newly designed lamp head for improved illumination

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, House wall / facade / front door, Home / Living, Hotel / catering

Housing	Aluminium, Polycarbonate	Max. Power	1x max. 20 W
Surface	Matt	Rated Input Voltage	220-240 V/AC
Length	148 mm	Control	Dimmable via optional light source
Width	108 mm	IK Protection Class	IK05
Height	261.5 mm		

Article	Housing Color	Colour of Light Output	Price
731151	Dark grey	Smoke-coloured	€ 99.95
731157	Dark grey	White	€ 99.95





ACHERNAR

·Exchangeable lamp GU10 [retrofit]

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Hotel / catering

Housing	Aluminium	Base Height	58 mm
Height	108 mm	Max. Power	1x max. 50 W
Ø	63 mm	Rated Input Voltage	220-240 V/AC
Base Length	15 mm	Control	Dimmable via optional light source
Base Width	49 mm		

Article	Housing Color	Price
731228	 White	€ 28.95
731229	 Light grey	€ 28.95
731230	 Dark grey	€ 28.95
731130	 Black	€ 28.95





ACHERNAR UP & DOWN

·Exchangeable lamp GU10 [retrofit]


Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Hotel / catering

Housing	Aluminium	Base Height	58 mm
Height	158 mm	Max. Power	2x max. 35 W
Ø	63 mm	Rated Input Voltage	220-240 V/AC
Base Length	15 mm	Control	Dimmable via optional light source
Base Width	49 mm		

Article	Housing Color	Price
731131	Black	€ 34.95
731231	White	€ 35.95
731232	Light grey	€ 35.95
731233	Dark grey	€ 35.95






CUBODO 2


Application Area
Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Hotel / catering

Housing	Aluminium	Power	8.5 W
Colour Temperature	3000 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	600 lm	Power Supply Unit incl.	Yes
Length	108 mm	Light Beam Angle	19 Degree
Width	108 mm	CRI (Ra)	80
Height	115 mm	IK Protection Class	IK04



731026


Article	Housing Color	Price
731024	Dark grey	€ 127.95
731025	Light grey	€ 127.95
731026	White	€ 127.95



CUBODO 2 UP & DOWN

Application Area
Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Hotel / catering


Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Colour Temperature	3000 K	Power Supply Unit incl.	Yes
Luminous Flux	1300 lm	Light Beam Angle	19 Degree
Length	108 mm	Light Beam Angle 2	19 Degree
Width	108 mm	CRI (Ra)	80
Height	115 mm	IK Protection Class	IK04
Power	16 W		



731015

Article	Housing Color	Price
731015	Dark grey	€ 143.95
731019	Light grey	€ 143.95
731020	White	€ 143.95






CUBODO 2 MINI

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Hotel / catering

Housing	Aluminium	Base Width	65 mm
Colour Temperature	3000 K	Base Height	20 mm
Luminous Flux	220 lm	Power	5 W
Length	90 mm	Rated Input Voltage	220-240 V/AC
Width	68 mm	Power Supply Unit incl.	Yes
Height	70 mm	Light Beam Angle	46 Degree
Base Length	65 mm	CRI (Ra)	77



731029

Article	Housing Color	Price
731029	Dark grey 	€ 95.95




CUBODO 2 MINI UP & DOWN

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Hotel / catering

Housing	Aluminium	Base Width	65 mm
Colour Temperature	3000 K	Base Height	20 mm
Luminous Flux	440 lm	Power	9.9 W
Length	90 mm	Rated Input Voltage	220-240 V/AC
Width	68 mm	Power Supply Unit incl.	Yes
Height	108 mm	Light Beam Angle	46 Degree
Base Length	65 mm	CRI (Ra)	77



731030

Article	Housing Color	Price
731030	Dark grey 	€ 119.95





CAN IP65

The CAN IP65 surface-mounted wall light is a robust and versatile solution for outdoor areas. Available as a classic wall light and as an up/down variant with light emission on both sides, it is ideal for demanding environments. The IP65 certification guarantees protection against dust and water. The widely used GU10 base enables quick and simple replacement of the lamp. Push terminals for rigid and flexible conductors facilitate simple installation. The CAN outdoor light is part of a versatile series and is also available as a pendant, ceiling, wall and reading light.



page 30



page 68



page 70



page 382





CAN IP65



- Replaceable lamp to offer an individual lighting solution
- Can be combined with the comprehensive product family of the CAN series

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Hotel / catering

Housing	Aluminium	Base Height	87 mm
Height	108 mm	Max. Power	1x max. 7.5 W
Ø	80 mm	Rated Input Voltage	220-240 V/AC
Base Length	26 mm	Control	Dimmable via optional light source
Base Width	65 mm		

Article	Housing Color	Price
731223	 White	€ 47.95
731224	 Black	€ 47.95



CAN UP & DOWN IP65


- Replaceable lamp to offer an individual lighting solution
- Can be combined with the comprehensive product family of the CAN series

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Hotel / catering

Housing	Aluminium	Base Height	166 mm
Height	212 mm	Max. Power	2x max. 7.5 W
Ø	80 mm	Rated Input Voltage	220-240 V/AC
Base Length	26 mm	Control	Dimmable via optional light source
Base Width	65 mm		

Article	Housing Color	Price
731225	 White	€ 71.95
731226	 Black	€ 71.95





JABBAH

The square JABBAH features integrated warm white COB LEDs and projects a 75° asymmetrical cone of light onto walls with a total luminous flux of 1,850 lumens. In addition, the double-sided JABBAH can be dimmed to 60% luminous flux via a DIP switch whenever a more subtle lighting effect is desired.






JABBAH

- Feed-through wiring possible
- Mounting plate can be disconnected via plug
- Quick and secure installation
- Incl. wall spacer for surface-mounted cable entry
- Power adjustable in 2 stages (model-dependent)

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Power Selectable	13 W, 25 W
Colour Temperature	3000 K	Rated Input Voltage	220-240 V/AC
Luminous Flux	1850 lm	Power Supply Unit incl.	Yes
Length	150 mm	Light Beam Angle	75 Degree
Width	150 mm	CRI (Ra)	80
Height	150 mm		




731127

Article	Housing Color		Price
731127	 Dark grey		€ 279.95



5-year guarantee
Benefit from the maximum quality promise:
All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.






ARCTURUS

- Continuously adjustable light emission angle 0-90°
- Uplight and downlight separately adjustable
- Ideal for customised lighting accents

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Hotel / catering


Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000 K	Light Beam Angle	90 Degree
Power	6 W	CRI (Ra)	80
Rated Input Voltage	220-240 V/AC		



731099

Article	Housing Color		Luminous Flux	Length	Width	Height	Base Length	Price
731099	Dark grey	WW	200 lm	110 mm	79 mm	172 mm	68 mm	€ 87.95
731100	Dark grey	WW	208 lm	105 mm	140 mm	145 mm	75 mm	€ 87.95






LINEAR


Application Area
Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Base Height	15 mm
Colour Temperature	3000 K	Rated Input Voltage	220-240 V/AC
Width	60 mm	Power Supply Unit incl.	Yes
Height	60 mm	Light Beam Angle	100 Degree
Base Width	53 mm	CRI (Ra)	80



731135


Article	Housing Color		Luminous Flux	Length	Base Length	Power	EEL	Price
731135	Dark grey	www	600 lm	250 mm	242 mm	8.0 W	G	€ 119.95
731134	Dark grey	www	1230 lm	500 mm	493 mm	14.0 W	F	€ 155.95



LINEAR UP & DOWN

Application Area
Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Park / public outdoor area, Hotel / catering

Housing	Aluminium	Base Height	15 mm
Colour Temperature	3000 K	Rated Input Voltage	220-240 V/AC
Width	60 mm	Power Supply Unit incl.	Yes
Height	60 mm	Light Beam Angle	100 Degree
Base Width	53 mm	CRI (Ra)	80



731129

Article	Housing Color		Luminous Flux	Length	Base Length	Power	Price
731136	Dark grey	www	1155 lm	250 mm	242 mm	14.0 W	€ 147.95
731129	Dark grey	www	1760 lm	500 mm	493 mm	20.0 W	€ 171.95








RILONGO

The RILONGO surface-mounted wall light impresses with its modern, simple design and stylishly sets the scene for facades, entrance areas and patios. The light emission on both sides creates effective lighting accents on the wall, providing both orientation and a pleasant atmosphere.

Made from robust die-cast aluminium and equipped with an IP54 protection rating, the light is ideal for permanent outdoor use. The E27 socket allows a free choice of light source up to max. 15 W and therefore offers flexible options for light colour and lighting mood.





RILONGO

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, House wall / facade / front door, Home / Living

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Length	103 mm	Control	Dimmable via optional light source
Width	250 mm	IK Protection Class	IK05
Height	110 mm	Colour of Light Output	White
Max. Power	1x max. 15 W		

Article	Housing Color	light emission	Price
730330	Dark grey	top / bottom	€ 63.95
731060	Dark grey	top / bottom / front [grille]	€ 63.95
731227	Dark grey	top / bottom / front	€ 63.95



Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.



ALKES

The ALKES series is not a traditional wall-mounted light, but, with its SMD-LED panel, has floodlight similarities. The highlight: the upper housing part is tilted forwards 45° from the façade to direct the warm white light in a targeted manner onto the surface to be illuminated. In addition, the ALKES also looks great when switched off with its modern design and rounded edges.




ALKES

- high luminous efficacy
- homogeneous light distribution

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000 K	Light Beam Angle	110 Degree
Rated Input Voltage	220-240 V/AC	CRI (Ra)	80



731138

Article	Housing Color		Luminous Flux	Length	Width	Height	Power	Price
731138	Dark grey	WW	920 lm	200 mm	126 mm	184 mm	21.0 W	€ 83.95
731140	Dark grey	WW	1720 lm	297 mm	165 mm	240 mm	36.0 W	€ 140.95




ALKES MOTION

- high luminous efficacy
- homogeneous light distribution

Application Area

Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Hotel / catering

Housing	Aluminium	Light Beam Angle	110 Degree
Colour Temperature	3000 K	CRI (Ra)	80
Rated Input Voltage	220-240 V/AC	Motion Detector	Yes
Power Supply Unit incl.	Yes		



731139

Article	Housing Color		Luminous Flux	Length	Width	Height	Power	Price
731139	Dark grey	WW	735 lm	200 mm	126 mm	184 mm	21.0 W	€ 99.95
731141	Dark grey	WW	1720 lm	297 mm	165 mm	240 mm	36.0 W	€ 156.95





GRUMIUM SQUARE CCT

Modular, compact, impactful - the GRUMIUM wall-mounted light can be installed on patios, building walls or in entrances to living spaces and, due to its optional covers in different designs, provides a flexible universal solution for many areas of application. The permanently installed and energy-saving LEDs delivering max. 10 watts are encompassed by a diffuser made of milky plastic and produce a pleasant warm-white light with a luminous flux of 730 lm. The Grumium outdoor light with die-cast aluminium housing comes in an angular and rounded design and has degree of protection IP54.




GRUMIUM SQUARE CCT

· light colour adjustable in 2 stages

Application Area


Garden / Terrace / Balcony / Walkways, Garage / carport / car park, House wall / facade / front door, Home / Living

Housing	Aluminium	Base Width	15 mm
Colour Temperature	3000/4000 K	Base Height	195 mm
Length	100 mm	Power	10 W
Width	70 mm	Rated Input Voltage	220-240 V/AC
Height	200 mm	Power Supply Unit incl.	Yes
Base Length	95 mm	CRI (Ra)	80



620123


Article	Housing Color		Luminous Flux	Shape cover	Price
620124	Dark grey	WW NW	205 lm	lines diagonal	€ 91.95
620125	Dark grey	WW NW	280 lm	lines horizontally	€ 91.95
620126	Dark grey	WW NW	300 lm	lines vertical	€ 91.95
620127	Dark grey	WW NW	440 lm	upside/below	€ 91.95
620123	Dark grey	WW NW	450 lm	borders	€ 91.95
731126	Dark grey	WW NW	530 lm	without	€ 63.95



5-year guarantee

Benefit from the maximum quality promise:

All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.



CASA

The CASA house number light has space for up to four digits and/or letters each 10 cm high, ensuring house numbers can be easily read. With a configurable twilight switch, the wall light automatically adjusts to the ambient brightness. The light colour can also be adjusted in two stages (3,000 K/4,000 K).

Multiple cable entries and the option of feed-through wiring mean that installation is simple and flexible. Anti-theft protection also prevents unauthorised removal.

Note: Stickers for numbers/letters are optionally available






CASA

- Space for four digits and letters each 10 cm high
- Adjustable daylight sensor
- Adjustable light colour 3,000/4,000 K
- Multiple cable entries incl. feed-through wiring
- Easy and quick mounting with anti-theft protection
- Set of number/letter stickers optionally available


Application Area

Reception / Communication, Garden / Terrace / Balcony / Walkways, Garage / carport / car park

Surface	Matt	Power	3 W
Colour Temperature	3000/4000 K	Rated Input Voltage	200-240 V/AC
Length	275 mm	Power Supply Unit incl.	Yes
Width	275 mm	Light Beam Angle	120 Degree
Height	64 mm	CRI (Ra)	80
Base Height	14 mm	Light Direction	Front
Base Ø	245 mm	IK Protection Class	IK08



Article	Housing Color	Luminous Flux Housing	Price
731159	Black  	250/260 lm PP - Polypropylene	€ 87.95
731158	White  	270/280 lm Polycarbonate	€ 87.95




Accessories

- 930807** Numbers set 0-9 for Casa
- 930808** Letters set A-F for Casa



€ 8.95

€ 5.45




page 484



page 485

ceiling and wall lights







MOB

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Height	92 mm	Control	Dimmable via optional light source
Ø	108 mm		
Max. Power	1x max. 9 W		

Article	Housing Color	Price
730408	 Dark grey	€ 57.95



Accessories

180195	LED, GX53, 230 V/AC, 4,000 K, 120 degrees		€ 17.95
180196	LED, GX53, 230 V/AC, 3,000 K, 120 degrees		€ 17.95






MENSÆ

- Corridor function
- Adjustable motion detector [hold time / detection area]
- Daylight sensor

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, House wall / facade / front door

Housing	Aluminium	Rated Input Voltage	100-240 V/AC
Colour Temperature	3000 K	Power Supply Unit incl.	Yes
Height	54 mm	CRI (Ra)	80
Base Height	28.5 mm	Motion Detector	Yes
Base Ø	170 mm	IK Protection Class	IK08
Power	16 W		




348071


Article	Housing Color		Luminous Flux	Length	Width	Ø	Light Beam Angle	Price
348071	■ Dark grey	ww	1400 lm	300 mm	300 mm		115 Degree	€ 199.95
348072	■ Dark grey	ww	1500 lm			300 mm	110 Degree	€ 199.95



Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.



built in wall lights



page 488



page 489



page 490



page 490





LIGHT BASE 2

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Colour Temperature	3000 K	Power Supply Unit incl.	Yes
Luminous Flux	55 lm	Installation Depth	70 mm
Length	96 mm	Cut Out Length	95 mm
Width	96 mm	Cutout L x W	95 x 95 mm
Height	77 mm	Cut Out Width	95 mm
Power	1.3 W	CRI (Ra)	80

Article	Housing Color	Price
763025	 Grey 	€ 79.95





LIGHT BASE II COB OUTDOOR

Housing Aluminium Width 100 mm
Length 100 mm


Article	Housing Color	light output	Height	Price
930419	 White	stripe	8 mm	€ 16.95
930414	 Light grey	stripe	8 mm	€ 15.95
930420	 Black	stripe	8 mm	€ 15.95
930416	 White	step	24 mm	€ 15.95
930417	 Light grey	step	24 mm	€ 15.95
930418	 Black	step	24 mm	€ 15.95
930421	 White	linear	24 mm	€ 16.95
930422	 Light grey	linear	24 mm	€ 15.95
930415	 Black	linear	24 mm	€ 15.95
930413	 White	round	24 mm	€ 16.95
930423	 Light grey	round	24 mm	€ 15.95
930424	 Black	round	24 mm	€ 15.95



LIGHT BASE 3

Housing	Aluminium
Colour Temperature	3000 K
Luminous Flux	88 lm
Length	245 mm
Width	85 mm
Height	78 mm
Power	4.3 W
Rated Input Voltage	220-240 V/AC

Power Supply Unit incl.	Yes
Installation Depth	78 mm
Light Beam Angle	115 Degree
Cut Out Length	245 mm
Cutout L x W	245 x 85 mm
Cut Out Width	85 mm
CRI (Ra)	90



930461


Article	Housing Color	Price
763026	Black	€ 95.95

IP65

A
↑
G

G






LIGHT BASE III OUTDOOR


Housing Aluminium Width 90 mm
Length 250 mm

Article	Housing Color	light output	Height	Price
930470	 White	stripe	9 mm	€ 47.95
930471	 Grey	stripe	9 mm	€ 47.95
930472	 Black	stripe	9 mm	€ 47.95
930461	 White	step	24 mm	€ 47.95
930468	 Light grey	step	24 mm	€ 47.95
930469	 Black	step	24 mm	€ 47.95
930473	 White	angled	24 mm	€ 47.95
930474	 Light grey	angled	24 mm	€ 47.95
930475	 Black	angled	24 mm	€ 47.95
930476	 White	rounded	24 mm	€ 47.95
930477	 Light grey	rounded	24 mm	€ 47.95
930478	 Black	rounded	24 mm	€ 47.95



page 494

spherical lamps







DORADUS

Light in its most beautiful form - the sphere is and remains one of the most striking of shapes. With the opportunity to illuminate it from within, what could be better. The spherical light looks great both indoors and outdoors. Using a dimmable LED lamp with RGB or colour change function achieves the optimal effect. Be mesmerised with cosy red, calming green and deep blue. With a warm white lamp too, the light emanating from this spherical light is something rather special.



DORADUS

- Spherical housing with IP65 protection
- Resistant to sea water
- Ready to use with 3 m connecting cable
- Incl. ground spike

Application Area

Garden / Terrace / Balcony / Walkways, Hotel / catering

Housing	Polyethylene	Primary Connection End	Power plug IP44
Max. Power	1x max. 23 W	Control	Dimmable via optional light source
Rated Input Voltage	220-240 V/AC	IP Protection Type Plug	IP 44
Primary Cable Length	3 m		

Article	Housing Color	Height	Ø	Price
836011	☐ White	230 mm	250 mm	€ 111.95
836930	☐ White	350 mm	380 mm	€ 135.95
836014	☐ White	420 mm	450 mm	€ 159.95
836931	☐ White	530 mm	560 mm	€ 255.95




Accessories


843533	RF-smart, E27, Zigbee, 6 W, RGB+2700-6500 K, 220 Grad		€ 37.95
843510	RF-smart, remote control, white, 1 zone, RGB/RGBW/RGB+CCT, IP20		€ 30.95
843511	RF-smart, remote control, black, 1 zone, RGB/RGBW/RGB+CCT, IP20		€ 30.95
843512	RF-smart, remote control, black, 8 zones, single/CCT/RGB/RGBW/RGB+CCT		€ 39.95
843513	RF-smart, wall remote control, white, 3 V, 4 zones, single/CCT/RGB/W/+CCT		€ 55.95
843514	RF-smart, wall remote control, white, 8 zones, single/CCT/RGB/RGBW/RGB+CCT		€ 87.95
843522	RF-smart, wall remote control, white, 230 V, 4 zones, single/CCT/RGB/W/+CCT		€ 59.95

Accessories for 836931

843534	RF-smart, E27, Zigbee, 12 W, RGB+2700-6500 K, 220 Grad		€ 51.95
--------	--	--	---------



energy distributor



page 498



page 502



page 500



page 504






ARAWAN

Sometimes it's about more than just light. With our multiple socket tower, available with or without light, another gap in our range is filled. Design your garden even more flexibly, in proven DEKO-LIGHT quality of course and at a price that won't break the bank.





ARAWAN

- Safe power distribution outdoors
- Total load max. 3,680 W
- Outlets and lights can be switched on separately
- Connection box with IP67 and accessories including in scope of delivery
- Feed-through wiring possible

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Home / Living, Hotel / catering

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Ø	100 mm	Primary Connection End	Connection box IP67
Connected Load max.	3680 W		

Article	Housing Color	Colour Temperature	Luminous Flux	Height	Power	Power Supply incl.	EEI	Price
733055	 Dark grey			400 mm				€ 95.95
733054	 Dark grey	 3000 K	150 lm	478 mm	4.8 W	Yes		€ 135.95



Accessories

931098 Cable gland PG/M20 incl. locknut + sealing ring, IP68




€ 1.75



PUKA MANA

A garden is pure nature and yet needs power in several different places. With the PUKA MANA, you can flexibly access power to operate lawnmowers and other gardening tools or simply to charge your e-bike or smartphone. The multiple socket tower has two socket outlets and can be installed particularly easily using our multi-outdoor cable connectors. The sophisticated cable routing ensures a clean visual design.





PUKA MANA

- Door can be completely closed when angled plugs are plugged in
- Total load: max. 3,680 W
- Easy to install thanks to IP68 cable connector
- Light can be switched on separately [only art. no. 733067]

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Home / Living, Hotel / catering

Housing	Aluminium	Connected Load max.	3680 W
Length	100 mm	Rated Input Voltage	220-240 V/AC
Width	100 mm	Primary Connection End	Connection box IP67

Article	Housing Color	Height	Socket / Base	Max. Power	IK Protection Class	Price
733066	 Dark grey	420 mm			IK10	€ 135.95
733067	 Dark grey	620 mm	E27	1x max. 13.0 W		€ 199.95



Accessories

931098 Cable gland PG/M20 incl. locknut + sealing ring, IP68

 € 1.75

Accessories for 733066

931073 Cover for Multiple socket tower Puka Mana 420 mm


 € 7.95



FACADO SOCKET

FACADO series standing lights have been proving quite the hit for some time on paved paths in gardens. Now, the classically elegant outdoor lights are becoming that much more versatile: The FACADO SOCKET contains two electrical outlet points, serving as a practical power distributor in gardens, on patios or on paths. The lamps can also be changed thanks to the E27 base and adapted to the desired lighting atmosphere. The FACADO SOCKET is available in two heights [65 and 100 cm].





FACADO SOCKET

- Total load: max. 3,680 W
- Outlets and light can be switched on separately
- Feed-through wiring possible
- Replaceable lamp [E27]

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Home / Living, Hotel / catering

Housing	Aluminium	Max. Power	1x max. 20 W
Width	108 mm	Connected Load max.	3680 W
Height	108 mm	Rated Input Voltage	220-240 V/AC

Article	Housing Color	Length	Price
733064	 Dark grey	650 mm	€ 159.95
733065	 Dark grey	1000 mm	€ 175.95



Accessories

931098 Cable gland PG/M20 incl. locknut + sealing ring, IP68



€ 1.75



LERNA

LERNA series power distributors offer a number of advantages. With two sockets and a total load of 3,680 W, they allow you to connect various devices while providing reliable lighting. Light and sockets can be switched separately (separate L+N). The socket cover latches open for additional convenience. The ability to adjust the light colour in two stages (3,000 K/4,000 K) allows you to choose the colour temperature that sets the perfect ambience. The downward orientation of the lighting also fully guarantees efficient illumination without creating light pollution. LERNA series bollard lights are available in two different sizes (600 mm and 1,000 mm). With a output of 7,4 W and 256 lm, the light itself is incredibly bright.






LERNA

- Socket cover latches open
- Total socket output: 3,680 W
- Light colour adjustable in two stages
- Light and socket can be switched separately (separate L+N)
- Light directed fully downwards to prevent light pollution

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Home / Living, Hotel / catering

Housing	Aluminium	Rated Input Voltage	200-240 V/AC
Colour Temperature	3000/4000 K	Power Supply Unit incl.	Yes
Luminous Flux	237/256 lm	Light Beam Angle	50 Degree
Length	120 mm	Light Beam Angle 2	100 Degree
Width	100 mm	CRI (Ra)	80
Power	7.4 W	IK Protection Class	IK06
Connected Load max.	3680 W		



733071

Article	Housing Color		Height	Price
733071	Dark grey		600 mm	€ 215.95
733070	Dark grey		1000 mm	€ 247.95



Accessories

931098 Cable gland PG/M20 incl. locknut + sealing ring, IP68



€ 1.75



page 508



page 511



page 512



page 513



page 514



page 515



page 516

surface mounted / ground spike





DEKO-LIGHT RF-SMART SPOTLIGHT RGB+CCT RF + ZIGBEE

The RF-Smart SPOT spotlight with ground spike offers dimmable brightness and colour saturation, 16 million colours and adjustable colour temperatures. This spotlight has eight pre-installed automatic colour programs and the ability to synchronise with other RF-Smart components, offering maximum flexibility. Can be controlled using RF-smart wireless remote controls (2.4 GHz, range approx. 30 m, not in scope of delivery) as well as all Zigbee 3.0 compatible controllers and apps such as Amazon Echo (Alexa), Google Assistant and Tuya (appropriate gateway required). The very narrow beam angle makes it ideal for column lighting and similar applications.






DEKO-LIGHT RF-SMART SPOTLIGHT RGB+CCT RF + ZIGBEE

- Adjustable brightness and colour saturation
- 843539: RGB 3 x 3 W [max. 9 W], CW / WW 2 x 9 W [max. 9 W], max. total output 9 W
- 843521: RGB 3 x 10 W [max. 25 W], CW / WW 2 x 25 W [max. 25 W], max. total output 25 W
- 16 million available colours and adjustable colour temperature
- 18 automatic programmes pre-installed
- Program and remote control synchronisation when operating multiple RF smart components (repeater function)
- Can be controlled with RF smart wireless remote controls (2.4 GHz, range approx. 30 m, not included in the scope of delivery)
- Can be controlled with all Zigbee 3.0 compatible controllers/apps such as Amazon Echo (Alexa), Google Assistant, Tuya (relevant gateway required, outdoor range up to 100 m)
- Very narrow light emission angle, perfect for column lighting or similar

Application Area

Object lighting / architecture, Garage / carport / car park

Housing	Aluminium, Plastic	Control	RF-Smart, ZigBee 3.0
Colour Temperature	2700-6500 K	Primary Cable Length	1.5 m
Rated Input Voltage	100-240 V/AC	CRI (Ra)	80
Power Supply Unit incl.	Yes	Light Direction	Front
Light Beam Angle	15 Degree	IP Protection Type Plug	IP 44
Swivelling Angle	355 Degree		



843521

Article	Housing Color	Luminous Flux	Length	Width	Height	Power	Price
843539	Anthracite	900 lm	72 mm	131 mm	135 mm	9.0 W	€ 111.95
843521	Anthracite	2200 lm	65 mm	170 mm	180 mm	25.0 W	€ 191.95



Accessories for 843521

843510	RF-smart, remote control, white, 1 zone, RGB/RGBW/RGB+CCT, IP20	€ 30.95
843511	RF-smart, remote control, black, 1 zone, RGB/RGBW/RGB+CCT, IP20	€ 30.95
843512	RF-smart, remote control, black, 8 zones, single/CCT/RGB/RGBW/RGB+CCT	€ 39.95
843513	RF-smart, wall remote control, white, 3 V, 4 zones, single/CCT/RGB/W/+CCT	€ 55.95
843514	RF-smart, wall remote control, white, 8 zones, single/CCT/RGB/RGBW/RGB+CCT	€ 87.95
843522	RF-smart, wall remote control, white, 230 V, 4 zones, single/CCT/RGB/W/+CCT	€ 59.95
930659	Wall bracket/display arm, metal, black, length: 800 mm	€ 47.95





DEKO-LIGHT, RF-SMART WIDE-SPOT, RGB+CCT RF + ZIGBEE

- Brightness and colour saturation are dimmable
- RGB 3 x 3 W (max. 9 W), CW / WW 2 x 12 W (max. 12 W), max. total power 12 W
- 16 million colours and adjustable colour temperature
- 18 pre-installed automatic programmes
- Programme and remote control synchronisation when operating multiple RF-Smart components (repeater function)
- Controllable with RF-Smart wireless remote controls (not included)
- Controllable via all Zigbee 3.0-compatible controllers / apps (gateway required)
- Wide-spot, ideal for even and wide-area lighting

Housing	Aluminium, Plastic	Power Supply Unit incl.	Yes
Colour Temperature	2700-6500 K	Light Beam Angle	60 Degree
Luminous Flux	1100 lm	Swivelling Angle	355 Degree
Length	70 mm	Control	RF-Smart, ZigBee 3.0
Width	80 mm	Primary Cable Length	1 m
Height	170 mm	CRI (Ra)	80
Power	12 W	Light Direction	Front
Rated Input Voltage	100-240 V/AC	IP Protection Type Plug	IP 44

Article	Housing Color	Colour Temperature	Price
843540	Anthracite	RGB WW CW 2700-6500 K	€ 135.95



5-year guarantee
Benefit from the maximum quality promise:
All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.



SPIKY

- Replaceable GU10 lamp (retrofit)
- Incl. 2 m connecting cable with IP44 plug
- Incl. ground spike
- Incl. Glare-reducing cover (art. no. 732161 only)

Application Area
Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Home / Living, Hotel / catering

Housing	Aluminium, Plastic	Control	Dimmable via optional light source
Surface	Matt	Swivelling Angle	180 Degree
Max. Power	1x max. 35 W	IP Protection Type Plug	IP 44
Rated Input Voltage	220-240 V/AC		
Primary Connection End	Power plug		

Article	Housing Color	Height	Ø	Primary Cable Length	Price
732161	Black	345 mm	100 mm	2.5 m	€ 27.95
732160	Dark grey	420 mm	60 mm	2 m	€ 31.95



Accessories


843532	RF-smart, GU10, Zigbee, 4 W, RGB+2700-6500 K, 25 Degree		€ 37.95
843510	RF-smart, remote control, white, 1 zone, RGB/RGBW/RGB+CCT, IP20		€ 30.95
843511	RF-smart, remote control, black, 1 zone, RGB/RGBW/RGB+CCT, IP20		€ 30.95
843512	RF-smart, remote control, black, 8 zones, single/CCT/RGB/RGBW/RGB+CCT		€ 39.95
843513	RF-smart, wall remote control, white, 3 V, 4 zones, single/CCT/RGB/W/+CCT		€ 55.95
843522	RF-smart, wall remote control, white, 230 V, 4 zones, single/CCT/RGB/W/+CCT		€ 59.95
843514	RF-smart, wall remote control, white, 8 zones, single/CCT/RGB/RGBW/RGB+CCT		€ 87.95



KEID

Application Area
Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Home / Living, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000 K	Light Beam Angle	45 Degree
Length	120 mm	Swivelling Angle	180 Degree
Height	457 mm	Primary Cable Length	0.5 m
Ø	75 mm	Primary Connection End	Connection box IP65
Rated Input Voltage	220-240 V/AC	CRI (Ra)	80



732094

Article	Housing Color		Luminous Flux	Power	Price
732094	Dark grey	WW	800 lm	10.3 W	€ 111.95
732095	Dark grey	WW	1350 lm	21.5 W	€ 119.95






COLT 8 W COB + 8 W RGBW

- Replaceable reflectors
- Including clear/frosted glass pane
- Including honeycomb filter
- Feed-through wiring possible

Application Area

Object lighting / architecture, Garage / carport / car park, Reception / Communication

Housing	Aluminium	Base Height	50 mm
Colour Temperature	3000 K	Swivelling Angle	180 Degree



732108

Article	Housing Color	Luminous Flux	Height	Ø	Base Ø	Power	Price
732127	Dark grey	340 lm	66 mm	78 mm	96 mm	8.6 W	€ 239.95
732108	Dark grey	470 lm	65 mm	77 mm	95 mm	7.0 W	€ 159.95



- Accessories
- 930441 Surface-mounted housing for Colt 8 W series, black
 - 930426 Ground spike for Colt series 4/8 W, M5, black



- Accessories for 732108
- 930431 12° reflector for Colt 8 W series
 - 930432 22° reflector for Colt 8 W series
 - 930587 Connecting cable with 230 V power plug



- Accessories for 732127
- 862122 FLAT, CV, UT 24 V/50 W
 - 862230 OCTO, CV, Mini 24 V/12 W
 - 872083 IP, CV, V6-40-24






COLT 15 W COB + 16 W RGBW

- Replaceable reflectors
- Including clear/frosted glass pane
- Including honeycomb filter
- Feed-through wiring possible

Application Area


Object lighting / architecture, Garage / carport / car park, Reception / Communication

Housing	Aluminium	Base Height	56 mm
Colour Temperature	3000 K	Base Ø	120 mm
Height	88 mm	Swivelling Angle	180 Degree
Ø	111 mm		



732109

Article	Housing Color		Luminous Flux	Power	Rated Input Voltage	Rated Input Voltage	Power Supply incl.	Price
732128	Dark grey	RGB WW	780 lm	16.0 W	24 V/DC		No	€ 359.95
732109	Dark grey	WW	1090 lm	14.0 W		220-240 V/AC	Yes	€ 199.95



Accessories

930442	Surface-mounted housing for Colt 15/30 W series, black		€ 55.95
930427	Ground spike for Colt series 15/25/30/36/65 W, M10, black		€ 9.95

Accessories for 732109

930434	12° reflector for Colt 15 W series		€ 8.95
930435	22° reflector for Colt 15 W series		€ 9.95
930587	Connecting cable with 230 V power plug		€ 15.95

Accessories for 732128

862122	FLAT, CV, UT 24 V/50 W		€ 41.95
862164	BASIC, CV, Q8H-24-75 W		€ 59.95
872083	IP, CV, V6-40-24		€ 59.95
872085	IP, CV, V6-75-24		€ 75.95
930426	Ground spike for Colt series 4/8 W, M5, black		€ 7.95




COLT 30 W COB + 25 W RGBW

- Replaceable reflectors
- Including clear/frosted glass pane
- Including honeycomb filter
- Feed-through wiring possible


Application Area
Object lighting / architecture, Garage / carport / car park, Reception / Communication

Housing	Aluminium	Base Height	56 mm
Colour Temperature	3000 K	Base Ø	120 mm
Height	112 mm	Swivelling Angle	180 Degree
Ø	131 mm		



732110

Article	Housing Color		Luminous Flux	Power	Rated Input Voltage	Rated Input Voltage	Power Supply incl.	Price
732129	Dark grey	RGB WW	1140 lm	25.0 W	24 V/DC		No	€ 399.95
732110	Dark grey	WW	2320 lm	29.0 W		220-240 V/AC	Yes	€ 231.95



Accessories

930442	Surface-mounted housing for Colt 15/30 W series, black		€ 55.95
930427	Ground spike for Colt series 15/25/30/36/65 W, M10, black		€ 9.95


Accessories for 732110

930437	12° reflector for Colt 30 W series		€ 9.95
930438	22° reflector for Colt 30 W series		€ 9.95
930587	Connecting cable with 230 V power plug		€ 15.95

Accessories for 732129

862163	BASIC, CV, Q8H-24-40 W		€ 37.95
862164	BASIC, CV, Q8H-24-75 W		€ 59.95
872083	IP, CV, V6-40-24		€ 59.95
872085	IP, CV, V6-75-24		€ 75.95
872094	IP, CV, V6-100-24		€ 91.95





wall washer



page 520



page 521






WALLWASHER CAPH 24 V

- Including 0.5 m connecting cable with WEIPU plug
- Including 0.5 m connecting cable with WEIPU plug

Application Area


Garden / Terrace / Balcony / Walkways, Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Advertising lighting

Housing	Aluminium	Power Supply Unit incl.	No
Colour Temperature	3000 K	Control	Dimmable via optional controller
Length	1000 mm	Primary Cable Length	0.5 m
Width	53.36 mm	Primary Connection End	WEIPU plug 5-pole
Height	81.07 mm	CRI (Ra)	80
Power	60 W		
Rated Input Voltage	24 V/DC		



732071

Article	Housing Color		Luminous Flux	Light Beam Angle	Light Beam Angle 2	Light Distribution	Price
732072	Dark grey	RGB WW	2480 lm	40 Degree	15 Degree	Asymetric	€ 332.95
732071	Dark grey	RGB WW	2800 lm	25 Degree		Symmetric	€ 332.95



Accessories

- 862164 BASIC, CV, Q8H-24-75 W
- 872085 IP, CV, V6-75-24
- 843502 RF-smart, starter set RGB/W/CCT, 12-48 V, 20 A incl. remote, IP20

	€ 59.95
	€ 75.95
	€ 79.95



Onlineshop
You can find more information about the products in the onlineshop:
Detailed images, videos, project reports, LDT files, EPREL data sheets and more.




WALLWASHER CAPH 230V

·Including 2 m connecting cable with IP44 shaped plug

Application Area

Garden / Terrace / Balcony / Walkways, Object lighting / architecture, Garage / carport / car park, House wall / facade / front door, Advertising lighting

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Colour Temperature	3000 K	Power Supply Unit incl.	Yes
Length	1000 mm	Primary Cable Length	2 m
Width	53.36 mm	Primary Connection End	Power plug IP44
Height	81.07 mm	CRI (Ra)	80
Power	38 W	IP Protection Type Plug	IP 44



732080

Article	Housing Color		Luminous Flux	Light Beam Angle	Light Beam Angle 2	Light Distribution	Price
732080	Dark grey	WW	2580 lm	40 Degree	15 Degree	Asymetric	€ 332.95
732079	Dark grey	WW	3000 lm	25 Degree		Symmetric	€ 332.95



Technical data sheet
New in the onlineshop: The technical data sheets offer even more information: Light and energy data, light distribution curves, dimensional drawings and more.

ground recessed lights



page 524




page 524



page 525



page 526



page 526



page 528



page 529



page 530



page 531



page 532



page 533



page 534



□
page 535



□
page 537



□
page 537



ATON

Application Area
Garden / Terrace / Balcony / Walkways

Height	111 mm	Cut Out Ø	70 mm
Installation Depth	148 mm	Control	Dimmable via optional light source
Max. Power	1x max. 7 W		
Rated Input Voltage	220-240 V/AC		

Article	Housing Color	Housing	Length	Width	Ø	IK Protection Class	Price
730474	Silver	Stainless steel			97 mm	IK08	€ 45.95
730475	Silver	Stainless steel / Aluminium	97 mm	97 mm			€ 45.95



PAVO

· Swivelling insert

Application Area
Garden / Terrace / Balcony / Walkways

Housing	Stainless steel, Aluminium	Rated Input Voltage	220-240 V/AC
Height	156 mm	Cut Out Ø	100 mm
Installation Depth	193 mm	Control	Dimmable via optional light source
Max. Power	1x max. 9 W	Swivelling Angle	25 Degree

Article	Housing Color	Length	Width	Ø	Price
730478	Silver			160 mm	€ 91.95
730479	Silver	160 mm	160 mm		€ 91.95






PEACOCK

·Including 0.5 m connecting cable with protected connection socket

Application Area

Garden / Terrace / Balcony / Walkways

Housing	Stainless steel, Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000 K	Installation Depth	48 mm
Luminous Flux	150 lm	Light Beam Angle	30 Degree
Height	43 mm	Cut Out Ø	44 mm
Ø	58 mm	CRI (Ra)	80
Power	2 W	Primary Connection End	Connection box IP67
Rated Input Voltage	220-240 V/AC	IK Protection Class	IK08
		Light Distribution	Symmetric



730459

Article Housing Color Price

730459  Silver  € 91.95






FLAT 230V 20 DEGREE

•Including 0.5 m connecting cable

Application Area
Garden / Terrace / Balcony / Walkways

Housing	Stainless steel, Aluminium	Light Beam Angle	20 Degree
Colour Temperature	3000 K	CRI (Ra)	80
Rated Input Voltage	220-240 V/AC	Primary Cable Length	0.5 m
Power Supply Unit incl.	Yes	Primary Connection End	Connection box
		Light Distribution	Symmetric



100111

Article	Housing Color	Luminous Flux	Height	Ø	Power	Installation Depth	Price
100111	Silver	400 lm	44 mm	116 mm	5.8 W	44 mm	€ 155.95
100114	Silver	860 lm	42 mm	173 mm	12.2 W	42 mm	€ 223.95



FLAT 230V 120 DEGREE

Application Area
Garden / Terrace / Balcony / Walkways

Housing	Stainless steel, Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000 K	Installation Depth	43 mm
Luminous Flux	40 lm	Light Beam Angle	120 Degree
Height	42 mm	Cut Out Ø	100 mm
Ø	116 mm	CRI (Ra)	65
Power	1.3 W	Primary Cable Length	0.5 m
Rated Input Voltage	220-240 V/AC	Primary Connection End	Connection box
		Light Distribution	Symmetric

Article	Housing Color	Price
730336	Silver	€ 123.95







HELIOS



•Incl. four heavy-duty anchors

Application Area

Garden / Terrace / Balcony / Walkways, Object lighting / architecture, Park / public outdoor area, Stairs / steps, Hotel / catering

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000 K	Light Beam Angle	90 Degree
Height	54 mm	CRI (Ra)	80
Ø	210 mm	IK Protection Class	IK10
Rated Input Voltage	220-240 V/AC		

Article	Housing Color		Luminous Flux	Power	Price
732143		Dark grey 	60 lm	4.0 W	€ 95.95
732049		Dark grey 	120 lm	4.0 W	€ 95.95
732050		Dark grey 	180 lm	6.0 W	€ 95.95






SOFT FLEX

- Adjustable light emission angle
- Including 1 m connecting cable
- Including honeycomb filter

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Park / public outdoor area

Housing	Stainless steel, Aluminium	Swivelling Angle	60 Degree
Colour Temperature	3000 K	CRI (Ra)	80
Rated Input Voltage	220-240 V/AC	Primary Cable Length	1 m
Power Supply Unit incl.	Yes	Primary Connection End	Connection box
Installation Depth	220 mm	Light Distribution	Symmetric



730266

Article	Housing Color		Luminous Flux	Height	Ø	Power	Light Beam Angle	Price
730267	Silver	ww	480 lm	128 mm	173 mm	9.3 W	15 Degree	€ 287.95
730266	Silver	ww	770 lm	190 mm	250 mm	18.4 W	25 Degree	€ 479.95






CANUM 24V SYMMETRICAL

Application Area
 Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Park / public outdoor area

Housing	Stainless steel, Aluminium	Installation Depth	150 mm
Colour Temperature	3000 K	Light Beam Angle	45 Degree
Luminous Flux	370 lm	Cut Out Ø	102 mm
Height	102 mm	Control	Dimmable via optional controller
Ø	116 mm	CRI (Ra)	80
Power	5.8 W	Primary Cable Length	2 m
Rated Input Voltage	24 V/DC	Primary Connection End	WEIPU plug 2-pole
Power Supply Unit incl.	No	Light Distribution	Symmetric



Article	Housing Color	Price
100133	Silver	€ 156.95



Accessories	
862230	OCTO, CV, Mini 24 V/12 W
872083	IP, CV, V6-40-24
843501	RF-smart, starter set LED single/CCT, 12-48 V, 20 A incl. remote control

	€ 17.95
	€ 59.95
	€ 79.95






CANUM 24V ASYMMETRICAL

- Including 0.5 m connecting cable with WEIPU plug
- Asymmetrical

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Park / public outdoor area

Housing	Stainless steel, Aluminium	Light Beam Angle	45 Degree
Colour Temperature	3000 K	Light Beam Angle 2	35 Degree
Luminous Flux	800 lm	Cut Out Ø	157 mm
Height	111 mm	Control	Dimmable via optional controller
Ø	173 mm	CRI (Ra)	80
Power	14 W	Primary Cable Length	0.5 m
Rated Input Voltage	24 V/DC	Primary Connection End	WEIPU plug 2-pole
Power Supply Unit incl.	No	Light Distribution	Asymetric
Installation Depth	153 mm		




730296

Article	Housing Color	Price
730296	Silver	€ 215.95



Accessories

- 872083** IP, CV, V6-40-24
- 843501** RF-smart, starter set LED single/CCT, 12-48 V, 20 A incl. remote control






CANUM RGB 24V SYMMETRICAL

Application Area
Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Park / public outdoor area

Housing	Stainless steel, Aluminium	Installation Depth	150 mm
Luminous Flux	370 lm	Light Beam Angle	30 Degree
Height	102 mm	Cut Out Ø	102 mm
Ø	116 mm	Control	Dimmable via optional controller
Power	7.4 W	Primary Cable Length	0.5 m
Rated Input Voltage	24 V/DC	Primary Connection End	WEIPU plug 4-pole
Power Supply Unit incl.	No	Light Distribution	Symmetric



730276

Article	Housing Color	Price
730276	Silver	€ 175.95



- Accessories
- 872083 IP, CV, V6-40-24
 - 843502 RF-smart, starter set RGB/W/CCT, 12-48 V, 20 A incl. remote, IP20






CANUM RGB 24V ASYMMETRICAL

·Including 0.5 m connecting cable with WEIPU plug

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Park / public outdoor area

Housing	Stainless steel, Aluminium	Light Beam Angle	50 Degree
Luminous Flux	650 lm	Light Beam Angle 2	35 Degree
Height	111 mm	Cut Out Ø	157 mm
Ø	173 mm	Control	Dimmable via optional controller
Power	16.9 W	Primary Cable Length	0.5 m
Rated Input Voltage	24 V/DC	Primary Connection End	WEIPU plug 4-pole
Power Supply Unit incl.	No	IK Protection Class	IK07
Installation Depth	153 mm	Light Distribution	Asymetric



730454

Article	Housing Color	Price
730454	Silver	€ 287.95



Accessories

872083	IP, CV, V6-40-24
843502	RF-smart, starter set RGB/W/CCT, 12-48 V, 20 A incl. remote, IP20

	€ 59.95
	€ 79.95






CANUM 230V SYMMETRICAL

•Including connecting cable

Application Area
Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Park / public outdoor area

Housing	Stainless steel, Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000 K	Installation Depth	150 mm
Luminous Flux	280 lm	Light Beam Angle	30 Degree
Height	102 mm	Cut Out Ø	102 mm
Ø	116 mm	CRI (Ra)	80
Power	4.1 W	Primary Cable Length	0.5 m
Rated Input Voltage	220-240 V/AC	Primary Connection End	Connection box
		Light Distribution	Symmetric



Article	Housing Color	Price
730255	Silver	€ 143.95



5-year guarantee
Benefit from the maximum quality promise:
All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.




CANUM 230V ASYMMETRICAL

- Asymmetrical
- Including 0.5 m connecting cable

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Park / public outdoor area

Housing	Stainless steel, Aluminium	Installation Depth	153 mm
Colour Temperature	3000 K	Light Beam Angle	45 Degree
Luminous Flux	700 lm	Light Beam Angle 2	35 Degree
Height	111 mm	Cut Out Ø	157 mm
Ø	173 mm	CRI (Ra)	80
Power	11.9 W	Primary Cable Length	0.5 m
Rated Input Voltage	220-240 V/AC	Primary Connection End	Connection box
Power Supply Unit incl.	Yes	IK Protection Class	IK09
		Light Distribution	Asymetric



730289

Article	Housing Color	Price
730289	Silver	€ 215.95



Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.






LINE

·Incl. connecting cable

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Park / public outdoor area

Housing	Stainless steel, Aluminium	Light Beam Angle	20 Degree
Colour Temperature	3000 K	Cut Out Width	68 mm
Width	68 mm	CRI (Ra)	80
Height	31.5 mm	Primary Cable Length	0.5 m
Rated Input Voltage	220-240 V/AC	Primary Connection End	Connection box
Power Supply Unit incl.	Yes	IK Protection Class	IK07
Installation Depth	80 mm	Light Distribution	Symmetric



730432

Article	Housing Color		Luminous Flux	Length	Power	Cut Out Length	Cutout L x W	Price
730434	Silver		1100 lm	549 mm	18.0 W	527 mm	527 x 68 mm	€ 319.95
730432	Silver		2300 lm	1025 mm	36.0 W	1007 mm	1007 x 68 mm	€ 509.95




LINE ASYMMETRICAL

Application Area

Garden / Terrace / Balcony / Walkways, Garage / carport / car park, Park / public outdoor area

Housing	Stainless steel, Aluminium	Installation Depth	90 mm
Colour Temperature	3000 K	Light Beam Angle	45 Degree
Width	63 mm	Light Beam Angle 2	35 Degree
Height	65 mm	Cut Out Width	58 mm
Rated Input Voltage	220-240 V/AC	CRI (Ra)	80
Power Supply Unit incl.	Yes	Primary Connection End	Connection box
		Light Distribution	Asymetric



730262

Article	Housing Color		Luminous Flux	Length	Power	Cut Out Length	Cutout L x W	Price
730292	Silver		340 lm	195 mm	5.5 W	180 mm	180 x 58 mm	€ 148.95
730262	Silver		730 lm	328 mm	11.9 W	313 mm	313 x 58 mm	€ 207.95





page 540



page 541

floodlight






DEKO-LIGHT RF-SMART FLOODLIGHT RGB+CCT RF + ZIGBEE

- Adjustable brightness and colour saturation
- 16 million available colours and adjustable colour temperature
- 18 automatic programmes pre-installed
- Program and remote control synchronisation when operating multiple RF smart components (repeater function)
- Can be controlled with RF smart wireless remote controls (2.4 GHz, range approx. 30 m, not included in the scope of delivery)
- Can be controlled with all Zigbee 3.0 compatible controllers/apps such as Amazon Echo (Alexa), Google Assistant, Tuya (relevant gateway required, outdoor range up to 100 m)

Application Area
Object lighting / architecture, Garage / carport / car park

Housing	Aluminium, Plastic	Control	RF-Smart, ZigBee 3.0
Colour Temperature	2700-6500 K	Primary Cable Length	1.5 m
Rated Input Voltage	100-240 V/AC	CRI (Ra)	80
Power Supply Unit incl.	Yes	Light Direction	Front
Light Beam Angle	160 Degree	IP Protection Type Plug	IP 44
Swivelling Angle	345 Degree		



843518

Article	Housing Color		Luminous Flux	Length	Width	Height	Power	Price
843518	Anthracite	RGB WW CW	3300 lm	40 mm	167 mm	227 mm	30.0 W	€ 199.95
843519	Anthracite	RGB WW CW	4800 lm	48 mm	220 mm	311 mm	50.0 W	€ 279.95
843520	Anthracite	RGB WW CW	10000 lm	60 mm	295 mm	403 mm	100.0 W	€ 439.95



Accessories

- 843510 RF-smart, remote control, white, 1 zone, RGB/RGBW/RGB+CCT, IP20
- 843511 RF-smart, remote control, black, 1 zone, RGB/RGBW/RGB+CCT, IP20
- 843512 RF-smart, remote control, black, 8 zones, single/CCT/RGB/RGBW/RGB+CCT
- 843513 RF-smart, wall remote control, white, 3 V, 4 zones, single/CCT/RGB/W/+CCT
- 843522 RF-smart, wall remote control, white, 230 V, 4 zones, single/CCT/RGB/W/+CCT
- 843514 RF-smart, wall remote control, white, 8 zones, single/CCT/RGB/RGBW/RGB+CCT
- 930659 Wall bracket/display arm, metal, black, length: 800 mm






ATIK

- IEC62662 - Protection against mechanical effects (IK Code)
- EN60598-2-24 - Lights for use in explosive gas and dust atmosphere (D designation)
- Including 2 m connecting cable with IP44 plug

Application Area


Garage / carport / car park, Industry / production / high-bay warehouse

Housing	Aluminium	Swivelling Angle	180 Degree
Colour Temperature	4000 K	Primary Cable Length	2 m
Length	319 mm	Primary Connection End	Power plug IP44
Width	90 mm	CRI (Ra)	80
Height	411 mm	IP Protection Type Plug	IP 44
Power Supply Unit incl.	Yes	IK Protection Class	IK08
Light Beam Angle	110 Degree		





Article	Housing Color		Luminous Flux	Power	Rated Input Voltage	EEL	Price
732096			21350 lm	152.0 W	220-240 V/AC		€ 351.95
732097			28450 lm	202.0 W	220-240 V/AC		€ 443.95
732098			31800 lm	242.0 W	220-240 V/AC		€ 499.95
732102			39900 lm	302.0 W	100-240 V/AC		€ 559.95





display lights







ATIS

When it comes to illuminating signs, façades, billboards or images, display lights are the perfect choice. They are easy to install, exceptionally efficient and suit almost any environment thanks to their timeless design. With corresponding IP protection, they can also be used outdoors, purposefully providing an additional lighting source in such environments.




ATIS

·rotatable and swivelling lamp head

Application Area
Object lighting / architecture, Advertising lighting

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Colour Temperature	3000 K	Power Supply Unit incl.	Yes
Luminous Flux	1150 lm	Light Beam Angle	100 Degree
Length	526 mm	Swivelling Angle	90 Degree
Width	144 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Base Length	95 mm	CRI (Ra)	80
Base Height	40 mm		
Power	15 W		



688020

Article	Housing Color		Price
688020	White		€ 183.95
688021	Black		€ 183.95




Onlineshop
You can find more information about the products in the onlineshop:
Detailed images, videos, project reports, LDT files, EPREL data sheets and more.




SYSTEM LAUTARO

- 548 Overview ring lights
- 550 pendant lights
- 558 surface mounted ceiling lights



System Lautaro




page 554




page 556




page 555




page 557




page 558



LAUTARO

LAUTARO is a new luminaire series which, despite its enormous configuration options, has one thing in common: it is round or ring-shaped and has a surrounding LED ring. But that is where the similarities end. All other product features can be selected, which is why LAUTARO is suitable for a wide range of commercial [and private] applications, including cafés, hotel lobbies, schools, stores and much more.



Is your desired variant not included in the standard range? Then simply configure your customised LAUTARO using our online configurator.



Note: Please note that the LAUTARO series are project items that are not available from stock. The delivery time is approx. 6 weeks.



PLEASANT LIGHT ALL ROUND - YOUR BENEFITS AT A GLANCE:

- BEG-eligible [for approx. 50% of models]
- DALI dimmable thanks to integrated power supply unit
- emergency current capable
- through-wiring for simple series connection
- tool-free connection with spring terminals
- easy to install and maintain thanks to durable, easily replaceable components
- invisible screw connection for a clean appearance

1,080 VARIANTS AS STANDARD - SPECIAL DESIGNS ON REQUEST MODULAR SYSTEM FOR MAXIMUM DESIGN FREEDOM:

- three profile sizes: 60×44 / 80×55 / 100×80 mm
- three colours: RAL 9005 [black] / RAL 9006 [silver] / RAL 9016 [white]
- four diameters: 600 / 900 / 1,200 / 1,500 mm
- three light colors: 2,700 K / 3,000 K / 4,000 K
- surface-mounted luminaires for direct light
- pendant luminaires for direct or direct-indirect light [separately switchable and dimmable]
- custom-made products on request - e.g. individual sizes or RAL of your choice



1,080 GOOD REASONS

The LAUTARO surface-mounted and pendant light offers so many variants. But don't worry: the configuration is very simple! LAUTARO is a new luminaire series which, despite its enormous configuration options, has one thing in common: it is round or ring-shaped and has a uniform, all-round light emission. But that's where the similarities end. All other product features can be selected, making LAUTARO ideal for a wide range of commercial [and private] applications, including reception areas, restaurants, atriums, open-plan offices and much more.

DALI for all

All LAUTARO variants are equipped with an integrated DALI power supply unit and are dimmable. The power supply units are suitable for emergency power and facilitate installation thanks to integrated loop-in/loop-out technology.

All information on the LAUTARO series can be found from page 588.



Is your desired variant not included in the standard range? Then simply configure your customised LAUTARO using our online configurator.



6 STEPS TO A CUSTOMISED LAUTARO

1. SELECT THE PRODUCT VARIANT

The LAUTARO is available as a surface-mounted or pendant luminaire - the latter with two types of suspension and direct or direct/indirect lighting.

2. SELECT THE PROFILE

There is a choice of three different profiles [height x width in mm]: 60x44, 80x55 and 100x80.

3. SELECT THE DIAMETER

In order to use the LAUTARO in different room sizes and applications, it is available in four diameters: 600, 900, 1,200 and 1,500 mm.

4. SELECT THE HOUSING COLOUR


Black, grey, white - each in matt with a powder-coated surface. Individual RAL colours are available on special request.

5. SELECT THE DIFFUSER

In addition to the opal diffuser, a microprismatic version is also available for use in workplaces with particularly low glare [UGR<19].

6. SELECT THE COLOUR TEMPERATURE

2,700K, 3,000K or 4,000K - incandescent lamp, warm white or neutral white. With these three colour temperatures, you can cover most lighting requirements.





LAUTARO 900/60 DOWN, SUSPENSION CENTRE

- DALI dimmable with integrated power supply
- continuous wiring possible
- tool-free connection with plug-in terminals
- easy to install / maintain
- long-lasting, easily replaceable components
- invisible screw connections
- customised designs available on request


Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, DIY store / discount store / supermarket / car dealership, Trade fair construction / shop fitting

Housing	Aluminium, Steel	Power Supply Unit incl.	Yes
Power	60 W	Light Beam Angle	90 Degree
Rated Input Voltage	198-264 V/AC	Control	DALI 2 / DT6, Push-Dim
Tread depth	60 mm	CRI (Ra)	90
Ø	900 mm	IK Protection Class	IK05
Pendulum Length	3000 mm		

Article	Housing Color	Colour Temperature	Gloss level lens	Luminous Flux	Price
950216	Light grey	2700 K	opal	6600 lm	€ 951.95
950217	Black	2700 K	opal	6600 lm	€ 951.95
950218	White	2700 K	opal	6600 lm	€ 951.95
950225	Light grey	2700 K	microprismatic	7000 lm	€ 975.95
950226	Black	2700 K	microprismatic	7000 lm	€ 975.95
950227	White	2700 K	microprismatic	7000 lm	€ 975.95
950219	Light grey	3000 K	opal	7000 lm	€ 951.95
950220	Black	3000 K	opal	7000 lm	€ 951.95
950221	White	3000 K	opal	7000 lm	€ 951.95
950228	Light grey	3000 K	microprismatic	7500 lm	€ 975.95
950229	Black	3000 K	microprismatic	7500 lm	€ 975.95
950230	White	3000 K	microprismatic	7500 lm	€ 975.95
950222	Light grey	4000 K	opal	7200 lm	€ 951.95
950223	Black	4000 K	opal	7200 lm	€ 951.95
950224	White	4000 K	opal	7200 lm	€ 951.95
950231	Light grey	4000 K	microprismatic	8100 lm	€ 975.95
950232	Black	4000 K	microprismatic	8100 lm	€ 975.95
950233	White	4000 K	microprismatic	8100 lm	€ 975.95





LAUTARO 900/60 DOWN, SUSPENSION PARALLEL


- DALI dimmable with integrated power supply
- continuous wiring possible
- tool-free connection with plug-in terminals
- easy to install / maintain
- long-lasting, easily replaceable components
- invisible screw connections
- customised designs available on request

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, DIY store / discount store / supermarket / car dealership, Trade fair construction / shop fitting

Housing	Aluminium, Steel	Power Supply Unit incl.	Yes
Power	60 W	Light Beam Angle	90 Degree
Rated Input Voltage	198-264 V/AC	Control	DALI 2 / DT6, Push-Dim
Tread depth	60 mm	CRI (Ra)	90
Ø	900 mm	IK Protection Class	IK05
Pendulum Length	3000 mm		

Article	Housing Color	Colour Temperature	Gloss level lens	Luminous Flux	Price
950234	Light grey	2700 K	opal	6600 lm	€ 951.95
950235	Black	2700 K	opal	6600 lm	€ 951.95
950236	White	2700 K	opal	6600 lm	€ 951.95
950243	Light grey	2700 K	microprismatic	7000 lm	€ 975.95
950244	Black	2700 K	microprismatic	7000 lm	€ 975.95
950245	White	2700 K	microprismatic	7000 lm	€ 975.95
950237	Light grey	3000 K	opal	7000 lm	€ 951.95
950238	Black	3000 K	opal	7000 lm	€ 951.95
950239	White	3000 K	opal	7000 lm	€ 951.95
950246	Light grey	3000 K	microprismatic	7500 lm	€ 975.95
950247	Black	3000 K	microprismatic	7500 lm	€ 975.95
950248	White	3000 K	microprismatic	7500 lm	€ 975.95
950240	Light grey	4000 K	opal	7200 lm	€ 951.95
950241	Black	4000 K	opal	7200 lm	€ 951.95
950242	White	4000 K	opal	7200 lm	€ 951.95
950249	Light grey	4000 K	microprismatic	8100 lm	€ 975.95
950250	Black	4000 K	microprismatic	8100 lm	€ 975.95
950251	White	4000 K	microprismatic	8100 lm	€ 975.95





LAUTARO 900/60 UP/DOWN, SUSPENSION CENTRE

- DALI dimmable with integrated power supply
- continuous wiring possible
- tool-free connection with plug-in terminals
- easy to install / maintain
- long-lasting, easily replaceable components
- invisible screw connections
- customised designs available on request


Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, DIY store / discount store / supermarket / car dealership, Trade fair construction / shop fitting

Housing	Aluminium, Steel	Light Beam Angle	90 Degree
Rated Input Voltage	198-264 V/AC	Control	DALI 2 / DT6, Push-Dim
Tread depth	60 mm		
Ø	900 mm	CRI (Ra)	90
Pendulum Length	3000 mm	IK Protection Class	IK05
Power Supply Unit incl.	Yes		

Article	Housing Color	Colour Temperature	Gloss level lens	Luminous Flux	Power	Price
950252	Light grey	2700 K	opal	9200 lm	89.0 W	€ 1282.95
950253	Black	2700 K	opal	9200 lm	89.0 W	€ 1282.95
950254	White	2700 K	opal	9200 lm	89.0 W	€ 1282.95
950261	Light grey	2700 K	microprismatic	10000 lm	89.0 W	€ 1267.95
950262	Black	2700 K	microprismatic	10000 lm	89.0 W	€ 1267.95
950263	White	2700 K	microprismatic	10000 lm	89.0 W	€ 1267.95
950257	White	3000 K	opal	9900 lm	85.0 W	€ 1282.95
950255	Light grey	3000 K	opal	9900 lm	89.0 W	€ 1282.95
950256	Black	3000 K	opal	9900 lm	89.0 W	€ 1282.95
950264	Light grey	3000 K	microprismatic	10500 lm	89.0 W	€ 1267.95
950265	Black	3000 K	microprismatic	10500 lm	89.0 W	€ 1267.95
950266	White	3000 K	microprismatic	10500 lm	89.0 W	€ 1267.95
950258	Light grey	4000 K	opal	10000 lm	89.0 W	€ 1282.95
950259	Black	4000 K	opal	10000 lm	89.0 W	€ 1282.95
950260	White	4000 K	opal	10000 lm	89.0 W	€ 1282.95
950267	Light grey	4000 K	microprismatic	11500 lm	89.0 W	€ 1267.95
950268	Black	4000 K	microprismatic	11500 lm	89.0 W	€ 1267.95
950269	White	4000 K	microprismatic	11500 lm	89.0 W	€ 1267.95





LAUTARO 900/60 UP/DOWN, SUSPENSION PARALLEL

- DALI dimmable with integrated power supply
- continuous wiring possible
- tool-free connection with plug-in terminals
- easy to install / maintain
- long-lasting, easily replaceable components
- invisible screw connections
- customised designs available on request

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, DIY store / discount store / supermarket / car dealership, Trade fair construction / shop fitting

Housing	Aluminium, Steel	Power Supply Unit incl.	Yes
Power	89 W	Light Beam Angle	90 Degree
Rated Input Voltage	198-264 V/AC	Control	DALI 2 / DT6, Push-Dim
Tread depth	60 mm	CRI (Ra)	90
Ø	900 mm	IK Protection Class	IK05
Pendulum Length	3000 mm		

Article	Housing Color	Colour Temperature	Gloss level lens	Luminous Flux	Price
950270	Light grey	WW 2700 K	opal	9200 lm	€ 1282.95
950271	Black	WW 2700 K	opal	9200 lm	€ 1282.95
950272	White	WW 2700 K	opal	9200 lm	€ 1282.95
950279	Light grey	WW 2700 K	microprismatic	10000 lm	€ 1267.95
950280	Black	WW 2700 K	microprismatic	10000 lm	€ 1267.95
950281	White	WW 2700 K	microprismatic	10000 lm	€ 1267.95
950273	Light grey	WW 3000 K	opal	9900 lm	€ 1282.95
950274	Black	WW 3000 K	opal	9900 lm	€ 1282.95
950275	White	WW 3000 K	opal	9900 lm	€ 1282.95
950282	Light grey	WW 3000 K	microprismatic	10500 lm	€ 1267.95
950283	Black	WW 3000 K	microprismatic	10500 lm	€ 1267.95
950284	White	WW 3000 K	microprismatic	10500 lm	€ 1267.95
950276	Light grey	NW 4000 K	opal	10000 lm	€ 1282.95
950277	Black	NW 4000 K	opal	10000 lm	€ 1282.95
950278	White	NW 4000 K	opal	10000 lm	€ 1282.95
950285	Light grey	NW 4000 K	microprismatic	11500 lm	€ 1267.95
950286	Black	NW 4000 K	microprismatic	11500 lm	€ 1267.95
950287	White	NW 4000 K	microprismatic	11500 lm	€ 1267.95





LAUTARO 900/60

- DALI-dimmable with integrated power supply unit
- Through-wiring possible
- Tool-free connection with plug-in terminals
- Easy to install and maintain
- Durable, easily replaceable components
- Concealed screw connections
- Customised designs available on request

Application Area

Reception / Communication, Object lighting / architecture, Corridor / stairwell, Office / conference, Shop / Retail / Sales area, Home / Living, Home office / study, Hotel / catering, Refurbishment, DIY store / discount store / supermarket / car dealership, Trade fair construction / shop fitting

Housing	Aluminium, Steel	Light Beam Angle	90 Degree
Tread depth	60 mm	Control	DALI 2 / DT6, Push-Dim
Ø	900 mm	CRI (Ra)	90
Power	60 W	IK Protection Class	IK05
Rated Input Voltage	198-264 V/AC		
Power Supply Unit incl.	Yes		

Article	Housing Color	Colour Temperature	Gloss level lens	Luminous Flux	Price
950918	Light grey	2700 K	opal	6600 lm	€ 799.95
950919	Black	2700 K	opal	6600 lm	€ 799.95
950920	White	2700 K	opal	6600 lm	€ 799.95
950927	Light grey	2700 K	microprismatic	7000 lm	€ 883.95
950928	Black	2700 K	microprismatic	7000 lm	€ 883.95
950929	White	2700 K	microprismatic	7000 lm	€ 883.95
950921	Light grey	3000 K	opal	7000 lm	€ 799.95
950922	Black	3000 K	opal	7000 lm	€ 799.95
950923	White	3000 K	opal	7000 lm	€ 799.95
950930	Light grey	3000 K	microprismatic	7500 lm	€ 883.95
950931	Black	3000 K	microprismatic	7500 lm	€ 883.95
950932	White	3000 K	microprismatic	7500 lm	€ 883.95
950924	Light grey	4000 K	opal	7200 lm	€ 799.95
950925	Black	4000 K	opal	7200 lm	€ 799.95
950926	White	4000 K	opal	7200 lm	€ 799.95
950933	Light grey	4000 K	microprismatic	8100 lm	€ 883.95
950934	Black	4000 K	microprismatic	8100 lm	€ 883.95
950935	White	4000 K	microprismatic	8100 lm	€ 883.95










SYSTEM PLANO

- 562 Overview PLANO luminaire system
- 564 luminaire system
- 580 Overview PLANO profiles
- 582 profile system



PLANO luminaire system



PLANO LUMINAIRE SYSTEM

Whether as a recessed version, surface-mounted ceiling luminaire or pendant luminaire as well as for wall mounting: the PLANO series is more than just another combination of profile and LED strip and is produced entirely in Europe.


The linear lighting solutions are based on four different profiles and can be configured individually. Thus, there are hardly any limits to the possible applications - whether in the office, in schools, in private living areas, in stores, showrooms and many more.



INDIVIDUAL SOLUTION

A PLANO profile luminaire always has the same design - and yet it is individual. Inside sits a profile with LED illumination in 2,700, 3,000 or 4,000 K. The surrounding luminaire body is made of extruded aluminum and has an anodized or powder-coated surface. You can individually determine the length, equipment as well as the

basic shape of the body, because the PLANO series is an individual lighting solution.



PROFIL

- colour
- length
- basic shape

ASSEMBLY

- installation
- built-in
- ceiling
- pendant
- wall

RADIATION DIRECTION

- up
- up / down

COLOUR TEMPERATURE


- 2700 K
- 3000 K
- 4000 K

COVER

- opal
- opal U
- microprismatic

CONTROL

- switchable
- DALI
- phase angle / section
- Casambi



PLANO DS
LUMINAIRE SYSTEM


- aluminium die casting
- direct light

assembly				cover			length	radiation dir.		colour	colour temperature			control			
ceiling structure	pendulum	wall structure	ceiling mounting	opal	opal U	microprismatic	individual	down	up+down	individual	2700 K	3000 K	4000 K	switchable	DALI	phase angle/section	Casambi
x	x			x	x	x	x	x		x	x	x	x	x	x	x	x

LED

Ra>90

IP20




CONFIGURATION EXAMPLE

- DS surface-mounted luminaire | 2400 mm | black
- 74 W
- 3000 K | 6827 lm
- EVG | DALI
- incl. U-cover opal
- incl. end caps

price on demand

Of course, you can configure our PLANO system entirely according to your wishes and circumstances.





PLANO ES
LUMINAIRE SYSTEM


- aluminium die casting
- direct light

assembly				cover			length	radiation dir.		colour	colour temperature			control			
ceiling structure	pendulum	wall structure	ceiling mounting	opal	opal U	microprismatic	individual	down	up+down	individual	2700 K	3000 K	4000 K	switchable	DALI	phase angle/section	Casambi
x	x			x	x	x	x	x	x	x	x	x	x	x	x	x	x

LED

Ra>90

IP20




CONFIGURATION EXAMPLE

- ES surface-mounted luminaire | 2400 mm | black
- 74 W
- 3000 K | 5425 lm
- EVG | DALI
- incl. U-cover flat opal
- incl. end caps

price on demand

Of course, you can configure our PLANO system entirely according to your wishes and circumstances.





PLANO ES
LUMINAIRE SYSTEM


- aluminium die casting
- direct light

assembly				cover			length	radiation dir.		colour	colour temperature			control			
ceiling structure	pendulum	wall structure	ceiling mounting	opal	opal U	microprismatic	individual	down	up+down	individual	2700 K	3000 K	4000 K	switchable	DALI	phase angle/section	Casambi
		x		x	x	x	x	x	x	x	x	x	x	x	x	x	x

LED

Ra>90

IP20





CONFIGURATION EXAMPLE

- ES wall-mounted luminaire | 2400 mm | black
- 97 W
- 3000 K | 7201 lm
- EVG | DALI
- incl. U-cover flat opal
- incl. end caps and wall bracket

price on demand

Of course, you can configure our PLANO system entirely according to your wishes and circumstances.





PLANO ES RECESSED LUMINAIRE SYSTEM


- aluminium die casting
- direct light

assembly				cover			length	radiation dir.		colour	colour temperature			control			
ceiling structure	pendulum	wall structure	ceiling mounting	opal	opal U	microprismatic	individual	down	up+down	individual	2700 K	3000 K	4000 K	switchable	DALI	phase angle/section	Casambi
			x	x	x	x	x	x		x	x	x	x	x	x	x	x

LED

Ra>90

IP20





CONFIGURATION EXAMPLE

- ES recessed ceiling luminaire | 2400 mm | black
- 97 W
- 3000 K | 7201 lm
- EVG | DALI
- incl. U-cover flat opal
- incl. end caps and mounting bracket

price on demand

Of course, you can configure our PLANO system entirely according to your wishes and circumstances.





**PLANO MS
LUMINAIRE SYSTEM**





- aluminium die casting
- direct light

assembly				cover			length	radiation dir.		colour	colour temperature			control			
ceiling structure	pendulum	wall structure	ceiling mounting	opal	opal U	microprismatic	individual	down	up+down	individual	2700 K	3000 K	4000 K	switchable	DALI	phase angle/section	Casambi
x	x			x	x	x	x	x	x	x	x	x	x	x	x	x	x

LED

Ra>90

IP20




CONFIGURATION EXAMPLE

- MS surface-mounted luminaire | 2400 mm | black
- 74 W
- 3000 K | 6990 lm
- EVG | DALI
- incl. U-cover opal
- incl. end caps

price on demand

Of course, you can configure our PLANO system entirely according to your wishes and circumstances.





PLANO MS RECESSED LUMINAIRE SYSTEM


- aluminium die casting
- direct light

assembly				cover			length	radiation dir.		colour	colour temperature			control			
ceiling structure	pendulum	wall structure	ceiling mounting	opal	opal U	microprismatic	individual	down	up+down	individual	2700 K	3000 K	4000 K	switchable	DALI	phase angle/section	Casambi
			x	x	x	x	x	x		x	x	x	x	x	x	x	x

LED

Ra>90

IP20



CONFIGURATION EXAMPLE

- MS recessed ceiling luminaire | 2400 mm | black
- 74 W
- 3000 K | 6990 lm
- EVG | DALI
- incl. U-cover opal
- incl. end caps and mounting bracket

price on demand

Of course, you can configure our PLANO system entirely according to your wishes and circumstances.





**PLANO BSH
LUMINAIRE SYSTEM**


- aluminium die casting
- direct light

assembly				cover			length	radiation dir.		colour	colour temperature			control			
ceiling structure	pendulum	wall structure	ceiling mounting	opal	opal U	microprismatic	individual	down	up+down	individual	2700 K	3000 K	4000 K	switchable	DALI	phase angle/section	Casambi
		x		x	x	x	x	x	x	x	x	x	x	x	x	x	x

LED

Ra>90

IP20





CONFIGURATION EXAMPLE

- BSH wall-mounted luminaire | 2400 mm | black
- 174 W,
- 3000 K | 10822 lm
- EVG | DALI
- incl. U-cover opal
- incl. end caps

price on demand

Of course, you can configure our PLANO system entirely according to your wishes and circumstances.






□ ■ □
page 582






□ ■ □
page 583



□ ■ □
page 584

PLANO profiles





PROFILE PLANO ES

- universal light profile
- Uplight for LED strips up to 15 mm wide
- Downlight for LED strips up to 22 mm wide
- incl. LED carrier

Housing Aluminium

Article	Housing Color	Surface	Length	Price
970574	 Black		2000 mm	€ 103.95
970576	 White		2000 mm	€ 151.95
970575	 Black		2500 mm	€ 127.95
970577	 White		2500 mm	€ 191.95
970572	 Aluminium	Anodised	2000 mm	€ 103.95
970573	 Aluminium	Anodised	2500 mm	€ 127.95

Accessories

988111	Plano ES opal indirect cover, 2 m		€ 19.95
988112	Plano ES opal indirect cover, 2.5 m		€ 23.95
988201	PLANO ES longitudinal connector		€ 7.95
988204	PLANO ES corner connector		€ 14.95
988206	PLANO aluminium wall bracket		€ 39.95
988095	PLANO ES and MS - cable suspension set, in pairs		€ 71.95

Accessories for 970572, 970573

988092	PLANO ES end cap surface-mounted, aluminium anodised		€ 19.95
988114	PLANO ES end cap high surface-mounted, black		€ 19.95
988207	Plano ES and MS anodised aluminium uplight dummy cover		€ 111.95

Accessories for 970572, 970574, 970576

988086	PLANO ES and BSH and MS flat opal uplight cover, 2 m		€ 31.95
988088	PLANO ES and BSH high opal cover, 2 m		€ 67.95
988090	PLANO ES and BSH and MS flat microprism uplight cover, 2 m		€ 55.95

Accessories for 970573, 970575, 970577



988087	PLANO ES and BSH and MS flat opal uplight cover, 2.5 m		€ 39.95
988089	PLANO ES and BSH high opal cover, 2.5 m		€ 83.95
988091	PLANO ES and BSH and MS flat microprism uplight cover, 2.5 m		€ 67.95

Accessories for 970574, 970575

988093	PLANO ES end cap surface-mounted, black		€ 19.95
988115	PLANO glued laminated timber end cap high surface-mounted, aluminium anodised		€ 31.95
988208	Plano ES and MS black uplight dummy cover		€ 79.95

Accessories for 970576, 970577

988094	PLANO ES end cap surface-mounted, white		€ 23.95
988209	Plano ES and MS white uplight dummy cover		€ 79.95



PROFILE PLANO MS

- universal light profile
- Uplight for LED strips up to 24 mm wide
- Downlight for LED strips up to 24 mm wide
- incl. LED carrier

Housing

Aluminium

Article	Housing Color	Surface	Length	Price
970580	 Black		2000 mm	€ 219.95
970582	 White		2000 mm	€ 271.95
970581	 Black		2500 mm	€ 271.95
970583	 White		2500 mm	€ 335.95
970578	 Aluminium	Anodised	2000 mm	€ 219.95
970579	 Aluminium	Anodised	2500 mm	€ 271.95

Accessories

988109	PLANO MS end cap high surface-mounted, aluminium anodised		€ 19.95
988110	PLANO MS end cap high surface-mounted, black		€ 19.95
988200	PLANO MS longitudinal connector		€ 7.95
988203	PLANO MS corner connector		€ 14.95
988206	PLANO aluminium wall bracket		€ 39.95

Accessories for 970578, 970579

988102	PLANO MS end cap surface-mounted, aluminium anodised		€ 19.95
988207	Plano ES and MS anodised aluminium uplight dummy cover		€ 111.95
988210	Plano MS anodised aluminium downlight dummy cover		€ 71.95

Accessories for 970578, 970580, 970582

988086	PLANO ES and BSH and MS flat opal uplight cover, 2 m		€ 31.95
988090	PLANO ES and BSH and MS flat microprism uplight cover, 2 m		€ 55.95
988096	PLANO MS flat opal downlight cover, 2 m		€ 39.95
988098	PLANO MS high opal downlight cover, 2 m		€ 79.95
988100	PLANO MS flat microprism downlight cover, 2 m		€ 55.95

Accessories for 970579, 970581, 970583



988087	PLANO ES and BSH and MS flat opal uplight cover, 2.5 m		€ 39.95
988091	PLANO ES and BSH and MS flat microprism uplight cover, 2.5 m		€ 67.95
988097	PLANO MS flat opal downlight cover, 2.5 m		€ 51.95
988099	PLANO MS high opal downlight cover, 2.5 m		€ 99.95
988101	PLANO MS flat microprism downlight cover, 2.5 m		€ 67.95

Accessories for 970580, 970581

988103	PLANO MS end cap surface-mounted, black		€ 23.95
988208	Plano ES and MS black uplight dummy cover		€ 79.95
988211	Plano MS black downlight dummy cover		€ 111.95

Accessories for 970582, 970583

988095	PLANO ES and MS - cable suspension set, in pairs		€ 71.95
988104	PLANO MS end cap surface-mounted, white		€ 23.95
988209	Plano ES and MS white uplight dummy cover		€ 79.95
988212	Plano MS white downlight dummy cover		€ 111.95



PROFILE PLANO BSH

- universal light profile
- Uplight for LED strips up to 31 mm wide
- Downlight for LED strips up to 31 mm wide
- incl. LED carrier

Housing Aluminium

Article	Housing Color	Surface	Length	Price
970586	 Black		2000 mm	€ 159.95
970588	 White		2000 mm	€ 159.95
970587	 Black		2500 mm	€ 199.95
970589	 White		2500 mm	€ 199.95
970584	 Aluminium	Anodised	2000 mm	€ 111.95
970585	 Aluminium	Anodised	2500 mm	€ 135.95

Accessories

988202	PLANO BSH longitudinal connector		€ 7.95
988205	PLANO BSH corner connector		€ 14.95
988206	PLANO aluminium wall bracket		€ 39.95
988095	PLANO ES and MS - cable suspension set, in pairs		€ 71.95

Accessories for 970584, 970585

988106	PLANO glued laminated timber end cap surface-mounted, aluminium anodised		€ 19.95
988115	PLANO glued laminated timber end cap high surface-mounted, aluminium anodised		€ 31.95

Accessories for 970584, 970586, 970588

988086	PLANO ES and BSH and MS flat opal uplight cover, 2 m		€ 31.95
988088	PLANO ES and BSH high opal cover, 2 m		€ 67.95
988090	PLANO ES and BSH and MS flat microprism uplight cover, 2 m		€ 55.95

Accessories for 970585, 970587, 970589

988087	PLANO ES and BSH and MS flat opal uplight cover, 2.5 m		€ 39.95
988089	PLANO ES and BSH high opal cover, 2.5 m		€ 83.95
988091	PLANO ES and BSH and MS flat microprism uplight cover, 2.5 m		€ 67.95

Accessories for 970586, 970587

988107	PLANO glued laminated timber end cap surface-mounted, black		€ 23.95
988116	PLANO glued laminated timber end cap high surface-mounted, black		€ 31.95


Accessories for 970588, 970589

988108	PLANO glued laminated timber end cap surface-mounted, white		€ 23.95
--------	---	--	---------



Lighting design

Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.







SYSTEM COMBO

- 590 concrete profile
 - 596 built-in profile
 - 600 facade profile
 - 604 insulation profile
 - 606 click profile
- 



page 594



page 595



page 598



page 599



page 602



page 603



page 605



page 605



page 608



page 609




page 610

COMBO profiles

COMBO PROFILE SYSTEM – INSTALLATION-FRIENDLY PROFILE-IN-PROFILE SOLUTION

Facades, gardens, living spaces: The patented COMBO PROFILE SYSTEM lends every architectural design a distinctive character. The linear system solution can be integrated into all common building materials. The profile system not only creates perfect light lines in exposed concrete, concrete, brick, stone, plasterboard, thermal insulation, wood, or facade panels — the installation profiles CON-CRETE, DRYWALL, FACADE, and INSULATION can also be quickly and cleanly installed by bricklayers, drywall or facade builders.

Equally important as the appearance is the fact that the lighting solutions can be easily integrated into the building structure even under challenging installation conditions. The lighting insert profile is simply clipped into the installation profiles after construction is completed.






MOUNTING / TRANSFORMER PROFILE CONCRETE


The mounting profile is installed during formwork construction and provides sufficient space for the luminaire profile as well as additional cabling. Optional plaster trim makes all work around the light line easier.

The transformer profile is used to house power supplies, allowing them to be concealed behind the luminaire in the case of long light lines or different circuit configurations.




INSTALLATION INSTRUCTIONS CONCRETE




1. Planning of mounting / transformer profile





2. Installation, finishing work



3. Installation of luminaire profile and power supply





PROFILE, SERIES COMBO, CONCRETE, MOUNTING PROFILE

Housing Aluminium



Article	Housing Color	Length	Price
970800	 Black	2000 mm	€ 91.95
970801	 White	2000 mm	€ 91.95
970802	 Black	3000 mm	€ 114.95
970803	 White	3000 mm	€ 114.95

Accessories

988180	Combo plaster moulding - flush, polystyrene 24x29x1000, white		€ 6.95
988179	Combo plaster moulding - plaster edge, polystyrene 40x29x1000, white		€ 6.95
988167	Combo concrete mounting bar wood, 1 m		€ 12.95
988168	Combo concrete mounting bar wood, 2 m		€ 25.95
970811	Combo connection profile for indoor plastering, natural aluminium, 2.5 m		€ 62.95
970812	Combo connection profile for indoor plastering, white, 2.5 m		€ 91.95
970810	Combo connection profile for indoor plastering, black, 2.5 m		€ 91.95
970814	Combo connection profile for filling jobs, natural aluminium, 2 m		€ 10.95
970818	Combo connection profile for filling jobs, white, 2 m		€ 22.95
970816	Combo connection profile for filling jobs, black, 2 m		€ 22.95
988133	Combo concrete end cap 2 pcs. mounting profile with edge covering, white		€ 4.95
988132	Combo concrete end cap 2 pcs. mounting profile with edge covering, black		€ 4.95
988165	Combo concrete connecting piece mounting profile, white		€ 4.95
988164	Combo concrete connecting piece mounting profile, black		€ 4.95
988161	Plano concrete connector and guard rail for concrete recessed profile		€ 17.95



Power supply units
You can find the right power supply unit in various designs and with the required voltage and power in the »Power supply units« section.



PROFILE, SERIES COMBO, CONCRETE, TRANSFORMER PROFILE

Housing Aluminium

Article	Housing Color	Length	Price
970804	Black	1000 mm	€ 68.95
970805	White	1000 mm	€ 68.95
970806	Black	2000 mm	€ 137.95
970807	White	2000 mm	€ 137.95
970808	Black	3000 mm	€ 206.95
970809	White	3000 mm	€ 206.95

Accessories

988180	Combo plaster moulding - flush, polystyrene 24x29x1000, white		€ 6.95
988179	Combo plaster moulding - plaster edge, polystyrene 40x29x1000, white		€ 6.95
988167	Combo concrete mounting bar wood, 1 m		€ 12.95
988168	Combo concrete mounting bar wood, 2 m		€ 25.95
970811	Combo connection profile for indoor plastering, natural aluminium, 2.5 m		€ 62.95
970812	Combo connection profile for indoor plastering, white, 2.5 m		€ 91.95
970810	Combo connection profile for indoor plastering, black, 2.5 m		€ 91.95
970814	Combo connection profile for filling jobs, natural aluminium, 2 m		€ 10.95
970818	Combo connection profile for filling jobs, white, 2 m		€ 22.95
970816	Combo connection profile for filling jobs, black, 2 m		€ 22.95
988135	Combo concrete end cap 2 pcs. transformer profile with edge covering, white		€ 4.95
988134	Combo concrete end cap 2 pcs. transformer profile with edge covering, black		€ 4.95
988163	Combo concrete connecting piece mounting profile - transformer profile, white		€ 4.95
988162	Combo concrete connecting piece mounting profile - transformer profile, black		€ 4.95




Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.

MOUNTING & TRANSFORMER PROFILE DRYWALL


The mounting profile can be neatly integrated on site and provides sufficient space for concealed cable routing – perfect for preparing light lines in drywall, plastered brick, thermal insulation, wood, fiberboard, etc. The luminaire profile is simply clipped in at the end.

For direct wall connection, the mounting flanges feature a predetermined breaking point for a clean separation. The transformer profile is used to house power supplies, allowing them to be concealed behind the luminaire in the case of long light lines or different circuit configurations.




INSTALLATION INSTRUCTIONS BRICK, PLASTERBOARD, WOOD




1. Planning of mounting / transformer profile



2. Installation, finishing work



3. Installation of luminaire profile and power supply





PROFILE, SERIES COMBO, BUILT-IN, MOUNTING PROFILE

Housing
 Aluminium


Article	Housing Color	Length	Price
970820	 Aluminium	1000 mm	€ 31.95
970821	 Black	1000 mm	€ 43.95
970822	 White	1000 mm	€ 43.95
970823	 Aluminium	2000 mm	€ 64.95
970824	 Black	2000 mm	€ 86.95
970825	 White	2000 mm	€ 86.95
970826	 Aluminium	3000 mm	€ 96.95
970827	 Black	3000 mm	€ 130.95
970828	 White	3000 mm	€ 130.95

Accessories

988180	Combo plaster moulding - flush, polystyrene 24x29x1000, white		€ 6.95
988179	Combo plaster moulding - plaster edge, polystyrene 40x29x1000, white		€ 6.95
970814	Combo connection profile for filling jobs, natural aluminium, 2 m		€ 10.95
970818	Combo connection profile for filling jobs, white, 2 m		€ 22.95
970816	Combo connection profile for filling jobs, black, 2 m		€ 22.95
988174	Combo connector and fall protection		€ 17.95
988177	Combo connector set 2 pcs. 0/0, natural aluminium		€ 9.95
988178	Combo connector set 2 pcs. 0/90, natural aluminium		€ 9.95
988175	Combo connector set 2 pcs. 90/0, natural aluminium		€ 24.95
988137	Combo built-in/facade/insulation end cap 2 pcs. mounting profile without bar, white		€ 4.95
988136	Combo built-in/facade/insulation end cap 2 pcs. mounting profile without bar, black		€ 4.95



Power supply units
 You can find the right power supply unit in various designs and with the required voltage and power in the »Power supply units« section.



PROFILE, SERIES COMBO, BUILT-IN, TRANSFORMER PROFILE

Housing Aluminium

Article	Housing Color	Length	Price
970833	Aluminium	1000 mm	€ 45.95
970834	Black	1000 mm	€ 85.95
970835	White	1000 mm	€ 85.95
970836	Aluminium	2000 mm	€ 91.95
970837	Black	2000 mm	€ 172.95
970838	White	2000 mm	€ 172.95
970839	Aluminium	3000 mm	€ 137.95
970840	Black	3000 mm	€ 218.95
970841	White	3000 mm	€ 218.95

Accessories

988180	Combo plaster moulding - flush, polystyrene 24x29x1000, white		€ 6.95
988179	Combo plaster moulding - plaster edge, polystyrene 40x29x1000, white		€ 6.95
970814	Combo connection profile for filling jobs, natural aluminium, 2 m		€ 10.95
970818	Combo connection profile for filling jobs, white, 2 m		€ 22.95
970816	Combo connection profile for filling jobs, black, 2 m		€ 22.95
988174	Combo connector and fall protection		€ 17.95
988177	Combo connector set 2 pcs. 0/0, natural aluminium		€ 9.95
988178	Combo connector set 2 pcs. 0/90, natural aluminium		€ 9.95
988175	Combo connector set 2 pcs. 90/0, natural aluminium		€ 24.95
988141	Combo built-in/facade/insulation end cap 2 pcs. transformer profile, white		€ 4.95
988138	Combo built-in/facade/insulation end cap 2 pcs. transformer profile, black		€ 4.95
988140	Combo built-in/facade/insulation end cap 2 pcs. connecting piece mounting profile - transformer profile, white		€ 4.95
988139	Combo built-in/facade/insulation end cap 2 pcs. connecting piece mounting profile - transformer profile, black		€ 4.95



5-year guarantee

Benefit from the maximum quality promise:

All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.


MOUNTING / TRANSFORMER PROFILE
FACADE



The 3 mm mounting profile enables lighting solutions in areas with low installation height, such as Trespa or aluminium facade panels. Installation takes place behind the facade panel; any height difference of more than 3 mm can be adjusted during installation of the light profiles using the mounting clips. In combination with a thermal insulation connection profile CT, the 3 mm mounting profile can also be subsequently inserted into the insulation before plastering work. Thanks to the thermal and mechanical separation from the luminaire profile, cracks along the light line are avoided.


By adding the 3 mm transformer profile, users can—beyond the applications of the 3 mm mounting profile—also integrate the corresponding power supplies into the light line. This allows for on-site replacement if needed. The mechanical separation between the light and transformer profiles ensures that damage, especially on plastered facades, is prevented.



INSTALLATION INSTRUCTIONS INSULATION AND FACADE PANELS



INSTALLATION INSTRUCTIONS INSULATION AND PLASTER



PROFILES, COMBO SERIES, FACADE, TRANSFORMER PROFILE

Housing
 Aluminium



Article	Housing Color	Length	Price
970869	Black	1000 mm	€ 85.95
970870	White	1000 mm	€ 85.95
970871	Black	2000 mm	€ 172.95
970872	White	2000 mm	€ 172.95

Accessories

970814	Combo connection profile for filling jobs, natural aluminium, 2 m		€ 10.95
970816	Combo connection profile for filling jobs, black, 2 m		€ 22.95
970818	Combo connection profile for filling jobs, white, 2 m		€ 22.95
988136	Combo built-in/facade/insulation end cap 2 pcs. mounting profile without bar, black		€ 4.95
988137	Combo built-in/facade/insulation end cap 2 pcs. mounting profile without bar, white		€ 4.95
988138	Combo built-in/facade/insulation end cap 2 pcs. transformer profile, black		€ 4.95
988139	Combo built-in/facade/insulation end cap 2 pcs. connecting piece mounting profile - transformer profile, black		€ 4.95
988140	Combo built-in/facade/insulation end cap 2 pcs. connecting piece mounting profile - transformer profile, white		€ 4.95
988141	Combo built-in/facade/insulation end cap 2 pcs. transformer profile, white		€ 4.95
988169	Combo connection profile with fabric for levelling work, 3mm, 2m, orange		€ 22.95
988175	Combo connector set 2 pcs. 90/0, natural aluminium		€ 24.95
988176	Combo connector set of 2 with angle joint 0/20-160°, natural aluminium		€ 9.95
988177	Combo connector set 2 pcs. 0/0, natural aluminium		€ 9.95
988178	Combo connector set 2 pcs. 0/90, natural aluminium		€ 9.95
988179	Combo plaster moulding - plaster edge, polystyrene 40x29x1000, white		€ 6.95
988180	Combo plaster moulding - flush, polystyrene 24x29x1000, white		€ 6.95



Power supply units
 You can find the right power supply unit in various designs and with the required voltage and power in the »Power supply units« section.



PROFILES, COMBO SERIES, FAÇADE, MOUNTING PROFILE

Housing

Aluminium

Article	Housing Color	Length	Price
970829	Black	2000 mm	€ 86.95
970830	White	2000 mm	€ 86.95
970831	Black	3000 mm	€ 130.95
970832	White	3000 mm	€ 130.95

Accessories

970814	Combo connection profile for filling jobs, natural aluminium, 2 m		€ 10.95
970816	Combo connection profile for filling jobs, black, 2 m		€ 22.95
970818	Combo connection profile for filling jobs, white, 2 m		€ 22.95
988136	Combo built-in/facade/insulation end cap 2 pcs. mounting profile without bar, black		€ 4.95
988137	Combo built-in/facade/insulation end cap 2 pcs. mounting profile without bar, white		€ 4.95
988138	Combo built-in/facade/insulation end cap 2 pcs. transformer profile, black		€ 4.95
988139	Combo built-in/facade/insulation end cap 2 pcs. connecting piece mounting profile - transformer profile, black		€ 4.95
988140	Combo built-in/facade/insulation end cap 2 pcs. connecting piece mounting profile - transformer profile, white		€ 4.95
988141	Combo built-in/facade/insulation end cap 2 pcs. transformer profile, white		€ 4.95
988169	Combo connection profile with fabric for levelling work, 3mm, 2m, orange		€ 22.95
988175	Combo connector set 2 pcs. 90/0, natural aluminium		€ 24.95
988176	Combo connector set of 2 with angle joint 0/20-160°, natural aluminium		€ 9.95
988177	Combo connector set 2 pcs. 0/0, natural aluminium		€ 9.95
988178	Combo connector set 2 pcs. 0/90, natural aluminium		€ 9.95
988179	Combo plaster moulding - plaster edge, polystyrene 40x29x1000, white		€ 6.95
988180	Combo plaster moulding - flush, polystyrene 24x29x1000, white		€ 6.95





Technical data sheet

New in the onlineshop: The technical data sheets offer even more information: Light and energy data, light distribution curves, dimensional drawings and more.

**MOUNTING / TRANSFORMER PROFILE
INSULATION**

The mounting profile allows for easy installation of recessed profiles into thermal insulation and can be equipped with all profiles after the surface has been finished. The mounting profile allows for easy installation of recessed profiles into thermal insulation and can be equipped with all profiles after the surface has been finished.






PROFILES, COMBO SERIES, INSULATION, MOUNTING PROFILE

Housing EPS Length 2000 mm

Article	Housing Color	Price
988170	 Black	€ 402.95
988171	 White	€ 402.95

Accessories

988180	Combo plaster moulding - flush, polystyrene 24x29x1000, white		€ 6.95
988178	Combo connector set 2 pcs. 0/90, natural aluminium		€ 9.95
988175	Combo connector set 2 pcs. 90/0, natural aluminium		€ 24.95
988177	Combo connector set 2 pcs. 0/0, natural aluminium		€ 9.95
988137	Combo built-in/facade/insulation end cap 2 pcs. mounting profile without bar, white		€ 4.95
988136	Combo built-in/facade/insulation end cap 2 pcs. mounting profile without bar, black		€ 4.95



PROFILES, COMBO SERIES, INSULATION, TRANSFORMER PROFILE

Housing EPS Length 1000 mm

Article	Housing Color	Price
988172	 Black	€ 218.95
988173	 White	€ 218.95

Accessories


988180	Combo plaster moulding - flush, polystyrene 24x29x1000, white		€ 6.95
988178	Combo connector set 2 pcs. 0/90, natural aluminium		€ 9.95
988175	Combo connector set 2 pcs. 90/0, natural aluminium		€ 24.95
988177	Combo connector set 2 pcs. 0/0, natural aluminium		€ 9.95
988141	Combo built-in/facade/insulation end cap 2 pcs. transformer profile, white		€ 4.95
988138	Combo built-in/facade/insulation end cap 2 pcs. transformer profile, black		€ 4.95
988140	Combo built-in/facade/insulation end cap 2 pcs. connecting piece mounting profile - transformer profile, white		€ 4.95
988139	Combo built-in/facade/insulation end cap 2 pcs. connecting piece mounting profile - transformer profile, black		€ 4.95

LUMINAIRE PROFILE

To complete your light lines within the various transformer and mounting profiles, the extensive range of accessories leaves nothing to be desired. Tools such as connectors with fall protection or cable holders significantly simplify installation. Depending on the nature of the transition to the mounting / transformer profile, you can cover it using the LT-0-20 or accentuate the resulting shadow gap with the LU-02-20. As a general rule, all luminaire profiles should be connected using connectors to prevent mechanical stress on the LED strips caused by differing expansion.



INSTALLATION INSTRUCTIONS LUMINAIRE PROFILE





PROFILE, SERIES COMBO, CLICK U-PROFILE

Housing		Aluminium			Length	Price
Article	Housing Color	Surface				
970848	White	Anodised			1000 mm	€ 27.95
970842	Silver				1000 mm	€ 25.95
970845	Black				1000 mm	€ 27.95
970849	White	Anodised			2000 mm	€ 54.95
970843	Silver				2000 mm	€ 49.95
970846	Black				2000 mm	€ 54.95
970850	White	Anodised			3000 mm	€ 82.95
970844	Silver				3000 mm	€ 75.95
970847	Black				3000 mm	€ 82.95

Accessories				
988126	Combo cover, H-02-20, high, milky, 1 m			€ 14.95
988127	Combo cover, H-02-20, high, milky, 2 m			€ 29.95
988128	Combo cover, H-02-20, high, milky, 3 m			€ 44.95
988122	Combo cover, B-02-20, wide, milky, 1 m			€ 11.95
988120	Combo cover, B-02-20, wide, milky, 2 m			€ 22.95
988121	Combo cover, B-02-20, wide, milky, 3 m			€ 33.95
988123	Combo click cover V4-HL25 opal, 1 m			€ 9.95
988124	Combo click cover V4-HL25 opal, 2 m			€ 17.95
988125	Combo click cover V4-HL25 opal, 3 m			€ 27.95
988148	Combo end cap 2 pcs. U-light profile, P-LU-02-20, grey			€ 6.45
988146	Combo end cap 2 pcs. U-light profile, P-LU-02-20, white			€ 4.95
988145	Combo end cap 2 pcs. U-light profile, P-LU-02-20, black			€ 4.95
988147	Combo end cap 2 pcs. U-light profile, B-LU-02-20, white			€ 10.95
988142	Combo end cap 2 pcs. U-light profile, H-LU-02-20, grey			€ 6.45
988144	Combo end cap 2 pcs. U-light profile, H-LU-02-20, white			€ 6.45
988143	Combo end cap 2 pcs. U-light profile, H-LU-02-20, black			€ 6.45
988184	Combo set 10 pcs. Mounting clip, height-adjustable V1, 10mm, blue			€ 23.95
988185	Combo set 10 pcs. Mounting clip, height-adjustable V2, 10mm, black			€ 23.95
988186	Combo set 10 pcs. Mounting clip, height-adjustable V3, 10mm, yellow			€ 23.95



LED stripes

Suitable LED strips can be found in the LED Strips chapter – available in various voltages and designs for indoor and outdoor applications.



PROFILE, SERIES COMBO, CLICK T-PROFILE

Housing

Aluminium

Article	Housing Color	Surface	Length	Price
970866	White	Anodised	1000 mm	€ 31.95
970860	Silver		1000 mm	€ 28.95
970863	Black		1000 mm	€ 31.95
970867	White	Anodised	2000 mm	€ 64.95
970861	Silver		2000 mm	€ 57.95
970864	Black		2000 mm	€ 64.95
970868	White	Anodised	3000 mm	€ 96.95
970862	Silver		3000 mm	€ 85.95
970865	Black		3000 mm	€ 96.95

Accessories

988122	Combo cover, B-02-20, wide, milky, 1 m		€ 11.95
988120	Combo cover, B-02-20, wide, milky, 2 m		€ 22.95
988121	Combo cover, B-02-20, wide, milky, 3 m		€ 33.95
988123	Combo click cover V4-HL-25 opal, 1 m		€ 9.95
988124	Combo click cover V4-HL-25 opal, 2 m		€ 17.95
988125	Combo click cover V4-HL-25 opal, 3 m		€ 27.95
988126	Combo cover, H-02-20, high, milky, 1 m		€ 14.95
988127	Combo cover, H-02-20, high, milky, 2 m		€ 29.95
988128	Combo cover, H-02-20, high, milky, 3 m		€ 44.95
988158	Combo end cap 2 pcs. T-light profile, P-LT-02-20, grey		€ 6.45
988160	Combo end cap 2 pcs. T-light profile, P-LT-02-20, white		€ 6.45
988159	Combo end cap 2 pcs. T-light profile, P-LT-02-20, black		€ 6.45
988155	Combo end cap 2 pcs. T-light profile, H-LT-02-20, grey		€ 6.45
988157	Combo end cap 2 pcs. T-light profile, H-LT-02-20, white		€ 6.45
988156	Combo end cap 2 pcs. T-light profile, H-LT-02-20, black		€ 6.45
988198	Combo click/flat/hinge wing recessed mounting spring set (2 pieces)		€ 3.25
988184	Combo set 10 pcs. Mounting clip, height-adjustable V1, 10mm, blue		€ 23.95
988185	Combo set 10 pcs. Mounting clip, height-adjustable V2, 10mm, black		€ 23.95
988186	Combo set 10 pcs. Mounting clip, height-adjustable V3, 10mm, yellow		€ 23.95



LED stripes

Suitable LED strips can be found in the LED Strips chapter – available in various voltages and designs for indoor and outdoor applications.



PROFILE, SERIES COMBO, CLICK U-PROFILE FLAT

Housing

Aluminium

Article	Housing Color	Surface	Length	Price
970857	White	Anodised	1000 mm	€ 27.95
970851	Silver		1000 mm	€ 25.95
970854	Black		1000 mm	€ 27.95
970858	White	Anodised	2000 mm	€ 54.95
970852	Silver		2000 mm	€ 49.95
970855	Black		2000 mm	€ 54.95
970859	White	Anodised	3000 mm	€ 82.95
970853	Silver		3000 mm	€ 75.95
970856	Black		3000 mm	€ 82.95

Accessories

988123	Combo click cover V4-HL25 opal, 1 m		€ 9.95
988124	Combo click cover V4-HL25 opal, 2 m		€ 17.95
988125	Combo click cover V4-HL25 opal, 3 m		€ 27.95
988126	Combo cover, H-02-20, high, milky, 1 m		€ 14.95
988127	Combo cover, H-02-20, high, milky, 2 m		€ 29.95
988128	Combo cover, H-02-20, high, milky, 3 m		€ 44.95
988149	Combo end cap, metallised, 1 pc., suitable for H-02-20 high cover		€ 6.95
988150	Combo end cap, black, 1 pc., suitable for H-02-20 high cover		€ 3.45
988151	Combo end cap, white, 1 pc., suitable for H-02-20 high cover		€ 3.45
988152	Combo end cap, metallised, 1 pc., suitable for V4-HL25 opal cover		€ 6.95
988153	Combo end cap, black, 1 pc., suitable for V4-HL25 opal cover		€ 3.45
988154	Combo end cap, white, 1 pc., suitable for V4-HL25 opal cover		€ 3.45
988184	Combo set 10 pcs. Mounting clip, height-adjustable V1, 10mm, blue		€ 23.95
988185	Combo set 10 pcs. Mounting clip, height-adjustable V2, 10mm, black		€ 23.95
988186	Combo set 10 pcs. Mounting clip, height-adjustable V3, 10mm, yellow		€ 23.95



LED stripes

Suitable LED strips can be found in the LED Strips chapter – available in various voltages and designs for indoor and outdoor applications.





ALUMINIUM PROFILES

- 614 linear light in 5 steps
- 618 assembly
- 620 homogeneous light image
- 622 U-profiles - flat + high - built-in / built-on
- 644 T-profiles - flat + high - built in
- 658 H- and groove-profiles
- 662 step/plinth/angle/corner-profiles - built-in/built-on
- 684 dry construction profiles
- 704 tile profiles
- 712 profiles for outdoor usw - walkable/trafficable

LINEAR LIGHT IN 5 STEPS

STEP BY STEP TO BECOMING A LINEAR LIGHT

PROFESSIONAL!

It has never been quicker and easier to put together an individually and perfectly coordinated linear light in max. 5 steps. Test how quickly and easily you can put your personal project into practice.

1

CHOOSE YOUR PROFILE

Whether for indoor or outdoor use, for wide or narrow LED stripes, whether the profile is to be should be low or high. Matching to this you can choose between different shapes and light transmittance of the covers.

2

CHOOSE THE RIGHT LED STRIPE

You can choose between strips for indoor or outdoor use, with one or more light colours, high-power strips for basic lighting or fewer lumens for ambient lighting. Various cut sizes and LED spacing also perfectly round off our range here.



3

SELECT THE REQUIRED POWER SUPPLY

In addition to the various protection classes for the respective place of use and voltages, you can choose from different designs and power classes. Our range is complemented by power supplies that can be dimmed directly or controlled via Dali, KNX or 1-10V.

4

DO YOU NEED A CONTROLLER TO STEER?

In this category, you can select the appropriate control controller or LED dimmer according to requirements and customer wishes. Whether control via radio, smartphone, DMX, Dali, etc. – almost no [control] wishes remain unfulfilled!



5

ACCESSORIES, MOUNTING MATERIAL & CO

In the last step, you will find everything that makes installation easier, faster and more comfortable and gives the linear desired light a perfect finish.



aluminium profiles



 
page 624




 
page 660




page 664




page 668




page 670



  
page 672




 
page 674




page 676




page 678




 
page 686



 
page 688




 
page 690



 page 692



 page 694



 page 696



 page 698



 page 700



 page 702



  page 706



 page 714



 page 716



 page 718





ASSEMBLY FOR PROFILES AND STRIPES

We provide our products individually made to measure on request.
You will receive the prices on request.



989100 – service package I – profile cut

profile is shortened to desired length, tolerance ± 1 mm | sawing loss 4 mm

989105 – drill hole end cap / profile

hole for cable outlet in end cap or profile



989200 – service package II – cover cut

cover is shortened to desired length, tolerance ± 1 mm | sawing loss 4 mm



989300 – service package III – stripe cut

LED stripe is adapted to desired length, taking into account segment and maximum total length, including soldering of a cable lead of the desired length and open, tinned wire ends

989305 – cable – connecting cable / cores 1 channel

989310 – cable – connecting cable / cores 2 channel

989315 – cable – connecting cable / cores 3 + 4 channel

989320 – cable – mini cable / cores 1 - 4 channel

989325 – cable – connecting cable / cores 5 channel

989301 – 2nd connecting cable

attachment of a 2nd connecting cable / cores for further connection with open tinned wire ends

989302 – connecting cable

attaching / soldering a fixed connection line / cores between 2 stripe pieces

[max. 1m connection line / cores incl., a longer connection will be charged by the metre]

original length and max. total length of the strip to be operated may not be exceeded by sections be exceeded

989350 – IP surcharge – sealing stripe

sealing a shortened IP stripe / gluing an end cap



989400 – service package IV – complete assembly

bringing together and assembling all components into a finished luminaire
incl. function test and cable flag

[for desired length, please add 2cm to the cut length of the LED stripe segment
for connection space, length tolerance ± 2 mm]




HOMOGENEOUS LIGHT IMAGE

How to achieve a homogeneous light image

In combination with a milky 40% cover and a matching LED stripe, a homogeneous light image can be created. The distance [pixel pitch] between the LEDs and the cover is decisive.

The rule of thumb here is:

The distance between the LEDs should be smaller than the distance between the LEDs and the cover.



PROFILE DESCRIPTION

mounting type: A = built-on
 E = built-in

Width of the series [10 profile] / of the matching LED stripe

AU - 01 - 10

basic form


series

TRANSLUCENCY / LIGHT TRANSMISSION

95% clear

75% mat

40% milky




Presentation of various LED strips with different pixel pitches in combination with three levels of cover light transmission. This selection illustrates the visual differences between various LED strips when combined with different covers in the AU-01-10 aluminum profile with a profile height of 7 mm.


120 LED/m
cutting option 50 mm / 6 LED



240 LED/m
cutting option 25 mm / 6 LED



700LED/m
cutting option 10 mm / 7 LED



COB 480 LED/m
cutting option 50 mm / 24 LED





With the kind support of BEST Bellemann Elektro Service Team GmbH, Rauenberg-Malschenberg



U- AND T-PROFILES

The profiles of these series are available in various designs. Thanks to their universal profile shape, they can be used flexibly in almost all areas. Thanks to their profile construction, they are ideally suited for the cover cut edges.




AU-01-05

·for LED strips up to 5.7 mm wide

Housing Aluminium
Length 2000 mm

Article	Housing Color	Surface	Price
970081	 Silver	Matt / Anodised	€ 13.95
970085	 White	Matt / Powder-coated	€ 12.95



Cover | PMMA - Polymethyl methacrylate

Clear

Milky



2 m

983551**983555****€ 9.95**

2 m

984055**€ 9.95**




2 m

984555**€ 9.95****end caps set** | 2 pieces | Plastic | € 3.95

White

Grey

Black

**978660****978661****978662****979160****979161****979162****979660****979661****979662**




AU-02-05

·for LED strips up to 5.7 mm wide

Housing Aluminium
 Length 2000 mm

Article	Housing Color	Surface	Price
970181	 Silver	Matt / Anodised	€ 14.95
970183	 Black	Matt / Anodised	€ 14.95
970185	 White	Matt / Powder-coated	€ 14.95



Cover | PMMA - Polymethyl methacrylate

Clear Milky

2 m **983551** **983555** € 9.952 m **984055** € 9.952 m **984555** € 9.95**end caps set** | 2 pieces | Plastic | € 3.95

White Grey Black

**978670** **978671** **978672****979170** **979171** **979172****979670** **979671**




AU-01-08

·for LED strips up to 9.3 mm wide

Housing Aluminium
 Length 2000 mm

Article	Housing Color	Surface	Price
970001	 Silver	Matt / Anodised	€ 18.95
970003	 Black	Matt / Anodised	€ 18.95
970005	 White	Matt / Powder-coated	€ 18.95







Cover | PMMA - Polymethyl methacrylate

Clear Matt Milky

2 m **983001** **983003** **983005** € 13.952 m **983501** **983503** **983505** € 13.952 m **984003** **984005** € 13.952 m **984503** **984505** € 13.95**end caps set** | 2 pieces | Plastic | € 3.95

White Grey Black

**978000** **978001** **978002****978500** **978501** **978502****979080** **979081** **979082****979580** **979581** **979582****930347** 3M double-sided adhesive tape 50,000x12x0.2 mm

€ 25.95

987002 Set of 2 retaining clips for AU-08

€ 3.45

987080 Universal holding clip mount (swivel) set of 2 pieces

€ 18.95






AU-02-08

·for LED strips up to 9.3 mm wide

Housing Aluminium
Length 2000 mm

Article	Housing Color	Surface	Price
970101	 Silver	Matt / Anodised	€ 22.95
970103	 Black	Matt / Anodised	€ 22.95
970105	 White	Matt / Powder-coated	€ 22.95



Cover | PMMA - Polymethyl methacrylate

Clear

Matt

Milky

2 m **983001** **983003** **983005** € 13.952 m **983501** **983503** **983505** € 13.952 m **984003** **984005** € 13.952 m **984503** **984505** € 13.95**end caps set** | 2 pieces | Plastic | € 3.95

White

Grey

Black

**978040** **978041** **978042****978540** **978541** **978542****979100** **979101** **979102****979600** **979601** **979602****930347** 3M double-sided adhesive tape 50,000x12x0.2 mm

€ 25.95

987002 Set of 2 retaining clips for AU-08

€ 3.45

987080 Universal holding clip mount (swivel) set of 2 pieces

€ 18.95






AU-01-10

·for LED strips up to 11.3 mm wide

Housing Aluminium

Article	Housing Color	Surface	Length	Price
970021	 Silver	Matt / Anodised	2000 mm	€ 18.95
970023	 Black	Matt / Anodised	2000 mm	€ 18.95
970028	 Silver	Matt / Anodised	3000 mm	€ 28.95
970025	 White	Matt / Powder-coated	2000 mm	€ 18.95








Cover | PMMA - Polymethyl methacrylate

Clear Matt Milky

				
2 m	983011	983013	983015	€ 13.95
3 m	983016	983017	983018	€ 20.95
				
2 m	983511	983513	983515	€ 13.95
3 m	983516	983517	983518	€ 20.95
				
2 m		984013	984015	€ 13.95
3 m		984017	984018	€ 20.95
				
2 m		984513	984515	€ 13.95
3 m		984517	984518	€ 20.95
				
2 m	985011			€ 13.95
3 m	985016			€ 20.95

end caps set | 2 pieces | Plastic | € 3.95

White Grey Black

**978010 978011 978012****978510 978511 978512****979000 979001 979002****979500 979501 979502****980000 980001 980002****930348** 3M double-sided adhesive tape 50,000x15x0.20 mm**€ 30.95****987004** Set of 2 retaining clips for AU-10**€ 3.45****987080** Universal holding clip mount (swivel) set of 2 pieces**€ 18.95****Lighting design**

Interested in our lighting design service?

Your contact person will be happy to answer any questions you may have.




AU-02-10

·for LED strips up to 11.3 mm wide

Housing Aluminium

Article	Housing Color	Surface	Length	Price
970121	 Silver	Matt / Anodised	2000 mm	€ 22.95
970123	 Black	Matt / Anodised	2000 mm	€ 22.95
970128	 Silver	Matt / Anodised	3000 mm	€ 35.95
970125	 White	Matt / Powder-coated	2000 mm	€ 22.95



Cover | PMMA - Polymethyl methacrylate

Clear Matt Milky



2 m	983011	983013	983015	€ 13.95
3 m	983016	983017	983018	€ 20.95



2 m	983511	983513	983515	€ 13.95
3 m	983516	983517	983518	€ 20.95



2 m		984013	984015	€ 13.95
3 m		984017	984018	€ 20.95



2 m		984513	984515	€ 13.95
3 m		984517	984518	€ 20.95



2 m	985011			€ 13.95
3 m	985016			€ 20.95

end caps set | 2 pieces | Plastic | € 3.95

White Grey Black



978050	978051	978052
---------------	---------------	---------------



978550	978551	978552
---------------	---------------	---------------



979020	979021	979022
---------------	---------------	---------------



979520	979521	979522
---------------	---------------	---------------



980010	980011	980012
---------------	---------------	---------------

930348 3M double-sided adhesive tape 50,000x15x0.20 mm**€ 30.95****987004** Set of 2 retaining clips for AU-10**€ 3.45****987080** Universal holding clip mount (swivel) set of 2 pieces**€ 18.95****Onlineshop**

You can find more information about the products in the onlineshop:
Detailed images, videos, project reports, LDT files, EPREL data sheets and more.




AU-01-12

·for LED strips up to 13.3 mm wide

Housing Aluminium

Article	Housing Color	Surface	Length	Price
970041	 Silver	Matt / Anodised	2000 mm	€ 22.95
970043	 Black	Matt / Anodised	2000 mm	€ 22.95
970048	 Silver	Matt / Anodised	3000 mm	€ 33.95
970045	 White	Matt / Powder-coated	2000 mm	€ 22.95



Cover | PMMA - Polymethyl methacrylate

Clear Matt Milky



1 m	983020	983022	983024	€ 6.45
2 m	983021	983023	983025	€ 13.95
3 m	983028	983027	983026	€ 20.95



1 m	983520	983522	983524	€ 6.45
2 m	983521	983523	983525	€ 13.95
3 m	983527		983526	€ 20.95




1 m		984022	984024	€ 6.45
2 m		984023	984025	€ 13.95
3 m			984026	€ 20.95




1 m		984522	984524	€ 6.45
2 m		984523	984525	€ 13.95
3 m			984526	€ 20.95

end caps set | 2 pieces | Plastic | € 3.95


White Grey Black




978020	978021	978022
---------------	---------------	---------------



978520	978521	978522
---------------	---------------	---------------



979010	979011	979012
---------------	---------------	---------------



979510	979511	979512
---------------	---------------	---------------

930348 3M double-sided adhesive tape 50,000x15x0.20 mm**€ 30.95****987006** Set of 2 retaining clips for AU-12**€ 3.45****987080** Universal holding clip mount (swivel) set of 2 pieces**€ 18.95**




AU-02-12

·for LED strips up to 13.3 mm wide

Housing Aluminium

Article	Housing Color	Surface	Length	Price
970141	 Silver	Matt / Anodised	2000 mm	€ 25.95
970143	 Black	Matt / Anodised	2000 mm	€ 25.95
970148	 Silver	Matt / Anodised	3000 mm	€ 35.95
970145	 White	Matt / Powder-coated	2000 mm	€ 25.95



Cover | PMMA - Polymethyl methacrylate

Clear Matt Milky

				
2 m	983021	983023	983025	€ 13.95
3 m	983028	983027	983026	€ 20.95






				
2 m	983521	983523	983525	€ 13.95
3 m	983527		983526	€ 20.95

				
2 m		984023	984025	€ 13.95
3 m			984026	€ 20.95

				
2 m		984523	984525	€ 13.95
3 m			984526	€ 20.95

end caps set | 2 pieces | Plastic | € 3.95

White Grey Black

**978060 978061 978062****978560 978561 978562****979030 979031 979032****979530 979531 979532****930348** 3M double-sided adhesive tape 50,000x15x0.20 mm**€ 30.95****987006** Set of 2 retaining clips for AU-12**€ 3.45****987080** Universal holding clip mount (swivel) set of 2 pieces**€ 18.95**




AU-01-15

·For LED strips up to 16.3 mm wide

Housing Aluminium

Article	Housing Color	Surface	Length	Price
970061	 Silver	Matt / Anodised	2000 mm	€ 22.95
970063	 Black	Matt / Anodised	2000 mm	€ 22.95
970068	 Silver	Matt / Anodised	3000 mm	€ 33.95
970065	 White	Matt / Powder-coated	2000 mm	€ 22.95







Cover | PMMA - Polymethyl methacrylate

Clear Matt Milky

2 m **983031** **983033** **983035** € 15.953 m **983038** **983037** **983036** € 22.952 m **983531** **983533** **983535** € 15.953 m **983539** **983536** € 22.952 m **984033** **984035** € 15.953 m **984036** € 22.952 m **984533** **984535** € 15.95**end caps set** | 2 pieces | Plastic | € 3.95

White Grey Black

**978030** **978031** **978032****978530** **978531** **978532****979090** **979091** **979092****979590** **979591** **979592****930349** 3M double-sided adhesive tape 50,000x20x0.20 mm

€ 38.95

987008 Set of 2 retaining clips for AU-15

€ 3.45

987080 Universal holding clip mount (swivel) set of 2 pieces

€ 18.95






AU-02-15

·For LED strips up to 16.3 mm wide

Housing Aluminium




Article	Housing Color	Surface	Length	Price
970161	 Silver	Matt / Anodised	2000 mm	€ 25.95
970163	 Black	Matt / Anodised	2000 mm	€ 25.95
970168	 Silver	Matt / Anodised	3000 mm	€ 35.95
970165	 White	Matt / Powder-coated	2000 mm	€ 25.95



Cover | PMMA - Polymethyl methacrylate

	Clear	Matt	Milky	
				
2 m	983031	983033	983035	€ 15.95
3 m	983038	983037	983036	€ 22.95
				
2 m	983531	983533	983535	€ 15.95
3 m		983539	983536	€ 22.95
				
2 m		984033	984035	€ 15.95
3 m			984036	€ 22.95
				
2 m		984533	984535	€ 15.95

end caps set | 2 pieces | Plastic | € 3.95

White	Grey	Black
		
978070	978071	978072
		
978570	978571	978572
		
979110	979111	979112
		
979610	979611	979612

930349 3M double-sided adhesive tape 50,000x20x0.20 mm

987008 Set of 2 retaining clips for AU-15

987080 Universal holding clip mount (swivel) set of 2 pieces



€ 38.95



€ 3.45



€ 18.95






ET-01-08

·For LED strips up to 9.3 mm wide

Housing Aluminium
Length 2000 mm





Article	Housing Color	Surface	Price
975001	 Silver	Matt / Anodised	€ 21.95
975003	 Black	Matt / Anodised	€ 21.95
975005	 White	Matt / Powder-coated	€ 21.95



Cover | PMMA - Polymethyl methacrylate

	Clear	Matt	Milky	
				
1 m	983000	983002	983004	€ 6.45
2 m	983001	983003	983005	€ 13.95
				
1 m	983500	983502	983504	€ 6.45
2 m	983501	983503	983505	€ 13.95
				
1 m		984002	984004	€ 6.45
2 m		984003	984005	€ 13.95
				
1 m		984502	984504	€ 6.45
2 m		984503	984505	€ 13.95

end caps set | 2 pieces | Plastic | € 3.95

White	Grey	Black
		
978080	978081	978082
		
978580	978581	978582
		
979120	979121	979122
		
979620	979621	979622

930347 3M double-sided adhesive tape 50,000x12x0.2 mm



€ 25.95

987002 Set of 2 retaining clips for AU-08



€ 3.45

987080 Universal holding clip mount (swivel) set of 2 pieces



€ 18.95






ET-02-08

·For LED strips up to 9.3 mm wide

Housing Aluminium
 Length 2000 mm




Article	Housing Color	Surface	Price
975101	 Silver	Matt / Anodised	€ 25.95
975103	 Black	Matt / Anodised	€ 25.95
975105	 White	Matt / Powder-coated	€ 25.95



Cover | PMMA - Polymethyl methacrylate

	Clear	Matt	Milky	
				
1 m	983000	983002	983004	€ 6.45
2 m	983001	983003	983005	€ 13.95
				
1 m	983500	983502	983504	€ 6.45
2 m	983501	983503	983505	€ 13.95
				
1 m		984002	984004	€ 6.45
2 m		984003	984005	€ 13.95
				
1 m		984502	984504	€ 6.45
2 m		984503	984505	€ 13.95

end caps set | 2 pieces | Plastic | € 3.95

White	Grey	Black
		
978120	978121	978122
		
978620	978621	978622
		
979140	979141	979142
		
	979641	

930347 3M double-sided adhesive tape 50,000x12x0.2 mm



€ 25.95

987002 Set of 2 retaining clips for AU-08



€ 3.45

987080 Universal holding clip mount (swivel) set of 2 pieces



€ 18.95






ET-01-10

For LED strips up to 11.3 mm wide

Housing Aluminium
Length 2000 mm

Article	Housing Color	Surface	Price
975021	 Silver	Matt / Anodised	€ 21.95
975023	 Black	Matt / Anodised	€ 21.95
975025	 White	Matt / Powder-coated	€ 21.95



Cover | PMMA - Polymethyl methacrylate

Clear Matt Milky

				
1 m	983010	983012	983014	€ 6.45
2 m	983011	983013	983015	€ 13.95

				
1 m	983510	983512	983514	€ 6.45
2 m	983511	983513	983515	€ 13.95


				
1 m		984012	984014	€ 6.45
2 m		984013	984015	€ 13.95


				
1 m		984512	984514	€ 6.45
2 m		984513	984515	€ 13.95


				
1 m	985010			€ 6.45
2 m	985011			€ 13.95


end caps set | 2 pieces | Plastic


White Grey Black

				
978090	978091	978092	€ 3.95	

				
978590	978591	978592	€ 3.95	

				
979040	979041	979042	€ 3.95	

				
979540		979542	€ 3.95	

				
980040	980041	980042	€ 3.95	

930348 3M double-sided adhesive tape 50,000x15x0.20 mm**€ 30.95****987004** Set of 2 retaining clips for AU-10**€ 3.45****987080** Universal holding clip mount (swivel) set of 2 pieces**€ 18.95****Lighting design**

Interested in our lighting design service?

Your contact person will be happy to answer any questions you may have.




ET-02-10

·For LED strips up to 11.3 mm wide

Housing Aluminium
 Length 2000 mm






Article	Housing Color	Surface	Price
975121	 Silver	Matt / Anodised	€ 25.95
975123	 Black	Matt / Anodised	€ 25.95
975125	 White	Matt / Powder-coated	€ 25.95



Cover | PMMA - Polymethyl methacrylate

	Clear	Matt	Milky	
				
1 m	983010	983012	983014	€ 6.45
2 m	983011	983013	983015	€ 13.95
				
1 m	983510	983512	983514	€ 6.45
2 m	983511	983513	983515	€ 13.95
				
1 m		984012	984014	€ 6.45
2 m		984013	984015	€ 13.95
				
1 m		984512	984514	€ 6.45
2 m		984513	984515	€ 13.95
				
1 m	985010			€ 6.45
2 m	985011			€ 13.95

end caps set | 2 pieces | Plastic | € 3.95

White	Grey	Black
		
978130	978131	978132
		
978630	978631	978632
		
979060	979061	979062
		
979560	979561	979562
		
980060	980061	

930348 3M double-sided adhesive tape 50,000x15x0.20 mm



€ 30.95

987004 Set of 2 retaining clips for AU-10



€ 3.45

987080 Universal holding clip mount (swivel) set of 2 pieces



€ 18.95



Onlineshop

You can find more information about the products in the onlineshop:
Detailed images, videos, project reports, LDT files, EPREL data sheets and more.




ET-01-12

·For LED strips up to 13.3 mm wide

Housing Aluminium
Length 2000 mm



Article	Housing Color	Surface	Price
975041	 Silver	Matt / Anodised	€ 25.95
975049	 Black	Matt / Anodised	€ 25.95
975045	 White	Matt / Powder-coated	€ 25.95



Cover | PMMA - Polymethyl methacrylate

	Clear	Matt	Milky	
				
1 m	983020	983022	983024	€ 6.45
2 m	983021	983023	983025	€ 13.95
				
1 m	983520	983522	983524	€ 6.45
2 m	983521	983523	983525	€ 13.95
				
1 m		984022	984024	€ 6.45
2 m		984023	984025	€ 13.95
				
1 m		984522	984524	€ 6.45
2 m		984523	984525	€ 13.95

end caps set | 2 pieces | Plastic | € 3.95

White	Grey	Black
		
978100	978101	978102
		
978600	978601	978602
		
979050	979051	979052
		
979550	979551	979552

930348 3M double-sided adhesive tape 50,000x15x0.20 mm



€ 30.95

987006 Set of 2 retaining clips for AU-12



€ 3.45

987080 Universal holding clip mount (swivel) set of 2 pieces



€ 18.95






ET-02-12

·For LED strips up to 13.3 mm wide

Housing Aluminium
 Length 2000 mm





Article	Housing Color	Surface	Price
975141	 Silver	Matt / Anodised	€ 28.95
975143	 Black	Matt / Anodised	€ 28.95
975145	 White	Matt / Powder-coated	€ 28.95



Cover | PMMA - Polymethyl methacrylate

	Clear	Matt	Milky	
				
1 m	983020	983022	983024	€ 6.45
2 m	983021	983023	983025	€ 13.95
				
1 m	983520	983522	983524	€ 6.45
2 m	983521	983523	983525	€ 13.95
				
1 m		984022	984024	€ 6.45
2 m		984023	984025	€ 13.95
				
1 m		984522	984524	€ 6.45
2 m		984523	984525	€ 13.95

end caps set | 2 pieces | Plastic | € 3.95

White	Grey	Black
		
978140	978141	978142
		
978640	978641	978642
		
979070	979071	979072
		
	979571	979572

930348 3M double-sided adhesive tape 50,000x15x0.20 mm

987006 Set of 2 retaining clips for AU-12

987080 Universal holding clip mount (swivel) set of 2 pieces



€ 30.95



€ 3.45



€ 18.95






ET-02-15

For LED strips up to 16.3 mm wide

Housing
Aluminium
Length
2000 mm




Article	Housing Color	Surface	Price
975161	 Silver	Matt / Anodised	€ 28.95
975163	 Black	Matt / Anodised	€ 28.95
975165	 White	Matt / Powder-coated	€ 28.95



Cover | PMMA - Polymethyl methacrylate

	Clear	Matt	Milky	
				
1 m	983030	983032	983034	€ 7.95
2 m	983031	983033	983035	€ 15.95
				
1 m	983530	983532	983534	€ 7.95
2 m	983531	983533	983535	€ 15.95
				
1 m		984032	984034	€ 7.95
2 m		984033	984035	€ 15.95
				
1 m		984532	984534	€ 7.95
2 m		984533	984535	€ 15.95

end caps set | 2 pieces | Plastic | € 3.95

White	Grey	Black
		
978150	978151	978152
		
978650	978651	978652
		
979150	979151	979152
		
979650	979651	979652

930349 3M double-sided adhesive tape 50,000x20x0.20 mm



€ 38.95

987008 Set of 2 retaining clips for AU-15



€ 3.45

987080 Universal holding clip mount (swivel) set of 2 pieces



€ 18.95





With the kind support of BEST Bellemann Elektro Service Team GmbH, Rauenberg-Malschenberg



H- AND GROOVE-PROFILES

Groove and H-profiles are offered with a comprehensive range of mounting accessories and are hard to beat in terms of versatility. The range of accessories includes cable suspensions, tension springs, sliding blocks and much more.





AU-10-12

For LED strips up to 13 mm wide

Housing

Aluminium

Article	Housing Color	Surface	Length	Price
970280	 Silver	Matt / Anodised	2000 mm	€ 28.95
970281	 Silver	Matt / Anodised	3000 mm	€ 43.95
970284	 White	Matt / Powder-coated	2000 mm	€ 28.95
970285	 White	Matt / Powder-coated	3000 mm	€ 43.95



Cover | Polycarbonate

Clear Milky Black



2 m	983096	983090	983093	€ 18.95
3 m	983097	983091	983094	€ 28.95
20 m	983098	983092		€ 159.95

980023 Mounting clip, set (2 pieces)

987025 Sliding block/longitudinal connector

987026 Sliding block/corner connector 120°


987027 Sliding block/corner connector 90°

end caps set | Aluminium | € 15.95

Silver



980021



€ 3.95

€ 7.95

€ 7.95

€ 7.95

Accessories for **970280, 970281**

980020 end caps set aluminium 2 pieces

19,95 €


980021 end caps set aluminium 2 pieces

19,95 €

980020



980021






With the kind support of Albtherme Waldbronn / Ziegler Technics buero@ziegler-technics.de

**STEP-, SOCKET-, ANGLE-, CORNER-PROFILES**

The perfect light is not always planned from the very start. With the mounting and corner profiles, you can also integrate linear light at a later stage.




AL-01-10

·For LED strips up to 11.3 mm wide

Housing Aluminium
Surface Matt, Anodised

Article	Housing Color	Length	Price
970503	 Silver	2000 mm	€ 47.95
970502	 Silver	3000 mm	€ 75.95



Cover | PMMA - Polymethyl methacrylate
Cover | Polycarbonate
Clear Matt Milky

end caps set | 2 pieces (left/right) | Plastic | € 3.95
Grey



1 m	983010	983012	983014	€ 6.45
1 m			983080	€ 8.95
2 m	983011	983013	983015	€ 13.95
2 m			983081	€ 17.95
3 m	983016	983017	983018	€ 20.95
3 m			983082	€ 25.95

978191

930105 Assembly adhesive 310 ml



€ 28.95







AL-02-10

For LED strips up to 11.3 mm wide

Housing Aluminium
Surface Matt, Anodised

Article	Housing Color	Length	Price
970523	Silver	2000 mm	€ 47.95
970522	Silver	3000 mm	€ 75.95



Cover | PMMA - Polymethyl methacrylate


Clear Matt Milky



1 m	983010	983012	983014	€ 6.45
2 m	983011	983013	983015	€ 13.95
3 m	983016	983017	983018	€ 20.95

end caps set | 2 pieces (left/right) | Plastic | € 3.95

Grey



978201

930105 Assembly adhesive 310 ml



€ 28.95







AV-01-20

·For LED strips up to 22 mm wide


Housing Aluminium
Surface Matt, Anodised
Length 2000 mm

Article	Housing Color	Price
970460	 Silver	€ 28.95




Cover | PMMA - Polymethyl methacrylate
Clear Milky


1 m	983040	983044	€ 8.95
2 m	983041	983045	€ 17.95
3 m		983046	€ 25.95



1 m		984044	€ 8.95
2 m		984045	€ 17.95



1 m		984544	€ 8.95
2 m		984545	€ 17.95



930105 Assembly adhesive 310 ml



€ 28.95







AV-02-20

·For LED strips up to 22 mm wide


Housing Aluminium
Surface Matt, Anodised
Length 2000 mm

Article	Housing Color	Price
970470	 Silver	€ 28.95



Cover | PMMA - Polymethyl methacrylate

	Clear	Matt	Milky
			
1 m	983040	983044	€ 8.95
2 m	983041	983045	€ 17.95
3 m		983046	€ 25.95
			
3 m		983539	€ 22.95
			
1 m		984044	€ 8.95
2 m		984045	€ 17.95
			
1 m		984544	€ 8.95
2 m		984545	€ 17.95



930105 Assembly adhesive 310 ml



€ 28.95







AM-01-10

·For LED strips up to 11.3 mm wide

Housing Aluminium
Length 2000 mm

Article	Housing Color	Surface	Price
970301	 Silver	Matt / Anodised	€ 29.95
970303	 Black	Matt / Anodised	€ 29.95
970305	 White	Matt / Powder-coated	€ 29.95



Cover | PMMA - Polymethyl methacrylate

Clear

Matt

Milky



1 m	983010	983012	983014	€ 6.45
2 m	983011	983013	983015	€ 13.95



1 m	983510	983512	983514	€ 6.45
2 m	983511	983513	983515	€ 13.95
3 m	983516	983517	983518	€ 20.95

end caps set | 2 pieces | Plastic | € 3.95

White

Grey

Black




978700	978701	978702
--------	--------	--------

930105 Assembly adhesive 310 ml



€ 28.95



AV-01-10

· For LED strips up to 11.3 mm wide

Housing Aluminium

Article	Housing Color	Surface	Length	Price
970401	 Silver	Matt / Anodised	2000 mm	€ 28.95
970404	 Silver	Matt / Anodised	3000 mm	€ 43.95
970403	 White	Matt / Powder-coated	2000 mm	€ 28.95




Foto: Daniel Veser - Architekturfotografie, Karlsruhe

Cover | PMMA - Polymethyl methacrylate

	Clear	Matt	Milky	
				
1 m	983010	983012	983014	€ 6.45
2 m	983011	983013	983015	€ 13.95
3 m	983016	983017	983018	€ 20.95

				
1 m	983510	983512	983514	€ 6.45
2 m	983511	983513	983515	€ 13.95
3 m	983516	983517	983518	€ 20.95

				
1 m		984012	984014	€ 6.45
2 m		984013	984015	€ 13.95
3 m		984017	984018	€ 20.95

				
1 m		984512	984514	€ 6.45
2 m		984513	984515	€ 13.95
3 m		984517	984518	€ 20.95

				
1 m	985010			€ 6.45
2 m	985011			€ 13.95
3 m	985016			€ 20.95

930105 Assembly adhesive 310 ml

930348 3M double-sided adhesive tape 50,000x15x0.20 mm

end caps set | 2 pieces | Plastic | € 3.95

White	Grey
	
978170	978171



€ 28.95

€ 30.95



Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.





EV-04-12

·For LED strips up to 13.3 mm wide

Housing Aluminium
Surface Matt, Anodised

Article	Housing Color	Length	Price
975411	 Silver	2000 mm	€ 31.95
975412	 Silver	3000 mm	€ 49.95




Cover | PMMA - Polymethyl methacrylate




	Clear	Matt	Milky	
				
1 m	983020	983022	983024	€ 6.45
2 m	983021	983023	983025	€ 13.95
3 m	983028	983027	983026	€ 20.95
				
1 m	983520	983522	983524	€ 6.45
2 m	983521	983523	983525	€ 13.95
3 m	983527		983526	€ 20.95
				
1 m		984022	984024	€ 6.45
2 m		984023	984025	€ 13.95
3 m			984026	€ 20.95
				
1 m		984522	984524	€ 6.45
2 m		984523	984525	€ 13.95
3 m			984526	€ 20.95

end caps set | Plastic | € 3.95

Grey



978341



930105 Assembly adhesive 310 ml



€ 28.95

987006 Set of 2 retaining clips for AU-12



€ 3.45

987080 Universal holding clip mount (swivel) set of 2 pieces



€ 18.95







AV-05-12

·For LED strips up to 12 mm wide

Housing Aluminium
Surface Matt, Anodised

Article	Housing Color	Length	Price
970550	 Silver	2000 mm	€ 31.95
970551	 Silver	3000 mm	€ 47.95



Cover | Polycarbonate

Milky



2 m 983100 € 18.95
3 m 983101 € 28.95




2 m 984570 € 18.95
3 m 984571 € 28.95


2 m 985570 € 18.95
3 m 985571 € 28.95

end caps set | 2 pieces
1x installation material | Aluminium | € 26.95

Silver



978370



979760



980550







AV-05-15

·For LED strips up to 15 mm wide

Housing Aluminium
Surface Matt, Anodised

Article	Housing Color	Length	Price
970560	 Silver	2000 mm	€ 39.95
970561	 Silver	3000 mm	€ 63.95



Cover | Polycarbonate

Milky



2 m 983110 € 24.95
3 m 983111 € 35.95




2 m 984580 € 24.95
3 m 984581 € 35.95




2 m 985580 € 24.95
3 m 985581 € 35.95

end caps set | 2 pieces
1x installation material | Aluminium | € 26.95

Silver



978380



979770



980560







AV-05-25

·For LED strips up to 25 mm wide or two 12 mm wide

Housing Aluminium
Surface Matt, Anodised


Article	Housing Color	Length	Price
970570	 Silver	2000 mm	€ 55.95
970571	 Silver	3000 mm	€ 79.95




Cover | Polycarbonate

	Milky		
			
2 m	983120	€ 28.95	
3 m	983121	€ 43.95	
			
2 m	984590	€ 28.95	
3 m	984591	€ 43.95	
			
2 m	985590	€ 28.95	
3 m	985591	€ 43.95	

end caps set | 2 pieces
1x installation material | Aluminium | € 26.95
Silver



978390



979780



980570

Accessories

987020 Universal sliding block/longitudinal connector, set of 2 pieces



€ 7.95

987060 Cable suspension (swivel), set of 2 pieces



€ 35.95



Foto: Daniel Vießer . Architekturfotografie, Karlsruhe




With the kind support of BEST Belermann Elektro Service Team GmbH, Rauenberg-Malschenberg



DRY CONSTRUCTION PROFILES

Our dry construction profiles offer you full creative freedom. Redefine linear light – whether as a primary light or for accent lighting.





EL-02-12

· For LED strips up to 14 mm wide

Housing Aluminium
Length 2000 mm

Article	Housing Color	Surface	Price
975491	Silver	Matt / Anodised	€ 65.95
975495	White	Matt / Powder-coated	€ 65.95



Cover | PMMA - Polymethyl methacrylate

	Clear	Matt	Milky	
				
1 m	983020	983022	983024	€ 6.45
2 m	983021	983023	983025	€ 13.95

end caps set | 2 pieces (left/right)
1x installation material | Plastic
end caps set | 2 pieces (left/right)
1x installation material | Aluminium


White	Grey	
		
978250	978251	€ 3.95
	978252	€ 26.95


930105 Assembly adhesive 310 ml

930346 3M double-sided adhesive tape 50,000x10x0.2 mm

987020 Universal sliding block/longitudinal connector, set of 2 pieces

987040 Sliding block with tensioning springs, set of 2 pieces






ET-03-10

· For LED strips up to 12 mm wide

Housing Aluminium
 Length 2500 mm



Article	Housing Color	Surface	Price
975471	 Silver	Matt / Anodised	€ 47.95
975475	 White	Matt / Powder-coated	€ 47.95



Cover | PMMA - Polymethyl methacrylate

	Clear	Matt	Milky	
				
1 m	983010	983012	983014	€ 6.45
2 m	983011	983013	983015	€ 13.95
3 m	983016	983017	983018	€ 20.95
				
1 m		984012	984014	€ 6.45
2 m		984013	984015	€ 13.95
3 m		984017	984018	€ 20.95
				
1 m		984512	984514	€ 6.45
2 m		984513	984515	€ 13.95
3 m		984517	984518	€ 20.95

end caps set | 2 pieces | Plastic

	White	Grey	
			
	978260	978261	€ 3.95
			
	979200	979201	€ 5.95
			
	979700	979701	€ 5.95

- 930105 Assembly adhesive 310 ml
- 970762 Support profile, LED support T-01-10
- 987020 Universal sliding block/longitudinal connector, set of 2 pieces
- 987040 Sliding block with tensioning springs, set of 2 pieces







EL-03-10

· For LED strips up to 12 mm wide

Housing

Aluminium

Article	Housing Color	Surface	Length	Price
975483	Silver	Matt / Anodised	2000 mm	€ 47.95
975485	White	Matt / Powder-coated	2500 mm	€ 63.95




Cover | PMMA - Polymethyl methacrylate

	Clear	Matt	Milky	
				
1 m	983010	983012	983014	€ 6.45
2 m	983011	983013	983015	€ 13.95
3 m	983016	983017	983018	€ 20.95
				
1 m		984012	984014	€ 6.45
2 m		984013	984015	€ 13.95
3 m		984017	984018	€ 20.95
				
1 m		984512	984514	€ 6.45
2 m		984513	984515	€ 13.95
3 m		984517	984518	€ 20.95

end caps set | 2 pieces (left/right) | Plastic

	White	Grey	
			
978270	978271	€ 3.95	
			
979210	979211	€ 5.95	
			
979710	979711	€ 5.95	







EL-04-12

- for LED strips up to 14 mm wide
- for plasterboard 12.5 mm thick

Housing	Aluminium
Surface	Natural
Length	3000 mm

Article	Housing Color	Price
975530	 Silver	€ 79.95



Cover | Polycarbonate

Milky



2 m	983090	€ 18.95
3 m	983091	€ 28.95




5-year guarantee

Benefit from the maximum quality promise:
 All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.



Foto: Daniel Vieser, Architektur fotografie, Karlsruhe




EU-01-36

· For LED strips up to 36 mm wide

Housing	Aluminium
Surface	Natural
Length	3000 mm

Article	Housing Color	Price
975501	Silver	€ 99.95



Cover | PMMA - Polymethyl methacrylate

Milky



3 m
 985601
 € 33.95

end caps set | 2 pieces
 1x installation material | Aluminium | € 15.95

Grey




978175
 € 15.95

985605
 Dummy cover



€ 24.95






EU-02-36

· For LED strips up to 36 mm wide

Housing	Aluminium
Surface	Matt, Anodised
Length	3000 mm

Article	Housing Color	Price
975525	Silver	€ 103.95



Cover | PMMA - Polymethyl methacrylate
 Milky



3 m	985601	€ 33.95
-----	--------	---------

985605	Dummy cover
--------	-------------



€ 24.95



5-year guarantee
 Benefit from the maximum quality promise:
 All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.



Lighting design

Interested in our lighting design service?

Your contact person will be happy to answer any questions you may have.





EU-10-12

· For LED strips up to 12 mm wide

Housing	Aluminium
Surface	Matt, Anodised
Length	3000 mm

Article	Housing Color	Price
975511	 Silver	€ 47.95



Cover | Polycarbonate
Milky




2 m	983090	€ 18.95
3 m	983091	€ 28.95



Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.







EV-11-12

· For LED strips up to 12 mm wide

Housing	Aluminium
Surface	Matt, Anodised
Length	3000 mm

Article	Housing Color	Price
975516	 Silver	€ 55.95



Cover | Polycarbonate
 Milky




2 m	983090	€ 18.95
3 m	983091	€ 28.95



5-year guarantee
 Benefit from the maximum quality promise:
 All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.







EV-12-12

· For LED strips up to 12 mm wide

Housing	Aluminium
Surface	Matt, Anodised
Length	3000 mm

Article	Housing Color	Price
975521	 Silver	€ 47.95



Cover | Polycarbonate
 Milky



2 m	983090	€ 18.95
3 m	983091	€ 28.95



Lighting design
 Interested in our lighting design service?
 Your contact person will be happy to answer any questions you may have.






With the kind support of BEST Bellemann Elektro Service Team GmbH, Rauenberg-Malschenberg



TILE PROFILES



Tile profiles play to every corner and closing area. Do away with conventional tile end profiles and set a new standard with linear light.



EL-03-12

- For LED strips up to 13.3 mm wide
- For tile thicknesses up to max. 12 mm


Housing	Aluminium		
Length	2500 mm		
Article	Housing Color	Surface	Price
975361	 Silver	Matt / Anodised	€ 47.95
975365	 White	Matt / Powder-coated	€ 47.95



Cover | PMMA - Polymethyl methacrylate

	Clear	Matt	Milky	
				
1 m	983020	983022	983024	€ 6.45
2 m	983021			€ 13.95
3 m	983028	983027	983026	€ 20.95
				
1 m		984022	984024	€ 6.45
3 m			984026	€ 20.95






EV-01-12

- For LED strips up to 13.3 mm wide
- For tile thicknesses up to max. 12 mm

Housing Aluminium
Length 2500 mm

Article	Housing Color	Surface	Price
975371	 Silver	Matt / Anodised	€ 79.95
975375	 White	Matt / Powder-coated	€ 79.95




Cover | PMMA - Polymethyl methacrylate

Clear Matt Milky



1 m	983020	983022	983024	€ 6.45
2 m	983021	983023	983025	€ 13.95
3 m	983028	983027	983026	€ 20.95





EV-02-12

- For LED strips up to 13.3 mm wide
- For tile thicknesses up to max. 12 mm



Housing

Aluminium

Length

2500 mm

Article	Housing Color	Surface	Price
975381	Silver	Matt / Anodised	€ 79.95
975385	White	Matt / Powder-coated	€ 79.95



Cover | PMMA - Polymethyl methacrylate

Clear

Matt

Milky



1 m	983020	983022	983024	€ 6.45
2 m	983021	983023	983025	€ 13.95
3 m	983028	983027	983026	€ 20.95





With the kind support of BEST Bellemann Elektro Service Team GmbH, Rauenberg-Malschenberg



PROFILES FOR OUTDOOR USE

Outdoor areas have different requirements than indoor areas. Our IP profiles are walkable and passable and inspire as a highlight in any outdoor design.





AU-05-15

For LED strips up to 15.6 mm wide

Housing	Aluminium
Surface	Natural
Length	2000 mm

Article	Housing Color	Price
970741	Silver	€ 33.95



Cover | PMMA - Polymethyl methacrylate
Milky



1 m	988084	€ 8.95
2 m	988085	€ 17.95

end caps set | 2 pieces (left/right) | Plastic | € 3.95
Grey



981031	€ 3.95
---------------	---------------

930104 Natural stone sealant 310 ml




€ 31.95

970764 Support profile, LED support T-01-15



€ 6.45






ET-05-15

For LED strips up to 15.6 mm wide

Housing	Aluminium
Surface	Matt, Anodised
Length	2000 mm

Article	Housing Color	Price
975741	Silver	€ 33.95




Cover | PMMA - Polymethyl methacrylate
Milky



- 1 m **988084** € 8.95
- 2 m **988085** € 17.95

end caps set | 2 pieces (left/right) | Plastic | € 3.95
Grey



- 981041** € 3.95

930104 Natural stone sealant 310 ml



- € 31.95

970764 Support profile, LED support T-01-15



- € 6.45







EU-01-12

For LED strips up to 12 mm wide

Housing	Aluminium
Surface	Matt, Anodised
Length	2000 mm

Article	Housing Color	Price
975781	Silver	€ 63.95



Cover | PMMA - Polymethyl methacrylate
Milky



1 m	988054	€ 8.95
2 m	988055	€ 17.95

end caps set | 2 pieces (left/right) | Plastic | € 3.95
Grey



981021	€ 3.95
---------------	---------------

930104 Natural stone sealant 310 ml

970762 Support profile, LED support T-01-10

990109 Foam underlay



€ 31.95



€ 6.45



€ 6.45





LED STRIPES

724	Quickfinder
728	COB
744	12V
746	24V
770	48V
784	230V
786	Mounting material for LED strips



page 729



page 732



page 734



page 745



page 747



page 748



page 750



page 751

led stripes



width in mm	Voltage [DC]	W/m	design	light colour	colour temperature	lm / m	LED / m	length in mm	protection rating	article number	page
4,0	24V	11,0	SMD	WW	2700 K	995	280	5000	IP20	840175	776
4,0	24V	11,0	SMD	WW	3000 K	1090	209	5000	IP20	840210	749
4,0	24V	11,5	SMD	NW	4000 K	1100	209	5000	IP20	840267	749
5,0	24V	9,6	SMD	WW	2700 K	770	120	5000	IP20	840158	748
5,0	24V	9,6	SMD	WW	3000 K	820	120	5000	IP20	840159	748
5,0	24V	11,0	SMD	WW CW	3000-6500 K	1025	196	5000	IP20	840350	750
5,0	24V	11,0	SMD	RGB		500	120	5000	IP20	840276	752
6,0	48V	4,0	SMD	WW	3000 K	400	520	15000	IP20	840317	783
7,4	24V	12,5	SMD	WW CW	3000-6500 K	1070	196	5000	IP65	840349	751
8,0	12V	7,0	SMD	WW	2700 K	570	120	5000	IP20	840164	745
8,0	12V	7,0	SMD	WW	3000 K	555	120	5000	IP20	840165	745
8,0	12V	7,0	SMD	NW	4000 K	670	120	5000	IP20	840166	745
8,0	12V	7,0	SMD	CW	6500 K	630	120	5000	IP20	840167	745
8,0	24V	14,0	SMD	WW	2700 K	1110	120	5000	IP20	840178	756
8,0	24V	14,0	SMD	WW	3000 K	1100	120	5000	IP20	840179	756
8,0	24V	14,0	SMD	NW	4000 K	1220	60	5000	IP20	840180	756
8,0	24V	14,0	SMD	WW	3000 K	1100	120	50000	IP20	930512	756
10,0	24V	8,0	Neon, 3D Bend	WW	2700 K	720	160	5000	IP67	840417	769
10,0	24V	8,0	Neon, 3D Bend	WW	3000 K	744	160	5000	IP67	840418	769
10,0	24V	8,0	Neon, 3D Bend	NW	4000 K	800	160	5000	IP67	840419	769
10,0	24V	9,5	SMD	WW	3000 K	705	120	10000	IP20	840291	747
10,0	24V	12,0	COB	WW	2700 K	1050	480	5000	IP20	840474	736
10,0	24V	12,0	COB	WW	3000 K	1360	480	5000	IP20	840475	736
10,0	24V	12,0	COB	NW	4000 K	1320	480	5000	IP20	840476	736
10,0	24V	13,0	SMD	RGB		580	60	5000	IP20	840254	754
10,0	24V	14,0	SMD	RGB		665	120	5000	IP20	840147	756
10,0	24V	15,0	COB	WW	2700 K	2100	288	5000	IP20	840466	742
10,0	24V	15,0	COB	WW	3000 K	2550	288	5000	IP20	840467	742
10,0	24V	15,0	COB	NW	4000 K	2690	288	5000	IP20	840468	742
10,0	24V	15,0	COB	CW	6500 K	2690	288	5000	IP20	840469	742
10,0	24V	15,0	SMD	WW CW	2700-6500 K	1550		5000	IP20	840480	738
10,0	24V	16,0	SMD	RGB WW	3000 K	820	60	5000	IP20	840236	759
10,0	24V	16,0	SMD	RGB NW	4000 K	765	60	5000	IP44	840373	760
10,0	24V	16,0	SMD	WW	3000 K	820	60	50000	IP20	930517	759
10,0	24V	16,5	SMD	RGB NW	4000 K	775	60	5000	IP20	840353	758
10,0	24V	17,2	SMD	WW CW	2700-6500 K	1765	140	5000	IP20	840378	761
10,0	24V	18,5	SMD	WW	2700 K	1215	240	5000	IP20	840192	762
10,0	24V	19,0	SMD	WW	3000 K	1605	240	5000	IP20	840193	762
10,0	24V	20,0	SMD	CW	6000 K	1720	120	5000	IP20	840124	762
10,0	24V	20,0	SMD	NW	4000 K	1770	240	5000	IP20	840194	762
10,0	24V	23,0	SMD	WW	3000 K	2650	160	5000	IP44	840333	764
10,0	24V	23,0	SMD	NW	4000 K	2780	160	5000	IP44	840334	764


width in mm	Voltage [DC]	W/m	design	light colour	colour temperature	lm / m	LED / m	length in mm	protection rating	article number	page
10,0	24V	23,0	SMD	WW	3000 K	3010	160	5000	IP20	840331	763
10,0	24V	23,0	SMD	NW	4000 K	3130	160	5000	IP20	840332	763
10,0	48V	4,0	SMD	WW	3000 K	485	520	15000	IP20	840318	782
10,0	48V	4,0	SMD	WW	3000 K	485	130	50000	IP20	840337	782
10,0	48V	4,0	SMD	NW	4000 K	530	520	15000	IP20	840320	782
10,0	48V	4,0	SMD	NW	4000 K	530	130	50000	IP20	840339	782
10,0	48V	4,0	SMD	WW	3000 K	400	130	50000	IP44	840338	783
10,0	48V	4,0	SMD	NW	4000 K	455	520	15000	IP44	840319	783
10,0	48V	4,0	SMD	NW	4000 K	455	130	50000	IP44	840340	783
10,0	48V	10,0	SMD	WW	2700 K	1210	140	15000	IP20	840393	780
10,0	48V	10,0	SMD	WW	3000 K	1240	140	15000	IP20	840394	780
10,0	48V	10,0	SMD	NW	4000 K	1300	140	15000	IP20	840395	780
10,0	48V	10,0	SMD	WW	2700 K	1210	140	50000	IP20	840401	780
10,0	48V	10,0	SMD	WW	3000 K	1240	140	50000	IP20	840402	780
10,0	48V	10,0	SMD	NW	4000 K	1300	140	50000	IP20	840403	780
10,0	48V	10,0	SMD	WW	2700 K	1210	140	5000	IP20	840440	780
10,0	48V	10,0	SMD	RGB		550	140	15000	IP20	840399	778
10,0	48V	10,0	SMD	RGB		550	140	50000	IP20	840407	778
10,0	48V	10,0	SMD	RGB		550	140	5000	IP20	840446	778
10,0	48V	10,0	SMD	WW CW	2700-6500 K	1200	224	15000	IP20	840434	772
10,0	48V	10,0	SMD	WW CW	2700-6500 K	1200	224	5000	IP20	840438	772
10,0	48V	10,0	SMD	WW CW	2700-6500 K	1200	224	50000	IP20	840436	772
11,5	24V	11,0	SMD	WW	2700 K	900	120	5000	IP67	840186	753
11,5	24V	11,0	SMD	WW	3000 K	930	36	5000	IP67	840187	753
12,0	24V	10,0	COB	WW	2700 K	850	480	2000	IP67	840409	729
12,0	24V	10,0	COB	WW	3000 K	900	480	2000	IP67	840410	729
12,0	24V	10,0	COB	WW	2700 K	850	480	5000	IP67	840411	729
12,0	24V	10,0	COB	WW	3000 K	900	480	5000	IP67	840412	729
12,0	24V	12,0	COB	WW	2700 K	1170	480	5000	IP67	840477	737
12,0	24V	12,0	COB	WW	3000 K	1220	480	5000	IP67	840478	737
12,0	24V	12,0	COB	NW	4000 K	1400	480	5000	IP67	840479	737
12,0	24V	15,0	COB	WW	2700 K	2060	288	5000	IP67	840470	743
12,0	24V	15,0	COB	WW	3000 K	2060	288	5000	IP67	840471	743
12,0	24V	15,0	COB	NW	4000 K	2160	288	5000	IP67	840472	743
12,0	24V	15,0	COB	CW	6500 K	2150	288	5000	IP67	840473	743
12,0	24V	15,0	COB	WW CW	2700-6500 K	1300		5000	IP67	840481	739
12,0	24V	16,0	COB	RGB WW	3000 K	800		5000	IP20	840482	740
12,0	24V	22,0	SMD	RGB NW	4000 K	985	240	5000	IP20	840309	765
12,0	24V	22,0	SMD	RGB WW	3000 K	955	140	5000	IP20	840308	765
12,0	48V	10,0	SMD	WW	3000 K	1240	140	5000	IP20	840442	780
12,0	48V	10,0	SMD	NW	4000 K	1300	140	5000	IP20	840444	780
12,0	48V	10,0	SMD	RGB WW	3000 K	660	112	50000	IP20	840456	776

width in mm	Voltage [DC]	W/m	design	light colour	colour temperature	lm / m	LED / m	length in mm	protection rating	article number	page
12,0	48V	10,0	SMD	RGB WW	3000 K	660	112	5000	IP20	840458	776
12,0	48V	10,0	SMD	RGB WW	3000 K	660	112	15000	IP20	840454	776
12,0	48V	10,0	SMD	RGB NW	4000 K	700	112	50000	IP20	840462	776
12,0	48V	10,0	SMD	RGB NW	4000 K	700	112	5000	IP20	840464	776
12,0	48V	10,0	SMD	RGB NW	4000 K	700	112	15000	IP20	840460	776
12,0	48V	10,0	SMD	RGB WW CW	2700-6500 K	800	180	15000	IP20	840448	774
12,0	48V	10,0	SMD	RGB WW CW	2700-6500 K	800	180	50000	IP20	840450	774
12,0	48V	10,0	SMD	RGB WW CW	2700-6500 K	800	180	5000	IP20	840452	774
12,0	48V	10,0	SMD	WW	2700 K	1090	140	15000	IP67	840396	781
12,0	48V	10,0	SMD	WW	3000 K	1120	140	15000	IP67	840397	781
12,0	48V	10,0	SMD	NW	4000 K	1180	140	15000	IP67	840398	781
12,0	48V	10,0	SMD	WW	2700 K	1090	140	50000	IP67	840404	781
12,0	48V	10,0	SMD	WW	3000 K	1120	140	50000	IP67	840405	781
12,0	48V	10,0	SMD	NW	4000 K	1180	140	50000	IP67	840406	781
12,0	48V	10,0	SMD	RGB		510	140	15000	IP67	840400	779
12,0	48V	10,0	SMD	RGB		510	140	50000	IP67	840408	779
12,0	48V	10,0	SMD	RGB		510	140	5000	IP67	840447	779
12,0	48V	10,0	SMD	WW CW	2700-6500 K	1100	224	50000	IP67	840437	773
12,0	48V	10,0	SMD	WW CW	2700-6500 K	1100	224	15000	IP67	840435	773
12,0	48V	10,0	SMD	WW CW	2700-6500 K	1100	224	5000	IP67	840439	773
12,0	48V	15,0	COB	WW	2700 K	1575	480	15000	IP67	840420	732
12,0	48V	15,0	COB	WW	3000 K	1650	480	15000	IP67	840421	732
12,0	48V	15,0	COB	NW	4000 K	1800	480	15000	IP67	840422	732
12,0	48V	15,0	COB	WW	2700 K	1575	480	5000	IP67	840423	732
12,0	48V	15,0	COB	WW	3000 K	1650	480	5000	IP67	840424	732
12,0	48V	15,0	COB	NW	4000 K	1800	480	5000	IP67	840425	732
12,0	48V	15,0	COB	WW NW CW	2700-6500 K	610	560	15000	IP67	840426	732
12,0	48V	15,0	COB	WW NW CW	2700-6500 K	610	560	5000	IP67	840427	732
14,0	24V	15,0	COB	RGB WW	2700 K	600	1344	2000	IP67	840414	730
14,0	24V	15,0	COB	RGB WW	2700 K	600	1344	5000	IP67	840416	730
14,0	24V	16,0	COB	RGB WW	3000 K	800		5000	IP67	840483	741
14,0	48V	18,5	COB	RGB WW	3000 K	890	1120	15000	IP67	840430	734
14,0	48V	18,5	COB	RGB NW	4000 K	1010	1120	15000	IP67	840431	734
14,0	48V	18,5	COB	RGB WW	3000 K	890	1120	5000	IP67	840432	734
14,0	48V	18,5	COB	RGB NW	4000 K	1010	1120	5000	IP67	840433	734
14,5	24V	13,5	SMD	RGB		670	60	5000	IP67	840256	755
14,5	24V	15,0	SMD	RGB WW	3000 K	740	60	5000	IP67	840239	757
14,5	48V	10,0	SMD	WW	2700 K	1090	140	5000	IP67	840441	781
14,5	48V	10,0	SMD	WW	3000 K	1120	140	5000	IP67	840443	781
14,5	48V	10,0	SMD	NW	4000 K	1180	140	5000	IP67	840445	781
14,5	48V	10,0	SMD	RGB WW	3000 K	600	112	50000	IP67	840457	777
14,5	48V	10,0	SMD	RGB WW	3000 K	600	112	5000	IP67	840459	777



width in mm	Voltage [DC]	W/m	design	light colour	colour temperature	lm / m	LED / m	length in mm	protection rating	article number	page
14,5	48V	10,0	SMD		3000 K	600	112	15000	IP67	840455	777
14,5	48V	10,0	SMD		4000 K	650	180	50000	IP67	840463	777
14,5	48V	10,0	SMD		4000 K	650	112	5000	IP67	840465	777
14,5	48V	10,0	SMD		4000 K	650	112	15000	IP67	840461	777
14,5	48V	10,0	SMD		2700-6500 K	750	112	15000	IP67	840449	775
14,5	48V	10,0	SMD		2700-6500 K	750	112	50000	IP67	840451	775
14,5	48V	10,0	SMD		2700-6500 K	750	112	5000	IP67	840453	775
14,5	48V	15,0	COB			670	840	15000	IP67	840428	732
14,5	48V	15,0	COB			670	840	5000	IP67	840429	732
16,0	24V	10,5	Neon, Top-View		3000 K	320	36	5000	IP68	840289	767
17,0	230V	14,0	SMD		3000 K	1470	84	15000	IP65	840386	785
17,0	230V	14,0	SMD		3000 K	1470	84	50000	IP65	840387	785
17,0	230V	14,0	SMD		4000 K	1596	82	15000	IP65	840388	785
17,0	230V	14,0	SMD		4000 K	1596	82	50000	IP65	840389	785
17,0	230V	14,0	SMD		2700 K	1442	82	15000	IP65	840390	785
17,0	230V	14,0	SMD		2700 K	1442	82	50000	IP65	840391	785

COB STRIPES

These LED strips are ideal if the focus is on a homogeneous light pattern.



COB 24V-10W SAUNA IP67



- UV-resistant
- durably temperature-resistant [-10°C to 105°C]
- Lifetime 75,000h L70B50 / 50,000h L80B10
- 2 m model ideal for home saunas with 2 m internal dimensions
- extra long supply line, Incl. mounting material

(p) LED Distance	2.08 mm	(l1) Length End Cap	10 mm
(c) Segment Length	50 mm	(l2) Primary Cable Length	1.8 m
(a) Light Beam Angle	180 Degree	Rated Input 1m	10 W
(r1) Bending Radius min.	50 mm	Rated Input Voltage	24 V/DC
(h1) Height	5.5 mm	CRI (Ra)	90
(h2) Height End Cap	6.5 mm	Control	Dimmable via optional controller
(h3) Height Hose	5.5 mm	Working Temperature	-10 to 105 °C
(b1) Width	12 mm	Channels	1
(b2) Width end cap	14.2 mm		
(b3) Width Hose	12 mm		

Article	Colour Temperature	(l3) Secondary Cable Length	Luminous Efficiency 1m	Luminous Flux 1m	Length	Price
840409	WW 2700 K		85 lm/W	850 lm	2000 mm	€ 79.95
840411	WW 2700 K	1.8 m	85 lm/W	850 lm	5000 mm	€ 179.95
840410	WW 3000 K		90 lm/W	900 lm	2000 mm	€ 79.95
840412	WW 3000 K	1.8 m	90 lm/W	900 lm	5000 mm	€ 179.95




Accessories

- 930737 Supply cable for 24 V COB Sauna stripe
- 930738 Connector for 24 V COB Sauna stripe
- 930736 Silicone end cap set of 2 pieces for 24 V COB Sauna stripe
- 930740 Plastic profile 1 m for 24 V COB Sauna stripe
- 930741 Plastic profile 2 m for 24 V COB Sauna stripe
- 930739 Silicone clamps for 24 V COB Sauna stripe
- 930850 Silicone adhesive 10 ml

	€ 9.95
	€ 13.95
	€ 0.75
	€ 3.95
	€ 7.95
	€ 1.45
	€ 3.95

COB 24V-15W SAUNA IP67



- for saunas and steam baths
- available as RGB or RGBW [2,700K] variant
- UV-resistant
- durably temperature-resistant [-10°C to 105°C]
- 2 m model ideal for home saunas with 2 m internal dimensions
- extra long supply line
- lifetime 75,000h L70B50 / 50,000 L80B10
- incl. mounting material

(p) LED Distance	1.3 mm	Colour Temperature	2700 K
(c) Segment Length	83.3 mm	Luminous Efficiency 1m	40 lm/W
(r1) Bending Radius min.	50 mm	Luminous Flux 1m	600 lm
(h1) Height	5 mm	Rated Input 1m	15 W
(h2) Height End Cap	6.5 mm	Rated Input Voltage	24 V/DC
(h3) Height Hose	5 mm	CRI (Ra)	90
(b1) Width	14 mm	Control	Dimmable via optional controller
(b2) Width end cap	16.2 mm	Working Temperature	-10 to 105 °C
(b3) Width Hose	14 mm	Channels	4
(l1) Length End Cap	10 mm		
(l2) Primary Cable Length	1.8 m		

Article	(l3) Secondary Cable Length	Length	Price
840414		2000 mm	€ 119.95
840416	1.8 m	5000 mm	€ 267.95




Accessories

- 930800** Supply cable for 24 V COB RGBW Sauna stripe
- 930801** Connector for 24 V COB RGBW Sauna stripe
- 930797** Silicone end cap set of 2 pieces for 24 V COB RGB/RGBW Sauna stripe
- 930803** Plastic profile 1 m for 24 V COB RGB/RGBW Sauna stripe
- 930804** Plastic profile 2 m for 24 V COB RGB/RGBW Sauna stripe
- 930802** Silicone clamps for 24 V COB RGB/RGBW Sauna stripe
- 930850** Silicone adhesive 10 ml

	€ 9.95
	€ 13.95
	€ 0.75
	€ 4.95
	€ 9.95
	€ 1.45
	€ 3.95



COB 48V-15W FACADE LONG RUN IP67



- for weather-exposed building facades
- for outdoor areas with direct sunlight
- UV-resistant
- permanently temperature-resistant (-40°C to 95°C)
- long service life with 75,000h L70B50 / 50,000h L80B10
- solder-free accessories
- 3M VHB 5604A adhesive tape with silicone primer pre-treatment

(c) Segment Length	100 mm	Rated Input 1m	15 W
(a) Light Beam Angle	120 Degree	Rated Input Voltage	48 V/DC
(r1) Bending Radius min.	50 mm	Control	Dimmable via optional controller
(l1) Length End Cap	10 mm	Working Temperature	-40 to 95 °C
(l2) Primary Cable Length	1 m		
(l3) Secondary Cable Length	1 m		

Article	Colour	Temperature (p)	LED Distance	(h1) Height	(h2) Height	(h3) Height	(b1) Width	EEL	Price
840428	RGB		1.19 mm	5 mm	5.5 mm	5 mm	14.5 mm		€ 719.95
840429	RGB		1.19 mm	5 mm	5.5 mm	5 mm	14.5 mm		€ 259.95
840426	WW	CW 2700-6500 K	1.79 mm	5.5 mm	6.5 mm	5.5 mm	12 mm	G	€ 539.95
840427	WW	CW 2700-6500 K	1.79 mm	5.5 mm	6.5 mm	5.5 mm	12 mm	G	€ 199.95
840420	WW	2700 K	2.08 mm	5.5 mm	6.5 mm	5.5 mm	12 mm	F	€ 399.95
840423	WW	2700 K	2.08 mm	5.5 mm	6.5 mm	5.5 mm	12 mm	F	€ 143.95
840421	WW	3000 K	2.08 mm	5.5 mm	6.5 mm	5.5 mm	12 mm	F	€ 399.95
840424	WW	3000 K	2.08 mm	5.5 mm	6.5 mm	5.5 mm	12 mm	F	€ 143.95
840422	NW	4000 K	2.08 mm	5.5 mm	6.5 mm	5.5 mm	12 mm	E	€ 399.95
840425	NW	4000 K	2.08 mm	5.5 mm	6.5 mm	5.5 mm	12 mm	E	€ 143.95



Accessories

930850	Silicone adhesive 10 ml		€ 3.95
843279	MULTI-LED dimmer 1-4 channels, DMX/auto/manual, 12-48 V, 20 A, flicker-free		€ 91.95

Accessories for **840420, 840421, 840422**

862276	BASIC, DIM, CV, LCP DALI, 48V, 240W, IP20		€ 175.95
---------------	---	---	----------

Accessories for **840420, 840421, 840422, 840423, 840424, 840425**

930737	Supply cable for 24 V COB Sauna stripe		€ 9.95
930738	Connector for 24 V COB Sauna stripe		€ 13.95

Accessories for **840420, 840421, 840422, 840423, 840424, 840425, 840426, 840427**

930736	Silicone end cap set of 2 pieces for 24 V COB Sauna stripe		€ 0.75
930739	Silicone clamps for 24 V COB Sauna stripe		€ 1.45
930740	Plastic profile 1 m for 24 V COB Sauna stripe		€ 3.95
930741	Plastic profile 2 m for 24 V COB Sauna stripe		€ 7.95
843341	DALI 2 PWM dimmer CV 2CH 12-48V, 8A/CH, DT6		€ 67.95
843501	RF-smart, starter set LED single/CCT, 12-48 V, 20 A incl. remote control		€ 79.95

Accessories for **840420, 840421, 840422, 840426, 840428**

862272	LONG-FLAT, CV, LT-240-48		€ 127.95
862281	Long-Flat, DIM, CV, 48V 80-240W		€ 127.95
872125	CV, HLG-600H-48 A		€ 391.95
872126	DIM, CV, HLG-600H-48B		€ 399.95
872145	IP, CV, V6-320-48		€ 175.95

Accessories for **840423, 840424, 840425**

862273	BASIC, DIM, CV, LCP DALI, 48V, 75W, IP20		€ 103.95
862275	BASIC, DIM, CV, LCP DALI, 48V, 150W, IP20		€ 135.95
872115	CV, PWM-200-48 KN		€ 195.95

Accessories for **840423, 840424, 840425, 840427, 840429**

862269	Long-Flat, DIM, CV, 48 V 50-150 W		€ 103.95
862270	LONG-FLAT, CV, LT-100-48		€ 77.95
862271	LONG-FLAT, CV, LT-150-48		€ 103.95
862274	BASIC, DIM, CV, 48 V 34-100 W		€ 115.95
862283	Long-Flat, DIM, CV, 48V 25-75W		€ 79.95
872142	LED power supply, IP, DIM, CV, 48 V, 33-100 W		€ 135.95
872143	LED power supply, IP, DIM, CV, 48 V, 66-200 W		€ 165.95



Accessories for **840426, 840427**

930865	End cap for Facade Long Run series		€ 6.95
930866	Connecting cable for Facade Long Run series		€ 9.95
843342	DALI 2 PWM dimmer CV 2CH 12-48V, 8A/CH, DT8		€ 67.95

Accessories for **840428, 840429**

930797	Silicone end cap set of 2 pieces for 24 V COB RGB/RGBW Sauna stripe		€ 0.75
930798	Supply cable for 24 V COB RGB Sauna stripe		€ 9.95
930799	Connector for 24 V COB RGB Sauna stripe		€ 13.95
930802	Silicone clamps for 24 V COB RGB/RGBW Sauna stripe		€ 1.45
930803	Plastic profile 1 m for 24 V COB RGB/RGBW Sauna stripe		€ 4.95
930804	Plastic profile 2 m for 24 V COB RGB/RGBW Sauna stripe		€ 9.95
843343	DALI 2 PWM dimmer CV 4CH 12-48V, 4A/CH, DT6		€ 75.95
843502	RF-smart, starter set RGB/W/CCT, 12-48 V, 20 A incl. remote, IP20		€ 79.95


COB 48 V-18.5 W FACADE LONG RUN IP67



- For weathered building façades
- For outdoor areas exposed to direct sunlight
- UV-resistant
- Permanently temperature-resistant (-40 °C to 95 °C)
- Long service life with 75,000 h L70B50/50,000 h L80B10
- Solder-free accessories
- 3M VHB 5604A adhesive tape with silicone primer pre-treatment

(p) LED Distance	1.56 mm	(l1) Length End Cap	10 mm
(c) Segment Length	100 mm	(l2) Primary Cable Length	1 m
(a) Light Beam Angle	120 Degree	(l3) Secondary Cable Length	1 m
(r1) Bending Radius min.	50 mm	Rated Input 1m	18.5 W
(h1) Height	0.5 mm	Rated Input Voltage	48 V/DC
(h2) Height End Cap	5.5 mm	CRI (Ra)	90
(h3) Height Hose	5.5 mm	Control	Dimmable via optional controller
(b1) Width	12 mm	Working Temperature	-40 to 95 °C
(b2) Width end cap	14 mm	Channels	4
(b3) Width Hose	14 mm		

Article	Colour Temperature		Luminous Efficiency 1m	Luminous Flux 1m	Length	Price
840432		3000 K	64 lm/W	890 lm	5000 mm	€ 303.95
840430		3000 K	64 lm/W	890 lm	15000 mm	€ 799.95
840433		4000 K	45 lm/W	1010 lm	5000 mm	€ 303.95
840431		4000 K	45 lm/W	1010 lm	15000 mm	€ 799.95



Accessories

930800	Supply cable for 24 V COB RGBW Sauna stripe		€ 9.95
930801	Connector for 24 V COB RGBW Sauna stripe		€ 13.95
930797	Silicone end cap set of 2 pieces for 24 V COB RGB/RGBW Sauna stripe		€ 0.75
930803	Plastic profile 1 m for 24 V COB RGB/RGBW Sauna stripe		€ 4.95
930804	Plastic profile 2 m for 24 V COB RGB/RGBW Sauna stripe		€ 9.95
930802	Silicone clamps for 24 V COB RGB/RGBW Sauna stripe		€ 1.45
930850	Silicone adhesive 10 ml		€ 3.95
843502	RF-smart, starter set RGB/W/CCT, 12-48 V, 20 A incl. remote, IP20		€ 79.95
843343	DALI 2 PWM dimmer CV 4CH 12-48V, 4A/CH, DT6		€ 75.95
843344	DALI 2 PWM dimmer CV 4CH 12-48V, 4A/CH, DT8		€ 75.95
843279	MULTI-LED dimmer 1-4 channels, DMX/auto/manual, 12-48 V, 20 A, flicker-free		€ 91.95

Accessories for **840430, 840431**


862272	LONG-FLAT, CV, LT-240-48		€ 127.95
862281	Long-Flat, DIM, CV, 48V 80-240W		€ 127.95
872125	CV, HLG-600H-48 A		€ 391.95
872126	DIM, CV, HLG-600H-48B		€ 399.95
872145	IP, CV, V6-320-48		€ 175.95

Accessories for **840432, 840433**

862269	Long-Flat, DIM, CV, 48 V 50-150 W		€ 103.95
862270	LONG-FLAT, CV, LT-100-48		€ 77.95
862271	LONG-FLAT, CV, LT-150-48		€ 103.95
862274	BASIC, DIM, CV, 48 V 34-100 W		€ 115.95
862283	Long-Flat, DIM, CV, 48V 25-75W		€ 79.95
872142	LED power supply, IP, DIM, CV, 48 V, 33-100 W		€ 135.95
872143	LED power supply, IP, DIM, CV, 48 V, 66-200 W		€ 165.95




COB 24V-12W STANDARD IP20



(p) LED Distance	2.08 mm	Length	5000 mm
(c) Segment Length	50 mm	Rated Input 1m	12 W
(a) Light Beam Angle	180 Degree	Rated Input Voltage	24 V/DC
(r1) Bending Radius min.	30 mm	CRI (Ra)	90
(h1) Height	2.2 mm	Control	Dimmable via optional controller
(b1) Width	10 mm	Working Temperature	-20 to 50 °C
(l2) Primary Cable Length	0.5 m	Channels	1
(l3) Secondary Cable Length	0.5 m		

Article	Colour Temperature	Luminous Efficiency 1m	Luminous Flux 1m	Price
840474	WW 2700 K	88 lm/W	1050 lm	€ 55.95
840475	WW 3000 K	113 lm/W	1360 lm	€ 55.95
840476	NW 4000 K	110 lm/W	1320 lm	€ 55.95





Accessories

862270	LONG-FLAT, CV, LT-100-48
862271	LONG-FLAT, CV, LT-150-48
862269	Long-Flat, DIM, CV, 48 V 50-150 W
862274	BASIC, DIM, CV, 48 V 34-100 W
872142	LED power supply, IP, DIM, CV, 48 V, 33-100 W
872143	LED power supply, IP, DIM, CV, 48 V, 66-200 W
862262	BASIC, DIM, CV, LCP DALI, 24V, 150W, IP20
862263	BASIC, DIM, CV, LCP DALI, 24V, 240W, IP20
872113	CV, PWM-120-24 KN
931101	Mounting roller for 8/10mm LED-Stripes, blue
931102	Mounting roller for 10/12mm LED-Stripes, blue


	€ 77.95
	€ 103.95
	€ 103.95
	€ 115.95
	€ 135.95
	€ 165.95
	€ 135.95
	€ 175.95
	€ 167.95
	€ 11.95
	€ 11.95

COB 24V-12W STANDARD IP67



(p) LED Distance	2.08 mm	(l2) Primary Cable Length	0.5 m
(c) Segment Length	50 mm	(l3) Secondary Cable Length	0.5 m
(a) Light Beam Angle	180 Degree	Length	5000 mm
(r1) Bending Radius min.	70 mm	Rated Input 1m	12 W
(h1) Height	4.5 mm	Rated Input Voltage	24 V/DC
(h2) Height End Cap	3.2 mm	CRI (Ra)	90
(h3) Height Hose	2.2 mm	Control	Dimmable via optional controller
(b1) Width	12 mm	Type of IP Protection	Silicone hose
(b2) Width end cap	14 mm	Working Temperature	-20 to 50 °C
(b3) Width Hose	12 mm	Channels	1
(l1) Length End Cap	10 mm		

Article	Colour Temperature	Luminous Efficiency 1m	Luminous Flux 1m	Price
840477	WW 2700 K	98 lm/W	1170 lm	€ 71.95
840478	WW 3000 K	102 lm/W	1220 lm	€ 71.95
840479	NW 4000 K	117 lm/W	1400 lm	€ 71.95





Accessories

862270	LONG-FLAT, CV, LT-100-48
862271	LONG-FLAT, CV, LT-150-48
862269	Long-Flat, DIM, CV, 48 V 50-150 W
862274	BASIC, DIM, CV, 48 V 34-100 W
872142	LED power supply, IP, DIM, CV, 48 V, 33-100 W
872143	LED power supply, IP, DIM, CV, 48 V, 66-200 W
862262	BASIC, DIM, CV, LCP DALI, 24V, 150W, IP20
862263	BASIC, DIM, CV, LCP DALI, 24V, 240W, IP20
872113	CV, PWM-120-24 KN
931102	Mounting roller for 10/12mm LED-Stripes, blue


	€ 77.95
	€ 103.95
	€ 103.95
	€ 115.95
	€ 135.95
	€ 165.95
	€ 135.95
	€ 175.95
	€ 167.95
	€ 11.95

COB 24V-15W STANDARD IP20



(p) LED Distance	1.73 mm	Luminous Flux 1m	1550 lm
(c) Segment Length	27.8 mm	Length	5000 mm
(a) Light Beam Angle	180 Degree	Rated Input 1m	15 W
(r1) Bending Radius min.	15 mm	Rated Input Voltage	24 V/DC
(h1) Height	1.8 mm	CRI (Ra)	90
(b1) Width	10 mm	Control	Dimmable via optional controller
(l2) Primary Cable Length	0.5 m	Working Temperature	-20 to 50 °C
(l3) Secondary Cable Length	0.5 m	Channels	2
Colour Temperature	2700-6500 K		

Article	Colour Temperature	Price
840480	WW CW 2700-6500 K	€ 119.95




Accessories

843501	RF-smart, starter set LED single/CCT, 12-48 V, 20 A incl. remote control	€ 79.95
843037	Casambi BT Dimmer CBU-PWM4 (CV, 12-24V, 6A DC)	€ 143.95
843279	MULTILED dimmer 1-4 channels, DMX/auto/manual, 12-48V, 20 A, flicker-free	€ 91.95
843341	DALI 2 PWM dimmer CV 2CH 12-48V, 8A/CH, DT6	€ 67.95
843342	DALI 2 PWM dimmer CV 2CH 12-48V, 8A/CH, DT8	€ 67.95
862270	LONG-FLAT, CV, LT-100-48	€ 77.95
862271	LONG-FLAT, CV, LT-150-48	€ 103.95
931101	Mounting roller for 8/10mm LED-Stripes, blue	€ 11.95
931102	Mounting roller for 10/12mm LED-Stripes, blue	€ 11.95




COB 24V-15W STANDARD IP67



(p) LED Distance	1.73 mm	(l3) Secondary Cable Length	0.5 m
(c) Segment Length	27.8 mm	Colour Temperature	2700-6500 K
(a) Light Beam Angle	180 Degree	Luminous Flux 1m	1300 lm
(r1) Bending Radius min.	50 mm	Length	5000 mm
(h1) Height	4.5 mm	Rated Input 1m	15 W
(h2) Height End Cap	6 mm	Rated Input Voltage	24 V/DC
(h3) Height Hose	4.5 mm	CRI (Ra)	90
(b1) Width	12 mm	Control	Dimmable via optional controller
(b2) Width end cap	14 mm	Type of IP Protection	Silicone hose
(b3) Width Hose	12 mm	Working Temperature	-20 to 50 °C
(l1) Length End Cap	10 mm	Channels	2
(l2) Primary Cable Length	0.5 m		



Article	Colour Temperature	Price
840481	WW CW 2700-6500 K	€ 135.95



Accessories

843501	RF-smart, starter set LED single/CCT, 12-48V, 20 A incl. remote control	€ 79.95
843037	Casambi BT Dimmer CBU-PWM4 (CV, 12-24V, 6A DC)	€ 143.95
843279	MULTI-LED dimmer 1-4 channels, DMX/auto/manual, 12-48V, 20 A, flicker-free	€ 91.95
843341	DALI 2 PWM dimmer CV 2CH 12-48V, 8A/CH, DT6	€ 67.95
843342	DALI 2 PWM dimmer CV 2CH 12-48V, 8A/CH, DT8	€ 67.95
862270	LONG-FLAT, CV, LT-100-48	€ 77.95
862271	LONG-FLAT, CV, LT-150-48	€ 103.95
931102	Mounting roller for 10/12mm LED-Stripes, blue	€ 11.95

COB 24V-16W STANDARD IP20




·high-performance adhesive tape 3M 300MP

(p) LED Distance	1.78 mm	Luminous Flux 1m	800 lm
(c) Segment Length	50 mm	Length	5000 mm
(a) Light Beam Angle	180 Degree	Rated Input 1m	16 W
(r1) Bending Radius min.	15 mm	Rated Input Voltage	24 V/DC
(h1) Height	1.8 mm	CRI (Ra)	90
(b1) Width	12 mm	Control	Dimmable via optional controller
(l2) Primary Cable Length	0.5 m	Working Temperature	-20 to 50 °C
(l3) Secondary Cable Length	0.5 m	Channels	4
Colour Temperature	3000 K		
Luminous Efficiency 1m	49 lm/W		

ArticlePrice

840482 € 159.95





Accessories

843542	RF-smart, Starter-Set RGB/W/CCT, 12-48V, 20A incl. Remote, IP20
843037	Casambi BT Dimmer CBU-PWM4 (CV, 12-24V, 6A DC)
843279	MULTI-LED dimmer 1-4 channels, DMX/auto/manual, 12-48 V, 20 A, flicker-free
843343	DALI 2 PWM dimmer CV 4CH 12-48V, 4A/CH, DT6
843344	DALI 2 PWM dimmer CV 4CH 12-48V, 4A/CH, DT8
862166	BASIC, CV, Q8H-24-100 W
872089	IP, CV, V6-240-24
862301	Basic, Casambi 3/4 Kanal, 24V, 150W, IP20
931102	Mounting roller for 10/12mm LED-Stripes, blue


	€ 91.95
	€ 143.95
	€ 91.95
	€ 75.95
	€ 75.95
	€ 77.95
	€ 147.95
	€ 167.95
	€ 11.95

COB 24V-16W STANDARD IP67



(p) LED Distance	1.78 mm	Colour Temperature	3000 K
(c) Segment Length	50 mm	Luminous Efficiency 1m	49 lm/W
(a) Light Beam Angle	180 Degree	Luminous Flux 1m	800 lm
(r1) Bending Radius min.	50 mm	Length	5000 mm
(h1) Height	4.5 mm	Rated Input 1m	16 W
(h2) Height End Cap	6 mm	Rated Input Voltage	24 V/DC
(h3) Height Hose	4.5 mm	CRI (Ra)	90
(b1) Width	14 mm	Control	Dimmable via optional controller
(b2) Width end cap	14 mm	Type of IP Protection	Silicone hose
(b3) Width Hose	14 mm	Working Temperature	-20 to 50 °C
(l1) Length End Cap	10 mm	Channels	4
(l2) Primary Cable Length	0.5 m		
(l3) Secondary Cable Length	0.5 m		



Article	Price
840483	€ 175.95



Accessories


843542	RF-smart, Starter-Set RGB/W/CCT, 12-48V, 20A incl. Remote, IP20		€ 91.95
843037	Casambi BT Dimmer CBU-PWM4 (CV, 12-24V, 6A DC)		€ 143.95
843279	MULTI-LED dimmer 1-4 channels, DMX/auto/manual, 12-48 V, 20 A, flicker-free		€ 91.95
843343	DALI 2 PWM dimmer CV 4CH 12-48V, 4A/CH, DT6		€ 75.95
843344	DALI 2 PWM dimmer CV 4CH 12-48V, 4A/CH, DT8		€ 75.95
862166	BASIC, CV, Q8H-24-100 W		€ 77.95
872089	IP, CV, V6-240-24		€ 147.95
862301	Basic, Casambi 3/4 Kanal, 24V, 150W, IP20		€ 167.95

COB 24V-15W PROFESSIONAL IP20



(p) LED Distance	3.47 mm	Length	5000 mm
(c) Segment Length	27.77 mm	Rated Input 1m	15 W
(a) Light Beam Angle	180 Degree	Rated Input Voltage	24 V/DC
(r1) Bending Radius min.	30 mm	CRI (Ra)	90
(h1) Height	2.2 mm	Control	Dimmable via optional controller
(b1) Width	10 mm	Working Temperature	-20 to 50 °C
(l2) Primary Cable Length	0.5 m	Channels	1
(l3) Secondary Cable Length	0.5 m		

Article	Colour Temperature	Luminous Efficiency 1m	Luminous Flux 1m	Price
840466	WW 2700 K	140 lm/W	2100 lm	€ 71.95
840467	WW 3000 K	170 lm/W	2550 lm	€ 71.95
840468	NW 4000 K	179 lm/W	2690 lm	€ 71.95
840469	CW 6500 K	179 lm/W	2690 lm	€ 71.95





Accessories

862270	LONG-FLAT, CV, LT-100-48
862271	LONG-FLAT, CV, LT-150-48
862269	Long-Flat, DIM, CV, 48 V 50-150 W
862274	BASIC, DIM, CV, 48 V 34-100 W
872142	LED power supply, IP, DIM, CV, 48 V, 33-100 W
872143	LED power supply, IP, DIM, CV, 48 V, 66-200 W
862262	BASIC, DIM, CV, LCP DALI, 24V, 150W, IP20
862263	BASIC, DIM, CV, LCP DALI, 24V, 240W, IP20
872113	CV, PWM-120-24 KN
931101	Mounting roller for 8/10mm LED-Stripes, blue
931102	Mounting roller for 10/12mm LED-Stripes, blue


	€ 77.95
	€ 103.95
	€ 103.95
	€ 115.95
	€ 135.95
	€ 165.95
	€ 135.95
	€ 175.95
	€ 167.95
	€ 11.95
	€ 11.95

COB 24V-15W PROFESSIONAL IP67



(p) LED Distance	3.47 mm	(l2) Primary Cable Length	0.5 m
(c) Segment Length	27.77 mm	(l3) Secondary Cable Length	0.5 m
(a) Light Beam Angle	180 Degree	Length	5000 mm
(r1) Bending Radius min.	70 mm	Rated Input 1m	15 W
(h1) Height	4.5 mm	Rated Input Voltage	24 V/DC
(h2) Height End Cap	3.2 mm	CRI (Ra)	90
(h3) Height Hose	2.2 mm	Control	Dimmable via optional controller
(b1) Width	12 mm	Type of IP Protection	Silicone hose
(b2) Width end cap	14 mm	Working Temperature	-20 to 50 °C
(b3) Width Hose	12 mm	Channels	1
(l1) Length End Cap	10 mm		

Article	Colour Temperature	Luminous Efficiency 1m	Luminous Flux 1m	Price
840470	2700 K	137 lm/W	2060 lm	€ 87.95
840471	3000 K	137 lm/W	2060 lm	€ 87.95
840472	4000 K	144 lm/W	2160 lm	€ 87.95
840473	6500 K	143 lm/W	2150 lm	€ 87.95



Accessories

862270	LONG-FLAT, CV, LT-100-48
862271	LONG-FLAT, CV, LT-150-48
862269	Long-Flat, DIM, CV, 48 V 50-150 W
862274	BASIC, DIM, CV, 48 V 34-100 W
872142	LED power supply, IP, DIM, CV, 48 V, 33-100 W
872143	LED power supply, IP, DIM, CV, 48 V, 66-200 W
862262	BASIC, DIM, CV, LCP DALI, 24V, 150W, IP20
862263	BASIC, DIM, CV, LCP DALI, 24V, 240W, IP20
872113	CV, PWM-120-24 KN
931102	Mounting roller for 10/12mm LED-Stripes, blue


	€ 77.95
	€ 103.95
	€ 103.95
	€ 115.95
	€ 135.95
	€ 165.95
	€ 135.95
	€ 175.95
	€ 167.95
	€ 11.95

12V LED STRIPES

These LED strips are ideally suited for all standard applications and special assemblies with the most diverse requirements. With voltages of 12V, different protection classes, lumens, number of LEDs, power and much more, you too can find the right LED strip for your application.




SMD 12V-7W SHORT CUT IP20



• high-performance adhesive 3M 9448A

(p) LED Distance	8.33 mm	Length	5000 mm
(c) Segment Length	25 mm	Rated Input Voltage	12 V/DC
(a) Light Beam Angle	120 Degree	CRI (Ra)	90
(r1) Bending Radius min.	20 mm	Control	Dimmable via optional controller
(h1) Height	3 mm	Working Temperature	-15 to 50 °C
(b1) Width	8 mm	Channels	1
(l2) Primary Cable Length	1 m		
(l3) Secondary Cable Length	1 m		

Article	Colour Temperature	Luminous Efficiency 1m	Luminous Flux 1m	Rated Input 1m	EEL	Price
840164	2700 K	81.43 lm/W	570 lm	7.0 W		€ 71.95
840165	3000 K	85.38 lm/W	555 lm	6.5 W		€ 71.95
840166	4000 K	95.71 lm/W	670 lm	7.0 W		€ 71.95
840167	6500 K	90 lm/W	630 lm	7.0 W		€ 71.95



Aluminium profiles


In the »Aluminum profiles« section you will find the right profile for every application with various covers and installation options.

24V LED STRIPES

These LED strips are ideal for all standard applications and special assemblies with a wide range of requirements. With voltages of 24V, different protection classes, lumens, number of LEDs, power and much more, you too will find the right LED strip for your application.




SMD 24V-10W LONG RUN IP20



·high-performance adhesive 3M 9448A

(p) LED Distance	8.33 mm	Luminous Flux 1m	705 lm
(c) Segment Length	50 mm	Length	10000 mm
(a) Light Beam Angle	120 Degree	Rated Input 1m	9.5 W
(r1) Bending Radius min.	20 mm	Rated Input Voltage	24 V/DC
(h1) Height	2 mm	CRI (Ra)	90
(b1) Width	10 mm	Control	Dimmable via optional controller
(l2) Primary Cable Length	1 m	Working Temperature	-15 to 50 °C
(l3) Secondary Cable Length	1 m	Channels	1
Colour Temperature	3000 K		
Luminous Efficiency 1m	74.21 lm/W		


Article Price

840291  € 319.95**Lighting design**

Interested in our lighting design service?

Your contact person will be happy to answer any questions you may have.


SMD 24V-10W SLIM IP20



·high-performance adhesive 3M 9448A

(p) LED Distance	8.33 mm	Length	5000 mm
(c) Segment Length	50 mm	Rated Input 1m	9.6 W
(a) Light Beam Angle	120 Degree	Rated Input Voltage	24 V/DC
(r1) Bending Radius min.	20 mm	CRI (Ra)	90
(h1) Height	3 mm	Control	Dimmable via optional controller
(b1) Width	5 mm	Working Temperature	-15 to 50 °C
(l2) Primary Cable Length	1 m	Channels	1
(l3) Secondary Cable Length	1 m		


Article	Colour Temperature	Luminous Efficiency 1m	Luminous Flux 1m	Price
840158	WW 2700 K	80 lm/W	770 lm	€ 63.95
840159	WW 3000 K	85 lm/W	820 lm	€ 63.95



Aluminium profiles

In the »Aluminum profiles« section you will find the right profile for every application with various covers and installation options.


SMD 24V-11W SLIM IP20



• high-performance adhesive 3M 9448A


(p) LED Distance	3.8 mm	Length	5000 mm
(c) Segment Length	26.3 mm	Rated Input Voltage	24 V/DC
(a) Light Beam Angle	120 Degree	CRI (Ra)	90
(r1) Bending Radius min.	20 mm	Control	Dimmable via optional controller
(h1) Height	2 mm	Working Temperature	-15 to 50 °C
(b1) Width	4 mm	Channels	1
(l2) Primary Cable Length	1 m		
(l3) Secondary Cable Length	1 m		

Article	Colour Temperature	Luminous Efficiency 1m	Luminous Flux 1m	Rated Input 1m	Price
840175	2700 K	90.45 lm/W	995 lm	11.0 W	€ 135.95
840210	3000 K	99.09 lm/W	1090 lm	11.0 W	€ 135.95
840267	4000 K	95.65 lm/W	1100 lm	11.5 W	€ 135.95

**Power supply units**

You can find the right power supply unit in various designs and with the required voltage and power in the »Power supply units« section.


SMD 24 V-11 W CCT SLIM IP20



·high-performance adhesive tape 3M 200MP


(p) LED Distance	10.2 mm	Colour Temperature	3000-6500 K
(c) Segment Length	71.4 mm	Luminous Efficiency 1m	93.18 lm/W
(a) Light Beam Angle	120 Degree	Luminous Flux 1m	1025 lm
(r1) Bending Radius min.	50 mm	Length	5000 mm
(h1) Height	1.2 mm	Rated Input 1m	11 W
(h2) Height End Cap	2.6 mm	Rated Input Voltage	24 V/DC
(b1) Width	5 mm	CRI (Ra)	90
(b2) Width end cap	5.5 mm	Control	Dimmable via optional controller
(l1) Length End Cap	15 mm	Working Temperature	-10 to 60 °C
(l2) Primary Cable Length	1 m	Channels	2
(l3) Secondary Cable Length	1 m		

Article	Colour Temperature	Price
840350	WW CW 3000-6500 K	€ 99.95



Aluminium profiles
In the »Aluminum profiles« section you will find the right profile for every application with various covers and installation options.

SMD 24V-12W SLIM IP65




- Including mounting material
- high-performance adhesive tape 3M 200MP

(p) LED Distance	5.1 mm	Colour Temperature	3000-6500 K
(c) Segment Length	71.4 mm	Luminous Efficiency 1m	85.6 lm/W
(a) Light Beam Angle	120 Degree	Luminous Flux 1m	1070 lm
(r1) Bending Radius min.	50 mm	Length	5000 mm
(h1) Height	5.3 mm	Rated Input 1m	12.5 W
(h2) Height End Cap	5.3 mm	Rated Input Voltage	24 V/DC
(h3) Height Hose	3.7 mm	CRI (Ra)	90
(b1) Width	5 mm	Control	Dimmable via optional controller
(b2) Width end cap	10 mm	Type of IP Protection	Silicone hose
(b3) Width Hose	7.4 mm	Working Temperature	-10 to 60 °C
(l1) Length End Cap	10.2 mm	Channels	2
(l2) Primary Cable Length	1 m		
(l3) Secondary Cable Length	1 m		

Article Colour Temperature Price

840349   3000-6500 K


€ 119.95



Power supply units

You can find the right power supply unit in various designs and with the required voltage and power in the »Power supply units« section.

SMD 24V-11W STANDARD IP20



·high-performance adhesive 3M 9448A

(p) LED Distance	8.33 mm	Luminous Flux 1m	500 lm
(c) Segment Length	50 mm	Length	5000 mm
(a) Light Beam Angle	110 Degree	Rated Input 1m	11 W
(r1) Bending Radius min.	20 mm	Rated Input Voltage	24 V/DC
(h1) Height	2 mm	CRI (Ra)	60
(b1) Width	5 mm	Control	Dimmable via optional controller
(l2) Primary Cable Length	1 m	Working Temperature	-15 to 50 °C
(l3) Secondary Cable Length	1 m	Channels	3
Luminous Efficiency 1m	45.45 lm/W		

Article	Price
840276 	€ 87.95

CV





3 CH

IP20








Aluminium profiles

In the »Aluminum profiles« section you will find the right profile for every application with various covers and installation options.

SMD 24V-11W STANDARD IP67




•Including mounting material

•high-performance adhesive 3M 9448A

(p) LED Distance	5.5 mm	(l2) Primary Cable Length	1 m
(c) Segment Length	33.3 mm	(l3) Secondary Cable Length	1 m
(a) Light Beam Angle	120 Degree	Length	5000 mm
(r1) Bending Radius min.	50 mm	Rated Input Voltage	24 V/DC
(h1) Height	5.5 mm	CRI (Ra)	90
(h2) Height End Cap	6.5 mm	Control	Dimmable via optional controller
(h3) Height Hose	5.5 mm	Type of IP Protection	Silicone hose
(b1) Width	11.5 mm	Working Temperature	-15 to 50 °C
(b2) Width end cap	12.5 mm	Channels	1
(b3) Width Hose	11.5 mm		
(l1) Length End Cap	10 mm		


Article	Colour Temperature	Luminous Efficiency 1m	Luminous Flux 1m	Rated Input 1m	EEL	Price
840186	2700 K	78.26 lm/W	900 lm	11.5 W		€ 147.95
840187	3000 K	84.55 lm/W	930 lm	11.0 W		€ 147.95



Power supply units

You can find the right power supply unit in various designs and with the required voltage and power in the »Power supply units« section.

SMD 24V-13W STANDARD IP20



·high-performance adhesive 3M 9448A

(p) LED Distance	16.66 mm	Luminous Flux 1m	580 lm
(c) Segment Length	100 mm	Length	5000 mm
(a) Light Beam Angle	120 Degree	Rated Input 1m	13 W
(r1) Bending Radius min.	20 mm	Rated Input Voltage	24 V/DC
(h1) Height	3 mm	Control	Dimmable via optional controller
(b1) Width	10 mm	Working Temperature	-15 to 50 °C
(l2) Primary Cable Length	1 m	Channels	3
(l3) Secondary Cable Length	1 m		
Luminous Efficiency 1m	44.62 lm/W		


Article Price

840254  € 107.95



Aluminium profiles
In the »Aluminum profiles« section you will find the right profile for every application with various covers and installation options.

SMD 24V-13W STANDARD IP67




- Including mounting material
- high-performance adhesive 3M 9448A

(p) LED Distance	16.66 mm	(l3) Secondary Cable Length	1 m
(c) Segment Length	100 mm	Luminous Efficiency 1m	49.6 lm/W
(a) Light Beam Angle	120 Degree	Luminous Flux 1m	670 lm
(r1) Bending Radius min.	50 mm	Length	5000 mm
(h1) Height	6 mm	Rated Input 1m	13.5 W
(h2) Height End Cap	6.5 mm	Rated Input Voltage	24 V/DC
(h3) Height Hose	5.5 mm	Control	Dimmable via optional controller
(b1) Width	13 mm	Type of IP Protection	Silicone hose
(b2) Width end cap	15.5 mm	Working Temperature	-15 to 50 °C
(b3) Width Hose	14.5 mm	Channels	3
(l1) Length End Cap	10 mm		
(l2) Primary Cable Length	1 m		

Article Price


840256  € 127.95



Power supply units

You can find the right power supply unit in various designs and with the required voltage and power in the »Power supply units« section.

SMD 24V-14W STANDARD IP20



·high-performance adhesive 3M 9448A



(a) Light Beam Angle	120 Degree	Rated Input Voltage	24 V/DC
(r1) Bending Radius min.	20 mm	Control	Dimmable via optional controller
(I2) Primary Cable Length	1 m		
(I3) Secondary Cable Length	1 m		

Article	Colour Temperature	(p) LED Distance	(c) Segment Length	(h1) Height	(b1) Width	EEL	Price
840147	RGB	10.4 mm	83.3 mm	2 mm	10 mm		€ 135.95
840178	WW 2700 K	5.56 mm	33.4 mm	3 mm	8 mm		€ 99.95
840179	WW 3000 K	5.56 mm	33.4 mm	3 mm	8 mm		€ 99.95
930512	WW 3000 K	5.56 mm	33.4 mm	3 mm	8 mm		€ 935.95
840180	NW 4000 K	5.56 mm	33.4 mm	3 mm	8 mm		€ 99.95



Aluminium profiles
 In the »Aluminum profiles« section you will find the right profile for every application with various covers and installation options.

SMD 24V-15W STANDARD IP67




- Including mounting material
- high-performance adhesive 3M 9448A

(p) LED Distance	16.7 mm	Colour Temperature	3000 K
(c) Segment Length	100 mm	Luminous Efficiency 1m	49 lm/W
(a) Light Beam Angle	120 Degree	Luminous Flux 1m	740 lm
(r1) Bending Radius min.	50 mm	Length	5000 mm
(h1) Height	5.5 mm	Rated Input 1m	15 W
(h2) Height End Cap	6.5 mm	Rated Input Voltage	24 V/DC
(h3) Height Hose	5.5 mm	CRI (Ra)	80
(b1) Width	14.5 mm	Control	Dimmable via optional controller
(b2) Width end cap	15.5 mm	Type of IP Protection	Silicone hose
(b3) Width Hose	14.5 mm	Working Temperature	-15 to 50 °C
(l1) Length End Cap	10 mm	Channels	4
(l2) Primary Cable Length	1 m		
(l3) Secondary Cable Length	1 m		

Article Price


840239  € 139.95



Power supply units

You can find the right power supply unit in various designs and with the required voltage and power in the »Power supply units« section.

SMD 24 V-16 W RGBNW STANDARD IP20




·high-performance adhesive tape 3M 200MP

(p) LED Distance	16.66 mm	Colour Temperature	4000 K
(c) Segment Length	166.66 mm	Luminous Efficiency 1m	46.97 lm/W
(a) Light Beam Angle	120 Degree	Luminous Flux 1m	775 lm
(r1) Bending Radius min.	50 mm	Length	5000 mm
(h1) Height	2 mm	Rated Input 1m	16.5 W
(h2) Height End Cap	3 mm	Rated Input Voltage	24 V/DC
(b1) Width	10 mm	CRI (Ra)	80
(b2) Width end cap	10.5 mm	Control	Dimmable via optional controller
(l1) Length End Cap	15 mm	Working Temperature	-10 to 60 °C
(l2) Primary Cable Length	1 m	Channels	4
(l3) Secondary Cable Length	1 m		


Article Price

840353   € 119.95



Aluminium profiles
In the »Aluminum profiles« section you will find the right profile for every application with various covers and installation options.


SMD 24V-16W RGBWW STANDARD IP20



·high-performance adhesive 3M 9448A



(p) LED Distance	16.66 mm	Luminous Efficiency 1m	51.25 lm/W
(c) Segment Length	100 mm	Luminous Flux 1m	820 lm
(a) Light Beam Angle	120 Degree	Rated Input 1m	16 W
(r1) Bending Radius min.	50 mm	Rated Input Voltage	24 V/DC
(h1) Height	3 mm	CRI (Ra)	80
(b1) Width	10 mm	Control	Dimmable via optional controller
(l2) Primary Cable Length	1 m	Working Temperature	-15 to 50 °C
(l3) Secondary Cable Length	1 m	Channels	4
Colour Temperature	3000 K		

Article	(h3) Height Hose	(b3) Width Hose	Length	Price
840236			5000 mm	€ 115.95
930517	2 mm	10 mm	50000 mm	€ 1039.95



Power supply units
You can find the right power supply unit in various designs and with the required voltage and power in the »Power supply units« section.

SMD 24V-16W STANDARD IP44



·high-performance adhesive tape 3M 200MP




(p) LED Distance	16.66 mm	Colour Temperature	4000 K
(c) Segment Length	166.66 mm	Luminous Efficiency 1m	47.81 lm/W
(a) Light Beam Angle	120 Degree	Luminous Flux 1m	765 lm
(r1) Bending Radius min.	50 mm	Length	5000 mm
(h1) Height	2.6 mm	Rated Input 1m	16 W
(h2) Height End Cap	3 mm	Rated Input Voltage	24 V/DC
(h3) Height Hose	2.6 mm	CRI (Ra)	80
(b1) Width	10 mm	Control	Dimmable via optional controller
(b2) Width end cap	10.5 mm	Type of IP Protection	Silicone
(b3) Width Hose	10 mm	Working Temperature	-10 to 60 °C
(l1) Length End Cap	15 mm	Channels	4
(l2) Primary Cable Length	1 m		
(l3) Secondary Cable Length	1 m		

Article	Price
840373  	€ 127.95



Aluminium profiles
 In the »Aluminum profiles« section you will find the right profile for every application with various covers and installation options.


SMD 24V-17W STANDARD IP20



(p) LED Distance	7.11 mm	Luminous Flux 1m	1765 lm
(c) Segment Length	50 mm	Length	5000 mm
(a) Light Beam Angle	120 Degree	Rated Input 1m	17.2 W
(r1) Bending Radius min.	50 mm	Rated Input Voltage	24 V/DC
(h1) Height	2 mm	CRI (Ra)	90
(b1) Width	10 mm	Control	Dimmable via optional controller
(I2) Primary Cable Length	1 m	Working Temperature	-10 to 40 °C
(I3) Secondary Cable Length	1 m	Channels	2
Colour Temperature	2700-6500 K		
Luminous Efficiency 1m	103 lm/W		


Article Colour Temperature

Price

840378 2700-6500 K**€ 159.95****Power supply units**

You can find the right power supply unit in various designs and with the required voltage and power in the »Power supply units« section.

SMD 24V-20W POWER IP20



·high-performance adhesive 3M 9448A


(a) Light Beam Angle	120 Degree	Rated Input Voltage	24 V/DC
(r1) Bending Radius min.	20 mm	CRI (Ra)	90
(h1) Height	2 mm	Control	Dimmable via optional controller
(b1) Width	10 mm	Working Temperature	-15 to 50 °C
(l2) Primary Cable Length	1 m	Channels	1
(l3) Secondary Cable Length	1 m		
Length	5000 mm		

Article	Colour Temperature	(p) LED Distance	(c) Segment Length	Luminous Efficiency 1m	Luminous Flux 1m	EEL	Price
840192	WW 2700 K	4.16 mm	25 mm	65.68 lm/W	1215 lm		€ 131.95
840193	WW 3000 K	4.16 mm	25 mm	84.47 lm/W	1605 lm		€ 131.95
840194	NW 4000 K	4.16 mm	25 mm	88.5 lm/W	1770 lm		€ 131.95
840124	CW 6000 K	8.33 mm	50 mm	86 lm/W	1720 lm		€ 155.95



Aluminium profiles
In the »Aluminum profiles« section you will find the right profile for every application with various covers and installation options.

SMD 24V-23W POWER IP20



• high-performance adhesive 3M 9448A

(p) LED Distance	6.25 mm	Length	5000 mm
(c) Segment Length	50 mm	Rated Input 1m	23 W
(a) Light Beam Angle	110 Degree	Rated Input Voltage	24 V/DC
(r1) Bending Radius min.	20 mm	CRI (Ra)	90
(h1) Height	2 mm	Control	Dimmable via optional controller
(b1) Width	10 mm	Working Temperature	-15 to 50 °C
(l2) Primary Cable Length	1 m	Channels	1
(l3) Secondary Cable Length	1 m		



Article	Colour Temperature	Luminous Efficiency 1m	Luminous Flux 1m	Price
840331	3000 K	130.9 lm/W	3010 lm	€ 199.95
840332	4000 K	136.1 lm/W	3130 lm	€ 199.95



Power supply units

You can find the right power supply unit in various designs and with the required voltage and power in the »Power supply units« section.

SMD 24V-23W POWER IP44



•high-performance adhesive 3M 9448A


(p) LED Distance	6.25 mm	Rated Input 1m	23 W
(c) Segment Length	50 mm	Rated Input Voltage	24 V/DC
(a) Light Beam Angle	110 Degree	CRI (Ra)	90
(r1) Bending Radius min.	20 mm	Control	Dimmable via optional controller
(h1) Height	3 mm	Type of IP Protection	Silicone
(b1) Width	10 mm	Working Temperature	-15 to 50 °C
(l2) Primary Cable Length	1 m	Channels	1
(l3) Secondary Cable Length	1 m		
Length	5000 mm		

Article	Colour Temperature	Luminous Efficiency 1m	Luminous Flux 1m	Price
840333	WW 3000 K	115.2 lm/W	2650 lm	€ 207.95
840334	NW 4000 K	120.9 lm/W	2780 lm	€ 207.95



Aluminium profiles
In the »Aluminum profiles« section you will find the right profile for every application with various covers and installation options.


SMD 24 V-22 W RGBW POWER IP20



•high-performance adhesive 3M 9448A

(p) LED Distance	10.4 mm	Length	5000 mm
(c) Segment Length	62.5 mm	Rated Input 1m	22 W
(a) Light Beam Angle	110 Degree	Rated Input Voltage	24 V/DC
(r1) Bending Radius min.	20 mm	CRI (Ra)	60
(h1) Height	2 mm	Control	Dimmable via optional controller
(b1) Width	12 mm	Working Temperature	-15 to 50 °C
(l2) Primary Cable Length	1 m	Channels	4
(l3) Secondary Cable Length	1 m		


Article	Colour Temperature	Luminous Efficiency 1m	Luminous Flux 1m	Price
840308	 3000 K	43.41 lm/W	955 lm	€ 143.95
840309	 4000 K	44.77 lm/W	985 lm	€ 143.95

**Power supply units**



You can find the right power supply unit in various designs and with the required voltage and power in the »Power supply units« section.

SIDE VIEW

The LED strip is arranged / installed vertically, allowing the Flex-Stripe to be bent to the left and right.
[Note the minimum bending radius in each case.]



NEON 24 V-10 W RGBW D FLEX LINE TOP-VIEW IP68




- Spot-free homogeneous illumination
- Very easy installation using adapted profile
- UV and salt water-resistant IP68
- Ultra-flexible and therefore very versatile
- Light-fast polyurethane encapsulation

(p) LED Distance	11.9 mm	Colour Temperature	3000 K
(c) Segment Length	71.43 mm	Luminous Efficiency 1m	30.48 lm/W
(a) Light Beam Angle	117 Degree	Luminous Flux 1m	320 lm
(r1) Bending Radius min.	150 mm	Length	5000 mm
(h1) Height	15 mm	Rated Input 1m	10.5 W
(h2) Height End Cap	18 mm	Rated Input Voltage	24 V/DC
(h3) Height Hose	15 mm	CRI (Ra)	80
(b1) Width	16 mm	Control	Dimmable via optional controller
(b2) Width end cap	18 mm	Type of IP Protection	PVC cover
(b3) Width Hose	16 mm	Working Temperature	-25 to 45 °C
(l1) Length End Cap	11.5 mm	Channels	4
(l2) Primary Cable Length	3 m		
(l3) Secondary Cable Length	3 m		

Article Price

840289  **€ 623.95**



Accessories


- 930448** Profile for D Flex Line TOP
930449 Profile for D Flex Line TOP
930533 Assembly kit for D Flex Line 16.0 x 15.0 mm
930593 Gel adhesive for bonding the end caps 3 g





€ 11.95
€ 9.95
€ 8.95
€ 4.95

NEON 24V-8W OMNIFLEX MINI IP67

The OMNIFLEX 24 V 8W IP67 LED strip is available in three different light colors [2,700 K, 3,000 K, 4,000 K]. With a length of 5 meters, it enables flexible use in different areas. Uniform illumination is guaranteed thanks to the point-free light distribution. The very small bending radii in all directions allow a great deal of design freedom when creating shapes. Straight lines are also no problem. All variants are possible thanks to the extensive range of accessories. With a primary and secondary feed of 300 cm each, flexible installation is guaranteed. Thanks to its salt water and UV resistance and IP67 protection rating, the OMNIFLEX LED strip is also ideal for outdoor use.



NEON 24V-8W OMNIFLEX MINI IP67



- Spot-free light pattern for homogeneous illumination
- Neon effect
- Small bending radius in all directions provides a great deal of freedom
- Minimum bending radius to the front: 60 mm/to the side: 100 mm
- 300 cm long primary and secondary infeed
- UV- and salt water-resistant
- A comprehensive range of accessories enables you to customise your design
- Including mounting material

(p) LED Distance	6.25 mm	(l2) Primary Cable Length	3 m
(c) Segment Length	100 mm	(l3) Secondary Cable Length	3 m
(a) Light Beam Angle	120 Degree	Length	5000 mm
(r1) Bending Radius min.	100 mm	Rated Input 1m	8 W
(r2) Bending Radius Left / Right	60 mm	Rated Input Voltage	24 V/DC
(h1) Height	10 mm	CRI (Ra)	80
(h2) Height End Cap	10 mm	Control	Dimmable via optional controller
(h3) Height Hose	10 mm	Type of IP Protection	Silicone hose
(b1) Width	10 mm	Working Temperature	-10 to 55 °C
(b2) Width end cap	10 mm	Channels	1
(b3) Width Hose	10 mm		
(l1) Length End Cap	10 mm		

Article	Colour Temperature	Luminous Efficiency 1m	Luminous Flux 1m	EEI	Price
840417	2700 K	90 lm/W	720 lm		€ 239.95
840418	3000 K	93 lm/W	744 lm		€ 239.95
840419	4000 K	100 lm/W	800 lm		€ 239.95



Accessories

- 930846** Assembly clamps set of 10 pieces for neon Omniflex Mini
- 930847** Aluminium profile 1 m for neon Omniflex Mini
- 930849** Flexible stainless steel profile 5 m for neon Omniflex Mini



€ 3.95

€ 7.95

€ 55.95

48V LED STRIPES

Our new LED stripes in 48V technology offer users numerous advantages. The key advantage: Compared to 12V and 24V stripes, 48V stripes allow longer running lengths. By comparison, conventional LED stripes with lower output voltage require a new feed after only 2.5 metres [single-sided feed] or 5 metres [feed from both sides], for continuous operation. LED stripes with 48V can be used up to a length of 25 metres [single-sided feed] or feed] or 50 metres [feed on both sides] - perfect for lighting coves, long corridors and simplified integration into existing installations, that only allow a single-sided feed.

Advantages of 48V LED stripes

- 48V = lower current
- 48V = longer running length
- 48V = thinner wire cross-sections
- 48V = faster installation
- 48V = more versatile applications
- 48V = lower brightness drop

In addition to the advantages mentioned above, our new 48V LED stripes have a very long service life of up to 75,000h for L70B50

and 50,000h for L80B10. Thanks to reel-to-reel production, the 48V LED stripes have no soldered joints. As we have set ourselves the goal to become climate-neutral, the LED stripes are packaged in an environmentally friendly paper-based packaging.

In addition to the new 48V LED stripes, we of course also offer accessories in the form of power supply units and controllers for the relevant control protocols [RF, DALI, KNX etc.] in order to cover all potential future applications for 48V stripes.







Foto: Daniel Vieser, Architekturfotografie, Karlsruhe

SMD 48V-10W LONG RUN CCT IP20




- ideal solution for long distances (up to 50m)
- fewer power supply points required
- smaller cable cross-section required compared to 12/24V
- up to 25m with single-ended power supply
- up to 50 metres with power supply at both ends
- reel-to-reel production process (long LED strips without any breaks)

(p) LED Distance	4.46 mm	Luminous Efficiency 1m	120 lm/W
(c) Segment Length	125 mm	Luminous Flux 1m	1200 lm
(a) Light Beam Angle	120 Degree	Rated Input 1m	10 W
(r1) Bending Radius min.	50 mm	Rated Input Voltage	48 V/DC
(h1) Height	2.5 mm	CRI (Ra)	90
(b1) Width	10 mm	Control	Dimmable via optional controller
(I2) Primary Cable Length	1 m	Working Temperature	-10 to 55 °C
(I3) Secondary Cable Length	1 m	Channels	2
Colour Temperature	2700-6500 K		

Article		Length	Price
840438	WW CW	5000 mm	€ 155.95
840434	WW CW	15000 mm	€ 467.95
840436	WW CW	50000 mm	€ 1559.95




SMD 48V-10W LONG RUN CCT IP67




- ideal solution for long distances (up to 50m)
- fewer power supply points required
- smaller cable cross-section required compared to 12/24V
- up to 25m with single-ended power supply
- up to 50 metres with power supply at both ends
- reel-to-reel production process (long LED strips without any breaks)

(p) LED Distance	4.46 mm	(l3) Secondary Cable Length	1 m
(c) Segment Length	125 mm	Colour Temperature	2700-6500 K
(a) Light Beam Angle	120 Degree	Luminous Efficiency 1m	110 lm/W
(r1) Bending Radius min.	50 mm	Luminous Flux 1m	1100 lm
(h1) Height	2.5 mm	Rated Input 1m	10 W
(h2) Height End Cap	6.5 mm	Rated Input Voltage	48 V/DC
(h3) Height Hose	5 mm	CRI (Ra)	90
(b1) Width	10 mm	Control	Dimmable via optional controller
(b2) Width end cap	14.2 mm	Type of IP Protection	Silicone hose
(b3) Width Hose	12 mm	Working Temperature	-10 to 55 °C
(l1) Length End Cap	10 mm	Channels	2
(l2) Primary Cable Length	1 m		

Article		Length	Price
840439	WW CW	5000 mm	€ 171.95
840435	WW CW	15000 mm	€ 515.95
840437	WW CW	50000 mm	€ 1719.95




SMD 48V-10W LONG RUN RGB+CCT IP20




- ideal solution for long distances (up to 50m)
- fewer power supply points required
- smaller cable cross-section required compared to 12/24V
- up to 25m with single-ended power supply
- up to 50 metres with power supply at both ends
- reel-to-reel production process (long LED strips without any breaks)

(p) LED Distance	5.56 mm	Luminous Efficiency 1m	80 lm/W
(c) Segment Length	167 mm	Luminous Flux 1m	800 lm
(a) Light Beam Angle	120 Degree	Rated Input 1m	10 W
(r1) Bending Radius min.	50 mm	Rated Input Voltage	48 V/DC
(h1) Height	2.5 mm	CRI (Ra)	90
(b1) Width	12 mm	Control	Dimmable via optional controller
(I2) Primary Cable Length	1 m	Working Temperature	-10 to 55 °C
(I3) Secondary Cable Length	1 m	Channels	5
Colour Temperature	2700-6500 K		

Article		Length	Price
840452	RGB WW CW	5000 mm	€ 199.95
840448	RGB WW CW	15000 mm	€ 599.95
840450	RGB WW CW	50000 mm	€ 1999.95




SMD 48V-10W LONG RUN RGB+CCT IP67




- ideal solution for long distances (up to 50m)
- fewer power supply points required
- smaller cable cross-section required compared to 12/24V
- up to 25m with single-ended power supply
- up to 50 metres with power supply at both ends
- reel-to-reel production process (long LED strips without any breaks)

(p) LED Distance	5.56 mm	(l3) Secondary Cable Length	1 m
(c) Segment Length	167 mm	Colour Temperature	2700-6500 K
(a) Light Beam Angle	120 Degree	Luminous Efficiency 1m	75 lm/W
(r1) Bending Radius min.	50 mm	Luminous Flux 1m	750 lm
(h1) Height	2.5 mm	Rated Input 1m	10 W
(h2) Height End Cap	6.5 mm	Rated Input Voltage	48 V/DC
(h3) Height Hose	6 mm	CRI (Ra)	90
(b1) Width	12 mm	Control	Dimmable via optional controller
(b2) Width end cap	16.5 mm	Type of IP Protection	Silicone hose
(b3) Width Hose	14.5 mm	Working Temperature	-10 to 55 °C
(l1) Length End Cap	10 mm	Channels	5
(l2) Primary Cable Length	1 m		

Article		Length	Price
840453		5000 mm	€ 219.95
840449		15000 mm	€ 659.95
840451		50000 mm	€ 2199.95



SMD 48V-10W LONG RUN RGB+W IP20




- ideal solution for long distances (up to 50m)
- fewer power supply points required
- smaller cable cross-section required compared to 12/24V
- up to 25m with single-ended power supply
- up to 50 metres with power supply at both ends
- reel-to-reel production process (long LED strips without any breaks)

(p) LED Distance	8.9 mm	Rated Input 1m	10 W
(c) Segment Length	125 mm	Rated Input Voltage	48 V/DC
(a) Light Beam Angle	120 Degree	CRI (Ra)	90
(r1) Bending Radius min.	50 mm	Control	Dimmable via optional controller
(h1) Height	2.5 mm	Working Temperature	-10 to 55 °C
(b1) Width	12 mm	Channels	4
(l2) Primary Cable Length	1 m		
(l3) Secondary Cable Length	1 m		

Article	Colour Temperature	Luminous Efficiency 1m	Luminous Flux 1m	Length	EEL	Price
840458	RGB WW 3000 K	66 lm/W	660 lm	5000 mm		€ 199.95
840454	RGB WW 3000 K	66 lm/W	660 lm	15000 mm		€ 599.95
840456	RGB WW 3000 K	66 lm/W	660 lm	50000 mm		€ 1999.95
840464	RGB NW 4000 K	70 lm/W	700 lm	5000 mm		€ 199.95
840460	RGB NW 4000 K	70 lm/W	700 lm	15000 mm		€ 599.95
840462	RGB NW 4000 K	70 lm/W	700 lm	50000 mm		€ 1999.95




SMD 48V-10W LONG RUN RGB+W IP67




- ideal solution for long distances (up to 50m)
- fewer power supply points required
- smaller cable cross-section required compared to 12/24V
- up to 25m with single-ended power supply
- up to 50 metres with power supply at both ends
- reel-to-reel production process (long LED strips without any breaks)

(c) Segment Length	125 mm	(l2) Primary Cable Length	1 m
(a) Light Beam Angle	120 Degree	(l3) Secondary Cable Length	1 m
(r1) Bending Radius min.	50 mm	Rated Input 1m	10 W
(h1) Height	2.5 mm	Rated Input Voltage	48 V/DC
(h2) Height End Cap	6.5 mm	CRI (Ra)	90
(h3) Height Hose	6 mm	Control	Dimmable via optional controller
(b1) Width	14.5 mm	Type of IP Protection	Silicone hose
(b2) Width end cap	16.5 mm	Working Temperature	-10 to 55 °C
(b3) Width Hose	14.5 mm	Channels	4
(l1) Length End Cap	10 mm		

Article	Colour Temperature	(p) LED Distance	Luminous Efficiency 1m	Luminous Flux 1m	Length	Price
840459	RGB WW 3000 K	8.9 mm	60 lm/W	600 lm	5000 mm	€ 219.95
840455	RGB WW 3000 K	8.9 mm	60 lm/W	600 lm	15000 mm	€ 659.95
840457	RGB WW 3000 K	8.9 mm	60 lm/W	600 lm	50000 mm	€ 2199.95
840463	RGB NW 4000 K	5.5 mm	65 lm/W	650 lm	50000 mm	€ 2199.95
840465	RGB NW 4000 K	8.9 mm	65 lm/W	650 lm	5000 mm	€ 219.95
840461	RGB NW 4000 K	8.9 mm	65 lm/W	650 lm	15000 mm	€ 659.95



SMD 48V-10W LONG RUN RGB IP20




- ideal solution for long distances (up to 50m)
- fewer power supply points required
- smaller cable cross-section required compared to 12/24V
- up to 25m with single-ended power supply
- up to 50 metres with power supply at both ends
- reel-to-reel production process (long LED strips without any breaks)

(p) LED Distance	7.14 mm	Luminous Flux 1m	550 lm
(c) Segment Length	100 mm	Rated Input 1m	10 W
(a) Light Beam Angle	120 Degree	Rated Input Voltage	48 V/DC
(r1) Bending Radius min.	50 mm	CRI (Ra)	65
(h1) Height	2.5 mm	Control	Dimmable via optional controller
(b1) Width	10 mm	Working Temperature	-10 to 55 °C
(l2) Primary Cable Length	1 m	Channels	3
(l3) Secondary Cable Length	1 m		
Luminous Efficiency 1m	55 lm/W		

Article		Length	Price
840446		5000 mm	€ 107.95
840399		15000 mm	€ 319.95
840407		50000 mm	€ 1063.95




SMD 48V-10W LONG RUN RGB IP67




- ideal solution for long distances (up to 50m)
- fewer power supply points required
- smaller cable cross-section required compared to 12/24V
- up to 25m with single-ended power supply
- up to 50 metres with power supply at both ends
- reel-to-reel production process (long LED strips without any breaks)

(p) LED Distance	7.14 mm	(l3) Secondary Cable Length	1 m
(a) Light Beam Angle	120 Degree	Luminous Efficiency 1m	51 lm/W
(r1) Bending Radius min.	50 mm	Luminous Flux 1m	510 lm
(h1) Height	2.5 mm	Rated Input 1m	10 W
(h2) Height End Cap	6.5 mm	Rated Input Voltage	48 V/DC
(h3) Height Hose	4.5 mm	CRI (Ra)	65
(b1) Width	10 mm	Control	Dimmable via optional controller
(b2) Width end cap	14.2 mm	Working Temperature	-10 to 55 °C
(b3) Width Hose	12 mm	Channels	3
(l1) Length End Cap	10 mm		
(l2) Primary Cable Length	1 m		

Article	(c) Segment Length	Length	Type of IP Protection	Price
840400	100 mm	15000 mm	Silicone hose	€ 367.95
840408	100 mm	50000 mm	Silicone hose	€ 1223.95
840447	125 mm	5000 mm		€ 119.95



SMD 48V-10W LONG RUN SINGLE IP20




- ideal solution for long distances (up to 50m)
- fewer power supply points required
- smaller cable cross-section required compared to 12/24V
- up to 25m with single-ended power supply
- up to 50 metres with power supply at both ends
- reel-to-reel production process (long LED strips without any breaks)

(p) LED Distance	7.14 mm	Rated Input 1m	10 W
(c) Segment Length	100 mm	Rated Input Voltage	48 V/DC
(a) Light Beam Angle	120 Degree	CRI (Ra)	90
(r1) Bending Radius min.	50 mm	Control	Dimmable via optional controller
(h1) Height	2.5 mm	Working Temperature	-10 to 55 °C
(I2) Primary Cable Length	1 m	Channels	1
(I3) Secondary Cable Length	1 m		

Article	Colour Temperature	(b1) Width	Luminous Efficiency 1m	Luminous Flux 1m	Length	EEL	Price
840440	WW 2700 K	10 mm	121 lm/W	1210 lm	5000 mm		€ 87.95
840393	WW 2700 K	10 mm	121 lm/W	1210 lm	15000 mm		€ 271.95
840401	WW 2700 K	10 mm	121 lm/W	1210 lm	50000 mm		€ 903.95
840394	WW 3000 K	10 mm	124 lm/W	1240 lm	15000 mm		€ 271.95
840402	WW 3000 K	10 mm	124 lm/W	1240 lm	50000 mm		€ 903.95
840442	WW 3000 K	12 mm	124 lm/W	1240 lm	5000 mm		€ 87.95
840395	NW 4000 K	10 mm	130 lm/W	1300 lm	15000 mm		€ 271.95
840403	NW 4000 K	10 mm	130 lm/W	1300 lm	50000 mm		€ 903.95
840444	NW 4000 K	12 mm	130 lm/W	1300 lm	5000 mm		€ 87.95




SMD 48V-10W LONG RUN SINGLE IP67




- Ideal for covered lighting and long run lengths
- Up to 50 m in single section with single-/double-sided infeed
- 3M 300 LSE [IP20] strong adhesive tape/3M VHB 5604A with primer pre-treatment [IP67]

(p) LED Distance	7.14 mm	(l3) Secondary Cable Length	1 m
(c) Segment Length	100 mm	Rated Input 1m	10 W
(a) Light Beam Angle	120 Degree	Rated Input Voltage	48 V/DC
(r1) Bending Radius min.	50 mm	CRI (Ra)	90
(h1) Height	2.5 mm	Control	Dimmable via optional controller
(h2) Height End Cap	6.5 mm	Type of IP Protection	Silicone hose
(h3) Height Hose	4.5 mm	Working Temperature	-10 to 55 °C
(b1) Width	10 mm	Channels	1
(l1) Length End Cap	10 mm		
(l2) Primary Cable Length	1 m		

Article	Colour Temperature	(b2) Width end cap	(b3) Width Hose	Luminous Efficiency 1m	Luminous Flux 1m	Price
840396	2700 K	14.2 mm	12 mm	109 lm/W	1090 lm	€ 319.95
840404	2700 K	14.2 mm	12 mm	109 lm/W	1090 lm	€ 1059.95
840441	2700 K	14.5 mm	14.5 mm	109 lm/W	1090 lm	€ 103.95
840397	3000 K	14.2 mm	12 mm	112 lm/W	1120 lm	€ 319.95
840405	3000 K	14.2 mm	12 mm	112 lm/W	1120 lm	€ 1059.95
840443	3000 K	14.5 mm	14.5 mm	112 lm/W	1120 lm	€ 103.95
840398	4000 K	14.2 mm	12 mm	118 lm/W	1180 lm	€ 319.95
840406	4000 K	14.2 mm	12 mm	118 lm/W	1180 lm	€ 1059.95
840445	4000 K	14.5 mm	14.5 mm	118 lm/W	1180 lm	€ 103.95



SMD 48V-4W LONG RUN SINGLE IP20



·high-performance adhesive tape 3M 200MP

(p) LED Distance	12.82 mm	(l2) Primary Cable Length	1 m
(c) Segment Length	166.66 mm	(l3) Secondary Cable Length	1 m
(a) Light Beam Angle	120 Degree	Rated Input 1m	4 W
(r1) Bending Radius min.	50 mm	Rated Input Voltage	48 V/DC
(h1) Height	1.3 mm	CRI (Ra)	80
(h2) Height End Cap	2.8 mm	Control	Dimmable via optional controller
(b1) Width	10 mm	Working Temperature	-15 to 50 °C
(b2) Width end cap	10.5 mm	Channels	1
(l1) Length End Cap	15 mm		

Article	Colour Temperature	Luminous Efficiency 1m	Luminous Flux 1m	Length	Price
840318	3000 K	121 lm/W	485 lm	15000 mm	€ 231.95
840337	3000 K	121 lm/W	485 lm	50000 mm	€ 799.95
840320	4000 K	133 lm/W	530 lm	15000 mm	€ 231.95
840339	4000 K	133 lm/W	530 lm	50000 mm	€ 799.95

CV

1 CH

IP20

A
↑
G

E




Aluminium profiles

In the »Aluminum profiles« section you will find the right profile for every application with various covers and installation options.

SMD 48V-4W LONG RUN SINGLE IP44

IP44



· high-performance adhesive tape 3M 200MP

(a) Light Beam Angle	120 Degree	CRI (Ra)	80
(r1) Bending Radius min.	50 mm	Control	Dimmable via optional controller
(l2) Primary Cable Length	1 m	Type of IP Protection	Silicone
(l3) Secondary Cable Length	1 m	Channels	1
Rated Input 1m	4 W		
Rated Input Voltage	48 V/DC		

Article	Colour Temperature	(p) LED Distance	(c) Segment Length	(h1) Height	(h2) Height End Cap	(h3) Height Hose	Price
840317	WW 3000 K	8.33 mm	50 mm	12 mm	12 mm	12 mm	€ 279.95
840338	WW 3000 K	12.82 mm	166.66 mm	2.6 mm	2.8 mm	2.6 mm	€ 899.95
840319	NW 4000 K	12.82 mm	166.66 mm	2.6 mm	2.8 mm	2.6 mm	€ 279.95
840340	NW 4000 K	12.82 mm	166.66 mm	2.6 mm	2.8 mm	2.6 mm	€ 899.95

**Power supply units**

You can find the right power supply unit in various designs and with the required voltage and power in the »Power supply units« section.

230V LED STRIPES


This LED stripe is ideally suited if the requirements and focus are on flexible, water-protected and long-lasting lighting routes in indoor and outdoor areas.

Due to the voltage of 230V, no additional power supply unit is required. The delivery is ready for connection with mounted Schuko plug and moulded endcap.

Applications of large distances, such as on buildings or hotel corridors can be operated in one piece up to 50m.



SMD 230V-14W LONG RUN IP65



- 230 V direct connection
- Ready to connect using IP44 shaped plug and end cap
- Total length to be operated up to 50 m
- Including mounting material

(p) LED Distance	11.9 mm	(l1) Length End Cap	27 mm
(c) Segment Length	166.7 mm	(l2) Primary Cable Length	3 m
(a) Light Beam Angle	120 Degree	Rated Input 1m	14 W
(r1) Bending Radius min.	150 mm	Rated Input Voltage	220-240 V/AC
(h1) Height	13.2 mm	CRI (Ra)	80
(h2) Height End Cap	18 mm	Type of IP Protection	PVC cover
(h3) Height Hose	13.2 mm	IP Protection Type Plug	IP 44
(b1) Width	17 mm	Working Temperature	-10 to 60 °C
(b2) Width end cap	21.8 mm	Channels	1
(b3) Width Hose	17 mm		

Article	Colour Temperature	Luminous Efficiency 1m	Luminous Flux 1m	Length	EEL	Price
840390	2700 K	103 lm/W	1442 lm	15000 mm		€ 615.95
840391	2700 K	103 lm/W	1442 lm	50000 mm		€ 1999.95
840386	3000 K	105 lm/W	1470 lm	15000 mm		€ 615.95
840387	3000 K	105 lm/W	1470 lm	50000 mm		€ 1999.95
840388	4000 K	114 lm/W	1596 lm	15000 mm		€ 615.95
840389	4000 K	114 lm/W	1596 lm	50000 mm		€ 1999.95



Accessories

930689	End cap set of 2 pieces for 230 V LED stripe
930690	Supply cable with shaped plug for 230 V LED stripe
930691	Flex connector for 230 V LED stripe
930692	Mounting clamp set of 10 pieces for 230 V LED stripe
930693	Plastic profile 1 m for 230 V LED stripe
930809	Plastic profile 2 m for 230 V LED stripe

	€ 3.95
	€ 27.95
	€ 19.95
	€ 7.95
	€ 11.95
	€ 19.95



ASSEMBLY KIT FOR IP65/IP67 LED STRIPS


- Set comprises:
 - 15 silicone retaining clips
 - 30 stainless steel screws
 - Five end caps
 - Supplied without silicone/adhesive



Housing	Silicone	
Article	for Stripes with outer dimensions	Price
840293	11-12 mm	€ 3.95
840294	13-15 mm	€ 3.95
840295	17-19 mm	€ 3.95
840392	8-10 mm	€ 3.95

3M™ DOUBLE-SIDED ADHESIVE TAPE

- For installing aluminium profiles/LED strips on smooth surfaces
- Not suitable for IP65/67 silicone strips



Length	50 m	Height	0.2 mm
Article	Width	Price	
930345	8 mm	€ 21.95	
930346	10 mm	€ 23.95	
930347	12 mm	€ 25.95	
930348	15 mm	€ 30.95	
930349	20 mm	€ 38.95	
930350	25 mm	€ 45.95	

3M™ DOUBLE-SIDED ADHESIVE TAPE FOR SILICONE SURFACES

- Special adhesive tape for LED strips with silicone tube/full potting
- High solvent resistance
- Excellent temperature resistance
- Strong initial bond
- High adhesive strength on most silicone surfaces and on substrates that are difficult to bond



Length	55 m	Height	0.127 mm
Width	12 mm		
Article	Width	Price	
930406	12 mm	€ 199.95	





POWER SUPPLIES

- 790 Overview power supplies
 - 792 DC - CV
 - 808 DC - CC
 - 818 AC - CV
- 



page 798



page 798



page 799



page 799



page 800



page 800



page 801



page 801



page 802



page 802



page 803



page 804

power supplies



☐ page 805



☐ page 805



☒ page 807



☐ page 807



☐ page 811



☒ page 811



☒ page 812



☒ page 812



☒ page 813



☒ page 813



☒ page 814



☒ page 814



☐ page 815



☒ page 817



☐ page 819



☒ page 819

PLANNING ELECTRICAL INSTALLATIONS EVEN BETTER

You will certainly notice the new technical data when browsing through our power supplies and ask yourself what it is all about? In future, we would like to support you even better in the planning and dimensioning of your installations. The background to this is that more and more power supplies for lighting are already being installed in standard buildings [directly in the luminaires or as an external power supply].

Due to the inrush currents inherent in the design, e.g. after a power failure and the subsequent simultaneous start of all power supplies, an overload of the circuit breakers may occur. In order to be able to take this into account during the planning stage, we provide you with the necessary data for all our power supplies.

WIRE CROSS SECTION

When installing voltage-stable [CV] or current-stable [CC] power supply units and associated components, always ensure that the cable cross-sections are sufficiently dimensioned, especially with regard to the dependence of the cablelength.

The specified cable cross-sections [mm²] were adapted to the commercially available cross-sections. The maximum cable length of 10 m should not be exceeded. »Red values« must be avoided urgently.

12 V	2 m	5 m	10 m	12 m
25 W	0,25	0,75	1,50	[2,50]
50 W	0,75	1,50	4,00	[4,00]
75 W	1,00	2,50	4,00	[6,00]
100 W	1,50	4,00	6,00	[10,00]
125 W	1,50	4,00	10,00	[10,00]
150 W	2,50	6,00	10,00	-
200 W	2,50	6,00	-	-
300 W	4,00	10,00	-	-
400 W	6,00	-	-	-

24 V	2 m	5 m	10 m	12 m
25 W	0,25	0,25	0,50	[0,50]
50 W	0,25	0,50	0,75	[1,00]
75 W	0,25	0,75	1,00	[1,50]
100 W	0,50	0,75	1,50	[2,50]
125 W	0,50	1,00	2,50	[2,50]
150 W	0,50	1,50	2,50	[4,00]
200 W	0,75	1,50	4,00	[4,00]
300 W	1,00	2,50	6,00	-
400 W	1,50	4,00	6,00	-

48 V	2 m	5 m	10 m	12 m
25 W	0,25	0,25	0,25	[0,25]
50 W	0,25	0,25	0,25	[0,25]
75 W	0,25	0,25	0,50	[0,50]
100 W	0,25	0,25	0,50	[0,50]
125 W	0,25	0,25	0,50	[0,75]
150 W	0,25	0,50	0,75	[0,75]
200 W	0,25	0,50	1,00	[1,00]
300 W	0,25	0,75	1,50	[1,50]
400 W	0,50	1,00	2,50	[2,50]

HOW MANY POWER SUPPLY UNITS PER CIRCUIT BREAKER?

The maximum number of power supply units that may be connected to the respective circuit breaker is directly dependent on the inrush current. In our quick finders you will find the number for the most common types of circuit breaker [B10A, B16A, C10A, C16A].

CAPACITIVE LOAD OF POWER SUPPLIES

Due to their design, power supplies sometimes represent very different capacitive loads. Especially in combination with motion detectors, twilight switches or switching/dimming actuators, this value [as with the capacitor in nF/pF], which is available for many power supplies and specified in our quick finders, plays an important role with regard to the suitability and durability of all components. Please also refer to the manufacturer's data sheets.

electr. data		dimmable via						usage / design		electrical limit values		power supply		
voltage	power	leading cut-off		1 - 10V	touch dimmer [push]	DALI	KNX	indoor	outdoor	design	capacitive load	max. quantity per automatic circuit breaker	item number	page
12V	20 W							x		flat	938uF	B10A=17, B16A=27, C10A=36, C16A=58	862232	869
12V	2,5- 25 W	x						x		basic	31.16nF	B10=35, B16=56, C10=35, C16=56	862240	873
12V	40 W							x		basic	251.7nF	B10A=11, B16A=18, C10A=24, C16A=39	862162	870

DO YOU KNOW OUR LONG-FLAT POWER SUPPLIES?

The popular Long-Flat power supply series for installation in ceiling coves, shadow gaps or all other installation situations with limited space is now available in on/off and trailing edge dimmable versions in 12V, 24V and 48V in a wide range of versions from 45-240W.

All Long-Flat power supplies can be found on page 799.



electr. data		dimmable via						usage / design			electrical limit values		power supply	
voltage	power	leading cut-off	1 - 10V	touch dimmer (push)	DALI	KNX	Casambi	indoor	outdoor	design	capacitive load	max. quantity per automatic circuit breaker	item number	page
12V	4 W							x	x	mini		B10A=17, B16A=28, C10A=37, C16A=59	872127	798
12V	6 W							x		flat	38.83nF	B10A=17, B16A=28, C10A=37, C16A=59	872629	799
12V	12 W							x	x	octo	101uF	B10A=17, B16A=27, C10A=36, C16A=58	862229	798
12V	12 W							x		flat		B10A=17, B16A=27, C10A=36, C16A=58	862231	799
12V	20 W							x		flat	938uF	B10A=17, B16A=27, C10A=36, C16A=58	862232	799
12V	9,6-25W	x						x		basic	31.16nF	B10=35, B16=56, C10=35, C16=56	862240	803
12V	40 W							x		basic	251.7nF	B10A=11, B16A=18, C10A=24, C16A=39	862162	800
12V	40 W							x	x	IP	621.5nF	B10A=5, B16A=9, C10A=12, C16A=19	872082	800
12V	40 W		x	x	x			x		basic		B10A=18, B16A=28, C10A=36, C16A=56	862253	805
12V	45 W							x		long-flat	462.1nF	B10A=5, B16A=9, C10A=12, C16A=19	862123	799
12V	50 W							x		flat	485.5nF	B10A=11, B16A=18, C10A=24, C16A=39	862121	799
12V	12-50 W	x						x		basic	1924uF	B10A=17, B16A=28, C10A=17, C16A=28	862220	803
12V	60 W							x		long-flat	462.1nF	B10A=5, B16A=9, C10A=12, C16A=19	862093	799
12V	60 W					x		x	x	IP		B10A=6, B16A=9, C10A=10, C16A=16	872109	807
12V	75 W							x		basic	870nF	B10A=11, B16A=18, C10A=24, C16A=39	862127	800
12V	75 W							x	x	IP	621.5nF	B10A=5, B16A=8, C10A=10, C16A=16	872084	800
12V	75 W		x	x	x			x		basic		B10A=10, B16A=16, C10A=20, C16A=32	862254	805
12V	100 W							x		basic	842.2nF	B10A=3, B16A=5, C10A=7, C16A=11	862165	800
12V	100 W							x	x	IP	621.5nF	B10A=3, B16A=5, C10A=7, C16A=11	872093	800
12V	100 W							x		long-flat	462.1nF	B10A=3, B16A=5, C10A=7, C16A=11	862125	799
12V	33-100 W	x						x	x	IP	93,14nF	B10=7, B16=15, C10=7, C16=15	872135	804
12V	34-100 W	x						x		basic	146,34nF	B10=7, B16=15, C10=7, C16=15	862241	803
12V	120 W					x		x		IP		B10A=2, B16A=4, C10A=4, C16A=6	872110	807
12V	150 W							x		long-flat	462.1nF	B10A=3, B16A=5, C10A=6, C16A=10	862172	799
12V	150 W							x		basic	591.2nF	B10A=2, B16A=4, C10A=6, C16A=9	862167	799
12V	150 W							x	x	IP	621.5nF	B10A=2, B16A=4, C10A=6, C16A=9	872086	800

electr. data		dimmable via						usage / design			electrical limit values		power supply	
voltage	power	leading cut-off	1 - 10V	touch dimmer (push)	DALI	KNX	Casambi	indoor	outdoor	design	capacitive load	max. quantity per automatic circuit breaker	item number	page
12V	66-200 W	x						x	x	IP	148,64nF	B10=3, B16=7, C10=3, C16=7	872137	804
12V	200 W							x	x	IP	621.5nF	B10A=2, B16A=3, C10A=4, C16A=7	872088	800
12V	200 W					x		x		IP		B10A=2, B16A=4, C10A=4, C16A=6	872111	807
24V	4 W							x	x	mini		B10A=59, B16A=94, C10A=123, C16A=197	872128	798
24V	6 W							x		flat	43.5nF	B10A=17, B16A=28, C10A=37, C16A=59	872630	799
24V	12 W							x	x	octo	620uF	B10A=17, B16A=27, C10A=36, C16A=58	862230	798
24V	12 W							x		flat	311uF	B10A=17, B16A=27, C10A=36, C16A=58	862233	799
24V	20 W							x		flat	446uF	B10A=17, B16A=27, C10A=36, C16A=58	862234	799
24V	9,6-25W	x						x		basic	9520uF	B10=35, B16=56, C10=35, C16=56	862221	803
24V	30W	x						x		long-flat		B16A=25, C16A=40	862277	803
24V	12-30W			x	x			x		long-flat		B10A=27, B16A=44, C10A=44, C16A=70	872146	807
24V	40 W							x		basic	762nF	B10A=11, B16A=18, C10A=24, C16A=39	862163	800
24V	40 W							x	x	IP	626.3nF	B10A=5, B16A=9, C10A=12, C16A=19	872083	800
24V	40 W		x	x	x			x		basic		B10A=18, B16A=28, C10A=36, C16A=56	862255	805
24V	45 W							x		long-flat	451.2nF	B10A=5, B16A=9, C10A=12, C16A=19	862124	799
24V	12-50 W	x						x		basic	10520uF	B10A=17, B16A=28, C10A=17, C16A=28	862222	803
24V	50 W							x		flat	604.5nF	B10A=11, B16A=18, C10A=24, C16A=39	862122	799
24V	60 W							x		long-flat	451.2nF	B10A=5, B16A=9, C10A=12, C16A=19	862094	799
24V	60 W					x		x		IP		B10A=6, B16A=9, C10A=10, C16A=16	872112	807
24V	12-60 W	x						x	x	*			872045	802
24V	60W	x						x		long-flat		B16A= 25, B16A=40	862278	803
24V	26-60W			x	x			x		long-flat		B10A=23, B16A=37, C10A=37, C16A=59	872147	807
24V	75 W							x		basic	760nF	B10A=11, B16A=18, C10A=24, C16A=39	862164	800
24V	75 W							x	x	IP	626.3nF	B10A=5, B16A=8, C10A=10, C16A=16	872085	800
24V	75 W		x	x	x			x		basic		B10A=10, B16A=16, C10A=20, C16A=32	862256	805
24V	25-75W	x						x		long-flat		B10A=2, B16A=4 C10A=5, C16A=9	862282	802

electr. data		dimmable via						usage / design			electrical limit values			power supply	
voltage	power														
		leading cut-off	1 - 10V	touch dimmer [push]	DALI	KNX	Casambi	indoor	outdoor	design	capacitive load	max. quantity per automatic circuit breaker	item number	page	
24V	90 W							x	x	IP		B10A=2, B16A=3, C10A=3, C16A=6	872103		
24V	100 W							x		basic	724.2nF	B10A=3, B16A=5, C10A=7, C16A=11	862166	800	
24V	33-100 W	x						x		IP	94, 13nF	B10=7, B16=15, C10=7, C16=15	872136	804	
24V	34-100 W	x						x		basic	140.74nF	B10=7, B16=15, C10=7, C16=15	862242	803	
24V	100 W							x		long-flat	451.2nF	B10A=3, B16A=5, C10A=7, C16A=11	862126	799	
24V	100 W							x	x	IP	626.3nF	B10A=3, B16A=5, C10A=7, C16A=11	872094	800	
24V	120 W					x		x	x	IP		B10A=2, B16A=4, C10A=4, C16A=6	872113	807	
24V	150 W							x		basic	591.2nF	B10A=2, B16A=4, C10A=6, C16A=9	862168	800	
24V	150 W							x		long-flat	451.2nF	B10A=3, B16A=5, C10A=6, C16A=10	862173	799	
24V	150 W							x	x	IP	626.3nF	B10A=2, B16A=4, C10A=6, C16A=9	872087	800	
24V	150 W						1K	x		basic		B10A=5, B16A= 9 C10A= 9, C16A=15	862299	807	
24V	150 W						2K	x		basic		B10A=5, B16A= 9 C10A= 9, C16A=15	862300	807	
24V	150 W						3/4K	x		basic		B10A=5, B16A= 9 C10A= 9, C16A=15	862301	807	
24V	30-150 W	x						x	x	*			872046	802	
24V	50-150 W	x						x		long-flat		B10A=2, B16A=3, C10A=4, C16A=7	862268	802	
24V	150 W		x	x	x			x		basic		B10A=5, B16A=9, C10A=10 C16A=18	862262	805	
24V	45-150W			x	x			x		long-flat		B10A=11, B16A=17 C10A=17, C16A=27	872148	807	
24V	200 W					x		x		IP		B10A=2, B16A=4, C10A=4, C16A=6	872114	807	
24V	66-200 W	x						x	x	IP	148.64nF	B10=3, B16=7, C10=3, C16=7	872138	804	
24V	240 W							x	x	IP	626.3nF	B10A=2, B16A=3, C10A=4, C16A=7	872089	800	
24V	240 W							x		long-flat	5600uF	B10A=1, B16A=2, C10A=3, C16A=5	862265	799	
24V	80-240W	x						x		long-flat		B10A=2, B16A=3 C10A=4, C16A=6	862280	802	
24V	240 W		x	x	x			x		basic		B10A=3, B16A=5, C10A=6, C16A=10	862263	805	
24V	320 W							x	x	IP	626.3nF	B10A=2, B16A=2, C10A=4, C16A=6	872091	800	
48V	40 W							x	x	IP		B10A=6, B16A=9, C10A=10, C16A=16	872105	801	
48V	60 W							x	x	IP		B10A=6, B16A=9, C10A=10, C16A=16	872106	801	

electr. data		dimmable via						usage / design			electrical limit values		power supply	
voltage	power	leading cut-off	1 - 10V	touch dimmer (push)	DALI	KNX	Casambi	indoor	outdoor	design	capacitive load	max. quantity per automatic circuit breaker	item number	page
48V	25-75W	x						x		long-flat		B10A=2, B16A=4 C10A=5, C16A=9	862283	802
48V	75 W		x	x	x			x		basic		B10A=10, B16A=16, C10A=20, C16A=32	862273	805
48V	90 W							x	x	IP		B10A=2, B16A=3, C10A=3, C16A=6	872107	801
48V	33-100 W	x						x		IP	6,6uF	B10=3 B16=5, C10=7, C16=11	872142	804
48V	34-100 W	x						x		basic	140,74nF	B10=7 B16=15, C10=7, C16=15	862274	803
48V	100 W							x		long-flat	451.2nF	B10A=3, B16A=5, C10A=7, C16A=11	862270	799
48V	120 W							x	x	IP		B10A=2, B16A=4, C10A=4, C16A=6	872108	801
48V	150 W		x	x	x			x		basic		B10A=5, B16A=9, C10A=10 C16A=18	862275	805
48V	50-150 W	x						x		long-flat		B10A=2, B16A=3, C10A=4, C16A=7	862269	802
48V	150 W							x		long-flat	451.2nF	B10A=3, B16A=5, C10A=6, C16A=10	862271	799
48V	80-240W	x						x		long-flat		B10A=2, B16A=3 C10A=4, C16A=6	862281	802
48V	320 W							x	x	IP	626.3nF	B10A=2, B16A=3, C10A=4, C16A=6	872145	800
48V	66-200 W	x						x	x	IP	6,6uF	B10=2, B16=3, C10=4 C16=7	872143	804
48V	200 W					x		x		IP		B10A=2, B16A=4, C10A=4, C16A=6	872115	807
48V	240 W		x	x	x			x		basic		B10A=3, B16A=5, C10A=6, C16A=10	862276	805
48V	240 W							x		long-flat	5600uF	B10A=1, B16A=2, C10A=3, C16A=5	862272	799
48V	600 W							x	x	IP		B10A=1, B16A=1, C10A=1, C16A=2	872125	801
48V	600 W		x					x	x	IP		B10A=1, B16A=1, C10A=1, C16A=2	872126	805

power supplies design



mini



round / octo



flat



basic



long-flat



IP

* special design




DEKO-LIGHT POWER SUPPLY UNITS CV | MINI DESIGN

- Flicker-free
- Secured against short circuits and overloads



Housing	Plastic	Width	27 mm
Power	4 W	Height	21 mm
Length	53 mm	Rated Input Voltage	220-240 V/AC

Article		Output Voltage	Output Current	Price
872127	■	12 V/DC	0-330 mA	€ 9.95
872128	■	24 V/DC	0-170 mA	€ 9.95




DEKO-LIGHT POWER SUPPLY UNITS CV IP | OCTO DESIGN

- Flicker-free
- Secured against short circuits and overloads



Housing	Plastic	Width	48 mm
Power	12 W	Height	24 mm
Length	50 mm	Rated Input Voltage	220-240 V/AC

Article		Output Voltage	Output Current	Price
862229	■	12 V/DC	0-1000 mA	€ 17.95
862230	■	24 V/DC	0-500 mA	€ 17.95




DEKO-LIGHT POWER SUPPLY UNITS CV | FLAT DESIGN

- Ideal for concealed mounting in ceiling coves
- Flicker-free
- Secured against short circuits and overloads
- Overheating protection




Housing	Plastic		Rated Input Voltage		220-240 V/AC		
Article	Output Voltage	Power	Output Current	Length	Width	Height	Price
872629	12 V/DC	6.0 W	0-500 mA	98 mm	46 mm	11 mm	€ 13.95
862231	12 V/DC	12.0 W	0-1000 mA	128 mm	50 mm	13 mm	€ 17.95
862232	12 V/DC	20.0 W	0-1670 mA	128 mm	50 mm	13 mm	€ 20.95
862121	12 V/DC	50.0 W	0-4160 mA	185 mm	62 mm	22 mm	€ 41.95
872630	24 V/DC	6.0 W	0-250 mA	98 mm	46 mm	11 mm	€ 13.95
862233	24 V/DC	12.0 W	0-500 mA	128 mm	50 mm	13 mm	€ 17.95
862234	24 V/DC	20.0 W	0-830 mA	128 mm	50 mm	13 mm	€ 20.95
862122	24 V/DC	50.0 W	0-2100 mA	185 mm	62 mm	22 mm	€ 41.95




DEKO-LIGHT POWER SUPPLY UNITS CV | LONG-FLAT DESIGN

- Ideal for concealed mounting in ceiling coves
- Flicker-free
- Secured against short circuits and overloads
- Overheating protection



Housing	Plastic		Rated Input Voltage		220-240 V/AC		
Article	Output Voltage	Power	Output Current	Length	Width	Height	Price
862123	12 V/DC	45.0 W	0-3750 mA	251 mm	30 mm	16 mm	€ 39.95
862093	12 V/DC	60.0 W	0-5000 mA	305 mm	30 mm	17 mm	€ 47.95
862125	12 V/DC	100.0 W	0-8340 mA	312 mm	30 mm	18.2 mm	€ 77.95
862172	12 V/DC	132.0 W	0-11000 mA	335 mm	30 mm	21.6 mm	€ 103.95
862124	24 V/DC	45.0 W	0-1870 mA	251 mm	30 mm	16 mm	€ 39.95
862094	24 V/DC	60.0 W	0-2500 mA	305 mm	30 mm	18.2 mm	€ 47.95
862126	24 V/DC	100.0 W	0-4170 mA	312 mm	30 mm	18.2 mm	€ 77.95
862173	24 V/DC	150.0 W	0-6250 mA	335 mm	30 mm	21.6 mm	€ 103.95
862265	24 V/DC	240.0 W	0-10000 mA	357 mm	32 mm	23 mm	€ 127.95
862270	48 V/DC	100.0 W	0-2080 mA	312 mm	30 mm	18.2 mm	€ 77.95
862271	48 V/DC	150.0 W	0-3125 mA	335 mm	30 mm	21.6 mm	€ 103.95
862272	48 V/DC	240.0 W	0-5000 mA	357 mm	32 mm	22.5 mm	€ 127.95



DEKO-LIGHT POWER SUPPLY UNITS CV | BASIC DESIGN

- Flicker-free
- Secured against short circuits and overloads
- Overheating protection



HousingPlasticRated Input Voltage220-240 V/AC

Article		Output Voltage	Power	Output Current	Length	Width	Height	Price
862162		12 V/DC	40.0 W	0-3300 mA	166 mm	52 mm	24 mm	€ 37.95
862127		12 V/DC	75.0 W	0-6300 mA	184 mm	61 mm	32 mm	€ 59.95
862165		12 V/DC	100.0 W	0-8300 mA	184 mm	61 mm	32 mm	€ 77.95
862167		12 V/DC	150.0 W	0-12500 mA	210 mm	67 mm	34 mm	€ 103.95
862163		24 V/DC	40.0 W	0-1700 mA	166 mm	52 mm	24 mm	€ 37.95
862164		24 V/DC	75.0 W	0-3100 mA	184 mm	61 mm	32 mm	€ 59.95
862166		24 V/DC	100.0 W	0-4200 mA	184 mm	61 mm	32 mm	€ 77.95
862168		24 V/DC	150.0 W	0-6250 mA	210 mm	67 mm	34 mm	€ 103.95




DEKO-LIGHT POWER SUPPLY UNITS CV IP | IP DESIGN

- Robust housing
- Flicker-free
- Secured against short circuits and overloads
- Overheating protection



HousingAluminiumRated Input Voltage100-240 V/AC

Article		Output Voltage	Power	Output Current	Length	Width	Height	Price
872082		12 V/DC	40.0 W	0-3340 mA	176 mm	58 mm	30.5 mm	€ 59.95
872084		12 V/DC	75.0 W	0-6250 mA	186 mm	64 mm	39 mm	€ 75.95
872093		12 V/DC	100.0 W	0-8340 mA	186 mm	64 mm	39 mm	€ 91.95
872086		12 V/DC	150.0 W	0-12500 mA	191 mm	70 mm	40 mm	€ 119.95
872088		12 V/DC	200.0 W	0-16670 mA	249 mm	72 mm	41 mm	€ 143.95
872083		24 V/DC	40.0 W	0-1670 mA	176 mm	58 mm	30.5 mm	€ 59.95
872085		24 V/DC	75.0 W	0-3125 mA	186 mm	64 mm	39 mm	€ 75.95
872094		24 V/DC	100.0 W	0-4170 mA	186 mm	64 mm	39 mm	€ 91.95
872087		24 V/DC	150.0 W	0-6250 mA	191 mm	70 mm	40 mm	€ 119.95
872089		24 V/DC	240.0 W	0-10000 mA	249 mm	72 mm	40 mm	€ 147.95
872091		24 V/DC	320.0 W	0-13340 mA	252 mm	90 mm	44 mm	€ 175.95
872145		48 V/DC	320.0 W	0-6660 mA	252 mm	90 mm	44 mm	€ 175.95






MEANWELL POWER SUPPLY UNITS CV IP | NPF SERIES

- Flicker-free
- Secured against short circuits and overloads
- Overheating protection
- Robust housing



Housing		Plastic	Rated Input Voltage		90-305 V/AC		
Output Voltage		48 V/DC					
Article		Power	Output Current	Length	Width	Height	Price
872105		40.0 W	0-840 mA	150 mm	53 mm	35 mm	€ 67.95
872106		60.0 W	0-1250 mA	150 mm	53 mm	35 mm	€ 75.95
872107		90.0 W	0-1880 mA	171 mm	63 mm	37.5 mm	€ 95.95
872108		120.0 W	0-2500 mA	191 mm	63 mm	37.5 mm	€ 111.95




MEANWELL POWER SUPPLY UNIT CV IP | ELG/HLG SERIES

- Output voltage/current can be adjusted via potentiometer
- Flicker-free
- Secured against short circuits and overloads
- Overheating protection



Housing	Aluminium	Length	280 mm				
Output Voltage	48 V/DC	Width	144 mm				
Power	600 W	Height	48.5 mm				
Output Current	0-12500 mA	Rated Input Voltage	90-305 V/AC				

Article	Price
872125 	€ 391.95





ABN LED SAFETY TRANSFORMER CV DIM IP

- Safety transformer [DC] in accordance with DIN 2006-7 EN 61558-2-6: 2010-04
- Reinforced double insulation [separate primary and secondary winding]
- Additional insulating plastic parts
- More stringent test conditions
- Suitable for applications in areas of increased personal protection in accordance with DIN EN 61558 for operating lights in swimming pools, fountains, wet rooms or similar.
- Primary dimming possible using leading-edge phase dimmers
- Maximum load: 80 % output in continuous operation



Housing	Plastic	Rated Input Voltage	220-240 V/AC
Output Voltage	24 V/DC	Channels	1

Article		Power	Length	Width	Height	Price
872045		12.0-60.0 W	150 mm	90 mm	70 mm	€ 295.95
872046		30.0-150.0 W	176 mm	116 mm	110 mm	€ 495.95



DEKO-LIGHT NETZGERÄTE CV DIM / BAUFORM LONG-FLAT

- dimmable with leading/trailing edge phase dimmers
- ideal for retrofitting existing installations, as primarily dimmable with rotary/ push-button dimmers [C-compatible]
- long, compact design
- not combinable with PWM dimmers such as RF, DMX, DALI, KNX
- flicker-free
- short-circuit and overload-proof
- overheating protection



Housing	Plastic	Channels	1
Width	32 mm		

Article		Output Voltage	Power	Length	Height	Rated Input Voltage	Price
862282		24 V/DC	25.0-75.0 W	400 mm	21.6 mm	198-264 V/AC	€ 79.95
862268		24 V/DC	50.0-150.0 W	400 mm	21.6 mm	220-240 V/AC	€ 103.95
862280		24 V/DC	80.0-240.0 W	443 mm	23 mm	220-240 V/AC	€ 127.95
862283		48 V/DC	25.0-75.0 W	400 mm	21.6 mm	198-264 V/AC	€ 79.95
862269		48 V/DC	50.0-150.0 W	400 mm	21.6 mm	220-240 V/AC	€ 103.95
862281		48 V/DC	80.0-240.0 W	443 mm	23 mm	220-240 V/AC	€ 127.95



KGP/NEXIVO POWER SUPPLY UNITS CV DIM / LONG-FLAT DESIGN

- Can be dimmed using trailing-edge phase dimmers
- Ideal for retrofitting existing installations, since it can be dimmed primarily with rotary/push-button dimmers [C-compatible]
- Long, extremely compact design
- Cannot be combined with PWM dimmers such as RF, DMX, DALI or KNX
- Flicker-free
- Secured against short circuits and overloads
- Overheating protection



Housing	Polycarbonate	Height	18.5 mm
Output Voltage	24 V/DC	Rated Input Voltage	220-240 V/AC
Width	30 mm	Channels	1

Article		Power	Length	Price
862278		0.0-60.0 W	300 mm	€ 143.95
862277		0.0-30.0 W	260 mm	€ 91.95




DEKO-LIGHT POWER SUPPLY UNITS CV DIM | BASIC DESIGN

- Can be dimmed using leading-edge/trailing-edge phase dimmers
- Ideal for retrofitting existing installations, since it can be dimmed primarily with rotary/push-button dimmers (C-compatible)
- Cannot be combined with PWM dimmers such as RF, DMX, DALI or KNX
- Flicker-free
- Secured against short circuits and overloads
- Overheating protection



Housing	Plastic	Channels	1
Rated Input Voltage	220-240 V/AC		

Article		Output Voltage	Power	Length	Width	Height	Price
862240		12 V/DC	9.6-25.0 W	128 mm	52 mm	30 mm	€ 43.95
862220		12 V/DC	12.0-50.0 W	184 mm	61 mm	32 mm	€ 59.95
862241		12 V/DC	34.0-100.0 W	210 mm	67 mm	34 mm	€ 115.95
862221		24 V/DC	9.6-25.0 W	128 mm	52 mm	30 mm	€ 43.95
862222		24 V/DC	12.0-50.0 W	184 mm	61 mm	32 mm	€ 59.95
862242		24 V/DC	34.0-100.0 W	210 mm	67 mm	34 mm	€ 115.95
862274		48 V/DC	34.0-100.0 W	210 mm	67 mm	34 mm	€ 115.95






DEKO-LIGHT POWER SUPPLY UNITS CV DIM IP | IP DESIGN

- Can be dimmed using leading-edge/trailing-edge phase dimmers
- Ideal for retrofitting existing installations, since it can be dimmed primarily with rotary/push-button dimmers [C-compatible]
- Cannot be combined with PWM dimmers such as RF, DMX, DALI or KNX
- Robust housing
- Flicker-free
- Secured against short circuits and overloads
- Overheating protection



Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Height	40 mm	Channels	1

Article		Output Voltage	Power	Length	Width	Price
872135		12 V/DC	33.0-100.0 W	191 mm	70 mm	€ 135.95
872137		12 V/DC	66.0-200.0 W	249 mm	72 mm	€ 165.95
872136		24 V/DC	33.0-100.0 W	191 mm	70 mm	€ 135.95
872138		24 V/DC	66.0-200.0 W	249 mm	72 mm	€ 165.95
872142		48 V/DC	33.0-100.0 W	191 mm	70 mm	€ 135.95
872143		48 V/DC	66.0-200.0 W	249 mm	72 mm	€ 165.95



Lighting design

Interested in our lighting design service?

Your contact person will be happy to answer any questions you may have.




DEKO-LIGHT POWER SUPPLY UNITS CV DIM | LCP DALI

- Can be dimmed using DALI2/DALI1
- Can be dimmed using 0-10 V/1-10 V
- Can be dimmed using touch dimmer via 230 V push-button (iPush)
- New Intelli-Push function [shortcut synchronises all connected power supply units when needed]
- Power supply unit and PWM dimmer in one device
- Secured against short circuits and overloads
- Overheating protection



Housing	Plastic	Channels	1
Rated Input Voltage	220-240 V/AC		

Article		Output Voltage	Power	Length	Width	Height	Price
862253		12 V/DC	40.0 W	185 mm	42.5 mm	28.5 mm	€ 79.95
862254		12 V/DC	75.0 W	295 mm	40 mm	32 mm	€ 103.95
862255		24 V/DC	40.0 W	185 mm	42.5 mm	28.5 mm	€ 79.95
862256		24 V/DC	75.0 W	295 mm	40 mm	32 mm	€ 103.95
862262		24 V/DC	150.0 W	295 mm	40 mm	32 mm	€ 135.95
862263		24 V/DC	240.0 W	360 mm	40 mm	32 mm	€ 175.95
862273		48 V/DC	75.0 W	295 mm	40 mm	32 mm	€ 103.95
862275		48 V/DC	150.0 W	295 mm	40 mm	32 mm	€ 135.95
862276		48 V/DC	240.0 W	360 mm	40 mm	32 mm	€ 175.95



MEANWELL POWER SUPPLY UNIT CV DIM IP | ELG/HLG SERIES

- Can be dimmed using 0-10 V/1-10 V
- Flicker-free, secured against short circuits and overloads
- Overheating protection



Housing	Aluminium	Width	144 mm
Output Voltage	48 V/DC	Height	48.5 mm
Power	600 W	Rated Input Voltage	90-305 V/AC
Length	280 mm	Channels	1

Article	Price
872126	€ 399.95





KGP/NEXIVO POWER SUPPLY UNITS CV DALI / LONG-FLAT DESIGN

- Can be dimmed using DALI1/DALI2
- Power supply unit and DALI PWM dimmer in one device
- Extremely compact design
- Flicker-free
- Secured against short circuits and overloads
- Overheating protection



Housing	Aluminium	Rated Input Voltage	100-305 V/AC
Output Voltage	24 V/DC	Channels	1
Width	30 mm		

Article		Power	Length	Height	Price
872146	☐	12.0-30.0 W	300 mm	16 mm	€ 51.95
872147	☐	26.0-60.0 W	350 mm	18 mm	€ 63.95
872148	☐	45.0-150.0 W	350 mm	18 mm	€ 103.95



5-year guarantee

Benefit from the maximum quality promise:
 All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.



DEKO-LIGHT POWER SUPPLY UNITS CV DIM | LCP CASAMBI

- Dimmable/can be controlled with Casambi via Bluetooth 4.0/5.1 Low Energy (BLE)
- Power supply unit and Casambi dimmer in one device
- Compact design
- Flicker-free (20 kHz)
- Secured against short circuits and overloads
- Overheating protection



Housing	Plastic	Functions	Bluetooth data transfer, Short-circuit proof, Protective extra-low voltage, Overloading protection, Lamp control gear 110, Furniture installation, Overtemperature protection
Output Voltage	24 V/DC		
Power	150 W		
Length	295 mm		
Width	40 mm		
Height	32 mm		
Rated Input Voltage	220-240 V/AC		

Article		Channels	Price
862299	☐	1	€ 159.95
862300	☐	2	€ 167.95
862301	☐	3 / 4	€ 167.95




MEANWELL POWER SUPPLY UNITS CV DIM | PWM KNX

- Can be dimmed using KNX bus
- Flicker-free, secured against short circuits and overloads
- Overheating protection



Housing	Plastic	Channels	1
Rated Input Voltage	90-305 V/AC		

Article		Output Voltage	Power	Length	Width	Height	Price
872109	☒	12 V/DC	60.0 W	150 mm	53 mm	35 mm	€ 127.95
872110	☒	12 V/DC	120.0 W	191 mm	63 mm	37.5 mm	€ 167.95
872111	☒	12 V/DC	200.0 W	195 mm	68 mm	39.5 mm	€ 195.95
872112	☒	24 V/DC	60.0 W	150 mm	53 mm	35 mm	€ 127.95
872113	☒	24 V/DC	120.0 W	191 mm	63 mm	37.5 mm	€ 167.95
872114	☒	24 V/DC	200.0 W	195 mm	68 mm	39.5 mm	€ 195.95
872115	☒	48 V/DC	200.0 W	195 mm	68 mm	39.5 mm	€ 195.95




electr. data			dimmable via				usage / design			electrical limit values		power supply	
current strength	power	voltage	leading cut-off	touch dimmer (push)	DALI	KNX	indoor	outdoor	design	capacitive load	max. quantity per automatic circuit breaker	item number	page
260 mA	6,0-12,0W	23-46V	x				x		basic		B10A= 17, B16A=28 C10A=37, C16A=59	862285	814
350 mA	0,9-3,9 W	2,5-11V					x	x	mini		B10A=70, B16A=112, C10A=140, C16A=224	872129	811
350 mA	2,1-4,0 W	6-12V	x				x	x	mini	10.00nF	B10A=35, B16A=56, C10A=74, C16A=118	872132	813
350 mA	0,7-6,0 W	2-18V					x		flat	40.44nF	B10A=17, B16A=28, C10A=37, C16A=59	872628	812
350 mA	3,9-9,0 W	11-26V	x				x		basic		B10A=17, B16A=28, C10A=37, C16A=59	862202	814
350 mA	6,0-10,0 W	17-29V					x		mini		B10A=57, B16A=92, C10A=57, C16A=92	862239	812
350 mA	6,3-12,0 W	18-35V	x				x		basic	20,65pF	B10A=17, B16A=28, C10A=37, C16A=59	862203	814
350 mA	0,7-12,0 W	2-35V					x		flat	194,0uF	B10A=11, B16A=18, C10A=24, C16A=39	862223	812
350 mA	6,3-12,0 W	18-37V	x				x	x	octo	190uF	B10A=35, B16A=56, C10A=74, C16A=118	862235	813
350 mA	9,1-15,0 W	26-43V	x				x		basic		B10A=38, B16A=61, C10A=38, C16A=61	862266	815
350 mA	0,7- 18,0 W	2-52V					x		basic	147nF	B10A=17, B16A=28, C10A=37, C16A=59	180512	812
350 mA	9,8- 20,0 W	28-57V	x				x		basic		B10A=11, B16A=18, C10A=24, C16A=39	862204	814
350 mA	0,7- 20,0 W	2-57V					x		flat	195uF	B10A=11, B16A=18, C10A=24, C16A=39	862224	812
450 mA	9,9-19,0 W	22-42V	x				x		quick		B10A=11, B16A=18, C10A=24, C16A=39	862257	814
500 mA	2,0-4,0 W	4-8V					x	x	mini	85,0pF	B10A=70, B16A=112, C10A=140, C16A=224	872130	811
500 mA	2,0-4,0 W	4-8V	x				x	x	mini	4.75nF	B10A=35, B16A=56, C10A=74, C16A=118	872014	814
500 mA	1,0-6,0 W	2-12V					x		flat	38.48nF	B10A=17, B16A=28, C10A=37, C16A=59	862130	812
500 mA	1,0- 12,0 W	2-24V					x		flat	298uF	B10A=11, B16A=18, C10A=24, C16A=39	862225	812
500 mA	6,5-10,0 W	13-20V					x		mini		B10A=57, B16A=92, C10A=57, C16A=92	862238	812
500 mA	6,0- 12,0 W	12-24V	x				x	x	octo	186uF	B10A=35, B16A=56, C10A=74, C16A=118	862236	814
500 mA	1,0- 18,0 W	2-38V					x		basic	147nF	B10A=17, B16A=28, C10A=37, C16A=59	180513	812
500 mA	1,0- 20,0 W	2-40V					x		flat	292uF	B10A=11, B16A=18, C10A=24, C16A=39	862226	812
500 mA	10,0-20,0 W	20-40V	x				x		basic		B10A=11, B16A=18, C10A=24, C16A=39	862205	814
500 mA	15,0-30,0 W	30-60V					x		basic	366nF	B10A=11, B16A=18, C10A=24, C16A=39	862196	812
500 mA	20,0-40,0 W	40-80V					x		basic	356nF	B10A=8, B16A=14, C10A=18, C16A=29	862197	812
500 mA	20,0-40,0 W	40-80V	x				x		basic	29.84nF	B10A=35, B16A=56, C10A=35, C16A=56	862136	814

electr. data			dimmable via				usage / design			electrical limit values			power supply	
current strength	power	voltage	leading cut-off				indoor			capacitive load	max. quantity per automatic circuit breaker	item number	page	
			touch dimmer (push)	DALI	KNX	indoor	outdoor	design						
700 mA	1,7-4,0 W	2-6V					x	x	mini	82pF	B10A=70, B16A=112, C10A=140, C16A=224	872131	811	
700 mA	2,0-4,0 W	2,5-6V	x				x	x	mini	10nF	B10A=35, B16A=56, C10A=74, C16A=118	872134	813	
700 mA	1,4-6,0 W	2-9V					x		flat	40.44nF	B10A=17, B16A=28, C10A=37, C16A=59	862048	812	
700 mA	1,4- 12,0 W	2-17V					x		flat	427uF	B10A=11, B16A=18, C10A=24, C16A=39	862227	812	
700 mA	7,0- 12,0 W	10-17V	x				x	x	octo	188uF	B10A=35, B16A=56, C10A=74, C16A=118	862237	813	
700 mA	1,4- 18,0 W	2-26V					x		basic	147nF	B10A=17, B16A=28, C10A=37, C16A=59	180514	812	
700 mA	1,4- 20,0 W	2-29V					x		flat	295uF	B10A=11, B16A=18, C10A=24, C16A=39	862228	812	
700 mA	9,8- 20,0 W	14-28V	x				x		basic		B10A=11, B16A=18, C10A=24, C16A=39	862207	814	
700 mA	9,1- 30,0 W	13-43V					x		basic		B10A=11, B16A=18, C10A=24, C16A=39	862198	812	
700 mA	20,3- 35,0 W	29-57V					x		basic	359,3nF	B10A=8, B16A=14, C10A=18, C16A=29	862199	812	
700 mA	19,6- 40,0 W	28-56V	x				x		basic		B10A=35, B16A=56, C10A=35, C16A=56	862208	814	
900mA	19,8- 40,0 W	22-44V					x		basic	13.5pF	B10A=8, B16A=14, C10A=18, C16A=29	862157	812	
900mA	19,8- 40,0 W	22-44V	x				x		basic	30nF	B10A=35, B16A=56, C10A=35, C16A=56	862264	814	
1050 mA	20,0- 40,0 W	19-38V					x		basic		B10A=8, B16A=14, C10A=18, C16A=29	862201	812	
1050 mA	20,0- 40,0 W	19-38V	x				x		basic		B10A=35, B16A=56, C10A=35, C16A=56	862209	814	
1050 mA	23,5- 45,0 W	22-43V	x				x		basic	33,46nF	B10A=35, B16A=56, C10A=35, C16A=56	862210	814	
1050 mA	23,1- 45,0 W	22-43V	x				x		quick	33,46nF	B10A=35, B16A=56, C10A=35, C16A=56	862258	814	
1300 mA	26,0- 50,0 W	20-39V	x				x		basic		B10A=35, B16A=56, C10A=35, C16A=56	862211	814	
1500 mA	40,0- 60,0 W	27-42V	x				x		quick		B10A=25, B16A=41, C10A=25, C16A=41	862259	814	
MULTI*	3,2- 12,0 W	15-54V		x	x		x		basic		B10A=23, B16A=37, C10A=46, C16A=74	862190	817	
MULTI*	5,0- 25,0 W	20-60V		x	x		x		basic		B10A=23, B16A=37, C10A=46, C16A=74	862191	817	
MULTI*	8,75- 45,0 W	21-70V		x	x		x		basic		B10A=12, B16A=20, C10A=25, C16A=40	862192	817	
MULTI*	14,7- 45,0 W	14-43V		x	x		x		basic		B10A=12, B16A=20, C10A=25, C16A=40	862193	817	
MULTI*	26,3- 75,5 W	25-71V		x	x		x		basic		B10A=3, B16A=5, C10A=6, C16A=10	862194	817	

* Due to the large number of possible settings, please refer to the detailed technical data on the specified product page.




power supplies design



TIPS AND TRICKS FOR CURRENT-STABLE POWER SUPPLIES

In contrast to voltage-stable power supplies [CV], current-stable power supply units, often abbreviated to CC [constant current], the output current is stable. This important factors that must be taken into focus during planning and installation.

- Do not connect LEDs to CC power supply units below voltage, as this can damage them and cause them to fail after a short period of operation.
- if possible: 1 luminaire = 1 power supply
- if necessary: operate max. 2 luminaires in a series connection on one power supply unit.
However, the voltage range and the power of the power supply must be checked carefully.



Netzgerätedaten prüfen! Check driver data!

Installationshinweis für Netzgerät stromstabil [CC]: LED nicht unter Spannung anschließen!
installation instruction for power supply constant current [CC]: Don't connect LED under voltage!




DEKO-LIGHT POWER SUPPLY UNITS CC | MINI DESIGN

- Flicker-free
- Secured against short circuits and overloads
- Overheating protection



Housing	Plastic	Height	21 mm
Length	53 mm	Rated Input Voltage	220-240 V/AC
Width	27 mm		

Article		Output Current	Power	Output Voltage	Price
872129	■	350 mA	0.9-3.9 W	2.5-11 V/DC	€ 9.95
872130	■	500 mA	2.0-4.0 W	4-8 V/DC	€ 9.95
872131	■	700 mA	1.7-4.0 W	2.5-6 V/DC	€ 9.95




HEP POWER SUPPLY UNITS CC | G5S10W

- Compact design
- Flicker-free
- Secured against short circuits and overloads
- Overheating protection



Housing	Plastic	Height	20 mm
Length	58.1 mm	Rated Input Voltage	220-240 V/AC
Width	39.1 mm		

Article		Output Current	Power	Output Voltage	Price
862239	□	350 mA	6.0-10.0 W	17-29 V/DC	€ 21.95
862238	□	500 mA	6.5-10.0 W	13-32 V/DC	€ 21.95



DEKO-LIGHT POWER SUPPLY UNITS CC | FLAT DESIGN

- Flicker-free
- Secured against short circuits and overloads
- Overheating protection




Housing

Plastic

Rated Input Voltage

220-240 V/AC

Article		Output Current	Power	Output Voltage	Length	Width	Height	Price
862224		350 mA	0.7-20.0 W	2-57 V/DC	128 mm	50 mm	13 mm	€ 22.95
862223		350 mA	0.7-12.0 W	2-35 V/DC	128 mm	50 mm	13 mm	€ 19.95
872628		350 mA	0.7-6.0 W	2-18 V/DC	98 mm	46 mm	11 mm	€ 13.95
862226		500 mA	1.0-20.0 W	2-40 V/DC	128 mm	50 mm	13 mm	€ 22.95
862225		500 mA	1.0-12.0 W	2-24 V/DC	128 mm	50 mm	13 mm	€ 19.95
862130		500 mA	1.0-6.0 W	2-12 V/DC	98 mm	46 mm	11 mm	€ 13.95
862228		700 mA	1.4-20.0 W	2-29 V/DC	128 mm	50 mm	13 mm	€ 22.95
862227		700 mA	1.4-12.0 W	2-17 V/DC	128 mm	50 mm	13 mm	€ 19.95
862048		700 mA	1.4-6.0 W	2-9 V/DC	98 mm	46 mm	11 mm	€ 13.95



DEKO-LIGHT POWER SUPPLY UNITS CC | BASIC DESIGN

- Flicker-free
- Secured against short circuits and overloads
- Overheating protection




Housing

Plastic

Rated Input Voltage

220-240 V/AC

Article		Output Current	Power	Output Voltage	Length	Width	Height	Price
180512		350 mA	0.7-18.0 W	2-52 V/DC	115 mm	45 mm	21 mm	€ 18.95
180513		500 mA	1.0-18.0 W	2-38 V/DC	115 mm	45 mm	21 mm	€ 18.95
862196		500 mA	15.0-30.0 W	30-60 V/DC	127 mm	43 mm	28 mm	€ 21.95
862197		500 mA	20.0-40.0 W	40-80 V/DC	127 mm	43 mm	28 mm	€ 23.95
180514		700 mA	1.4-18.0 W	2-26 V/DC	115 mm	45 mm	21 mm	€ 18.95
862198		700 mA	14.0-30.0 W	21-43 V/DC	127 mm	43 mm	28 mm	€ 21.95
862199		700 mA	20.0-40.0 W	29-57 V/DC	127 mm	43 mm	28 mm	€ 23.95
862157		900 mA	19.0-40.0 W	22-44 V/DC	127 mm	43 mm	28 mm	€ 23.95
862201		1050 mA	20.0-40.0 W	19-38 V/DC	127 mm	43 mm	28 mm	€ 23.95



DEKO-LIGHT POWER SUPPLY UNITS CC DIM | BASIC DESIGN

- Can be dimmed using trailing-edge phase dimmers
- Flicker-free
- Short circuit, overload and overheating protection




Housing

Plastic

Rated Input Voltage

220-240 V/AC

Article		Output Current	Power	Output Voltage	Length	Width	Height	Price
862285		260 mA	6.0-12.0 W	23-46 V/DC	115 mm	39 mm	22 mm	€ 25.95
862202		350 mA	4.5-9.0 W	13-26 V/DC	115 mm	39 mm	22 mm	€ 22.95
862203		350 mA	6.3-12.0 W	18-35 V/DC	115 mm	39 mm	22 mm	€ 29.95
862204		350 mA	9.8-20.0 W	28-57 V/DC	127 mm	44 mm	28 mm	€ 31.95
862205		500 mA	10.0-20.0 W	20-40 V/DC	127 mm	44 mm	28 mm	€ 31.95
862136		500 mA	20.0-40.0 W	40-80 V/DC	166 mm	52 mm	24 mm	€ 37.95
862207		700 mA	9.8-19.6 W	14-28 V/DC	127 mm	44 mm	28 mm	€ 31.95
862208		700 mA	19.0-40.0 W	28-56 V/DC	166 mm	52 mm	24 mm	€ 37.95
862264		900 mA	19.6-40.0 W	22-44 V/DC	166 mm	52 mm	25 mm	€ 37.95
862209		1050 mA	20.0-40.0 W	19-38 V/DC	166 mm	52 mm	25 mm	€ 37.95
862210		1050 mA	23.0-45.0 W	22-43 V/DC	166 mm	52 mm	25 mm	€ 39.95
862211		1300 mA	25.0-50.0 W	20-39 V/DC	166 mm	52 mm	25 mm	€ 41.95



DEKO-LIGHT POWER SUPPLY UNITS CC DIM | QUICK DESIGN

- Particularly quick and easy to install with integrated three-pin feed-through wiring
- Push terminals for wires from 0.5 to 1.5 mm²
- Push terminals also on secondary side
- No additional installation material required
- Can be dimmed using compatible [C-compatible] trailing-edge phase dimmers
- Flicker-free
- Secured against short circuits and overloads
- Overheating protection



Housing

Plastic

Height

32 mm

Length

208 mm


Rated Input Voltage

220-240 V/AC

Width

60 mm

Article		Output Current	Power	Output Voltage	Price
862257		450 mA	9.9-19.0 W	22-42 V/DC	€ 29.95
862258		1050 mA	23.1-44.1 W	22-42 V/DC	€ 37.95
862259		1500 mA	40.5-63.0 W	27-42 V/DC	€ 45.95



HEP POWER SUPPLY UNIT CC DIM | G6LT15W350LR-Z


- Can be dimmed using trailing-edge phase dimmers
- Flicker-free
- Secured against short circuits and overloads
- Overheating protection



Housing	Plastic	Length	85 mm
Output Current	350 mA	Width	40.4 mm
Power	9.1-15 W	Height	22 mm
Output Voltage	26-43 V/DC	Rated Input Voltage	220-240 V/AC

Article Price

862266  € 25.95



Technical data sheet

New in the onlineshop: The technical data sheets offer even more information: Light and energy data, light distribution curves, dimensional drawings and more.

DEKO-LIGHT MULTI-CURRENT DALI 2.0 POWER SUPPLIES DALI 2
IE-12D| IE-25D | IE-45D | IE-45HD| IE-75D

A must for every electrician: the new MULT-CC DALI 2.0 power supplies from DEKO-LIGHT are a real all-purpose weapon for universal use.

They can be controlled via DALI1 or DALI2 [fully upward and downward compatible] or via Intelli-Push. In this case, the multi-current-power supplies do not require any additional control components and are controlled by means of cost-effective 230V standard push-buttons. With the new Intelli-Push function, they also have a pioneering synchronisation option if one of the connected power supplies no longer runs synchronously with the others.

In addition, the MULTI-power supplies can also be operated undimmed without control as a reliable and universal power supplier. With a total of five models, the new DALI series covers a CC current range from 180mA to 1600mA and power ratings from 4 to 75 watts.

- plastic housing
- compact housing design
- suitable for indoor use
- flicker free
- short-circuit proof and overload protection
- overheat control
- current range adjustable via DIP switch
- DALI 2 BUS ready according to IEC 62386
- fully downward compatible with DALI 1
- dimming range: 1-100%
- dimmable via DALI or touch dimmer function [push] new Intelli-Push function [key combination synchronises all connected power supplies]
- can also be operated without control as universal power supply unit universal power supply [no dimming function]
- 3.2-75 watts and 37 CC variants in only 3 different housing sizes




design example 114 x 52 x 24 mm



design example 133 x 71 x 24 mm



design example 159 x 79 x 30 mm



controllable with DALI2, DALI1 or by touch dim using a regular 230V push-button

TOUCH-DIM / INTELLI-PUSH VIA 230V PUSH BUTTON
WITHOUT ADDITIONAL CONTROL:

- | | |
|-----------------------------|---|
| press button short | switch lamp on/off |
| press button long | dim lamp bright/dark/bright |
| press button for 15 seconds | All connected power supplies are synchronised to the same brightness. |

electr. data		dimmable via				usage / design			electrical limit values		power supply	
current strength	power	electronic power supply	conventional transformer		leading edge	leading cut-off	indoor	outdoor design	capacitive load	max. quantity per automatic circuit breaker	item number	page
electronic power supply units:												
12V	0,0-70,0 W	x			x	x		basic	97.79nF	B10A=8, B16A=14, C10A=18, C16A=29	180515	819
12V	0,0-105,0 W	x			x	x		basic	139.58nF	B10A=5, B16A=9, C10A=12, C16A=19	180529	819
wound transformers:												
12V	11,5-20,0 W		x	x		x		*			000097	819
12V	34,5-60,0 W		x	x		x		*			000099	819
12V	60,5-105,0 W		x	x		x		*			000107	819
12V	86,5-150,0 W		x	x		x		*			000103	819
12V	115,0-200,0 W		x	x		x		*			000104	819
12V	172,5-300,0 W		x	x		x		*			000106	819
12V	287,5-500,0 W		x	x		x		*			000109	819


DEKO-LIGHT TRANSFORMER CV DIM | ULTRA 12 VOLT/AC

- Can be dimmed using trailing-edge phase dimmers
- 11.5 V lamp-friendly voltage
- Flicker-free
- Secured against short circuits and overloads
- Overheating protection
- 180515: 0-70 W halogen or 0-50 W LED/max. 6 LEDs
- 180529: 0-105 W halogen or 0-50 W LED/max. 6 LEDs



Housing	Plastic	Width	44 mm
Output Voltage	11.5 V/AC	Height	28 mm
Length	113 mm	Rated Input Voltage	220-240 V/AC

Article		Power	Price
180529		0.0-105.0 W	€ 18.95
180515		0.0-70.0 W	€ 14.95



ABN TRANSFORMERS CV DIM | 12 VOLT/AC

- Conventional wound transformer [L load]
- 11.5 V lamp-friendly voltage
- Can be dimmed using leading-edge phase dimmers



Housing	Plastic	Rated Input Voltage	220-240 V/AC
Output Voltage	11.5 V/AC		

Article		Power	Apparent power	Length	Width	Height	Price
000097		11.5-20.0 W	20 VA	82 mm	56 mm	50 mm	€ 71.95
000099		34.5-60.0 W	60 VA	100 mm	70 mm	61 mm	€ 105.95
000107		60.0-105.0 W	105 VA	107 mm	78 mm	66 mm	€ 129.95
000103		86.5-150.0 W	150 VA	130 mm	88 mm	78 mm	€ 154.95
000104		115.0-200.0 W	200 VA	130 mm	88 mm	88 mm	€ 179.95
000106		172.0-300.0 W	300 VA	130 mm	88 mm	103 mm	€ 199.95
000109		287.5-500.0 W	500 VA	177 mm	107 mm	130 mm	€ 349.95



Accessories for 000103, 000104, 000106

000111 Housing Pyra 120-300 VA



€ 16.95

Accessories for 000107

000110 Housing Pyra 105 VA



€ 16.95





CONTROLLER

- 850 Casambi Bluetooth
 - 852 DALI / DMX dimmer
 - 824 RF-Smart
- 



☒ ☐
page 826



☒ ☐
page 827



☒ ☐
page 828



☒ ☐
page 831



☒ ☐
page 832



☒ ☐
page 834



☒ ☐
page 835



☐ ☒
page 836



☒ ☐
page 841



☐ ☐
page 843



☐ ☐
page 844



☐ ☐
page 847

controller



☐ page 848



☒ page 849



☐ page 850



☐ page 850



☒ ☐ page 851



☐ page 851



☒ page 852



☒ page 852



☐ page 853



☐ page 854



☐ page 854



☐ page 855



☐ page 855

RF-SMART: COMPONENTS

We hereby present the multifunctional RF-smart control system from DEKO-LIGHT. It enables the switching and dimming of devices with 230V mains voltage and offers LED dimmers for LED strips with 1-5 channels from 12V to 48V voltage. Dimmers in IP67 design are available for outdoor use. The system is complemented by luminaires with an integrated RF module, such as outdoor spotlights and LED retrofit luminaires. RF-smart components can be controlled with RF radio remote controls and Zigbee 3.0 compatible radio modules. This enables control via smartphone, tablet or voice and offers comprehensive smart home functions. Installation is quick and easy.



simple control via RF remote controls



smart control via ZigBee 3.0



control via push-button

remote controls

The remote controls can be used to control the components on different channels in one or more zones. The remote controls are available as mobile versions or for wall mounting.

- 1 zone [1-2 oder 3-5 channels]
- 4 zones [1-5 channels]
- 8 zones [1-5 channels]
- power supply via 2x AAA batteries [3V]
- 230V direct connection [optional]



PIR motion detector

The PIR motion detector detects movement at an angle of 120° and a range of 1 to 7 metres - ideal for precise, energy-efficient lighting control.

- power supply via 1x CR123A battery



page 848

repeater

With the repeater, the wireless range of the remote controls can be extended by up to 30 metres.

- 230V AC



page 847



illuminants

The LED retrofit illuminants are equipped with an RF-smart radio module and fit into standard GU10 and E27 sockets.

- GU10 RGB+CCT
- E27 A60/MAX RGB+CCT
- 230V AC
- controllable via remote control and ZigBee 3.0



page 863



page 865



page 866

luminaires

The RF-smart lights are equipped with a ZigBee-compatible wireless module and can therefore also be controlled via the market-leading smart home systems from Amazon, Google & Co.

- FLOOD RGB+CCT
- SPOT RGB+CCT
- 230V AC
- IP67 / IP44
- controllable via remote control and ZigBee 3.0



page 540



page 509



page 510

Triac dimmer

The triac dimmers work with phase cut-off dimming and enable the switching and/or dimming of devices with 230V mains voltage.

- 230V AC
- IP20 / IP67
- on/off, Dimmen
- controllable via remote control, push-button and ZigBee 3.0



page 832



page 833

LED dimmer

The LED dimmers can be used to control LED stripes with 1-5 channels and 12V to 48V voltage.

- 12-48V DC
- IP20 / IP67
- on/off, dimming, automatic programmes, RGB/CCT colour settings
- controllable via remote control, push-button and ZigBee 3.0



page 834



page 835




DEKO-LIGHT RF-SMART STARTER-SET 4, 230V TRIAC DIMMER + RF PUSH-BUTTON REMOTE CONTROL

- Easy commissioning and operation (on/off - light-dark-bright)
- Light switch haptics
- Fits perfectly into existing switch programmes
- Intelli-Push Dim function (on/off, brightness) via potential-free push-button
- can also be controlled with all RF-Smart remote controls
- controllable with all Zigbee 3.0 compatible controllers / apps (gateway required)
- Program and remote control synchronisation when operating multiple RF Smart components (repeater function)
- Control of 230 V (R/C) components
- Minimum brightness adjustable in ten levels
- Switch mode adjustable (dimming deactivated)
- Up to 10x LED-LM / 7x LED ballast can be connected (max. 300 W for R/C loads)
- one control zone
- Mounting using adhesive pad or screws
- Operation remote control with 1x CR 2032 battery (not included)
- Set consisting of: 1 x 843503 / 1 x 843535

Housing	Plastic	Control	RF-Smart, Trailing-edge dimmer, ZigBee 3.0, Intelli Push-Dim
Power	1.0-300 W		
Output Current	1.36 A	Channels	1
Rated Input Voltage	100-240 V/AC		

Article	Price
843537 	€ 75.95



Accessories

843536
Battery, Varta, CR2032, Lithium 3 V



€ 3.95



DEKO-LIGHT RF-SMART STARTER-SET 1, 230V TRIAC DIMMER + RF-REMOTE CONTROL

- Dimmable brightness
- Intelli-Push dim function [on/off, brightness] via potential-free push-button
- Can be controlled with all RF-smart wireless remote controls [2.4 GHz, range approx. 30 m]
- Can be controlled with all Zigbee 3.0 compatible controllers/apps such as Amazon Echo [Alexa], Google Assistant, Tuya [relevant gateway required, outdoor range up to 100 m]
- Program and remote control synchronisation when operating multiple RF-smart components [repeater function]
- Control of 230 V [R/C] components
- Minimum brightness adjustable in ten steps
- Adjustable switch mode [dimming disabled]
- Up to 10x LED-LM/7x LED ballast units can be connected [max. 300 W for R/C loads]
- One control zone
- Remote control requires 2x AAA batteries [not included in the scope of delivery]
- Set consisting of: 1x 843503 + 1x 843508

Housing	Plastic	Rated Input Voltage	100-240 V/AC
Length	49 mm	Control	RF-Smart, Trailing-edge dimmer, ZigBee 3.0, Intelli Push-Dim
Power	1.0-300 W		
Output Current	1.36 A	Channels	1

Article	Price
843500 	€ 79.95





DEKO-LIGHT RF-SMART STARTER-SET 5, LED DIMMER + RF PUSH-BUTTON REMOTE CONTROL SINGLE

- Easy commissioning and operation (on/off - light-dark-bright)
- Light switch haptics
- Fits perfectly into existing switch programmes
- Intelli-Push Dim function (on/off, brightness) via pontential-free push-button
- Soft-On / Soft-Off for gentle switching on / off
- additionally controllable with all RF-Smart radio remote controls
- controllable with all Zigbee 3.0 compatible controllers / apps (gateway required)
- Program and remote control synchronisation when operating multiple RF Smart components (repeater function)
- Control of single components
- flicker-free (image/video recordings)
- Power: max. 20 A / controller, max. 10 A / channel
- 12 V = 240 W, 24 V = 480 W, 48 V = 960 W
- one control zone
- Mounting with adhesive pad or screws
- Operation remote control with 1x CR2032 battery (not included)
- Set consisting of: 1 x 843505 / 1 x 843535

Housing	Plastic	Control	RF-Smart, ZigBee 3.0, Intelli Push-Dim
Output Current	20 A		
Rated Input Voltage	12-48 V/DC	Channels	1

Article	Price
843538	€ 75.95



Accessories

843536
Battery, Varta, CR2032, Lithium 3 V



€ 3.95



DEKO-LIGHT RF-SMART STARTER-SET 2, LED-DIMMER + RF-REMOTE CONTROL SINGLE/CCT

- Dimmable brightness and colour saturation
- Intelli-Push dim function [on/off, brightness] via potential-free push-button
- Can be controlled with all RF-smart wireless remote controls [2.4 GHz, range approx. 30 m]
- Can be controlled with all Zigbee 3.0 compatible controllers/apps such as Amazon Echo [Alexa], Google Assistant, Tuya [relevant gateway required, outdoor range up to 100 m]
- Program and remote control synchronisation when operating multiple RF-smart components [repeater function]
- Control of single/CCT components
- Flicker-free [images/videos]
- Power: max. 20 A/controller, max. 10 A/channel
- 12 V = 240 W, 24 V = 480 W, 48 V = 960 W
- One control zone
- Remote control requires 2x AAA batteries [not included in the scope of delivery]
- Set consisting of: 1x 843505 + 1x 843508

Housing	Plastic	Control	RF-Smart, ZigBee 3.0,
Output Current	20 A		Intelli Push-Dim
Rated Input Voltage	12-48 V/DC	Channels	1, 2

Article	Price
843501	€ 79.95






DEKO-LIGHT RF-SMART STARTER-SET 3, LED-DIMMER + RF-REMOTE CONTROL RGB/RGBW/RGB+CCT

- Dimmable brightness and colour saturation
- 16 million adjustable colours and adjustable colour temperature
- 18 pre-installed automatic programs
- Intelli-Push dim function [on/off, brightness] via potential-free push-button
- Can be controlled with RF-smart wireless remote controls [2.4 GHz, range approx. 30 m]
- Can be controlled with all Zigbee 3.0 compatible controllers/apps such as Amazon Echo [Alexa], Google Assistant, Tuya [relevant gateway required, outdoor range up to 100 m]
- Program and remote control synchronisation when operating multiple RF-smart components [repeater function]
- Control of RGB components
- Flicker-free [images/videos]
- Power: max. 20 A/controller, max. 10 A/channel
- 12 V = 240 W, 24 V = 480 W, 48 V = 960 W
- One control zone
- Remote control requires 2x AAA batteries [not included in the scope of delivery]
- Set consisting of: 1x 843505 + 1x 843510

Housing	Plastic	Control	RF-Smart, ZigBee 3.0,
Output Current	20 A		Intelli Push-Dim
Rated Input Voltage	12-48 V/DC	Channels	3

Article	Price
843502	€ 79.95





DEKO-LIGHT RF-SMART STARTER-SET 6, RGB/W/CCT

- Brightness and colour saturation dimmable
- 16 million colours or colour temperature adjustable
- 18 automatic programmes pre-installed
- Convenient operation via stand / handheld remote control
- Soft-On / Soft-Off for gentle switching on / off
- Intelli-Push Dim function (on/off, brightness) via potential-free push-button
- Controllable with RF-Smart radio remote controls
- controllable with all Zigbee 3.0 compatible controllers / apps (gateway required)
- Program and remote control synchronisation when operating multiple RF Smart components (repeater function)
- Control of single / WW-CW / RGB / RGBW / RGB+CCT components
- flicker-free (image / video recordings)
- Power: max. 20 A / controller, max. 10 A / channel
- 12 V = 240 W, 24 V = 480 W, 48 V = 960 W
- three control zones
- Operation remote control with 2 x AAA battery (not included)
- Set consisting of: 1 x 843505 / 1 x 843525

Housing	Plastic	Control	RF-Smart, ZigBee 3.0,
Output Current	20 A		Intelli Push-Dim
Rated Input Voltage	12-48 V/DC	Channels	1, 2, 3, 4, 5

Article	Price
843542 	€ 91.95





DEKO-LIGHT RF-SMART TRIAC DIMMER 230 V

- Dimmable brightness
- Intelli-Push dim function [on/off, brightness] via potential-free push-button
- Can be controlled with RF-smart wireless remote controls [2.4 GHz, range approx. 30 m, not included in the scope of delivery]
- Can be controlled with all Zigbee 3.0 compatible controllers/apps such as Amazon Echo [Alexa], Google Assistant, Tuya [relevant gateway required, outdoor range up to 100 m]
- Program and remote control synchronisation when operating multiple RF-smart components [repeater function]
- Control of 230 V (R/C) components
- Minimum brightness adjustable in ten steps
- Adjustable switch mode [dimming disabled]
- Up to 10x LED-LM/7x LED ballast units can be connected [max. 300 W for R/C loads]

Output Current	1.36 A	Power	1.0-300 W
Housing	Plastic	Rated Input Voltage	100-240 V/AC
Length	49 mm	Control	RF-Smart, Trailing-edge dimmer, ZigBee 3.0, Intelli Push-Dim
Width	49 mm	Channels	1
Height	25 mm		

Article	Price
843503 	€ 55.95





DEKO-LIGHT RF-SMART OUTDOOR TRIAC-DIMMER 230V

- Dimmable brightness
- Intelli-Push dim function [on/off, brightness] via potential-free push-button
- Can be controlled with RF-smart wireless remote controls [2.4 GHz, range approx. 30 m, not included in the scope of delivery]
- Can be controlled with all Zigbee 3.0 compatible controllers/apps such as Amazon Echo [Alexa], Google Assistant, Tuya [relevant gateway required, outdoor range up to 100 m]
- Program and remote control synchronisation when operating multiple RF-smart components [repeater function]
- Control of 230 V (R/C) components
- Minimum brightness adjustable in ten steps
- Adjustable switch mode [dimming disabled, additional load relays can be connected]
- Up to 10x LED-LM/7x LED ballast units can be connected [max. 300 W for R/C loads]
- IP67 outdoor distribution board with up to four cable entry points from 4-14 mm and two blanking plugs

Output Current	1.36 A	Power	1.0-300 W
Housing	Plastic	Rated Input Voltage	100-240 V/AC
Length	170 mm	Control	RF-Smart, Trailing-edge dimmer, ZigBee 3.0, Intelli Push-Dim
Width	155 mm	Channels	1
Height	65 mm		

Article	Price
843504 	€ 71.95





DEKO-LIGHT RF-SMART LED-DIMMER 5-IN-1,
5 CHANNEL SINGLE/CCT/RGB/RGBW/RGB+CCT

- Dimmable brightness and colour saturation
- 16 million adjustable colours and adjustable colour temperature
- 18 pre-installed automatic programs
- Intelli-Push dim function [on/off, brightness] via potential-free push-button
- Can be controlled with RF-smart wireless remote controls [2.4 GHz, range approx. 30 m, not included in the scope of delivery]
- Can be controlled with all Zigbee 3.0 compatible controllers/apps such as Amazon Echo [Alexa], Google Assistant, Tuya [relevant gateway required, outdoor range up to 100 m]
- Program and remote control synchronisation when operating multiple RF-smart components [repeater function]
- Control of single/CCT/RGB/RGBW/RGB+CCT components
- Flicker-free [images/videos]
- Power: max. 20 A/controller, max. 10 A/channel
- 12 V = 240 W, 24 V = 480 W, 48 V = 960 W

Housing	Plastic	Rated Input Voltage	12-48 V/DC
Length	120 mm	Control	RF-Smart, ZigBee 3.0, Intelli Push-Dim
Width	47 mm	Channels	1, 2, 3, 4, 5
Height	23 mm		
Output Current	20 A		

Article	Price
843505 	€ 55.95





DEKO-LIGHT RF-SMART OUTDOOR LED-DIMMER 5-IN-1, 5 CHANNEL SINGLE/CCT/RGB/RGBW/RGB+CCT

- Dimmable brightness and colour saturation
- 16 million adjustable colours and adjustable colour temperature
- 18 pre-installed automatic programs
- Can be controlled with RF-smart wireless remote controls [2.4 GHz, range approx. 30 m, not included in the scope of delivery]
- Can be controlled with all Zigbee 3.0 compatible controllers/apps such as Amazon Echo [Alexa], Google Assistant, Tuya [relevant gateway required, outdoor range up to 100 m]
- Program and remote control synchronisation when operating multiple RF-smart components [repeater function]
- Control of single/CCT/RGB/RGBW/RGB+CCT components
- Flicker-free [images/videos]
- Power: max. 20 A/controller, max. 10 A/channel
- 12 V = 240 W, 24 V = 480 W, 48 V = 960 W
- Input/output pre-fitted on each 20 cm connecting cable

Housing	Plastic	Output Current	20 A
Length	185 mm	Rated Input Voltage	12-48 V/DC
Width	87 mm	Control	RF-Smart, ZigBee 3.0
Height	31 mm	Channels	1, 2, 3, 4, 5

Article	Price
843506	€ 87.95





DEKO-LIGHT RF-SMART RF-REMOTE CONTROL, SINGLE/CCT

- Dimmable brightness
- Adjustable colour temperature, if necessary
- One control zone
- Range approx. 30 m
- Can be used as a wall-mounted or hand-held remote control [magnetic holder included in the scope of delivery]
- Very simple installation and operation
- Battery-operated with 2x AAA [not included in the scope of delivery]
- Low power consumption
- Control of single/CCT components

Housing	Plastic	Rated Input Voltage	3 V/DC
Height	24 mm	Control	RF-Smart
Ø	70 mm	Channels	1, 2

Article		Price
843508		€ 30.95
843509		€ 30.95



Lighting design
Interested in our lighting design service?
Your contact person will be happy to answer any questions you may have.




DEKO-LIGHT RF-SMART RF-REMOTE CONTROL, RGB/RGBW/RGB+CCT

- Dimmable brightness
- Adjustable colour saturation and colour temperature, if necessary
- 16 million adjustable colours
- Automatic programs can be controlled
- One control zone
- Range approx. 30 m
- Can be used as a wall-mounted or hand-held remote control [magnetic holder included in the scope of delivery]
- Very simple installation and operation
- Battery-operated with 2x AAA [not included in the scope of delivery]
- Low power consumption
- Control of RGB components

Housing	Plastic	Rated Input Voltage	3 V/DC
Height	24 mm	Control	RF-Smart
Ø	70 mm	Channels	3

Article		Price
843510		€ 30.95
843511		€ 30.95



Onlineshop
You can find more information about the products in the onlineshop:
Detailed images, videos, project reports, LDT files, EPREL data sheets and more.



DEKO-LIGHT RF-SMART RF REMOTE CONTROL, 3 ZONES, SINGLE

- Dimmable brightness
- Up to three different control zones
- Three storable scenes
- Range approx. 30 m
- Can be used as a stand/handheld remote control
- Very simple installation and operation
- Battery-operated with 2x AAA [not included in the scope of delivery]
- Low power consumption
- Controls single components

Housing	Plastic	Rated Input Voltage	3 V/DC
Length	143 mm	Control	RF-Smart
Width	57 mm	Channels	1
Height	44 mm		

Article	Price
843523 	€ 39.95





DEKO-LIGHT RF-SMART RF REMOTE CONTROL, 3 ZONES, SINGLE/CCT

- Dimmable brightness
- Up to three different control zones
- Three storable scenes
- Range approx. 30 m
- Can be used as a stand/handheld remote control
- Very simple installation and operation
- Battery-operated with 2x AAA [not included in the scope of delivery]
- Low power consumption
- Controls CCT and/or single components

Housing	Plastic	Rated Input Voltage	3 V/DC
Length	143 mm	Control	RF-Smart
Width	57 mm	Channels	1, 2
Height	44 mm		

Article	Price
843524 	€ 39.95





DEKO-LIGHT RF-SMART RF-REMOTE CONTROL,
3 ZONES SINGLE/CCT/RGB/RGBW/RGB+CCT

- Dimmable brightness
- Can be used as a stand/handheld remote control
- Adjustable colour saturation and colour temperature, if necessary
- 16 million adjustable colours, if necessary
- Separate white light button
- Automatic program and program speed can be controlled
- Up to three different control zones
- Range approx. 30 m
- Very simple installation and operation
- Battery-operated with 2x AAA [not included in the scope of delivery]
- Low power consumption
- Controls single/CCT/RGB/RGBW/RGB+CCT components

Housing	Plastic	Rated Input Voltage	3 V/DC
Length	143 mm	Control	RF-Smart
Width	57 mm	Channels	1, 2, 3, 4, 5
Height	44 mm		

Article	Price
843525 	€ 39.95





**DEKO-LIGHT RF-SMART RF-REMOTE CONTROL,
8 ZONES SINGLE/CCT/RGB/RGBW/RGB+CCT**

- Dimmable brightness
- Adjustable colour saturation and colour temperature, if necessary
- 16 million adjustable colours, if necessary
- Separate white light button
- Automatic program and program speed can be controlled
- Up to eight different control zones
- Range approx. 30 m
- Wall bracket included in the scope of delivery
- Very simple installation and operation
- Battery-operated with 2x AAA [not included in the scope of delivery]
- Low power consumption
- Control of single/CCT/RGB/RGBW/RGB+CCT components

Housing	Plastic	Rated Input Voltage	3 V/DC
Length	153 mm	Control	RF-Smart
Width	47 mm	Channels	1, 2, 3, 4, 5
Height	19 mm		

Article Price

843512  € 39.95








DEKO-LIGHT RF-SMART PUSH-BUTTON WALL-MOUNTED REMOTE CONTROL 1 ZONE

- Easy commissioning and operation (on/off - light-dark-bright)
- Light switch haptics
- Fits perfectly into existing switch programmes
- one control zone
- Range approx. 30 m
- Mounting with adhesive pad or screws
- Battery operation with 1x CR 2032 battery (not included)
- Low power consumption
- Control of single components

Housing	Plastic	Rated Input Voltage	3 V/DC
Length	86 mm	Control	RF-Smart
Width	86 mm	Channels	1
Height	14.5 mm		

Article	Price
843535 	€ 21.95



Accessories
843536 Battery, Varta, CR2032, Lithium 3 V



€ 3.95




DEKO-LIGHT RF-SMART RF-WALL REMOTE CONTROL,
4 ZONES, 3V, SINGLE/CCT/RGB/RGBW/RGB+CCT

- Dimmable brightness
- Adjustable colour saturation and colour temperature, if necessary
- 16 million adjustable colours, if necessary
- Automatic program and program speed can be controlled
- Separate white light button
- Up to four different control zones
- Range approx. 30 m
- Magnetic wall bracket included in the scope of delivery
- Very simple installation and operation
- Battery-operated with 2x AAA [not included in the scope of delivery]
- Low power consumption
- Control of single/CCT/RGB/RGBW/RGB+CCT components

Housing	Plastic	Rated Input Voltage	3 V/DC
Length	86 mm	Control	RF-Smart
Width	86 mm	Channels	1, 2, 3, 4, 5
Height	16 mm		

Article	Price
843513 ☐	€ 55.95





DEKO-LIGHT RF-SMART RF WALL-MOUNTED REMOTE CONTROL, 4 ZONES, 230 V, SINGLE/CCT/RGB/RGBW/RGB+CCT

- Wall-mounted remote control for fixed installation
- Dimmable brightness
- Adjustable colour saturation and colour temperature, if necessary
- 16 million adjustable colours, if necessary
- Automatic program and program speed can be controlled
- Separate white light button
- Up to four different control zones
- Range approx. 30 m
- Simple operation
- Installation on 68 mm single switch box
- 230 V/AC mains operation
- Low power consumption
- Control of single/CCT/RGB/RGBW/RGB+CCT components

Housing	Plastic	Rated Input Voltage	100-240 V/AC
Length	86 mm	Control	RF-Smart
Width	86 mm	Channels	1, 2, 3, 4, 5
Height	9 mm		

Article	Price
843522 ☐	€ 59.95






DEKO-LIGHT RF-SMART RF WALL-MOUNTED REMOTE CONTROL, 8 ZONES, SINGLE/CCT/RGB/RGBW/RGB+CCT

- Dimmable brightness
- Adjustable colour saturation and colour temperature, if necessary
- 16 million adjustable colours, if necessary
- Automatic program and program speed can be controlled
- Separate white light button
- Up to eight different control zones
- Range approx. 30 m
- Delayed switch-off function [60 s]
- Simple commissioning
- Battery-operated with 2x AAA [not included in the scope of delivery]
- Numerous installation options [68 mm switch socket for operating with optional 230 V power supply]
- Low power consumption
- Control of single/CCT/RGB/RGBW/RGB+CCT components

Housing	Plastic	Rated Input Voltage	3 V/DC
Length	146 mm	Control	RF-Smart
Width	106 mm	Channels	1, 2, 3, 4, 5
Height	20 mm		

Article	Price
843514 	€ 87.95



Accessories

872144 RF-smart, 230 V power supply for 8-zone wall-mounted remote control (3 V DC)

€ 13.95




DEKO-LIGHT RF-SMART RF-REPEATER

- Extends the range of an RF remote control by up to 30 m
- Supports up to 12 remote controls and/or 12 zones simultaneously
- Suitable for outdoor and indoor use
- Incl. 1 m connecting cable with IP44 mains plug
- Compatible with all RF-smart remote controls

Housing	Plastic	Height	34 mm
Length	103 mm	Rated Input Voltage	100-240 V/AC
Width	34 mm	Control	RF-Smart

Article	Price
843507 ☐	€ 27.95





DEKO-LIGHT RF-SMART PIR MOTION DETECTOR

- Can be rotated/swivelled 360°
- Self-adhesive magnetic holder included in the scope of delivery
- Very simple installation and operation
- Detection angle: 120°
- Detection range: 1-7 m
- RF range: approx. 30 m
- Switches on all RF-smart dimmers, lights/lamps (even when combined with other RF-smart remote controls)
- Motion detector can switch several dimmers, lights/lamps at the same time
- Controls the night light mode of all RF-smart dimmers, lights/lamps (843512 required for programming)
- Preset switching time and daylight threshold value
- Switching time can be adjusted (843512 required for programming)
- Daylight threshold value can be adjusted (843512 required for programming)
- Battery-operated with 1x CR123A [not included in the scope of delivery]
- Low power consumption



Housing	Plastic	Rated Input Voltage	3 V/DC
Height	56 mm	Control	RF-Smart
Ø	49 mm	Channels	1

ArticlePrice

843527  € 30.95



Accessories

843528	Photo battery, CR 123 A, lithium 3 V / 1600 mAh
843503	RF-smart, Triac dimmer, 230 V, 300 W, IP20
843504	RF-smart, Triac dimmer, 230 V, 300 W, IP67
843505	RF-smart, LED dimmer 5-in-1, 5 channel, 12-48 V, 20 A, IP20
843506	RF-smart, LED dimmer 5-in-1, 5 channel, 12-48 V, 20 A, IP67
843532	RF-smart, GU10, Zigbee, 4 W, RGB+2700-6500 K, 25 Degree
843533	RF-smart, E27, Zigbee, 6 W, RGB+2700-6500 K, 220 Grad
843534	RF-smart, E27, Zigbee, 12 W, RGB+2700-6500 K, 220 Grad
843518	RF-smart, Flood, 230 V, 30 W, RGB+CCT, IP65
843519	RF-smart, Flood, 230 V, 50 W, RGB+CCT, IP65
843520	RF-smart, Flood, 230 V, 100 W, RGB+CCT, IP65
843521	RF-smart, Spot, 230 V, 25 W, RGB+CCT, IP65
843530	Eventus RF-smart, 30W, RF+Zigbee, RGB/CCT, white
843531	Eventus RF-smart, 30W, RF+Zigbee, RGB/CCT, black

	€ 7.95
	€ 55.95
	€ 71.95
	€ 55.95
	€ 87.95
	€ 37.95
	€ 37.95
	€ 51.95
	€ 199.95
	€ 279.95
	€ 439.95
	€ 191.95
	€ 159.95
	€ 159.95



RF-SMART DMX GATEWAY

- RF gateway for operation on standard DMX controllers
- Easy to couple DMX systems to the RF-smart system
- Controls all RF-smart dimmers, lights/lamps (even when combined with other RF-smart remote controls)
- DMX start address can be adjusted via menu keys
- Status LED
- Up to 16 differently controllable zones of 1-5 channels
- Suitable for single/CCT/RGB/W+CCT components
- Occupies 80 DMX channels (regardless of actual channel usage)
- Power supply via supplied USB cable (USB power adapter 5 VDC not included in the scope of delivery)
- Does not support the RF-smart repeater function
- RF range: approx. 30 m

Housing	Plastic	Power	2.5 W
Length	188 mm	Rated Input Voltage	5 V/DC
Width	47 mm	Control	RF-Smart
Height	23 mm	Channels	1, 2, 3, 4, 5

Article	Price
843529 	€ 47.95



Accessories

930887	USB-A plug-in power supply 5 V DC, 1,000 mA, black
843503	RF-smart, Triac dimmer, 230 V, 300 W, IP20
843504	RF-smart, Triac dimmer, 230 V, 300 W, IP67
843505	RF-smart, LED dimmer 5-in-1, 5 channel, 12-48 V, 20 A, IP20
843506	RF-smart, LED dimmer 5-in-1, 5 channel, 12-48 V, 20 A, IP67
843532	RF-smart, GU10, Zigbee, 4 W, RGB+2700-6500 K, 25 Degree
843533	RF-smart, E27, Zigbee, 6 W, RGB+2700-6500 K, 220 Grad
843534	RF-smart, E27, Zigbee, 12 W, RGB+2700-6500 K, 220 Grad
843518	RF-smart, Flood, 230 V, 30 W, RGB+CCT, IP65
843519	RF-smart, Flood, 230 V, 50 W, RGB+CCT, IP65
843520	RF-smart, Flood, 230 V, 100 W, RGB+CCT, IP65
843521	RF-smart, Spot, 230 V, 25 W, RGB+CCT, IP65
843530	Eventus RF-smart, 30W, RF+Zigbee, RGB/CCT, white
843531	Eventus RF-smart, 30W, RF+Zigbee, RGB/CCT, black

	€ 6.95
	€ 55.95
	€ 71.95
	€ 55.95
	€ 87.95
	€ 37.95
	€ 37.95
	€ 51.95
	€ 199.95
	€ 279.95
	€ 439.95
	€ 191.95
	€ 159.95
	€ 159.95



CASAMBI BLUETOOTH CBU-TED | 230 V SWITCHING/DIMMING

- suitable for R loads [incandescent bulb, high-voltage halogen]
- suitable for C loads [dimmable high-voltage LED, electrical power supply units]
- Power in switching range: incandescent bulb, high-voltage halogen, high-voltage LED, electrical ballasts: max. 150 W
- Output in dimming range: dimmable high-voltage LED, electrical ballasts: max. 50 W/ max. two components
- suitable for 230 V AC lights
- Install the Casambi module in a distributor box, suspended ceiling or similar
- Control and configuration via smartphone app

Housing	Plastic	Power	1.0-50 W
Length	40.4 mm	Rated Input Voltage	220-240 V/AC
Width	36.3 mm	Control	Casambi
Height	14 mm	Channels	1

Article		Price
843008	☐	€ 115.95



CASAMBI BLUETOOTH CBU-ASD | DALI/0-10 V | 1-10 V

- Module generates either DALI, 0-10 V or 1-10 V control signal
- Control signal for each ballast unit or power supply unit
- Install the Casambi module in a distributor box, suspended ceiling or similar
- Control and configuration via smartphone app

Housing	Plastic	Rated Input Voltage	220-240 V/AC
Length	56.5 mm	Control	Casambi
Width	35.8 mm	Channels	1
Height	22.3 mm		

Article		Price
843011	☐	€ 119.95





CASAMBI BLUETOOTH CBU-PWM4 | LED ONE-TO FOUR-CHANNEL DIMMER

- Module suitable for controlling 12 V/24 V LED strips
- One to four channels [WW, CW, WW-CW, RGB, RGBW]
- Power: 144 W at 24 V, 72 W at 12 V
- Install the Casambi module in a distributor box, suspended ceiling or similar
- Control and configuration via smartphone app

Housing	Plastic	Output Current	6 A
Length	72.6 mm	Rated Input Voltage	12-24 V/DC
Width	30 mm	Control	Casambi
Height	18 mm	Channels	1, 2, 3, 4

Article		Price
843037	☐	€ 143.95



CASAMBI BLUETOOTH WALL-MOUNTED CONTROLLER XPRESS

- Bluetooth wall controller compatible with Casambi system
- Installation with screws or adhesive tape
- No wiring required
- Battery operation [3 V button cell]
- Configured via smartphone app

Housing	Plastic	Height	12 mm
Length	90 mm	Rated Input Voltage	3 V/DC
Width	90 mm	Control	Casambi

Article		Price
843049	☒	€ 319.95
843050	☐	€ 319.95





DEKO-LIGHT MULTI-DIMMER 4,
4-CHANNEL 3-IN-1 CONTROL/PWM DIMMER

- Easy programming of all settings incl. memory function
- 3-IN-1 control DMX / automatic / manual
- Use as 1, 2, 3, 4 channel dimmer, individually dimmable
- 24 colour change programmes pre-installed [automatic mode]
- Flicker-free 2kHz for image and video recordings
- DMX signal / master-slave pluggable via CAT5

Performance:

- 4x 60W [240W] at 12V, 4x 120W [480W] at 24V, 4x 240W [960W] at 48V
- max. 20A [4x 5A per channel]

Housing	Metal	Output Current	20 A
Length	116 mm	Rated Input Voltage	12-48 V/DC
Width	57 mm	Channels	1, 2, 3, 4
Height	26.8 mm		

Article	Price
843279 	€ 91.95



DEKO-LIGHT R-DMX 3+1

- complies with DMX 512/1990, RDM protocol/2009
- supports automatic DMX address assignment
- incl. DIN rail adapter and 2 m CAT5 cable [RJ45]

• flicker-free

Performance:

- 4x 48W [192W] at 12V, 4x 96W [384W] at 24V
- max. 16A [4x 4A per channel]

Housing	Metal	Output Current	16 A
Length	120 mm	Rated Input Voltage	12-24 V/DC
Width	43 mm	Channels	1, 2, 3, 4
Height	23 mm		

Article	Price
843273 	€ 69.95





DALI TRIAC DIMMER

- Can be controlled using DALI1/DALI2, DT6, one channel
- Can alternatively be controlled using push-dim button [8-230 V/AC]
- Dimmable brightness/trailing-edge phase dimmers
- Adjustable minimum brightness [push-dim only]
- Optimal for extending DALI systems or installing in Triac dimmable lighting due to its compact size
- LED output [C load] max. 200 W/230 V/max. 10x LM or ECG
- Halogen output [R load] 400 W/230 V, no limit on the number of lamps
- Power consumption at DALI bus: max. 2 mA

Housing	Plastic	Output Current	1.8 A
Length	45.5 mm	Rated Input Voltage	100-240 V/AC
Width	45.5 mm	Control	DALI 1 / DT6, DALI 2 / DT6, Push-Dim
Height	20.3 mm	Channels	1
Power	1.0-400 W		

Article Price

843340 ☐ € 59.95



Accessories

930942 DIN rail/mounting adapter for Dali Triac dimmer



€ 1.45



DEKO-LIGHT DALI LED PWM DIMMER 12-48 V, 1/2 CHANNEL

- DT6 = occupies 2 Dali channels
- 2x 1-channel mode (WW/CW) or 1x 2 channel mode (WW-CW, CCT)
- Can be dimmed 0-100 %, overload protection, reverse polarity protection
- Flicker-free, suitable for videos (PWM 2 kHz)
- For 12 V-48 V DC (CV) LED strips/lights
- Output power: 2x 8 A = 16 A

Housing	Plastic	Rated Input Voltage	12-48 V/DC
Length	167 mm	Control	DALI 1 / DT6, DALI 2 / DT6
Width	51 mm	Channels	1, 2
Height	23 mm		
Output Current	16 A		

Article		Price
843341	☐	€ 67.95



DEKO-LIGHT DALI DT8 LED PWM DIMMER 12-48 V, 2 CHANNEL

- DT8 = occupies 1 Dali channel
- 1x 2-channel mode (WW-CW, CCT)
- Can be dimmed 0-100 %, overload protection, reverse polarity protection
- Flicker-free, suitable for videos (PWM 2 kHz)
- For 12 V-48 V DC (CV) LED strips/lights
- Output power: 2x 8 A = 16 A

Housing	Plastic	Rated Input Voltage	12-48 V/DC
Length	167 mm	Control	DALI 1 / DT8, DALI 2 / DT8
Width	51 mm	Channels	2
Height	23 mm		
Output Current	16 A		

Article		Price
843342	☐	€ 67.95






DEKO-LIGHT DALI LED PWM DIMMER 12-48 V, 3/4 CHANNEL

- DT6 = occupies 4 Dali channels
- 1x 3-channel mode (RGB) or 1x 4-channel mode (RGBW)
- Can be dimmed 0-100 %, overload protection, reverse polarity protection
- Flicker-free, suitable for videos (PWM 2 kHz)
- For 12 V-48 V DC (CV) LED strips/lights
- Output power: 4x 4 A = 16 A

Housing	Plastic	Rated Input Voltage	12-48 V/DC
Length	167 mm	Control	DALI 1 / DT6, DALI 2 / DT6
Width	51 mm	Channels	1, 2, 3, 4
Height	23 mm		
Output Current	16 A		

Article Price

843343 ☐ € 75.95



DEKO-LIGHT DALI DT8 LED PWM DIMMER 12-48 V, 4 CHANNEL

- DT8 = occupies 1 Dali channel
- 1x 4-channel mode (RGBW)
- Can be dimmed 0-100 %, overload protection, reverse polarity protection
- Flicker-free, suitable for videos (PWM 2 kHz)
- For 12 V-48 V DC (CV) LED strips/lights
- Output power: 4x 4 A = 16 A

Housing	Plastic	Rated Input Voltage	12-48 V/DC
Length	167 mm	Control	DALI 1 / DT8, DALI 2 / DT8
Width	51 mm	Channels	4
Height	23 mm		
Output Current	16 A		

Article Price

843344 ☐ € 75.95





ILLUMINANTS

860	MR16 / GU53
861	G9 - GU10
864	E27
867	GX53





page 860



page 860



page 861



page 861



page 862



page 862



page 864



page 864



page 867





LEDVANCE LED MR16

Housing	Glass	Ø	50 mm
Light Beam Angle	36 Degree	Rated Input Voltage	12 V/AC/DC
Life Time L70 / B50	15000 h	CRI (Ra)	80



Article	Housing Color	Colour Temperature	Luminous Flux	Power	Power Consumption	Height	EEL	Price
180368	Colourless	3000 K	210 lm	2.0 W	2 kWh/1000h	44 mm		€ 7.95
180748	Colourless	3000 K	345 lm	3.4 W	4 kWh/1000h	44 mm		€ 7.95
180309	Colourless	4000 K	210 lm	2.1 W	3 kWh/1000h	46 mm		€ 7.95
180318	Colourless	4000 K	345 lm	3.4 W	4 kWh/1000h	44 mm		€ 7.95

MR16 GU5,3

CV

IP20

1 CH

LEDVANCE LED MR16 DIMMABLE

Housing	Glass	Rated Input Voltage	12 V/AC/DC
Light Beam Angle	36 Degree	CRI (Ra)	90
Life Time L70 / B50	25000 h	Control	Dimmable via optional power supply unit
Height	44 mm		
Ø	50 mm		



Article	Housing Color	Colour Temperature	Luminous Flux	Power	Power Consumption	EEL	Price
180746	Colourless	3000 K	230 lm	2.2 W	3 kWh/1000h		€ 10.95
180749	Colourless	3000 K	345 lm	3.4 W	4 kWh/1000h		€ 11.95
180751	Colourless	3000 K	621 lm	6.1 W	7 kWh/1000h		€ 21.95
180264	Colourless	4000 K	230 lm	3.4 W	4 kWh/1000h		€ 11.95
180750	Colourless	4000 K	345 lm	3.4 W	4 kWh/1000h		€ 11.95

MR16 GU5,3

CV

IP20


1 CH

LEDVANCE LED P PIN G9

Housing	Plastic	Life Time L70 / B50	15000 h
Colour Temperature	2700 K	Rated Input Voltage	220-240 V/AC
Light Beam Angle	300 Degree	CRI (Ra)	80



Article	Housing Color		Luminous Flux	Power	Power Consumption	Height	Ø	EEL	Price
180295	Colourless		200 lm	1.9 W	2 kWh/1000h	43 mm	14 mm		€ 5.95
180287	Colourless		320 lm	2.6 W	3 kWh/1000h	43 mm	14 mm		€ 7.95
180286	Colourless		470 lm	4.2 W	5 kWh/1000h	49 mm	18 mm		€ 10.95




NEW

LEDVANCE LED GU10

Housing	Glass	Life Time L70 / B50	15000 h
Colour Temperature	2700 K	Height	54 mm
Luminous Flux	350 lm	Ø	50 mm
Power	3.7 W	Rated Input Voltage	220-240 V/AC
Light Beam Angle	36 Degree	CRI (Ra)	80
Power Consumption	4 kWh/1000h		



Article	Housing Color		Price
180752	Silver		€ 5.95



5-year guarantee

Benefit from the maximum quality promise:
All DEKO-LIGHT brand products come with a five-year manufacturer's guarantee.



PHILIPS MASTER VALUE LED GU10 DIMMABLE

Housing	Glass	Rated Input Voltage	220-240 V/AC
Height	54 mm	Control	Trailing-edge dimmer
Ø	50 mm	Channels	1



Article	Housing Color	Colour Temp.	Luminous Flux	Power	Light Beam Angle	Power Consump.	EEL	Price
180296	Silver	2700 K	270 lm	2.8 W	36 Degree	3 kWh/1000h		€ 7.95
180744	Silver	2700 K	345 lm	4.0 W	36 Degree	4 kWh/1000h		€ 8.95
180319	Silver	2700 K	355 lm	3.7 W	60 Degree	4 kWh/1000h		€ 9.95
180317	Silver	3000 K	365 lm	3.7 W	36 Degree	4 kWh/1000h		€ 11.95
180753	Silver	3000 K	365 lm	3.7 W	60 Degree	4 kWh/1000h		€ 9.95
180297	Silver	3000 K	575 lm	5.5 W	36 Degree	6 kWh/1000h		€ 13.95
180747	Silver	4000 K	380 lm	3.7 W	36 Degree	4 kWh/1000h		€ 11.95
180299	Silver	4000 K	380 lm	3.7 W	60 Degree	4 kWh/1000h		€ 11.95
180298	Silver	4000 K	575 lm	5.5 W	36 Degree	6 kWh/1000h		€ 13.95



OSRAM PARATHOM LED GU10 DIMMABLE

Housing	Glass	Height	52 mm
Colour Temperature	2700 K	Ø	50 mm
Luminous Flux	575 lm	Rated Input Voltage	220-240 V/AC
Power	6.1 W	CRI (Ra)	90
Light Beam Angle	60 Degree	Control	Trailing-edge dimmer
Power Consumption	7 kWh/1000h	Channels	1
Life Time L70 / B50	25000 h		



Article	Housing Color	Price
180745	Silver	€ 13.95



DEKO-LIGHT RF-SMART LAMP GU10 RGB+CCT WITH RF ZIGBEE CONTROL

- Dimmable brightness and colour saturation
- 16 million available colours and adjustable colour temperature
- 18 pre-installed automatic programs
- Program and remote control synchronisation when operating multiple RF-smart components [repeater function]
- Can be controlled with RF-smart wireless remote controls [2.4 GHz, range approx. 30 m, not included in the scope of delivery]
- Can be controlled with all controllers/apps compatible with Zigbee 3.0, such as Amazon Echo [Alexa], Google Assistant and Tuya [relevant gateway required, outdoor range up to 100 m]

Housing	Plastic	Height	57 mm
Colour Temperature	2700-6500 K	Ø	50 mm
Luminous Flux	300 lm	Rated Input Voltage	100-240 V/AC
Power	4 W	CRI (Ra)	80
Light Beam Angle	25 Degree	Control	RF-Smart, ZigBee 3.0
Power Consumption	4 kWh/1000h	Channels	5
Life Time L70 / B50	50000 h		

Article	Housing Color	Colour Temperature	Price
843532	☐ White	☒ RGB ☒ WW ☒ CW 2700-6500 K	€ 37.95



Accessories

843510	RF-smart, remote control, white, 1 zone, RGB/RGBW/RGB+CCT, IP20		€ 30.95
843511	RF-smart, remote control, black, 1 zone, RGB/RGBW/RGB+CCT, IP20		€ 30.95
843513	RF-smart, wall remote control, white, 3 V, 4 zones, single/CCT/RGB/W/+CCT		€ 55.95
843514	RF-smart, wall remote control, white, 8 zones, single/CCT/RGB/RGBW/RGB+CCT		€ 87.95
843522	RF-smart, wall remote control, white, 230 V, 4 zones, single/CCT/RGB/W/+CCT		€ 59.95
843523	RF-smart, Standard Remote, black, 3 zones, Single		€ 39.95
843524	RF-smart, Standard Remote, black, 3 zones, Single/CCT		€ 39.95
843525	RF-smart, Standard Remote, black, 3 zones, Single/CCT/RGB/RGBW/RGB+CCT		€ 39.95
843512	RF-smart, remote control, black, 8 zones, single/CCT/RGB/RGBW/RGB+CCT		€ 39.95
843527	RF-smart, PIR motion detector, white, 120deg/7m, 3V		€ 30.95
843529	RF-smart, DMX-Gateway, 5V DC, 16 Zonen Single/CCT/RGB/W/+CCT		€ 47.95




LEDVANCE LED RETROFIT E27 A60 DIMMABLE

Housing	Glass	Power Consumption	6 kWh/1000h
Colour Temperature	2700 K	Life Time L70 / B50	15000 h
Luminous Flux	806 lm	Rated Input Voltage	220-240 V/AC
Power	5.9 W	CRI (Ra)	80
Light Beam Angle	300 Degree	Control	Trailing-edge dimmer
Height	105 mm	Channels	1
Ø	60 mm		



Article	Housing Color	Price
180754	Colourless	€ 6.95




LEDVANCE LED CLASSIC E27 A75 DIMMABLE

Housing	Glass	Power Consumption	8 kWh/1000h
Colour Temperature	2700 K	Life Time L70 / B50	15000 h
Luminous Flux	1055 lm	Rated Input Voltage	220-240 V/AC
Power	7.5 W	CRI (Ra)	80
Light Beam Angle	360 Degree	Control	Trailing-edge dimmer
Height	105 mm	Channels	1
Ø	60 mm		



Article	Housing Color	Price
180277	Colourless	€ 10.95



Technical data sheet
New in the onlineshop: The technical data sheets offer even more information:
Light and energy data, light distribution curves, dimensional drawings and more.



DEKO-LIGHT RF-SMART LAMP E27 A60 RGB+CCT WITH RF ZIGBEE CONTROL

- Dimmable brightness and colour saturation
- 16 million available colours and adjustable colour temperature
- 18 pre-installed automatic programs
- Program and remote control synchronisation when operating multiple RF-smart components [repeater function]
- Can be controlled with RF-smart wireless remote controls [2.4 GHz, range approx. 30 m, not included in the scope of delivery]
- Can be controlled with all controllers/apps compatible with Zigbee 3.0, such as Amazon Echo [Alexa], Google Assistant and Tuya [relevant gateway required, outdoor range up to 100 m]

Housing	Plastic	Power Consumption	6 kWh/1000h
Luminous Flux	550 lm	Life Time L70 / B50	50000 h
Power	6 W	Rated Input Voltage	100-240 V/AC
Light Beam Angle	220 Degree	CRI (Ra)	80
Height	100 mm	Control	RF-Smart, ZigBee 3.0
Ø	57 mm	Channels	5

Article	Housing Color	Colour Temperature	Price
843533	☐ White	2700-6500 K	€ 37.95



Accessories

843510	RF-smart, remote control, white, 1 zone, RGB/RGBW/RGB+CCT, IP20		€ 30.95
843511	RF-smart, remote control, black, 1 zone, RGB/RGBW/RGB+CCT, IP20		€ 30.95
843513	RF-smart, wall remote control, white, 3 V, 4 zones, single/CCT/RGB/W/+CCT		€ 55.95
843514	RF-smart, wall remote control, white, 8 zones, single/CCT/RGB/RGBW/RGB+CCT		€ 87.95
843522	RF-smart, wall remote control, white, 230 V, 4 zones, single/CCT/RGB/W/+CCT		€ 59.95
843523	RF-smart, Standard Remote, black, 3 zones, Single		€ 39.95
843524	RF-smart, Standard Remote, black, 3 zones, Single/CCT		€ 39.95
843525	RF-smart, Standard Remote, black, 3 zones, Single/CCT/RGB/RGBW/RGB+CCT		€ 39.95
843512	RF-smart, remote control, black, 8 zones, single/CCT/RGB/RGBW/RGB+CCT		€ 39.95
843527	RF-smart, PIR motion detector, white, 120deg/7m, 3V		€ 30.95
843529	RF-smart, DMX-Gateway, 5V DC, 16 Zonen Single/CCT/RGB/W/+CCT		€ 47.95



DEKO-LIGHT RF-SMART LAMP E27 MAX RGB+CCT
WITH RF ZIGBEE CONTROL

- Dimmable brightness and colour saturation
- 16 million available colours and adjustable colour temperature
- 18 pre-installed automatic programs
- Program and remote control synchronisation when operating multiple RF-smart components [repeater function]
- Can be controlled with RF-smart wireless remote controls [2.4 GHz, range approx. 30 m, not included in the scope of delivery]
- Can be controlled with all controllers/apps compatible with Zigbee 3.0, such as Amazon Echo [Alexa], Google Assistant and Tuya [relevant gateway required, outdoor range up to 100 m]

Housing	Plastic	Power Consumption	12 kWh/1000h
Luminous Flux	1100 lm	Life Time L70 / B50	50000 h
Power	12 W	Rated Input Voltage	100-240 V/AC
Light Beam Angle	220 Degree	CRI (Ra)	80
Height	147 mm	Control	RF-Smart, ZigBee 3.0
Ø	70 mm	Channels	5

Article	Housing Color	Colour Temperature	Price
843510	☐ White	☒ RGB ☐ WW ☐ CW 2700-6500 K	€ 51.95
E27 IP20 5 CH A t G F			

Accessories

843510	RF-smart, remote control, white, 1 zone, RGB/RGBW/RGB+CCT, IP20
843511	RF-smart, remote control, black, 1 zone, RGB/RGBW/RGB+CCT, IP20
843513	RF-smart, wall remote control, white, 3 V, 4 zones, single/CCT/RGB/WW/+CCT
843514	RF-smart, wall remote control, white, 8 zones, single/CCT/RGB/RGBW/RGB+CCT
843522	RF-smart, wall remote control, white, 230 V, 4 zones, single/CCT/RGB/W/+CCT
843523	RF-smart, Standard Remote, black, 3 zones, Single
843524	RF-smart, Standard Remote, black, 3 zones, Single/CCT
843525	RF-smart, Standard Remote, black, 3 zones, Single/CCT/RGB/RGBW/RGB+CCT
843512	RF-smart, remote control, black, 8 zones, single/CCT/RGB/RGBW/RGB+CCT
843527	RF-smart, PIR motion detector, white, 120deg/7m, 3V
843529	RF-smart, DMX-Gateway, 5V DC, 16 Zonen Single/CCT/RGB/W+CCT

	€ 30.95
	€ 30.95
	€ 55.95
	€ 87.95
	€ 59.95
	€ 39.95
	€ 39.95
	€ 39.95
	€ 39.95
	€ 30.95
	€ 47.95

ISOLED LED GX53

Housing	Aluminium	Height	28 mm
Power	6 W	Ø	75 mm
Light Beam Angle	120 Degree	Rated Input Voltage	220-240 V/AC
Power Consumption	6 kWh/1000h	CRI (Ra)	80
Life Time L70 / B50	25000 h		



Article	Housing Color	Colour Temperature	Luminous Flux	Price
180196	☐ White	☒ 3000 K	500 lm	€ 17.95
180195	☐ White	☒ 4000 K	525 lm	€ 17.95

GX53

IP20

1 CH

A

↑

G

D





KEBA CE
M630 IP66 Max depth 57
Max 2205 268 450VAC
Max 3225
The screws of cover are tightened
with 10 Nm in IP test

	ACCESSORIES
872	indoor
875	outdoor
883	chemical products



page 872



page 873



page 874



page 874



page 875



page 875



page 876



page 881




page 882



page 883

SAFETY SPACER

- For safe installation of downlights in ceilings with insulating material
- Creates the necessary clearance around the light to enable better air circulation
- Observe the installation requirements of the specific light.
- For ceiling installation rings from dia. 62 to 90 mm



Housing	Plastic	Ø	62 mm
Height	80 mm		

Article	Housing Color	Price
829063	 Black	€ 3.45

SOCKET GU5,3

- Heat-resistant connecting cable
- Ceramic fitting



Housing	Ceramic	Power	35 W
Ø	17 mm	Secondary Connection End	Open cables
Rated Input Voltage	12 V/AC/DC	Connection Type	Open cables


Article	Housing Color	Length	Height	Secondary Cable Length	Price
100200	☐ White		150 mm	0.15 m	€ 0.75
100250	☐ White	500 mm	500 mm	0.5 m	€ 1.25



SOCKET GU10 (PROTECTION CLASS II)

Housing	Ceramic	Power	35 W
Height	150 mm	Primary Cable Length	15 cm
Ø	28 mm	Primary Connection End	With free strand / conductor ends
Rated Input Voltage	220-240 V/AC		

Article	Housing Color	Price
100202	☐ White	€ 1.55




SOCKET GU10 (SAFETY CLASS I)

- With spacer and connection box
- Separate connection for protective conductors
- When using installation rings, VDE regulations require a screw connection between the spacer and installation ring



Housing	Ceramic	Primary Cable Length	10 cm
Rated Input Voltage	220-240 V/AC	Primary Connection End	Screw terminal
Power	35 W		

Article	Housing Color	Price
100204	☐ White	€ 3.25



DEKO-LIGHT QUICK CONNECTION BOX 2-WAY 230 V

- Fast through-wiring of power supplies or lamps
- 3-pin quick terminal for cables from 0.5 to 1.5 mm²
- 15 cm pre-installed 3-pin cable for connecting SKI/SKII power supply units/lamps
- Quick-action closure secured with additional screw
- For inserting into ceilings with a round cut-out from 68 mm and a 25 mm ceiling cavity

Housing	Plastic	Rated Input Voltage	220-240 V/AC
Length	80 mm	Rated Current	16 A
Width	40 mm	Primary Connection End	Connection box IP20
Height	25 mm	Secondary Connection End	Open cables

Article	Housing Color	Price
930694	☒ Black	€ 4.95




TRIAC-DIMMER TRAILING EDGE

- Suitable for dimming:
- **R loads (incandescent bulb) 10-350 W**
- **C loads (electrical ballasts) 10-350 W**
- **Max. five ballasts**
- **Adjustable minimum load/brightness**
- **Perfectly matched to DEKO-LIGHT power supply units**
- **Suitable for 68 mm flush-mounted/cavity wall sockets**



Housing	Plastic	Power	355 W
Length	83.5 mm	Control	Trailing-edge dimmer
Width	83.5 mm	Rated Current	1.6 A
Height	43.5 mm	Connection Type	Clamp
Rated Input Voltage	220-240 V/AC		

Article	Housing Color	Price
930060	White	€ 53.95



OVERVOLTAGE PROTECTION WITH CONTROL DISPLAY

- Compact protection of lights in the event of problems with the mains supply
- Prevents premature failure
- In the event of a fault, the overvoltage protection trips, protecting the light by disconnecting it from the mains supply
- Control LED to indicate the operating status
- Suitable for single-phase, non-dimmable lights
- With mounting bracket for installation in light fittings or junction boxes



Housing	Plastic	Rated Current	10 A
Length	37 mm	Primary Connection End	With free strand / conductor ends
Width	30 mm	Secondary Connection End	Open cables
Height	20 mm		
Rated Input Voltage	230-277 V/AC		

Article	Housing Color	Price
843055	Black	€ 15.95





GROUND SPIKE WITH THREADED BUSHING

- Robust design
- For anchoring surface-mounted spotlights in soil

Article	Housing Color	Housing	Height	Ø	Price
930426	 Black	Aluminium	170 mm	33 mm	€ 7.95
930427	 Black	Aluminium	219 mm	43.8 mm	€ 9.95
700229	 Black	Plastic	160 mm	43 mm	€ 3.95
730349	 Black	Plastic	210 mm	45 mm	€ 5.45
700230	 Black	Plastic	210 mm	50 mm	€ 3.95



WALL BRACKET/DISPLAY ARM

- Robust housing
- Load capacity: max. 4.5 kg
- Ideal for illuminating advertising boards on façades
- Accessories for façade lighting
- Supplied without installation materials due to wide range of possible applications

Housing	Metal	Width	150 mm
Length	800 mm	Height	100 mm

Article	Housing Color	Price
930659	 Black	€ 47.95

WEIPU DISTRIBUTOR BOX

- for wiring 12V/24V/48V DC outdoor components
- reverse polarity protected
- Robust design
- 2 socket outlets



Housing	Plastic	Height	38 mm
Length	57 mm	Rated Input Voltage	12-48 V/DC
Width	57 mm	Rated Current	8.5 A



Article	Secondary Connection End	Connection Type	Price
730300	WEIPU socket 2-pole	WEIPU plug 2-pole	€ 51.95
730301	WEIPU socket 4-pole	WEIPU plug 4-pole	€ 54.95
940010	WEIPU socket 5-pole	WEIPU plug 5-pole	€ 62.95





WEIPU HQ SOCKET / PLUG | 2-PIN

Housing	Plastic	Rated Input Voltage	12-48 V/DC
Height	65 mm	Rated Current	8.5 A
Ø	27 mm		

Article	Connection Type	Price
940060	WEIPU plug 2-pole	€ 10.95
940058	WEIPU socket 2-pole	€ 10.95
940059	WEIPU socket 2-pole	€ 10.95



WEIPU HQ SOCKET / PLUG | 4-PIN

Housing	Plastic	Rated Input Voltage	12-48 V/DC
Height	65 mm	Rated Current	8.5 A
Ø	27 mm		

Article	Connection Type	Price
940062	WEIPU plug 4-pole	€ 11.95
940061	WEIPU socket 4-pole	€ 11.95
940063	WEIPU socket 4-pole	€ 11.95



WEIPU HQ SOCKET / PLUG | 5-PIN

Housing	Plastic	Rated Input Voltage	12-48 V/DC
Height	65 mm	Rated Current	8.5 A
Ø	27 mm		

Article	Connection Type	Price
940057	WEIPU plug 5-pole	€ 12.95
940056	WEIPU socket 5-pole	€ 12.95





WEIPU HQ FEEDER CABLE | SOCKET 2-PIN

Housing	Plastic	Rated Current	8.5 A
Ø	27 mm	Connection Type	WEIPU socket 2-pole
Rated Input Voltage	12-48 V/DC		



Article	Height	Price
940037	1000 mm	€ 17.95
940038	3000 mm	€ 23.95
940039	5000 mm	€ 29.95



WEIPU HQ FEEDER CABLE | SOCKET 4-PIN

Housing	Plastic	Rated Current	8.5 A
Ø	27 mm	Connection Type	WEIPU socket 4-pole
Rated Input Voltage	12-48 V/DC		



Article	Height	Price
940033	1000 mm	€ 21.95
940034	3000 mm	€ 33.95
940035	5000 mm	€ 44.95



WEIPU HQ FEEDER CABLE | SOCKET | 5-PIN

Housing	Plastic	Rated Current	8.5 A
Ø	27 mm	Connection Type	WEIPU socket 5-pole
Rated Input Voltage	12-48 V/DC		



Article	Height	Price
940029	1000 mm	€ 25.95
940030	3000 mm	€ 37.95
940031	5000 mm	€ 47.95





WEIPU HQ CONNECTION CABLE | 2-PIN

Housing	Plastic	Rated Current	8.5 A
Ø	27 mm	Secondary Connection End	WEIPU socket 2-pole
Rated Input Voltage	12-48 V/DC	Connection Type	WEIPU plug 2-pole



Article	Height	Price
940049	1000 mm	€ 27.95
940050	3000 mm	€ 33.95
940051	5000 mm	€ 39.95



WEIPU HQ CONNECTION CABLE | 4-PIN

Housing	Plastic	Rated Current	8.5 A
Ø	27 mm	Secondary Connection End	WEIPU socket 4-pole
Rated Input Voltage	12-48 V/DC	Connection Type	WEIPU plug 4-pole



Article	Height	Price
940045	1000 mm	€ 33.95
940046	3000 mm	€ 45.95
940047	5000 mm	€ 54.95



WEIPU HQ CONNECTION CABLE | 5-PIN

Housing	Plastic	Rated Current	8.5 A
Ø	27 mm	Secondary Connection End	WEIPU socket 5-pole
Rated Input Voltage	12-48 V/DC	Connection Type	WEIPU plug 5-pole



Article	Height	Price
940041	1000 mm	€ 37.95
940042	3000 mm	€ 48.95
940043	5000 mm	€ 57.95





MULTI OUTDOOR CABLE CONNECTOR | CONNECTION SLEEVE

- Watertight M25 cable glands
- For two cables measuring 4-14 mm
- For two to five wires measuring 0.5-4 mm²
- Adapter sleeves included in scope of delivery

Housing	PA 6.6 - Polyamide 6.6	Height	32.56 mm
Length	112.53 mm	Rated Input Voltage	12-450 V/AC
Width	29.5 mm	Rated Current	24 A

Article	Housing Color	Price
930571	■ Black, Yellow	€ 7.95



MULTI OUTDOOR Y-SHAPED CABLE CONNECTOR | CONNECTION SLEEVE

- Waterproof M25 cable glands
- For three cables measuring 4-14 mm (adapter sleeves included in the scope of delivery)
- For two to three wires measuring 0.5-4 mm²

Housing	PA 6.6 - Polyamide 6.6	Height	32.56 mm
Length	139.71 mm	Rated Input Voltage	12-450 V/AC
Width	71.88 mm	Rated Current	24 A

Article	Housing Color	Price
930573	■ Black, Yellow	€ 8.95





MULTI OUTDOOR CABLE DISTRIBUTOR TWO-WAY

- For wiring low-voltage and 230 V outdoor components
- Robust housing
- For wires measuring 0.5-2.5 mm²
- For two cables measuring 5-12 mm
- Versatile thanks to the adapter sleeves included in the scope of delivery
- Watertight M20 cable glands
- Cover: Quick-action coupling (screwless)



Housing	PA 6.6 - Polyamide 6.6	Rated Input Voltage	12-450 V/AC
Height	46.31 mm	Rated Current	24 A
Ø	65.33 mm		

Article	Housing Color	Price
930578	Black	€ 5.95



MULTI OUTDOOR CABLE DISTRIBUTOR TWO-WAY

- Watertight M20 cable glands
- For two cables measuring 5-12 mm
- Adapter sleeves included in scope of delivery
- For wires measuring 0.5-2.5 mm²
- Screwed cover (screws included in scope of delivery)



Housing	PA 6.6 - Polyamide 6.6	Height	42 mm
Length	125 mm	Rated Input Voltage	12-450 V/AC
Width	70 mm	Rated Current	24 A

Article	Housing Color	Price
930712	Black	€ 7.95





MULTI OUTDOOR CABLE DISTRIBUTOR FOUR-WAY

- Watertight M25 cable glands
- For two to four cables measuring 4-14 mm
- Adapter sleeves and two blanking plugs included in scope of delivery
- For wires measuring 0.5-4.0 mm²
- Screwed cover (screws included in scope of delivery)



Housing	PA 6.6 - Polyamide 6.6	Height	35.3 mm
Length	112.54 mm	Rated Input Voltage	12-450 V/AC
Width	93.3 mm	Rated Current	24 A

Article	Housing Color	Price
930575	Black	€ 9.95

IP68
max.2m



MULTI OUTDOOR CABLE DISTRIBUTOR FOUR-WAY

- Watertight M25 cable glands
- For two to four cables measuring 4-14 mm
- Adapter sleeves and two blanking plugs included in scope of delivery
- For wires measuring 0.5-4.0 mm²
- Screwed cover (screws included in scope of delivery)



Housing	PA 6.6 - Polyamide 6.6	Height	35.3 mm
Length	112.54 mm	Rated Input Voltage	12-450 V/AC
Width	93.3 mm	Rated Current	24 A

Article	Housing Color	Price
930735	Black	€ 15.95

IP68
max.2m



MULTI OUTDOOR CABLE DISTRIBUTORTEN-WAY

- Watertight M25 cable glands
- For two to ten cables measuring 4-14 mm
- Adapter sleeves and eight blanking plugs included in scope of delivery
- For wires measuring 0.5-4 mm²
- Screwed cover (screws included in scope of delivery)
- For wiring low-voltage and 230 V outdoor components
- Versatile thanks to the adapter sleeves included in the scope of delivery



Housing	PA 6.6 - Polyamide 6.6	Height	49.1 mm
Length	182.95 mm	Rated Input Voltage	12-450 V/AC
Width	135.3 mm	Rated Current	24 A

Article	Housing Color	Price
930574	Black	€ 31.95

IP68
max.2m



GEL ADHESIVE FOR BONDING END CAPS

- Cyanoacrylate instant adhesive
- 3 g tube
- Strong initial bond
- Excellent adhesion to almost all surfaces, such as metals, steel, stainless steel, zinc-plated steel, aluminium, plastics (e.g. ABS, GFRP, hard PC) and ceramic materials
- Curing time: 8-12 hours
- Observe the safety and application instructions



Length	60 mm	Height	10 mm
Width	20 mm		

Article	Price
930593	€ 4.95

ASSEMBLY ADHESIVE

- Bond+Seal Power
- 310 ml cartridge
- Heavy-duty, elastic 1-component structural adhesive
- Excellent adhesion to almost all surfaces, such as metals, steel, stainless steel, galvanised steel, aluminium, plastics (e.g. ABS, GFRP, hard PVC) or ceramic materials
- UV-resistant
- Approved for use with foodstuffs according to NSF (NSF, P1 registered: 136996)
- High degree of initial strength
- Can be painted over with all commercially available paint systems (except alkyd resin paints)



Height	230 mm	Ø	49 mm
--------	--------	---	-------

Article	Price
930105	€ 28.95

NATURAL STONE SEALANT

- 310 ml cartridge
- Suitable for bonding profile covers and for use in wet rooms
- Does not attack the surface of LEDs/strips
- Permanently elastic
- Highly resistant to weathering, UV and ageing and excellent colour fastness
- Ideal for high loads outdoors



Height	230 mm	Ø	49 mm
--------	--------	---	-------

Article	Price
930104	€ 31.95

ELECTRIC CHARACTERISTICS

CV

constant voltage

CC

constant current

SELV

safety extra-long voltage

flicker free

solar panel

USB charging socket

battery operation

LAMP

E14

base of lamp

FUNCTIONALITY

swivel-mounted +
rotatable and swivel-mounted + rotatable

radiation direction

SURFACE

NANO coating IP XX [see product description]
lotus effect: Water rolls off and takes all dirty surface
particles with it.

surface paintable /
individual design

CONTROL

movement sensor [IR / HF]

presence detector

DMX control

dimmable

1 CH

4-6 CH

number of channels

emergency power supply

SAFETY

IP65

IP protection class

walkable

passable

safety lamp control gear

components may be installed on fixtures of materials,
the fire behavior of which is not always known.


max. surface temperature of lamp control gear

lights with limited surface temperature

protection class I

protection class II
[protective isolation]


protection class III
[protective low voltage]



light colours / channels




selectable light colour



human centric lighting




dim to warm



Colour rendering index RA



colour consistency SDCM




UGR



power switch




phase switch



tool-free installation



corridor function



control type




BEG eligible




suitable for VDU workstations



passable




Through-wiring possible



light can be switched separately



IP protection



seawater resistant



IK Impact resistance



mix'n match



Nightsaver



EVERYTHING IN VIEW

Optik Eberle, retail trade, conversion

design:


Optik Eberle
Marktstraße 24
75305 Neuenbürg
optik-eberle.de

scope:

consulting, lighting design, 3D visualisation, product delivery

photo:

Andris Balodis



FLEXIBLE SHOPPING EXPERIENCE

EDEKA, retail trade, refurbishment

realisation:

meerLICHT
Lunser Dorfstraße 12
27321 Thedinghausen
meerlicht.de

scope:

consulting, lighting design, 3D visualisation, product delivery

photo:

Andris Balodis



DRAWING WITH LIGHT

La Croix Architekten, office, new building

design and lighting design:


La Croix Architekten
Reiteilstraße 8
76297 Stutensee
lacroix-architekten.de

scope:

product delivery

photo:

Daniel Wieser . Architekturfotografie, Hildesheim/Karlsruhe



NEW LIGHT FOR MORE EFFICIENCY

high-bay warehouse, LED light-band system, refurbishment

realisation:

Elektrotechnik
Mike Kronenwett
Bahnhofstraße 8
76307 Karlsbad

extent:

consulting inkl. Amortisationsrechnung,
lighting design, 3D visualization, Projektlieferung

photo:

Roman Schinzel



OFFICE AND BIORHYTHM

EMSR, office building, new building

design and realisation:

EMSR-Technik GmbH
Dieselstraße 32
61200 Wölfersheim
emsrtechnik.de

scope:

consulting, lighting design, 3D visualisation, product delivery

photo:

Roman Schinzel



MODERN LOUNGE

Base One / Mohr Solutions, Ingenieure company building, conversion

design and realisation:

OKTEC GmbH
Wiesenstraße 8/1
73054 Eislöwen
ok-tec.de

lighting design:

lighting design Rottke
lichtplanung-rottke.de

scope:

consulting, product delivery

photo:

Alexander Cevolani



LINEAR AND TRANSPARENT

mars solutions, office- and event areas, core refurbishment

design and realisation:

OKTEC GmbH
Wiesenstraße 8/1
73054 Eislöwen
ok-tec.de

lighting design:

lighting design Rottke
lichtplanung-rottke.de

scope:

consulting, product delivery

photo:

Alexander Cevolani



MODERN THERAPY CENTRE

Physiotherapie Senger, practice rooms, refurbishment

design and realisation:

Elektro Huml GmbH
Egmatinger Straße 9
85635 Siegersbrunn
elektro-huml.de

scope:

consulting, lighting design, 3D visualisation, product delivery

photo:

Tanja Dörfner



MORE LIGHT AND QUALITY OF LIFE

Wilhelmshilfe e.V., nursing home, refurbishment

design and realisation:

OKTEC GmbH
Wiesenstraße 8/1
73054 Eislingen
ok-tec.de

lighting design:

lighting design Rottke
lichtplanung-rottke.de

scope:

consulting, lighting design, 3D visualisation, product delivery

photo:

Alexander Cevolani



MODERN LEARNING

Mühlbachschule, educational institution, refurbishment

design:

K+H | KILIAN + PARTNER
kh-architekten.de

realisation:

Endlichhofer Elektrotechnik
endlichhofer.de

lighting design:


Ingenieurbüro Markus Reuder
reuder.de

scope:

product delivery

photo:

Daniel Wieser . Architekturfotografie, Hildesheim/Karlsruhe



LIGHT FOR THE HIDDEN CHAMPION

WIBU-Systems, company, new building

design:

Architekturbüro archis
archis.de

project development:

IBA Immobilien
iba-heinze.de

project management:

mdbm
mdbm-baumanagement.de

general contractor:

Wolff+Müller
wolff-mueller.de

electrical installation:

Prinzing Elektrotechnik
prinzing-elektro.de

scope:

consulting, lighting design, product delivery

photos:

Andris Balodis





EVERY PLATE IN THE IDEAL LIGHT

Becks, restaurant, general refurbishment

design and realisation:

SH-Lichttechnik
Wörthstraße 74
72766 Reutlingen

lighting design:

Sven Hackius

scope:

consulting, product delivery

photo:

Andris Balodis



LIGHT IN THE ROCK

Mawell, hotel, new building

design:

KommInvest GmbH & Co. KG
komm-invest.de

realisation:

FARMBAU Fertigungssysteme GmbH
farmbau.eu

lighting design:

Lichtdesign Gommel

scope:

consulting, product delivery

photo:

Andris Balodis



GARDEN DREAM IN BERLIN

private building, garden landscape, new building

design and realisation:

Gärten von Klein GmbH & Co. KG
Gut-Asselborn Nr. 1
51429 Bergisch Gladbach
gaertenvonklein.de

lighting design:

Günter Klein

scope:

consulting, product delivery

photo:

Grit Erlebach



LINEARES LICHT BIS IN DEN LETZTEN WINKEL

private building, linear light, new building

design and realisation:

BEST – Bellemann Elektro Service Team GmbH
Letzenbergstraße 37a
69231 Rauenberg-Malschenberg

lighting design:

Michael Berger
best-elektro.de

scope:

product delivery

0			
000097	819	180196	867
000099	819	180264	860
000103	819	180277	864
000104	819	180286	861
000106	819	180287	861
000107	819	180295	861
000109	819	180296	862
		180297	862
		180298	862
		180299	862
		180309	860
		180317	862
		180318	860
		180319	862
		180368	860
		180512	812
		180513	812
		180514	812
		180515	819
		180529	819
		180730	33
		180731	33
		180732	34
		180733	34
		180734	35
		180735	35
		180736	35
		180737	35
		180741	35
		180742	35
		180743	35
		180744	862
		180745	862
		180746	860
		180747	862
		180748	860
		180749	860
		180750	860
		180751	860
		180752	861
		180753	862
		180754	864
1			
100032	157		
100078	156		
100079	156		
100084	149		
100088	149		
100089	149		
100111	526		
100114	526		
100122	149		
100123	152		
100124	153		
100125	152		
100133	530		
100138	153		
100139	152		
100140	146		
100141	146		
100142	147		
100143	146		
100144	146		
100145	147		
100146	148		
100147	148		
100148	149		
100149	146		
100150	146		
100151	148		
100152	159		
100153	159		
100154	152		
100156	159		
100157	159		
100158	154		
100159	158		
100160	158		
100200	872		
100202	872		
100204	873		
100250	872		
110017	91		
110019	90		
110038	86		
110039	86		
110040	86		
110041	86		
110042	86		
110043	86		
110044	87		
110045	87		
110046	87		
110047	87		
110048	87		
110049	87		
110050	88		
110051	88		
110052	88		
110053	88		
110054	88		
110055	88		
110056	89		
110057	89		
110058	89		
110059	89		
110060	89		
110061	89		
122416	78		
122417	79		
180195	867		
		341183	164
		341184	164
		341194	162
		341195	162
		341196	162
		341200	163
		341202	163
		341236	181
		341237	181
		341242	180
		341243	180
		341249	164
		341250	164
		341333	184
		341334	184
		341335	184
		341336	184
		341337	182
		341338	182
		341339	182
		341340	182
		341341	167
		341342	167
		341343	168
		341344	168
		341345	186
		341346	186
		341347	186
		341348	186
		341349	186
		341350	186
		341351	186
		341352	186
		342177	26
		342178	26
		342181	26
		342182	26
		342189	22
		342190	22
		342191	22
		342192	22
		342193	22
		342194	22
		342195	22
		342196	22
		342197	22
		342198	22
		342199	22
		342200	22
		342201	20
		342202	20
		342203	20
		342204	20
		342205	20
		342206	20
		342207	20
		342208	20
		342209	20
		342210	20
		342211	20
		342212	20
		342213	24
		342214	24
		342219	202
		342220	202
		342221	202
		342228	212
		342229	212
		342230	212
		342231	214
		342232	214
		342233	214
		342237	24
		342238	24
		342241	24
		342242	24
		342243	28
		342244	28
		342245	28
		342246	28
		342247	29
		342248	29
		342251	200
		342252	200
		342253	200
		342254	30
		342255	30
		342256	30
		342257	30
		342258	204
		342259	204
		342260	204
		342261	205
		342262	205
		342263	205
		343022	209
		343025	195
		343026	195
		343030	206
		343032	207
		343037	190
		343038	190
		343039	192
		343040	192
		346015	194
		346016	194
		346026	196
		346027	196
		346028	196
		346063	213
		346064	213
		346065	213
		346066	215
		346067	215
		346068	215
		346086	191
		346087	191
		346088	192
		346089	192
		348022	78
		348023	78
		348024	79
		348025	79
		348071	485
		348072	485
		348107	56
		348122	57
		348123	58
		348124	54
		348125	55
		348127	59
		348153	60
		348154	60
		348155	60
		348156	60
		348157	60
		348158	60
		348159	60
		348160	60
		348161	62
		348162	62
		348163	62
		348164	62
		348165	62
		348166	62
		348167	62
		348168	62
		348175	55
		348176	59
		348177	58
		348178	57
		348179	54
		348180	44
		348181	44
		348182	44
		348183	44
		348186	42
		348187	42
		348188	42
		348189	42
		348190	42
		348191	42
		348192	42
		348193	42
		348194	42
		348195	42
		348196	42
		348197	42
		348198	40
		348199	40
		348200	40
		348201	40
		348202	40
		348203	40
		348204	40
		348205	40
		348206	40
		348207	40
		348208	40
		348209	40
		348210	56
		348213	64
		348214	64
		348215	64
		348216	64
		348223	65
		348224	65
		348225	65
		348226	65
		348233	57

707148.....	369	707245.....	398	710045.....	313	720001.....	270
707149.....	369	707246.....	384	710047.....	313	720002.....	270
707150.....	369	707247.....	384	710048.....	324, 356	720003.....	270
707151.....	369	707248.....	384	710050.....	324, 356	720004.....	270
707152.....	369	707249.....	290	710051.....	327, 359	720005.....	270
707153.....	369	707250.....	290	710053.....	327, 359	720006.....	274
707154.....	369	707251.....	381	710054.....	331, 361	720007.....	274
707155.....	287	707252.....	381	710056.....	331, 361	720008.....	274
707156.....	287	707253.....	289	710057.....	322, 354	720009.....	274
707161.....	408	707254.....	289	710059.....	322, 354	720010.....	275
707162.....	408	707255.....	381	710060.....	331, 361	720011.....	275
707163.....	295	707256.....	381	710062.....	331, 361	720012.....	275
707164.....	295	707257.....	289	710063.....	321, 353	720013.....	275
707165.....	296	707258.....	289	710065.....	321, 353	720014.....	276
707166.....	296	707264.....	365	710066.....	320, 352	720015.....	276
707167.....	296	707265.....	365	710068.....	320, 352	720016.....	276
707168.....	296	707266.....	365	710077.....	320, 352	720017.....	276
707175.....	297	707267.....	365	710078.....	323, 355	720018.....	277
707176.....	297	707268.....	364	710079.....	320, 352	720019.....	277
707177.....	297	707269.....	364	710082.....	326, 358	720020.....	278
707178.....	297	707270.....	364	710083.....	326, 358	720021.....	278
707183.....	406	707271.....	364	710084.....	323, 355	720022.....	278
707184.....	406	707274.....	248	710086.....	323, 355	720023.....	278
707187.....	292	707277.....	248	710087.....	323, 355	720024.....	279
707188.....	292	707280.....	249	710094.....	324, 356	720025.....	279
707189.....	378	707283.....	249	710096.....	324, 356	720026.....	277
707190.....	378	707284.....	366	710097.....	328	720027.....	277
707191.....	378	707285.....	366	710099.....	328	720028.....	279
707192.....	378	707286.....	366	710103.....	320, 352	720029.....	279
707193.....	379	707287.....	366	710104.....	322, 354	720030.....	280
707194.....	379	707292.....	366	710106.....	322, 354	720031.....	280
707195.....	376	707293.....	366	710107.....	345	720032.....	282
707196.....	376	707294.....	366	710108.....	321, 353	720033.....	282
707197.....	376	707295.....	366	710109.....	321, 353	720034.....	283
707198.....	376	707296.....	367	710110.....	325, 357	720035.....	283
707199.....	377	707297.....	367	710112.....	325, 357	720036.....	281
707200.....	377	707298.....	367	710113.....	312, 343	720037.....	281
707201.....	294	707299.....	367	710114.....	312, 343	720038.....	280
707202.....	294	707304.....	367	710115.....	312, 343	720039.....	280
707203.....	409	707305.....	367	710116.....	312, 343	720040.....	282
707204.....	409	707306.....	367	710117.....	325, 357	720041.....	282
707205.....	378	707307.....	367	710118.....	325, 357	720042.....	273
707206.....	378	707328.....	375	710500.....	340	720043.....	273
707207.....	378	707329.....	375	710501.....	340	720044.....	273
707208.....	378	707330.....	375	710502.....	340	720045.....	273
707209.....	379	707331.....	375	710503.....	340	720046.....	283
707210.....	379	707332.....	375	710504.....	340	720047.....	283
707211.....	298	707333.....	375	710505.....	340	730255.....	534
707212.....	298	707334.....	375	710506.....	344	730262.....	537
707213.....	407	707335.....	375	710507.....	344	730266.....	529
707214.....	407	710000.....	310	710508.....	344	730267.....	529
707215.....	299	710002.....	310	710509.....	344	730276.....	532
707216.....	299	710003.....	310	710510.....	344	730289.....	535
707217.....	401	710005.....	310	710511.....	344	730292.....	537
707218.....	401	710006.....	310	710512.....	341	730296.....	531
707219.....	372	710008.....	310	710513.....	341	730300.....	875
707220.....	372	710009.....	314	710514.....	346	730301.....	875
707221.....	372	710011.....	314	710515.....	346	730330.....	474
707222.....	372	710012.....	314	710516.....	346	730336.....	526
707223.....	373	710014.....	314	710517.....	346	730349.....	875
707224.....	373	710015.....	316	710520.....	347	730408.....	484
707226.....	244	710017.....	316	710521.....	347	730432.....	537
707227.....	244	710018.....	316, 348	710523.....	347	730434.....	537
707228.....	244	710020.....	316, 348	710524.....	347	730454.....	533
707229.....	247	710024.....	330, 360	710525.....	348	730459.....	525
707230.....	247	710026.....	330, 360	710526.....	348	730474.....	524
707231.....	247	710027.....	318	710527.....	349	730475.....	524
707232.....	403	710029.....	318	710528.....	349	730478.....	524
707233.....	403	710030.....	318	710530.....	350	730479.....	524
707234.....	399	710032.....	318	710531.....	350	730483.....	229
707235.....	399	710033.....	319	710532.....	350	730484.....	230
707238.....	399	710035.....	319	710533.....	350	730485.....	231
707239.....	399	710036.....	317	710535.....	351	730486.....	229
707240.....	402	710038.....	317	710536.....	351	730487.....	230
707241.....	402	710039.....	315	710538.....	320, 352	730488.....	231
707242.....	402	710041.....	315	710539.....	360	730489.....	229
707243.....	402	710042.....	315	710540.....	360	730490.....	230
707244.....	398	710044.....	315	720000.....	270	730491.....	231

730492.....	428	731183.....	456	733004.....	436	840388.....	785
730493.....	428	731184.....	456	733040.....	432	840389.....	785
730494.....	428	731185.....	456	733041.....	432	840390.....	785
730495.....	424	731186.....	456	733042.....	432	840391.....	785
730496.....	424	731187.....	457	733043.....	434	840392.....	787
730497.....	424	731188.....	457	733044.....	434	840393.....	780
730498.....	424	731189.....	457	733045.....	434	840394.....	780
730499.....	422	731190.....	457	733054.....	498	840395.....	780
730500.....	422	731191.....	457	733055.....	498	840396.....	781
730501.....	422	731192.....	457	733064.....	502	840397.....	781
730502.....	422	731193.....	449	733065.....	502	840398.....	781
730503.....	422	731194.....	449	733066.....	500	840399.....	778
730504.....	422	731195.....	449	733067.....	500	840400.....	779
730505.....	422	731196.....	448	733068.....	438	840401.....	780
730506.....	422	731197.....	448	733069.....	438	840402.....	780
730509.....	229	731198.....	448	733070.....	504	840403.....	780
730510.....	229	731199.....	455	733071.....	504	840404.....	781
730511.....	229	731200.....	455	733072.....	430	840405.....	781
730519.....	427	731201.....	455	733073.....	430	840406.....	781
730520.....	427	731202.....	454	763025.....	488	840407.....	778
730521.....	427	731203.....	454	763026.....	490	840408.....	779
731015.....	464	731204.....	454			840409.....	729
731019.....	464	731205.....	452	8		840410.....	729
731020.....	464	731206.....	452	829063.....	872	840411.....	729
731024.....	464	731207.....	452	836011.....	494	840412.....	729
731025.....	464	731208.....	453	836014.....	494	840414.....	730
731026.....	464	731209.....	453	836930.....	494	840416.....	730
731029.....	465	731210.....	453	836931.....	494	840417.....	769
731030.....	465	731211.....	444	840124.....	762	840418.....	769
731031.....	458	731212.....	444	840147.....	756	840419.....	769
731060.....	474	731213.....	444	840158.....	748	840420.....	732
731099.....	471	731214.....	445	840159.....	748	840421.....	732
731100.....	471	731215.....	445	840164.....	745	840422.....	732
731126.....	478	731216.....	445	840165.....	745	840423.....	732
731127.....	468	731217.....	446	840166.....	745	840424.....	732
731129.....	472	731218.....	446	840167.....	745	840425.....	732
731130.....	462	731219.....	446	840175.....	749	840426.....	732
731131.....	462	731220.....	447	840178.....	756	840427.....	732
731133.....	459	731221.....	447	840179.....	756	840428.....	732
731134.....	472	731222.....	447	840180.....	756	840429.....	732
731135.....	472	731223.....	466	840186.....	753	840430.....	734
731136.....	472	731224.....	466	840187.....	753	840431.....	734
731138.....	476	731225.....	467	840192.....	762	840432.....	734
731139.....	477	731226.....	467	840193.....	762	840433.....	734
731140.....	476	731227.....	474	840194.....	762	840434.....	772
731141.....	477	731228.....	462	840210.....	749	840435.....	773
731144.....	459	731229.....	462	840236.....	759	840436.....	772
731151.....	461	731230.....	462	840239.....	757	840437.....	773
731153.....	460	731231.....	462	840254.....	754	840438.....	772
731154.....	460	731232.....	462	840256.....	755	840439.....	773
731155.....	460	731233.....	462	840267.....	749	840440.....	780
731156.....	460	732049.....	528	840276.....	752	840441.....	781
731157.....	461	732050.....	528	840289.....	767	840442.....	780
731158.....	480	732071.....	520	840291.....	747	840443.....	781
731159.....	480	732072.....	520	840293.....	787	840444.....	780
731160.....	232	732079.....	521	840294.....	787	840445.....	781
731161.....	232	732080.....	521	840295.....	787	840446.....	778
731162.....	232	732094.....	513	840308.....	765	840447.....	779
731163.....	234	732095.....	513	840309.....	765	840448.....	774
731164.....	234	732096.....	541	840317.....	783	840449.....	775
731165.....	234	732097.....	541	840318.....	782	840450.....	774
731166.....	235	732098.....	541	840319.....	783	840451.....	775
731167.....	235	732102.....	541	840320.....	782	840452.....	774
731168.....	235	732108.....	514	840331.....	763	840453.....	775
731169.....	450	732109.....	515	840332.....	763	840454.....	776
731170.....	450	732110.....	516	840333.....	764	840455.....	777
731171.....	450	732127.....	514	840334.....	764	840456.....	776
731172.....	450	732128.....	515	840337.....	782	840457.....	777
731173.....	450	732129.....	516	840338.....	783	840458.....	776
731174.....	450	732143.....	528	840339.....	782	840459.....	777
731175.....	451	732156.....	222	840340.....	783	840460.....	776
731176.....	451	732157.....	225	840349.....	751	840461.....	777
731177.....	451	732158.....	222	840350.....	750	840462.....	776
731178.....	451	732159.....	225	840353.....	758	840463.....	777
731179.....	451	732160.....	512	840373.....	760	840464.....	776
731180.....	451	732161.....	512	840378.....	761	840465.....	777
731181.....	456	732162.....	219	840386.....	785	840466.....	742
731182.....	456	732163.....	220	840387.....	785	840467.....	742

840468.....	742	862162.....	800	862277.....	803	930418.....	489
840469.....	742	862163.....	800	862278.....	803	930419.....	489
840470.....	743	862164.....	800	862280.....	802	930420.....	489
840471.....	743	862165.....	800	862281.....	802	930421.....	489
840472.....	743	862166.....	800	862282.....	802	930422.....	489
840473.....	743	862167.....	800	862283.....	802	930423.....	489
840474.....	736	862168.....	800	862285.....	814	930424.....	489
840475.....	736	862172.....	799	862299.....	807	930426.....	875
840476.....	736	862173.....	799	862300.....	807	930427.....	875
840477.....	737	862180.....	329	862301.....	807	930461.....	490
840478.....	737	862181.....	329	872014.....	813	930468.....	490
840479.....	737	862182.....	329	872045.....	802	930469.....	490
840480.....	738	862183.....	329	872046.....	802	930470.....	490
840481.....	739	862184.....	329	872082.....	800	930471.....	490
840482.....	740	862185.....	329	872083.....	800	930472.....	490
840483.....	741	862190.....	817	872084.....	800	930473.....	490
843008.....	850	862191.....	817	872085.....	800	930474.....	490
843011.....	850	862192.....	817	872086.....	800	930475.....	490
843037.....	851	862193.....	817	872087.....	800	930476.....	490
843049.....	851	862194.....	817	872088.....	800	930477.....	490
843050.....	851	862196.....	812	872089.....	800	930478.....	490
843055.....	874	862197.....	812	872091.....	800	930512.....	756
843273.....	852	862198.....	812	872093.....	800	930517.....	759
843279.....	852	862199.....	812	872094.....	800	930571.....	879
843340.....	853	862201.....	812	872105.....	801	930573.....	879
843341.....	854	862202.....	814	872106.....	801	930574.....	882
843342.....	854	862203.....	814	872107.....	801	930575.....	881
843343.....	855	862204.....	814	872108.....	801	930578.....	880
843344.....	855	862205.....	814	872109.....	807	930593.....	883
843500.....	827	862207.....	814	872110.....	807	930659.....	875
843501.....	829	862208.....	814	872111.....	807	930694.....	873
843502.....	830	862209.....	814	872112.....	807	930712.....	880
843503.....	832	862210.....	814	872113.....	807	930735.....	881
843504.....	833	862211.....	814	872114.....	807	930908.....	32
843505.....	834	862220.....	803	872115.....	807	930909.....	32
843506.....	835	862221.....	803	872125.....	801	930913.....	36
843507.....	847	862222.....	803	872126.....	805	930914.....	36
843508.....	836	862223.....	812	872127.....	798	930920.....	257
843509.....	836	862224.....	812	872128.....	798	930922.....	257
843510.....	837	862225.....	812	872129.....	811	930946.....	257
843511.....	837	862226.....	812	872130.....	811	930947.....	257
843512.....	841	862227.....	812	872131.....	811	930954.....	259
843513.....	844	862228.....	812	872132.....	813	930955.....	259
843514.....	846	862229.....	798	872134.....	813	930956.....	260
843518.....	540	862230.....	798	872135.....	804	930957.....	260
843519.....	540	862231.....	799	872136.....	804	930958.....	261
843520.....	540	862232.....	799	872137.....	804	930959.....	261
843521.....	508	862233.....	799	872138.....	804	930965.....	32
843522.....	845	862234.....	799	872142.....	804	930966.....	32
843523.....	838	862235.....	813	872143.....	804	930967.....	95, 137
843524.....	839	862236.....	813	872145.....	800	930968.....	95, 137
843525.....	840	862237.....	813	872146.....	806	930969.....	95, 137
843527.....	848	862238.....	811	872147.....	806	930970.....	95, 137
843529.....	849	862239.....	811	872148.....	806	930971.....	95, 137
843530.....	392	862240.....	803	872628.....	812	930972.....	95, 137
843531.....	392	862241.....	803	872629.....	799	930973.....	95, 137
843532.....	863	862242.....	803	872630.....	799	930974.....	95, 137
843533.....	865	862253.....	805			930975.....	95, 137
843534.....	866	862254.....	805	9		930976.....	95, 137
843535.....	843	862255.....	805	930060.....	874	931007.....	175
843537.....	826	862256.....	805	930104.....	883	931009.....	175
843538.....	828	862257.....	814	930105.....	883	931010.....	177
843539.....	508	862258.....	814	930301...77, 187, 193, 291,	385	931012.....	177
843540.....	511	862259.....	814	930302...77, 187, 193, 291,	385	931013.....	175
843542.....	831	862262.....	805	930303...77, 187, 193, 291,	385	931015.....	175
862048.....	812	862263.....	805	930345.....	787	931016.....	177
862093.....	799	862264.....	814	930346.....	787	931018.....	177
862094.....	799	862265.....	799	930347.....	787	931019.....	175
862121.....	799	862266.....	815	930348.....	787	931021.....	175
862122.....	799	862268.....	802	930349.....	787	931022.....	177
862123.....	799	862269.....	802	930350.....	787	931024.....	177
862124.....	799	862270.....	799	930366...77, 187, 193, 291,	385	931025.....	175
862125.....	799	862271.....	799	930406.....	787	931027.....	175
862126.....	799	862272.....	799	930413.....	489	931028.....	177
862127.....	800	862273.....	805	930414.....	489	931030.....	177
862130.....	812	862274.....	803	930415.....	489	931031.....	175
862136.....	814	862275.....	805	930416.....	489	931033.....	175
862157.....	812	862276.....	805	930417.....	489	931034.....	177

931036	177	950234	555	970028	632	970808	595
931037	175	950235	555	970041	636	970809	595
931039	175	950236	555	970043	636	970820	598
931040	177	950237	555	970045	636	970821	598
931042	177	950238	555	970048	636	970822	598
931043	95, 137	950239	555	970061	640	970823	598
931044	95, 137	950240	555	970063	640	970824	598
931045	95, 137	950241	555	970065	640	970825	598
931046	95, 137	950242	555	970068	640	970826	598
931047	95, 137	950243	555	970081	624	970827	598
931048	95, 137	950244	555	970085	624	970828	598
931049	95, 137	950245	555	970101	630	970829	603
931050	95, 137	950246	555	970103	630	970830	603
931051	95, 137	950247	555	970105	630	970831	603
931052	95, 137	950248	555	970121	634	970832	603
931053	77, 291, 385	950249	555	970123	634	970833	599
931054	77, 291, 385	950250	555	970125	634	970834	599
931055	77, 291, 385	950251	555	970128	634	970835	599
931056	77, 291, 385	950252	556	970141	638	970836	599
931057	77, 291, 385	950253	556	970143	638	970837	599
931058	77, 291, 385	950254	556	970145	638	970838	599
931059	187, 193	950255	556	970148	638	970839	599
931060	187, 193	950256	556	970161	642	970840	599
931061	187, 193	950257	556	970163	642	970841	599
931062	187, 193	950258	556	970165	642	970842	608
931063	187, 193	950259	556	970168	642	970843	608
931064	187, 193	950260	556	970181	626	970844	608
931088	258	950261	556	970183	626	970845	608
931089	258	950262	556	970185	626	970846	608
931090	260	950263	556	970280	660	970847	608
931091	260	950264	556	970281	660	970848	608
931168	250	950265	556	970284	660	970849	608
931169	251	950266	556	970285	660	970850	608
940010	875	950267	556	970301	672	970851	610
940029	877	950268	556	970303	672	970852	610
940030	877	950269	556	970305	672	970853	610
940031	877	950270	557	970401	674	970854	610
940033	877	950271	557	970403	674	970855	610
940034	877	950272	557	970404	674	970856	610
940035	877	950273	557	970460	668	970857	610
940037	877	950274	557	970470	670	970858	610
940038	877	950275	557	970502	664	970859	610
940039	877	950276	557	970503	664	970860	609
940041	878	950277	557	970522	666	970861	609
940042	878	950278	557	970523	666	970862	609
940043	878	950279	557	970550	678	970863	609
940045	878	950280	557	970551	678	970864	609
940046	878	950281	557	970560	680	970865	609
940047	878	950282	557	970561	680	970866	609
940049	878	950283	557	970570	682	970867	609
940050	878	950284	557	970571	682	970868	609
940051	878	950285	557	970572	582	970869	602
940056	876	950286	557	970573	582	970870	602
940057	876	950287	557	970574	582	970871	602
940058	876	950918	558	970575	582	970872	602
940059	876	950919	558	970576	582	975001	644
940060	876	950920	558	970577	582	975003	644
940061	876	950921	558	970578	583	975005	644
940062	876	950922	558	970579	583	975021	648
940063	876	950923	558	970580	583	975023	648
950216	554	950924	558	970581	583	975025	648
950217	554	950925	558	970582	583	975041	652
950218	554	950926	558	970583	583	975045	652
950219	554	950927	558	970584	584	975049	652
950220	554	950928	558	970585	584	975101	646
950221	554	950929	558	970586	584	975103	646
950222	554	950930	558	970587	584	975105	646
950223	554	950931	558	970588	584	975121	650
950224	554	950932	558	970589	584	975123	650
950225	554	950933	558	970741	714	975125	650
950226	554	950934	558	970800	594	975141	654
950227	554	950935	558	970801	594	975143	654
950228	554	970001	628	970802	594	975145	654
950229	554	970003	628	970803	594	975161	656
950230	554	970005	628	970804	595	975163	656
950231	554	970021	632	970805	595	975165	656
950232	554	970023	632	970806	595	975361	706
950233	554	970025	632	970807	595	975365	706

975371.....	708
975375.....	708
975381.....	710
975385.....	710
975411.....	676
975412.....	676
975471.....	688
975475.....	688
975483.....	690
975485.....	690
975491.....	686
975495.....	686
975501.....	694
975511.....	698
975516.....	700
975521.....	702
975525.....	696
975530.....	692
975741.....	716
975781.....	718
988170.....	605
988171.....	605
988172.....	605
988173.....	605

KS Licht – Your lighting wholesaler in Essen

Contact, customer service and information for customers

LIGHT Impressions 2026 | 2027

Directly linked to our product range, advice and project services:

In the KS Multi Brand Business online shop, you will find the latest products, new releases and special offers, as well as information to support you with advice, quotations and project management:

- Online stock availability check
- Catalogues, browsable catalogues and product links
- Technical data, tender specifications, light distribution curves and LDT files
- Easily find and order spare parts
- View your individual terms and conditions, delivery and payment terms
- Relevant product recommendations, variants and alternative products
- Direct contact with our sales team

Customer Information

All prices are net, plus statutory VAT. The retail prices quoted are recommended retail prices. Upon publication of this catalogue, previous price lists cease to be valid.

Illustrations, colours, shapes, designs and technical specifications are for illustrative purposes only and are not binding. Subject to changes and errors.

Goods are generally dispatched ex works, carriage forward.

For orders with a net value of less than €70.00, a minimum order surcharge of €8.00 will be applied.

Ordering & Delivery

When placing orders, please always specify the item number, colour and quantity. This reduces the need for follow-up enquiries and speeds up processing. Express and direct deliveries are available on request.

Custom-made items, components assembled to the customer's specifications and lamps are excluded from exchange.

Our General Terms and Conditions apply and are available at www.ks-germany.com/de/agb.

Kontakt

KS Licht- und Elektrotechnik GmbH

Manderscheidtstraße 8 c
45141 Essen
Germany

Verkauf & Service

Tel.: +49 (0)201-89924-0
verkauf@ks-germany.com

Online

ks-lys.dk
www.ks-germany.com

Pflichtangaben

KS Licht- und Elektrotechnik GmbH · Sitz der Gesellschaft: Essen · Geschäftsführer: Kai Becker
Registergericht: Amtsgericht Essen · Handelsregister: HRB 12736 · Steuer-Nr.: 111/5708/2689 ·
USt-IdNr.: DE190673411



KS Licht- und Elektrotechnik GmbH

Manderscheidtstraße 8 C
45141 Essen
Germany

Tel.: +49 (0)201-89924-0
E-Mail: verkauf@ks-germany.com

Onlineshop: ks-lys.dk
Internet: www.ks-germany.com

