

Deko Light GmbH Office Three Motion 343024 / UGR-Tabelle

Leuchte: Deko Light GmbH 343024 Office Three Motion

Lampen: 1 x Floor-/Lamp

Blendungsbewertung nach UGR											
ρ Decke		70	70	50	50	30	70	70	50	50	30
ρ Wände		50	30	50	30	30	50	30	50	30	30
ρ Boden		20	20	20	20	20	20	20	20	20	20
Raumgröße X Y		Blickrichtung quer zur Lampenachse					Blickrichtung längs zur Lampenachse				
2H	2H	5.2	5.8	6.3	6.8	8.2	6.6	7.2	7.7	8.2	9.6
	3H	4.9	5.4	6.0	6.5	7.9	6.3	6.8	7.4	7.8	9.3
	4H	4.8	5.2	5.9	6.3	7.7	6.1	6.6	7.3	7.7	9.1
	6H	4.6	5.0	5.7	6.1	7.6	6.0	6.4	7.1	7.5	8.9
	8H	4.5	4.9	5.6	6.0	7.5	5.9	6.3	7.0	7.4	8.9
	12H	4.4	4.8	5.6	5.9	7.4	5.8	6.2	6.9	7.3	8.8
4H	2H	4.8	5.2	5.9	6.3	7.7	6.1	6.6	7.3	7.7	9.1
	3H	4.4	4.8	5.6	5.9	7.4	5.8	6.2	6.9	7.3	8.8
	4H	4.3	4.6	5.4	5.7	7.2	5.6	6.0	6.8	7.1	8.6
	6H	4.1	4.4	5.2	5.5	7.0	5.5	5.8	6.6	6.9	8.4
	8H	4.0	4.3	5.2	5.4	6.9	5.4	5.6	6.5	6.8	8.3
	12H	3.9	4.1	5.1	5.3	6.8	5.3	5.5	6.5	6.7	8.2
8H	4H	4.0	4.3	5.2	5.4	6.9	5.4	5.6	6.5	6.8	8.3
	6H	3.8	4.0	5.0	5.2	6.7	5.2	5.4	6.4	6.6	8.1
	8H	3.7	3.9	4.9	5.1	6.6	5.1	5.3	6.3	6.4	8.0
	12H	3.6	3.8	4.8	4.9	6.5	5.0	5.2	6.2	6.3	7.9
12H	4H	3.9	4.1	5.1	5.3	6.8	5.3	5.5	6.5	6.7	8.2
	6H	3.7	3.9	4.9	5.1	6.6	5.1	5.3	6.3	6.4	8.0
	8H	3.6	3.8	4.8	4.9	6.5	5.0	5.2	6.2	6.3	7.9
Variation der Beobachterposition für Leuchtenabstände S											
S = 1.0H	+6.5 / -29.1					+6.6 / -30.1					
S = 1.5H	+9.3 / -30.4					+9.4 / -31.6					
S = 2.0H	+11.3 / -31.3					+11.4 / -32.5					
Standardtabelle	BK00					BK00					
Korrektursummand	-12.0					-10.6					
Korrigierte Blendindizes bezogen auf 9632lm Gesamtlichtstrom											

Die UGR-Werte werden gemäß CIE Publ. 117 berechnet. Spacing-to-Height-Ratio = 0.25.